

MP aes attributes backends **basexx** **bit32** blobs  
boolean buffers builders caches **callback**  
callbacks catcodes characters chemistry  
commands containers context converters  
**coroutine** ctxrunner **debug** dir directives  
document documentdata drivers environment  
experiments figures **file** **fio** floats **font** fonts  
functions global graphics **gzip** images  
interactions interfaces **io** job **language**  
languages layouts **lfs** libraries lmx loaders  
logs lpdf **lpeg** **lua** luac luatex lxml **math**  
mathematics **md5** metapost **mime** moduledata  
modules mp **mplib** noads **node** nodes number  
objects optional **os** **package** pagebuilders  
parametersets **pdf** **pdfdecode** **pdfe** physics  
**pngdecode** publications regimes resolvers  
sandbox scripts set **sha2** **sio** **socket** sorters  
sparse statistics **status** storage streams  
**string** structures **table** **tex** texconditionals  
**texconfig** texconstants texifs **texio**  
texisdefined texmodes texsystemmodes thirddata  
**token** tokens tracers trackers typesetters  
updaters url userdata **utf8** utilities  
visualizers **xcomplex** **xdecimal** **xmath** xml **xzip**  
**zip** **zlib**

ConT<sub>E</sub>Xt LMTX

# global (alias: \_G)

<b>CONTEXT</b>	number	<b>ctxrunner</b>	table
<b>FFISUPPORTED</b>	boolean	<b>debug</b>	table
<b>JITSUPPORTED</b>	boolean	<b>dimen</b>	function
<b>LUAMAJORVERSION</b>	number	<b>dir</b>	table
<b>LUAMINORVERSION</b>	number	<b>directives</b>	table
<b>LUATEXENGINE</b>	string	<b>document</b>	table
<b>LUATEXFORMATID</b>	number	<b>documentdata</b>	table
<b>LUATEXFUNCTIONALITY</b>	number	<b>dofile</b>	function
<b>LUATEXVERSION</b>	number	<b>done</b>	boolean
<b>LUAVERSION</b>	number	<b>drivers</b>	table
<b>MP</b>	function	<b>environment</b>	table
<b>aes</b>	table	<b>error</b>	function
<b>arg</b>	table	<b>experiments</b>	table
<b>asnumber_p</b>	function	<b>figures</b>	table
<b>assert</b>	function	<b>file</b>	table
<b>attributes</b>	table	<b>fio</b>	table
<b>backends</b>	table	<b>floats</b>	table
<b>basexx</b>	table	<b>flushsimplerule</b>	function
<b>bit32</b>	table	<b>flushspecialrule</b>	function
<b>blobs</b>	table	<b>font</b>	table
<b>blockrequire</b>	function	<b>fonts</b>	table
<b>boolean</b>	table	<b>functions</b>	table
<b>buffers</b>	table	<b>getmetatable</b>	function
<b>builders</b>	table	<b>getscriptstatus</b>	function
<b>caches</b>	table	<b>global</b>	table
<b>callback</b>	table	<b>graphics</b>	table
<b>callbacks</b>	table	<b>gzip</b>	table
<b>catcodes</b>	table	<b>handledefinitions</b>	function
<b>characters</b>	table	<b>handletransformstring</b>	function
<b>checkimage</b>	function	<b>images</b>	table
<b>chemistry</b>	table	<b>inspect</b>	function
<b>collectgarbage</b>	function	<b>interactions</b>	table
<b>combine</b>	function	<b>interfaces</b>	table
<b>commands</b>	table	<b>io</b>	table
<b>containers</b>	table	<b>ipairs</b>	function
<b>context</b>	function	<b>job</b>	table
<b>converters</b>	table	<b>language</b>	table
<b>copyarray</b>	function	<b>languages</b>	table
<b>copydictionary</b>	function	<b>last_pdf</b>	number
<b>coroutine</b>	table	<b>layouts</b>	table
<b>createmask</b>	function	<b>lfs</b>	table

<b>libraries</b>	table	<b>popleaderlevel</b>	function
<b>lmx</b>	table	<b>print</b>	function
<b>load</b>	function	<b>publications</b>	table
<b>loaders</b>	data table	<b>pushleaderlevel</b>	function
<b>loadfile</b>	function	<b>rawequal</b>	function
<b>loadstring</b>	function	<b>rawget</b>	function
<b>logs</b>	table	<b>rawlen</b>	function
<b>lpdf</b>	table	<b>rawset</b>	function
<b>lpeg</b>	table	<b>recolor</b>	function
<b>lua</b>	table	<b>regimes</b>	table
<b>luac</b>	table	<b>require</b>	function
<b>luatex</b>	table	<b>required</b>	function
<b>lxml</b>	table	<b>resolvers</b>	table
<b>math</b>	table	<b>ruledspace</b>	function
<b>mathematics</b>	table	<b>sandbox</b>	table
<b>mathshapekern</b>	function	<b>scripts</b>	table
<b>md5</b>	table	<b>select</b>	function
<b>metapost</b>	table	<b>set</b>	table
<b>mime</b>	table	<b>setinspector</b>	function
<b>moduledata</b>	table	<b>setmathparameters</b>	function
<b>modules</b>	table	<b>setmetatable</b>	function
<b>mp</b>	function	<b>sha2</b>	table
<b>mplib</b>	table	<b>shipbox_ref_h</b>	number
<b>next</b>	function	<b>shipbox_ref_v</b>	number
<b>noads</b>	table	<b>sio</b>	table
<b>node</b>	table	<b>socket</b>	table
<b>nodes</b>	table	<b>sorters</b>	table
<b>number</b>	table	<b>sparse</b>	table
<b>objects</b>	table	<b>statistics</b>	table
<b>optional</b>	table	<b>status</b>	table
<b>optionalrequire</b>	function	<b>storage</b>	table
<b>os</b>	table	<b>streams</b>	table
<b>p_number_p</b>	userdata	<b>string</b>	table
<b>p_number_u</b>	userdata	<b>structures</b>	table
<b>package</b>	table	<b>table</b>	table
<b>pagebuilders</b>	table	<b>tex</b>	table
<b>pairs</b>	function	<b>texconditionals</b>	data table
<b>parametersets</b>	table	<b>texconfig</b>	table
<b>pcall</b>	function	<b>texconstants</b>	data table
<b>pdf</b>	table	<b>texifs</b>	data table
<b>pdfdecode</b>	table	<b>texio</b>	table
<b>pdfc</b>	table	<b>texisdefined</b>	data table
<b>physics</b>	table	<b>texmodes</b>	data table
<b>pngdecode</b>	table	<b>texsystemmodes</b>	data table

<b>thirddata</b>	table	<b>userdata</b>	table
<b>toboolean</b>	function	<b>utf</b>	table
<b>todecimal</b>	function	<b>utf8</b>	table
<b>token</b>	table	<b>utilities</b>	table
<b>tokens</b>	table	<b>visualizers</b>	table
<b>tonumber</b>	function	<b>warn</b>	function
<b>tostring</b>	function	<b>xcomplex</b>	table
<b>tracers</b>	table	<b>xdecimal</b>	table
<b>trackers</b>	table	<b>xmath</b>	table
<b>type</b>	function	<b>xml</b>	table
<b>typesetters</b>	table	<b>xpcall</b>	function
<b>unpack</b>	function	<b>xzip</b>	table
<b>updaters</b>	table	<b>zip</b>	table
<b>url</b>	table	<b>zlib</b>	table

## aes (context)

**decode** function  
**encode** function

**random** function

# attributes (context)

## **alternates** table

N attribute  
D data  
F enable  
F handler  
F register  
D registered  
D values

## **applyoverloads** function

## **checkvalues** function

## **colorintents** table

N attribute  
D data  
F enable  
F handler  
F register  
D registered

## **colors** table

N attribute  
F cmyk  
F cmyktogray  
F cmyktorgb  
F colorcomponents  
D counts  
B couple  
F currentmodel  
F currentnamedmodel  
D data  
N default  
F defineintermediatecolor  
F definemultitonecolor  
F defineprocesscolor  
F defineprocesscolordirect  
F definesimplegray  
F definespotcolor  
F definetransparency  
F enable  
F filter  
N forced  
F forcedmodel  
F forcesupport

F formatcolor  
F formatgray  
F getpagecolormodel  
F gray  
F graytohsv  
F handler  
T helpers  
F complement  
F inbetween  
F justone  
F hsvtogray  
F hsvtorgb  
F hwbtorgb  
F iccprofile  
F isblack  
F labtorgb  
F labtoxyz  
N main  
S model  
D models  
F mpcolor  
F mpnamedcolor  
F mpoptions  
F namedcolorattributes  
N none  
F popset  
F processcolorcomponents  
F pushset  
F register  
D registered  
F registerspotcolor  
F rgb  
F rgbtocmyk  
F rgbtogray  
F rgbtohsv  
F rgbtoxyz  
N selector  
F setlist  
F setmodel  
F setpagecolormodel  
D sets

F spec	
F spot	
F spotcolorname	
F spotcolorparent	
F spotcolorvalue	
B supported	
F toattributes	
F transparencycomponents	
B triggering	
F usecolors	
D valid	
F value	
D values	
B weightgray	
F xyztolab	
F xyztorgb	
<b>counts</b>	data table
<b>define</b>	function
<b>effects</b>	table
N attribute	
D data	
F enable	
F handler	
F register	
D registered	
D values	
<b>getvalue</b>	function
<b>getvalues</b>	function
<b>handlers</b>	table
<b>hasvalues</b>	function
<b>list</b>	data table
<b>markasoverload</b>	function
<b>names</b>	data table
<b>negatives</b>	table
N attribute	
D data	
F enable	
F handler	
F register	
D registered	
F set	
<b>numbers</b>	data table
<b>ofnode</b>	function
<b>private</b>	function

<b>public</b>	function
<b>registervalue</b>	function
<b>restore</b>	function
<b>save</b>	function
<b>setcleaner</b>	function
<b>showcurrent</b>	function
<b>states</b>	table
F disabletriggering	
F enabletriggering	
F finalize	
F initialize	
F process	
F selective	
F simple	
F stacked	
F stacker	
<b>system</b>	function
<b>tooverloads</b>	function
<b>transparencies</b>	table
N attribute	
D data	
F enable	
F forcesupport	
F handler	
T names	
N color	
N colorburn	
N colordodge	
N darken	
N difference	
N exclusion	
N hardlight	
N hue	
N lighten	
N luminosity	
N multiply	
N none	
N normal	
N overlay	
N saturation	
N screen	
N softlight	
N none	
F register	

D registered	F handler
B supported	B hasorder
F toattribute	D listwise
B triggering	F register
F value	D registered
D values	F resolve_begin
<b>unsetvalue</b>	F resolve_end
<b>values</b>	F resolve_reset
<b>viewerlayers</b>	F resolve_step
N attribute	D scopes
F cleanup	F setfeatures
D data	F start
F define	F stop
F definedlayoutcomponent	B supported
F enable	D values
F forcesupport	



# backends (context)

**closeout** function

**codeinjections** table

F registerboxresource

F restoreboxresource

**current** string

**defaults** table

T codeinjections

F prerollreference

F vfstartcolor

F vfstopcolor

T nodeinjections

F cmykcolor

F destination

F graycolor

F injectknockout

F injectoverprint

F reference

F rgbcolor

F spotcolor

F transparency

T registrations

F transparency

D tables

**getcallbackstate** function

**included** table

B context

B date

B id

B metadata

B pdf

**initialize** function

**latelua** function

**nodeinjections** table

**nothing** function

**openout** function

**registered** table

T pdf

T codeinjections

F addbookmarks

F analyzenormalsymbol

F analyzesymbol

F attachmentid

F bitmap

F clonefield

F copyimage

F definefield

F definefieldset

F defineviewerlayer

F embedfile

F embedimage

F enabletags

F exportformdata

F fieldsurrounding

F flushmergelayer

F getbookmarks

F getboxresourcebox

F getdefaultfieldvalue

F getfieldcategory

F getfieldset

F getformatoption

F getinfo

F getpreviewfigure

F getrefobj

F insertrenderingwindow

F jp2

F jpg

F maptag

F mergebookmarks

F mergecomments

F mergefields

F mergereferences

F mergeviewerlayers

F newimage

F png

F prerollreference

F presetsymbol

F presetsymbollist

F processrendering

F registerdocumentcloseaction

F registerdocumentopenaction

F registeredsymbol

F registerpagecloseaction

- F registerpageopenaction
- F registerpattern
- F registersymbol
- F ruleactionbox
- F ruleactiondraw
- F ruleactionfill
- F ruleactionmp
- F ruleactionstroke
- F saveboxresource
- F scanimage
- F setattachmentsupport
- F setencryption
- F setfieldcalculationset
- F setfigurealternative
- F setfigurecolorspace
- F setfiguremask
- F setformat
- F setformsmethod
- F setpagetransition
- F settaggingsupport
- F setxmpfile
- F startlayer
- F startunicodetoactualtext
- F startunicodetoactualtextdirect
- F stoplayer
- F stopunicodetoactualtext
- F stopunicodetoactualtextdirect
- F supportedformats
- F unicodetoactualtext
- F useviewerlayer
- F validfield
- F validfieldcategory
- F validfieldset
- F vfstartcolor
- F vfstopcolor
- F wrapimage
- S name
- T nodeinjections
  - F addtags
  - F annotation
  - F attachfile

- F changestackedlayer
- F cmykcolor
- F comment
- F destination
- F effect
- F getboxresourcedimensions
- F graycolor
- F injectbitmap
- F insertu3d
- F knockout
- F negative
- F overprint
- F positive
- F reference
- F rgbcolor
- F spotcolor
- F startalternate
- F startlayer
- F startstackedlayer
- F stopalternate
- F stoplayer
- F stopstackedlayer
- F transparency
- F typesetfield
- F useboxresource
- T registrations
  - F cmykindexcolor
  - F cmykspotcolor
  - F getspotcolorreference
  - F grayindexcolor
  - F grayspotcolor
  - F rgbindexcolor
  - F rgbspotcolor
  - F spotcolorname
  - F transparency

T tables	
<b>registrations</b>	table
<b>setencryption</b>	function
<b>tables</b>	table
<b>writeout</b>	function

## basexx (extra lua)

**decode16**    function

**decode64**    function

**decode85**    function

**decodeLZW**   function

**decodeRL**    function

**encode16**    function

**encode64**    function

**encode85**    function

**encodeLZW**   function

**encodeRL**    function

## bit32 (basic lua)

**arshift** function  
**band** function  
**bnot** function  
**bor** function  
**btest** function  
**bxor** function

**extract** function  
**lrotate** function  
**lshift** function  
**replace** function  
**rrotate** function  
**rshift** function

## blobs (context)

<b>append</b>	function
<b>dimensions</b>	function
<b>dispose</b>	function
<b>new</b>	function
<b>pack</b>	function
<b>strdp</b>	function
<b>strhd</b>	function

<b>strht</b>	function
<b>strwd</b>	function
<b>tohpack</b>	function
<b>tonodes</b>	function
<b>tovpack</b>	function
<b>write</b>	function

## boolean (context)

**tocontext** function

**tonumber** function

# buffers (context)

<b>append</b>	function	<b>F define</b>	
<b>assign</b>	function	<b>F hassomecontent</b>	
<b>collectcontent</b>	function	<b>F next</b>	
<b>empty</b>	function	<b>F place</b>	
<b>erase</b>	function	<b>F reset</b>	
<b>exists</b>	function	<b>F save</b>	
<b>get</b>	function	<b>prepend</b>	function
<b>getcontent</b>	function	<b>raw</b>	function
<b>getlines</b>	function	<b>run</b>	function
<b>gettexbuffer</b>	function	<b>samplefile</b>	function
<b>loadcontent</b>	function	<b>undent</b>	function
<b>parallel</b>	table		

# builders (context)

**checkparcontext** function

**checksidefloat** function

**kernel** table

F collapsing

F hyphenating

F kerning

F ligaturing

F mlisttohlist

**local\_box\_filter** function

**paragraphs** table

T constructors

N attribute

F define

F disable

F enable

F handler

T methods

F basic

F default

F hpack

F oneline

D names

D numbers

F set

F start

F stop

T expansion

F trace

F keptogether

F registertogether

T solutions

T splitters

F define

F optimize

T registered

F reset

F set

F split

F start

F stop

F tag

**profiling** table

F add

F distance

F fixedprofile

F get

F list

F pagehandler

F profilebox

F set

**vspacing** table

D categories

F checkstrutdepth

F collapsevbox

T data

D map

D skip

D snapmethods

F definesnapmethod

B fixed

F flushcontributions

F forcepageflush

F forcestrutdepth

F getnofpreviouslines

F inject

F injectdisable

F injectpenalty

F injectskip

F interceptsamepagecontent

F pagehandler

F pageoverflow

F popatsame

F pushatsame

F setmap

F setskip

F snapbox

F synchronizepage

F tocategories

F tocategory

F vboxhandler



## cache (context)

<b>base</b>	string	<b>loadcontent</b>	function
<b>collapsecontent</b>	function	<b>loaddata</b>	function
<b>configfiles</b>	function	<b>more</b>	string
<b>contentstate</b>	function	<b>savecontent</b>	function
<b>defaults</b>	table	<b>savadata</b>	function
<b>getfirstreadablefile</b>	function	<b>setfirstwritablefile</b>	function
<b>getreadablepaths</b>	function	<b>setluanames</b>	function
<b>getwritablepath</b>	function	<b>treehash</b>	function
<b>hashed</b>	function	<b>usedpaths</b>	function
<b>is_writable</b>	function		

## callback (basic tex)

**find**        function  
**known**     function  
**list**        function

**register**   overloaded function  
**usage**       function

# callbacks (context)

**freeze** function

**functions** table

F start\_page\_number

F stop\_page\_number

**known** function

**list** data table

**pop** function

**push** function

**register** function

**report** function

**supported** table

B alignment\_filter

B append\_line\_filter

B append\_to\_vlist\_filter

B begin\_paragraph

B build\_page\_insert

B buildpage\_filter

B define\_font

B find\_format\_file

B find\_log\_file

B get\_attribute

B get\_math\_dictionary

B get\_noad\_class

B glyph\_run

B handle\_overload

B hpack\_filter

B hpack\_quality

B hyphenate

B insert\_par

B intercept\_lua\_error

B intercept\_tex\_error

B kerning

B ligaturing

B linebreak\_filter

B local\_box\_filter

B make\_extensible

B math\_rule

B missing\_character

B mlist\_to\_hlist

B open\_data\_file

B packed\_vbox\_filter

B paragraph\_context

B post\_linebreak\_filter

B pre\_dump

B pre\_linebreak\_filter

B pre\_output\_filter

B process\_character

B process\_jobname

B register\_extensible

B show\_error\_message

B show\_lua\_call

B show\_warning\_message

B show\_whatsit

B start\_file

B start\_run

B stop\_file

B stop\_run

B trace\_memory

B vpack\_filter

B vpack\_quality

B wrapup\_run

## catcodes (context)

**names** data table

**numbers** data table

**register** function

# characters (context)

<b>adobename</b>	function	<b>T anudatta</b>	
<b>bidi</b>	data table	<b>T before_half</b>	
<b>blockrange</b>	function	<b>T before_main</b>	
<b>blocks</b>	data table	<b>T before_postscript</b>	
<b>casemap</b>	table	<b>T before_subscript</b>	
<b>categories</b>	data table	<b>T below_mark</b>	
<b>category</b>	function	<b>T consonant</b>	
<b>categorytags</b>	data table	<b>T dependent_vowel</b>	
<b>classifiers</b>	table	<b>T halant</b>	
<b>collapsed</b>	data table	<b>T independent_vowel</b>	
<b>combined</b>	data table	<b>T nukta</b>	
<b>contextname</b>	function	<b>T post_mark</b>	
<b>csletters</b>	data table	<b>T pre_mark</b>	
<b>data</b>	data table	<b>T ra</b>	
<b>decomposed</b>	data table	<b>T stress_tone_mark</b>	
<b>description</b>	function	<b>T twopart_mark</b>	
<b>descriptions</b>	data table	<b>T vowel_modifier</b>	
<b>detailltags</b>	data table	<b>initialize</b>	function
<b>directions</b>	table	<b>is_character</b>	data table
<b>emoji</b>	table	<b>is_command</b>	data table
<b>F compact</b>		<b>is_hyphenator</b>	data table
<b>F known</b>		<b>is_letter</b>	data table
<b>F resolve</b>		<b>is_mark</b>	data table
<b>emojized</b>	function	<b>is_punctuation</b>	data table
<b>encodes</b>	data table	<b>is_spacing</b>	data table
<b>entities</b>	data table	<b>is_symbol</b>	data table
<b>fallbacks</b>	data table	<b>lcchars</b>	data table
<b>filters</b>	data table	<b>lccode</b>	function
<b>fractions</b>	table	<b>lccodes</b>	data table
<b>fromnumber</b>	function	<b>lettered</b>	function
<b>fschars</b>	data table	<b>lhash</b>	data table
<b>fscodes</b>	data table	<b>linebreaks</b>	data table
<b>getrange</b>	function	<b>lower</b>	function
<b>graphemes</b>	data table	<b>mathlists</b>	data table
<b>hangul</b>	data table	<b>mirrors</b>	table
<b>indigroups</b>	table	<b>otfscripts</b>	data table
<b>T above_mark</b>		<b>private</b>	table
<b>T after_half</b>		<b>ranges</b>	data table
<b>T after_main</b>		<b>registerentities</b>	function
<b>T after_postscript</b>		<b>remap_hangul_syllabe</b>	function
<b>T after_subscript</b>		<b>scripthash</b>	table

<b>setactivecatcodes</b>	function	D accentmapping	
<b>setlettercatcodes</b>	function	D commandmapping	
<b>setothercatcodes</b>	function	F defineaccents	
<b>shape</b>	function	F safechar	
<b>shaped</b>	function	F strtoutf	
<b>shash</b>	data table	F strtoutfpattern	
<b>shchars</b>	data table	F toutf	
<b>shcodes</b>	data table	F toutfpattern	
<b>showstring</b>	function	<b>textclasses</b>	table
<b>specialchars</b>	data table	<b>tonumber</b>	function
<b>specials</b>	data table	<b>ucchars</b>	data table
<b>splits</b>	table	<b>uccode</b>	function
T char		<b>uccodes</b>	data table
T compat		<b>uhash</b>	data table
<b>subscripts</b>	table	<b>unicodechar</b>	function
<b>superscripts</b>	table	<b>upper</b>	function
<b>synonyms</b>	data table	<b>verbosemarks</b>	data table
<b>tex</b>	table		

## chemistry (context)

<b>component</b>	function	<b>method</b>	string
<b>define</b>	function	<b>molecule</b>	function
<b>definitions</b>	data table	<b>moleculeparser</b>	userdata
<b>format</b>	string	<b>start</b>	function
<b>inlinechemical</b>	function	<b>stop</b>	function
<b>instance</b>	string	<b>undefine</b>	function

## containers (context)

**cleannname** function  
**content** function  
**define** function  
**is\_usable** function

**is\_valid** function  
**read** function  
**usecache** boolean  
**write** function



## converters (context)

<b>A</b>	function	<b>cn-c</b>	function
<b>A:es</b>	function	<b>convert</b>	function
<b>A:ru</b>	function	<b>decimals</b>	function
<b>A:sl</b>	function	<b>define</b>	function
<b>AK</b>	function	<b>gregorian_to_hebrew</b>	function
<b>Alphabetic</b>	function	<b>gregorian_to_jalali</b>	function
<b>Alphabetic:es</b>	function	<b>hebrewnumerals</b>	function
<b>Alphabetic:ru</b>	function	<b>helpers</b>	table
<b>Alphabetic:sl</b>	function	<b>hexstringtonumber</b>	function
<b>Character</b>	function	<b>i</b>	function
<b>Characters</b>	function	<b>isleapyear</b>	function
<b>I</b>	function	<b>jalali_to_gregorian</b>	function
<b>KA</b>	function	<b>lchexnumber</b>	function
<b>KR</b>	function	<b>lchexnumbers</b>	function
<b>R</b>	function	<b>leapyear</b>	function
<b>RK</b>	function	<b>lower</b>	function
<b>Romannumerals</b>	function	<b>max</b>	function
<b>Russiannumerals</b>	function	<b>maxchrs</b>	function
<b>Sloveniannumerals</b>	function	<b>nicenumber</b>	function
<b>Spanishnumerals</b>	function	<b>nofdays</b>	function
<b>Word</b>	function	<b>number</b>	function
<b>Words</b>	function	<b>numbers</b>	function
<b>a</b>	function	<b>octnumber</b>	function
<b>a:es</b>	function	<b>octstringtonumber</b>	function
<b>a:ru</b>	function	<b>ordinal</b>	function
<b>a:sl</b>	function	<b>r</b>	function
<b>abjadnodotnumerals</b>	function	<b>rawcharacter</b>	function
<b>abjadnumerals</b>	function	<b>romannumerals</b>	function
<b>alphabetic</b>	function	<b>russiannumerals</b>	function
<b>alphabetic:es</b>	function	<b>sequences</b>	data table
<b>alphabetic:ru</b>	function	<b>settime</b>	function
<b>alphabetic:sl</b>	function	<b>sloveniannumerals</b>	function
<b>character</b>	function	<b>spaceddigits</b>	function
<b>characters</b>	function	<b>spanishnumerals</b>	function
<b>chineseallnumerals</b>	function	<b>textime</b>	function
<b>chinesecapnumerals</b>	function	<b>toabjad</b>	function
<b>chinesenumerals</b>	function	<b>tochinese</b>	function
<b>chr</b>	function	<b>tohebrew</b>	function
<b>chrs</b>	function	<b>toroman</b>	function
<b>cn</b>	function	<b>totime</b>	function
<b>cn-a</b>	function	<b>uchexnumber</b>	function

**uchexnumbers**

**upper**

**verbose**

D data

function

function

table

F translate

**weekday**

**word**

**words**

function

function

function

## coroutine (basic lua)

<b>close</b>	function
<b>create</b>	function
<b>isyieldable</b>	function
<b>resume</b>	function

<b>running</b>	function
<b>status</b>	function
<b>wrap</b>	function
<b>yield</b>	function

# ctxrunner (context)

<b>load</b>	function	<b>prepfiles</b>	data table
<b>preparedfile</b>	function	<b>resolve</b>	function

## debug (basic lua)

**getinfo**    function

**sethook**    function

**traceback** function

## dir (context)

<b>collectpattern</b>	function
<b>current</b>	function
<b>expandname</b>	function
<b>found</b>	function
<b>glob</b>	function
<b>globdirs</b>	function
<b>globfiles</b>	function

<b>globpattern</b>	function
<b>ls</b>	function
<b>makedirs</b>	function
<b>mkdirs</b>	function
<b>pop</b>	function
<b>push</b>	function

## directives (context)

<b>data</b>	data table
<b>default</b>	function
<b>disable</b>	function
<b>done</b>	table
<b>enable</b>	function
<b>list</b>	function
<b>name</b>	string

<b>register</b>	function
<b>report</b>	function
<b>reset</b>	function
<b>show</b>	function
<b>value</b>	function
<b>values</b>	function

# document (context)

<b>arguments</b>	data table		D modes	
<b>files</b>	table		D modules	
<b>functions</b>	table	<b>setargument</b>		function
<b>getargument</b>	function	<b>setcommandline</b>		function
<b>getfilename</b>	function	<b>setdefaultargument</b>		function
<b>options</b>	table	<b>setenvironments</b>		function
T commandline		<b>setfilename</b>		function
D environments		<b>setfilenames</b>		function
D modes		<b>setmodes</b>		function
D modules		<b>setmodules</b>		function
T ctxfile		<b>variables</b>		data table
D environments				



# documentdata (context)

**variable** function

# drivers (context)

<b>applyanchor</b>	function	F updatefontstate
<b>applyorientation</b>	function	T whatsit
<b>convert</b>	function	S name
<b>converters</b>	table	T json
F analyze		T actions
F engine		F cleanup
F lmtx		F convert
F resyncbox		F finalize
<b>enable</b>	function	F initialize
<b>gethpos</b>	function	F outputfilename
<b>getpos</b>	function	F prepare
<b>getrpos</b>	function	F wrapup
<b>getvpos</b>	function	T flushers
<b>helpers</b>	table	F character
<b>install</b>	function	F popleaderlevel
<b>instances</b>	table	F pushleaderlevel
T empty		F rule
T actions		F setstate
F convert		F simplerule
F prepare		F specialrule
T flushers		F updatefontstate
F popleaderlevel		T whatsit
F pushleaderlevel		S name
T whatsit		T lua
S name		T actions
T js		F cleanup
T actions		F convert
F cleanup		F finalize
F convert		F initialize
F finalize		F outputfilename
F initialize		F prepare
F outputfilename		F wrapup
F prepare		T flushers
F wrapup		F character
T flushers		F popleaderlevel
F character		F pushleaderlevel
F popleaderlevel		F rule
F pushleaderlevel		F simplerule
F rule		F specialrule
F simplerule		F updatefontstate
F specialrule		T whatsit

S name	T actions	
T mpo	F cleanup	
T actions	F convert	
F finalize	F finalize	
F initialize	F initialize	
T flushers	F outputfilename	
F character	F prepare	
F popleaderlevel	F wrapup	
F pushleaderlevel	T flushers	
F rule	F character	
F simplerule	F fontchar	
F specialrule	F group	
T Whatsit	F image	
S name	F literal	
T mps	F popleaderlevel	
T actions	F poporientation	
F cleanup	F pushleaderlevel	
F convert	F pushorientation	
F finalize	F restore	
F initialize	F rule	
F outputfilename	F save	
F prepare	F setmatrix	
F wrapup	F setstate	
T flushers	F simplerule	
F character	F specialrule	
F popleaderlevel	F startclipping	
F pushleaderlevel	F startmatrix	
F rule	F startmirroring	
F simplerule	F startrotation	
F specialrule	F startscaling	
F updatefontstate	F stopclipping	
T Whatsit	F stopmatrix	
S name	F stopmirroring	
T none	F stoprotation	
T actions	F stopscaling	
T flushers	F updatefontstate	
F popleaderlevel	T Whatsit	
F pushleaderlevel	S name	
T Whatsit	<b>lmtxversion</b>	number
S name	<b>outputfilename</b>	function
T pdf	<b>report</b>	function

## environment (context)

<b>argument</b>	function	<b>luafile</b>	function
<b>arguments</b>	data table	<b>luafilechunk</b>	function
<b>basicengines</b>	data table	<b>luatexengine</b>	string
<b>currentrun</b>	number	<b>luatexfunctionality</b>	number
<b>definefilefallback</b>	function	<b>luatexversion</b>	number
<b>definefilesynonym</b>	function	<b>maxnofruns</b>	number
<b>engineflags</b>	data table	<b>oldhome</b>	string
<b>filename</b>	string	<b>originalarguments</b>	data table
<b>filenames</b>	table	<b>outputfilename</b>	string
<b>files</b>	table	<b>ownbin</b>	string
<b>filesynonyms</b>	data table	<b>ownmain</b>	string
<b>forcedruns</b>	number	<b>ownname</b>	string
<b>getargument</b>	function	<b>ownpath</b>	string
<b>homedir</b>	string	<b>prerollrun</b>	boolean
<b>initex</b>	boolean	<b>rawarguments</b>	data table
<b>initexmode</b>	boolean	<b>reconstructcommandline</b>	function
<b>initializearguments</b>	function	<b>relativepath</b>	function
<b>initializefilenames</b>	function	<b>setargument</b>	function
<b>inputfilebarename</b>	string	<b>splitarguments</b>	function
<b>inputfilename</b>	string	<b>suffix</b>	string
<b>inputfilesuffix</b>	string	<b>texfile</b>	function
<b>jitsupported</b>	boolean	<b>texmfos</b>	string
<b>jobfilefullname</b>	string	<b>texos</b>	string
<b>jobfilename</b>	string	<b>texroot</b>	string
<b>jobfilesuffix</b>	string	<b>truefilename</b>	function
<b>jobname</b>	string	<b>uselua module</b>	function
<b>kindofrun</b>	number	<b>usemodules</b>	function
<b>lmtxmode</b>	number	<b>validengines</b>	data table
<b>loadexamodes</b>	function	<b>version</b>	string
<b>loadluafile</b>	function		

# experiments (context)

<b>data</b>	data table	<b>register</b>	function
<b>default</b>	function	<b>report</b>	function
<b>disable</b>	function	<b>reset</b>	function
<b>enable</b>	function	<b>show</b>	function
<b>list</b>	function	<b>value</b>	function
<b>name</b>	string	<b>values</b>	function

# figures (context)

<b>applyratio</b>	function	<b>F resetstore</b>	
<b>badname</b>	function	<b>F scan</b>	
<b>bases</b>	data table	<b>F serialize</b>	
<b>bitmapimage</b>	function	<b>T sizes</b>	
<b>boxnumber</b>	number	<b>B art</b>	
<b>cachepaths</b>	data table	<b>B bleed</b>	
<b>check</b>	function	<b>B crop</b>	
<b>checkers</b>	data table	<b>B media</b>	
<b>conversions</b>	data table	<b>B none</b>	
<b>converters</b>	data table	<b>B trim</b>	
<b>current</b>	function	<b>F storedata</b>	
<b>defaultdepth</b>	number	<b>F totable</b>	
<b>defaultheight</b>	number	<b>T types</b>	
<b>defaultsearch</b>	boolean	<b>N jbig2</b>	
<b>defaultwidth</b>	number	<b>N jp2</b>	
<b>done</b>	function	<b>N jpg</b>	
<b>dummy</b>	function	<b>N none</b>	
<b>existsers</b>	data table	<b>N pdf</b>	
<b>exists</b>	function	<b>N png</b>	
<b>formats</b>	data table	<b>N stream</b>	
<b>found</b>	data table	<b>F wrap</b>	
<b>get</b>	function	<b>include</b>	function
<b>getinfo</b>	function	<b>includers</b>	data table
<b>getpdfinfo</b>	function	<b>initialize</b>	function
<b>getrealpage</b>	function	<b>loaded</b>	data table
<b>guess</b>	function	<b>localpaths</b>	data table
<b>guessfromstring</b>	function	<b>magics</b>	data table
<b>hash</b>	function	<b>mergegoodies</b>	function
<b>identifiers</b>	data table	<b>nofmissing</b>	number
<b>identify</b>	function	<b>nofprocessed</b>	number
<b>images</b>	table	<b>order</b>	data table
<b>F check</b>		<b>paths</b>	data table
<b>F checksize</b>		<b>patterns</b>	data table
<b>F copy</b>		<b>pop</b>	function
<b>F create</b>		<b>preferquality</b>	boolean
<b>F embed</b>		<b>programs</b>	data table
<b>F embedfromstore</b>		<b>push</b>	function
<b>F fetchdata</b>		<b>registerpattern</b>	function
<b>T keys</b>		<b>registerresource</b>	function
<b>F print</b>		<b>registersuffix</b>	function
<b>F resetdata</b>		<b>remappers</b>	data table

<b>resources</b>	data table	<b>setorder</b>	function
<b>scale</b>	function	<b>setpaths</b>	function
<b>set</b>	function	<b>suffixes</b>	data table
<b>setconversion</b>	function	<b>used</b>	data table
<b>setlookups</b>	function		

## file (basic lua)

<b>addsuffix</b>	function
<b>basename</b>	function
<b>checksum</b>	function
<b>collapsepath</b>	function
<b>copy</b>	function
<b>dirname</b>	function
<b>expandname</b>	function
<b>extname</b>	function
<b>is_qualified_path</b>	function
<b>is_readable</b>	function
<b>is_rootbased_path</b>	function
<b>is_writable</b>	function
<b>isreadable</b>	function
<b>iswritable</b>	function
<b>join</b>	function
<b>joinpath</b>	function
<b>loadchecksum</b>	function
<b>nameonly</b>	function
<b>nametotable</b>	function
<b>needs Updating</b>	function

<b>needsupdating</b>	function
<b>pathpart</b>	function
<b>readdata</b>	function
<b>removesuffix</b>	function
<b>replacesuffix</b>	function
<b>reslash</b>	function
<b>robustname</b>	function
<b>savechecksum</b>	function
<b>savedata</b>	function
<b>size</b>	function
<b>splitbase</b>	function
<b>splitname</b>	function
<b>splitpath</b>	function
<b>strip</b>	function
<b>suffix</b>	function
<b>suffixes</b>	function
<b>suffixesonly</b>	function
<b>suffixonly</b>	function
<b>syncmtimes</b>	function
<b>withinbase</b>	function



## fio (extra lua)

<b>getposition</b>	function
<b>read2dot14</b>	function
<b>readbytes</b>	function
<b>readbytetable</b>	function
<b>readcardinal1</b>	function
<b>readcardinal1le</b>	function
<b>readcardinal2</b>	function
<b>readcardinal2le</b>	function
<b>readcardinal3</b>	function
<b>readcardinal3le</b>	function
<b>readcardinal4</b>	function
<b>readcardinal4le</b>	function
<b>readcardinaltable</b>	function
<b>readcline</b>	function
<b>readcstring</b>	function
<b>readfixed2</b>	function
<b>readfixed4</b>	function
<b>readinteger1</b>	function

<b>readinteger1le</b>	function
<b>readinteger2</b>	function
<b>readinteger2le</b>	function
<b>readinteger3</b>	function
<b>readinteger3le</b>	function
<b>readinteger4</b>	function
<b>readinteger4le</b>	function
<b>readintegertable</b>	function
<b>setposition</b>	function
<b>skipposition</b>	function
<b>writecardinal1</b>	function
<b>writecardinal1le</b>	function
<b>writecardinal2</b>	function
<b>writecardinal2le</b>	function
<b>writecardinal3</b>	function
<b>writecardinal3le</b>	function
<b>writecardinal4</b>	function
<b>writecardinal4le</b>	function

# floats (context)

<b>analysemethod</b>	function	<b>nofstacked</b>	function
<b>checkedpagefloat</b>	function	<b>pop</b>	function
<b>collect</b>	function	<b>push</b>	function
<b>consult</b>	function	<b>resave</b>	function
<b>flush</b>	function	<b>save</b>	function
<b>getvariable</b>	function	<b>stacked</b>	function
<b>hasstacked</b>	function		

## font (basic tex)

<b>addcharacters</b>	function
<b>current</b>	function
<b>define</b>	function
<b>getfont</b>	function
<b>getfontdimen</b>	function
<b>getfontspec</b>	function
<b>getmathindex</b>	function

<b>getmathspec</b>	function
<b>id</b>	function
<b>max</b>	function
<b>nextid</b>	function
<b>setfont</b>	function
<b>setfontdimen</b>	function

# fonts (context)

## analyzers table

- D features
- D initializers
- D methods
- F setstate
- D states
- B useunicodemarks

## callbacks table

- F callback
- F devirtualize

## checkers table

- F getmissing
- D mapping
- F missing
- F placeholder

## cid table

- F getmap
- F loadfile

## collections table

- F checkenabled
- F clonevector
- F define
- T definitions
- F direct
- F found
- F prepare
- F process
- F register
- F registermain
- F report
- F reset
- T vectors

## constructors table

- F addcharacters
- F addcoreunicodes
- F aftercopyingcharacters
- F applyfinalizers
- F applymanipulators
- F assignmathparameters
- F beforecopyingcharacters
- F beforepassingfonttotex

- D cache
- F calculatescale
- F checkedfeatures
- F checkedfilename
- F collectprocessors
- F currentfonthasfeature
- D designsizes
- F enhanceparameters
- T enhancers
- T afm
  - F apply
  - F patch
- T patches
  - F register
  - F report
- F register
- F report
- T otf
  - F addfeature
  - F apply
  - F enhance
  - F patch
- T patches
  - F register
  - F report
- F register
- F report
- T tfm
  - F apply
  - F patch
- T patches
  - F register
  - F report
- F register
- F report
- N factor
- T features
  - D afm
  - D otf
  - D tfm
- F finalize

F getfeatureaction	S defaultnodealternate
F getmathparameter	D features
F getprivate	F featuresinitializer
T handlers	F featuresprocessor
T afm	F getactualtext
B autoprefixed	F getalternate
D cache	F getgsub
D features	F getkern
F getkern	F getmultiple
T helpdata	F getstreamhash
D bothkerned	F getsubstitution
D leftkerned	T handlers
D ligatures	F ctx_camelcasing
D rightkerned	F devanagari_remove_joiners
D texligatures	F devanagari_reorder_matras
F load	F devanagari_reorder_pre_base_reordering_consonants
T readers	F devanagari_reorder_reph
F getinfo	F gpos_context
F loadfont	F gpos_contextchain
F loadshapes	F gpos_cursive
F setfeatures	F gpos_mark2base
B syncspace	F gpos_mark2ligature
N version	F gpos_mark2mark
T otf	F gpos_pair
F addfeature	F gpos_single
F basemodeinitializer	F gsub_alternate
D cache	F gsub_context
F collectlookups	F gsub_contextchain
T coverup	F gsub_ligature
T actions	F gsub_multiple
F alternate	F gsub_reversecontextchain
F chainposition	F gsub_single
F chainsubstitution	F trigger_space_kerns
F kern	T helpers
F ligature	F blockligatures
F multiple	F pardirstate
F pair	F txtfirststate
F single	F load
F substitution	F loadoutlinedata
F register	F loadstreamdata
S stepkey	F modeinitializer
F dataset	D mpscache
F datasetpositionprocessor	D pdfcache
S defaultbasealternate	F plugininitializer

F pluginprocessor	F chainedcontext
T plugins	F context
T text	F extension
D pngcache	F ligature
B pngenabled	F multiple
T readers	F reversechainedcontextsingle
F addunicodetable	F single
F avar	F gvar
F cbdt	F head
F cblc	T helpers
F cff	F axistofactors
F cff2	F cleanname
F cffcheck	F getaxisscale
T cffencoder	F getfactors
F checkhash	F getscales
F cmap	F gotodatatable
F colr	F normalizedaxis
F compact	T normalizedaxisishash
F condense	F readvariationdata
F cpal	F reportskippedtable
F ebdt	F setvariabledata
F eblc	F hhea
F ebsc	F hmtx
F expand	F hvar
F extend	F kern
F fvar	F loadfont
F gdef	F loadshapes
F getcomponents	F loca
F getinfo	F math
F glyf	F maxp
F gpos	F mvar
T gposhandlers	F name
F chainedcontext	F os/2
F context	F pack
F cursive	F parsecharstrings
F extension	F post
F marktobase	F registerextender
F marktoligature	F rehash
F marktomark	F sbix
F pair	F stat
F single	T streamreader
F gsub	F close
T gsubhandlers	F getposition
F alternate	F getsize

F look	F writecardinal2le
F open	F writecardinal3
F read2dot14	F writecardinal3le
F readbyte	F writecardinal4
F readbytes	F writecardinal4le
F readbytetable	F writeinteger1
F readcardinal	F writeinteger1le
F readcardinal1	F writeinteger2
F readcardinal1le	F writeinteger2le
F readcardinal2	F writeinteger3
F readcardinal2le	F writeinteger3le
F readcardinal3	F writeinteger4
F readcardinal3le	F writeinteger4le
F readcardinal4	F writestring
F readcardinal4le	F stripredundant
F readcardinaltable	F svg
F readchar	N tableversion
F readcline	F unifymissing
F readcstring	F unpack
F readfixed2	F vhea
F readfixed4	F vmtx
F readinteger	F vorg
F readinteger1	F vvar
F readinteger1le	F woff2otf
F readinteger2	F registerpalette
F readinteger2le	F registerplugin
F readinteger3	F reorderlookups
F readinteger3le	F scriptandlanguage
F readinteger4	F setdynamics
F readinteger4le	F setfeatures
F readintegertable	T statistics
F readsignedbyte	D usedfeatures
F readstring	D svgcache
F readtag	B svgenabled
F setposition	T tables
F size	D baselines
F skip	D features
F skiplong	D featuretypes
F skipposition	D languages
F skipshort	D scripts
F writebyte	F texthandler
F writecardinal1	T vectors
F writecardinal1le	T arab
F writecardinal2	T gpos

- N curs
- N kern
- N mark
- N mkmk
- T gsub
  - N calt
  - N ccmp
  - N cswh
  - N dlig
  - N fina
  - N init
  - N isol
  - N liga
  - N medi
  - N mset
  - N rclt
  - N rlig
- N version
- T pfb
  - F loadvector
- T tfm
  - D cache
  - D features
  - N maxnestingdepth
  - N maxnestingsize
  - T readers
    - F loadpk
    - F loadtfm
    - F loadtfmvf
    - F loadvf
    - F pktopdf
    - F showpk
  - F reencode
  - F setfeatures
  - N version
- T vf
  - T combinations
  - F combine
  - T combiner
    - D commands
  - D helpers
  - D math
  - N version
  - D whatever

- F hashfeatures
- F hashinstance
- T hashmethods
  - F normal
  - F virtual
- F initializefeatures
- D loadedfonts
- N noffontsloaded
- N nofsharedfonts
- N nofsharedhashes
- N nofsharedvectors
- N privateoffset
- D privateslots
- F readanddefine
- F registerfeature
- F resetfeature
- B resolvevirtualtoo
- F scale
- F scaled
- F setfactor
- F setfeature
- F setmathparameter
- F setname
- B sharefonts
- F trytosharefont
- N version

<b>current</b>	function
<b>currentid</b>	function
<b>definers</b>	table
F addlookup	
F analyze	
F applypostprocessors	
F checkedmode	
F checkedscript	
S defaultlookup	
F define	
F getspecification	
F internal	
F loadfont	
F makespecification	
T methods <ul style="list-style-type: none"> <li>F install</li> <li>D variants</li> </ul>	
F read	



F register	
F registered	
F registerfallbackfont	
F registersplit	
F resetnullfont	
F resolve	
T resolvers	
F file	
F name	
F spec	
<b>definetypeface</b>	function
<b>dropins</b>	table
F clone	
F getshape	
F getshapes	
F nextid	
F provide	
F registerglyph	
F registerglyphs	
F swap	
F swapone	
<b>effects</b>	table
<b>encodings</b>	table
T agl	
D ctxcodes	
D extras	
D names	
D synonyms	
D unicodes	
D cache	
F is_known	
D known	
F load	
F make_unicode_vector	
D math	
N version	
<b>enhanceid</b>	function
<b>expansions</b>	data table
<b>formats</b>	data table
<b>getalternate</b>	function
<b>getindices</b>	function
<b>getkern</b>	function
<b>getmultiple</b>	function
<b>getsubstitution</b>	function

<b>getters</b>	table
T alternate	
F opentype	
T kern	
F opentype	
F type1	
F type3	
T multiple	
F opentype	
T substitution	
F opentype	
<b>goodies</b>	table
D colorschemes	
T data	
T dejavu-math	
S author	
S comment	
S copyright	
B initialized	
T mathematics	
T alternates	
T dotless	
S comment	
S feature	
N value	
T bigslots	
T parameters	
N AccentBaseDepth	
N AccentTopShiftUp	
N DelimiterPercent	
N DelimiterShortfall	
N DisplayOperatorMinHeight	
N FlattenedAccentTopShiftUp	
N FractionRuleThickness	
N NoLimitSubFactor	
N NoLimitSupFactor	
N PrimeRaiseComposedPercent	
N RadicalDegreeBottomRaisePercent	
N RadicalRuleThickness	
T tweaks	
T aftercopying	
S name	
S version	
D designsizes	

D filenames		F appendcommandtable
F getcompositions		F checkflags
T list		F checkmerge
F load		F checksteps
F prepare_features		F collectanchors
F register		F combineglyphs
F registerpostprocessor		D commands
F report		F composecharacters
T suffixes		F descriptiontoslot
<b>handlers</b>	table	F dimenfactor
<b>hashes</b>	table	F expandglyph
D characters		T extraprivates
D classes		F fontpatternhassize
D csnames		F getcoloredglyphs
D descriptions		F getdigitwidth
D dynamics		F getinstancespec
D emwidths		F getparameters
D exheights		F getprivatecharornode
D features		F getprivatenode
D identifiers		F getprivates
D italics		F getprivateslot
D lastmathids		F hasprivate
D marks		F indextoslot
D mathparameters		F mathscriptslots
D modes		F name
D originals		F nametoslot
D parameters		F newprivateslot
T processes		F prependcommands
D properties		F prependcommandtable
D quads		F privateslot
D resources		F registerglyphbox
T setdynamics		F scalecommands
T shapes		F setboxdirectly
D spaces		F setboxglyph
D spacings		F setboxglyphs
T streams		F setdigitwidth
D unicones		F setmetaglyph
D unislots		F setmetaglyphs
D variants		F splitfontpattern
D xheights		F tochar
<b>helpers</b>	table	T vfinjectors
F addextraprivate		F startcolor
F addprivate		F stopcolor
F appendcommands		T vfspecials

- T backgrounds
- T outlines
- infofont** function
- iterators** table
  - F characters
  - F descriptions
  - F glyphs
- loggers** table
  - F format
  - F onetimemessage
  - F register
  - F reportdefinedfonts
  - F reportusedfeatures
- mappings** table
  - F addtounicode
  - F fromunicode16
  - F getentry
  - F loadfile
  - F loadline
  - F makenameparser
  - D overloads
  - F reset
  - F tounicode
  - F tounicode16
  - F tounicode16sequence
- metapost** table
  - F boundingbox
  - F boxtomp
  - F draw
  - F fill
  - F glyph
  - F maxbounds
  - F paths
  - F widthline
  - F zeroline
- names** data table
- nulldata** data table
- privateoffsets** table
  - B keepnames
  - N mathbase
  - N mathextrabase
  - N textbase
  - N textextrabase
- protrusions** data table

- readers** table
  - F afm
  - F check\_lua
  - F check\_tfm
  - F lua
  - F ofm
  - F opentype
  - F otf
  - F pfb
  - D sequence
  - F tfm
  - F ttc
  - F ttf
  - F woff
- registersanitizer** function
- reserveid** function
- select** table
  - D alternatives
  - F bodyfont
  - D data
  - F default
  - D defaults
  - F definefallbackfamily
  - F definefontfamily
  - F definefontfamilypreset
  - D extras
  - F fallback
  - D fallbacks
  - F features
  - F filefallback
  - F fontdata
  - F fontfallback
  - F fontsynonym
  - F goodies
  - F mathfallback
  - D methods
  - D presets
  - F registerfallback
  - F registerfiles
  - F registerfontalternative
  - F registerfontfamily
  - F textfallback
  - F typeface
  - F typescript

F userdata  
**specifiers** table  
D contextmerged  
F contextnumber  
D contextnumbers  
D contextsetups  
F contexttostring  
F definecontext  
F mergecontext  
F presetcontext  
F registercontext  
F showcontext  
F splitcontext  
D synonyms  
D variants  
**symbols** table

T emoji  
F checked  
F resolved  
F uselibrary  
**tables** table  
**toeffect** function  
**tracers** table  
**treatments** table  
F applyfixes  
D data  
S filename  
F ignoredfile  
F report  
F trace  
**typefaces** table

# functions (context)

**dummy** function

# graphics (context)

## backgrounds table

- F fetchmultipar
- F pair
- F path
- F point

## bitmaps table

- F flush
- F new
- F placeholder
- F tocontext

## identifiers table

- F bitmap
- F jp2
- F jpg
- F png

## identify function

## synchronizers table

- F collapse
- F collect
- F extend
- F getbottom
- F getd
- F geth
- F getkind
- F getsizes
- F gettask
- F gettop
- F getw
- F getx
- F gety
- F prune

## gzip (extra lua)

**compress**    function  
**compressed** function  
**decompress** function

**load**        function  
**save**        function  
**suffix**      function

# images (context)

<b>check</b>	function		B crop	
<b>checksize</b>	function		B media	
<b>copy</b>	function		B none	
<b>create</b>	function		B trim	
<b>embed</b>	function		<b>storedata</b>	function
<b>embedfromstore</b>	function		<b>totable</b>	function
<b>fetchdata</b>	function		<b>types</b>	table
<b>keys</b>	table		N jbig2	
<b>print</b>	function		N jp2	
<b>resetdata</b>	function		N jpg	
<b>resetstore</b>	function		N none	
<b>scan</b>	function		N pdf	
<b>serialize</b>	function		N png	
<b>sizes</b>	table		N stream	
B art			<b>wrap</b>	function
B bleed				



# interactions (context)

**attachments** data table

**fields** table

- F clone
- F define
- F defineset
- F insert

**general** table

- F getidentity
- F getidentityvariable

**help** table

- F collect
- F reference
- F register

**javascripts** table

- F addtopreamble
- F code
- D codes
- F flushpreambles

D functions

D preambles

F setpreamble

F storecode

F storepreamble

F usepreamblenow

F usescripts

**linkedList**s data table

**pages** table

F setpagetransition

F setupcanvas

**references** table

F setcloseddocumentaction

F setclosepageaction

F setopendocumentaction

F setopenpageaction

**renderings** data table

# interfaces (context)

<b>arrays</b>	table	<b>namesofscanners</b>	table
<b>cachedsetups</b>	data table	<b>namespaces</b>	table
<b>cachesetup</b>	function	F define	
<b>cardinals</b>	table	F list	
<b>checkedspecification</b>	function	<b>numbers</b>	table
<b>complete</b>	data table	<b>registernamespace</b>	function
<b>constants</b>	data table	<b>registerscanner</b>	function
<b>corenamespaces</b>	data table	<b>scanners</b>	data table
<b>currentinterface</b>	string	<b>setconstant</b>	function
<b>currentresponse</b>	string	<b>setcount</b>	function
<b>definecommand</b>	function	<b>setdimen</b>	function
<b>defined</b>	function	<b>setelement</b>	function
<b>doifelsemessage</b>	function	<b>setformat</b>	function
<b>elements</b>	data table	<b>setmacro</b>	function
<b>floats</b>	table	<b>setmessage</b>	function
<b>formats</b>	data table	<b>setmessages</b>	function
<b>getmessage</b>	function	<b>settranslation</b>	function
<b>getnamespace</b>	function	<b>setupstrings</b>	data table
<b>getsetupstring</b>	function	<b>setvariable</b>	function
<b>hashedsetups</b>	data table	<b>showmessage</b>	function
<b>implement</b>	function	<b>storedscanners</b>	data table
<b>integers</b>	table	<b>tolist</b>	function
<b>interfacedcommand</b>	function	<b>translations</b>	data table
<b>interfaces</b>	table	<b>usednamespaces</b>	data table
<b>knownscanner</b>	function	<b>variables</b>	data table
<b>message</b>	function	<b>writestatus</b>	function
<b>nameofscanner</b>	function		

## io (basic lua)

<b>ask</b>	function	<b>output</b>	overloaded function
<b>bytes</b>	function	<b>pathseparator</b>	string
<b>characters</b>	function	<b>popen</b>	overloaded function
<b>close</b>	function	<b>read</b>	function
<b>copydata</b>	function	<b>readall</b>	function
<b>exists</b>	function	<b>readnumber</b>	function
<b>fileseparator</b>	string	<b>readstring</b>	function
<b>flush</b>	function	<b>savedata</b>	function
<b>input</b>	overloaded function	<b>size</b>	function
<b>lines</b>	overloaded function	<b>stderr</b>	userdata
<b>loadchunk</b>	function	<b>stdin</b>	userdata
<b>loaddata</b>	function	<b>stdout</b>	userdata
<b>loadlines</b>	function	<b>tmpfile</b>	function
<b>newreader</b>	function	<b>type</b>	function
<b>noflines</b>	function	<b>write</b>	function
<b>open</b>	overloaded function		

# job (context)

<b>comment</b>	function	D tobesaved	
<b>datasets</b>	table	<b>parwrappers</b>	table
D collected		D collected	
F extend		D tobesaved	
F getdata		<b>passes</b>	table
F setdata		F check	
D tobesaved		D collected	
<b>disablesave</b>	function	F count	
<b>embedded</b>	table	F define	
D collected		F find	
D tobesaved		F first	
<b>fileobjreferences</b>	table	F get	
D collected		F getcollected	
D tobesaved		F getdata	
<b>files</b>	table	F getfield	
D collected		F gettobesaved	
F context		F inlist	
B forcerun		F last	
F run		F list	
D tobesaved		F save	
<b>getrandomseed</b>	function	F savetagged	
<b>initialize</b>	function	D tobesaved	
<b>load</b>	function	<b>positions</b>	table
<b>loadother</b>	function	F b_column	
<b>objects</b>	table	F b_region	
D collected		F c	
F get		D collected	
F number		F column	
F page		F columnofpos	
F save		F copy	
F set		F depth	
D tobesaved		F e_column	
<b>pack</b>	boolean	F e_region	
<b>packversion</b>	number	F enhance	
<b>pagestates</b>	table	F extra	
D collected		F get	
F countervalue		F getcolumndata	
F extend		F getfree	
F realpage		F gethpos	
F realpageorder		F getpos	
F setstate		F getreserved	

F getrpos  
F getsync  
F gettobesaved  
F getvpos  
F hangafter  
F hangindent  
F height  
F hsize  
N lastx  
N lasty  
F leftskip  
F lowerleft  
F lowerright  
F markregionbox  
F n  
F onsamepage  
F overlapping  
F p  
F page  
F paragraph  
F parindent  
F position  
F r  
F region  
F registerhandlers  
F replace  
F rightskip  
F set  
F setall  
F setregionbox

F setspec  
F settobesaved  
D tobesaved  
F upperleft  
F upperright  
F used  
F whd  
F width  
F x  
F xy  
F y

**register**                   function  
**save**                    function  
**structure**               table

D collected  
T components  
T tobesaved  
T branches  
S name  
S type

**variables**               table

D checksums  
D collected  
F getchecksum  
F makechecksum  
F restore  
F save  
F setchecksum  
D tobesaved

**version**                number

## language (basic tex)

<b>clean</b>	function
<b>clearhyphenation</b>	function
<b>clearpatterns</b>	function
<b>current</b>	function
<b>gethjcode</b>	function
<b>has_language</b>	function
<b>hyphenate</b>	function
<b>hyphenation</b>	function
<b>hyphenationmin</b>	function

<b>id</b>	function
<b>new</b>	function
<b>patterns</b>	function
<b>postexhyphenchar</b>	function
<b>posthyphenchar</b>	function
<b>preexhyphenchar</b>	function
<b>prehyphenchar</b>	function
<b>sethjcode</b>	function
<b>setwordhandler</b>	function

# languages (context)

<b>addgoodiesdata</b>	function	F installmethod	
<b>addgoodiesfile</b>	function	F lasttrace	
<b>appliedoptions</b>	table	F loadpatterns	
<b>associate</b>	function	F registerexception	
<b>associated</b>	data table	F registerpattern	
<b>association</b>	function	F setfeatures	
<b>counters</b>	data table	<b>installed</b>	function
<b>current</b>	function	<b>installhandler</b>	function
<b>data</b>	data table	<b>labels</b>	table
<b>decimals</b>	data table	F define	
<b>define</b>	function	F split	
<b>explicitthyphen</b>	function	<b>loadable</b>	function
<b>flatten</b>	function	<b>loadwords</b>	function
<b>frequencies</b>	table	<b>logger</b>	table
F averagecharwidth		F report	
F getdata		<b>nofflattened</b>	function
<b>getdata</b>	function	<b>numbers</b>	data table
<b>getnumber</b>	function	<b>postexhyphenchar</b>	function
<b>goodiefiles</b>	function	<b>posthyphenchar</b>	function
<b>hjcounts</b>	table	<b>preexhyphenchar</b>	function
<b>hyphenate</b>	function	<b>prehyphenchar</b>	function
<b>hyphenators</b>	table	<b>registered</b>	data table
T dictionaries		<b>registeredactions</b>	table
D featuresets		<b>replacements</b>	table
F handler		F add	
T methods		F addlist	
F expanded		F handler	
B none		F set	
F original		<b>serializediscretionary</b>	function
F tex		<b>setexceptions</b>	function
F traditional		<b>setgoodieshandler</b>	function
F popmethod		<b>setoptions</b>	function
F pushmethod		<b>setpatterns</b>	function
F setmethod		<b>setsynonym</b>	function
F setup		<b>setwordhandler</b>	function
F showhyphenationtrace		<b>showdiscretionaries</b>	function
T traditional		<b>strippedgoodiewords</b>	function
F definefeatures		<b>tolang</b>	function
F gettrace		<b>transliteration</b>	table
F hyphenate		F exception	
F injectthyphens		F handler	

F register		<b>visualizediscretionaries</b>	function
F set		<b>words</b>	table
F use		F check	
<b>unload</b>	function	T data	
<b>urls</b>	table	F disable	
D characters		F enable	
N lefthyphenmin		T enablers	
D mapping		B enables	
B packslashes		F found	
N righthyphenmin		F load	
F setcharacters		T methods	
<b>version</b>	number	N threshold	



# layouts (context)

<b>getcanvas</b>	function	<b>status</b>	table
<b>getpagedimensions</b>	function	F isleftpage	
<b>setupcanvas</b>	function	F lefttorrightpageaction	

## lfs (extra lua)

<b>attributes</b>	overloaded function
<b>chdir</b>	overloaded function
<b>currentdir</b>	function
<b>dir</b>	overloaded function
<b>isdir</b>	overloaded function
<b>isfile</b>	overloaded function
<b>isfound</b>	function
<b>isreadabledir</b>	function
<b>isreadablefile</b>	function
<b>iswriteabledir</b>	function

<b>iswriteablefile</b>	function
<b>link</b>	overloaded function
<b>mkdir</b>	overloaded function
<b>makedirs</b>	function
<b>modification</b>	function
<b>readlink</b>	function
<b>rmdir</b>	overloaded function
<b>setexecutable</b>	function
<b>symlink</b>	function
<b>touch</b>	overloaded function

## libraries (context)

**basiclua** data table

**basictex** data table

**builtin** data table

**extralua** data table

**extratex** data table

**functions** data table

**globals** data table

# lmx (context)

<b>color</b>	function
<b>convert</b>	function
<b>convertfile</b>	function
<b>convertstring</b>	function
<b>einject</b>	function
<b>eprint</b>	function
<b>escape</b>	function
<b>finalized</b>	function
<b>finject</b>	function
<b>fprint</b>	function
<b>get</b>	function
<b>getvariables</b>	function
<b>htmfile</b>	function
<b>html</b>	table
F a	
F td	
F th	
<b>include</b>	function
<b>inherited</b>	table
S color-background-four	
S color-background-one	
S color-background-three	
S color-background-two	
S title	
<b>initialize</b>	function
<b>inject</b>	function
<b>lmxfile</b>	function

<b>loadedfile</b>	function
<b>make</b>	function
<b>new</b>	function
<b>overloaderror</b>	function
<b>popupfile</b>	function
<b>print</b>	function
<b>pv</b>	function
<b>report</b>	function
<b>reset</b>	function
<b>result</b>	function
<b>set</b>	function
<b>show</b>	function
<b>showerror</b>	function
<b>stripcss</b>	function
<b>tv</b>	function
<b>type</b>	function
<b>urlescape</b>	function
<b>variable</b>	function
<b>variables</b>	table
S color-background-blue	
S color-background-body	
S color-background-green	
S color-background-main	
S color-background-purple	
S color-background-yellow	
S title-default	

# logs (context)

<b>application</b>	function	<b>setformats</b>	function
<b>categories</b>	function	<b>setformatters</b>	function
<b>direct</b>	function	<b>setlogfile</b>	function
<b>disable</b>	function	<b>setmessenger</b>	function
<b>enable</b>	function	<b>setprocessor</b>	function
<b>finalactions</b>	function	<b>settarget</b>	function
<b>flush</b>	function	<b>settimedlog</b>	function
<b>loggingerrors</b>	function	<b>settranslations</b>	function
<b>messenger</b>	function	<b>show</b>	function
<b>new</b>	function	<b>start_page_number</b>	function
<b>newline</b>	function	<b>start_run</b>	function
<b>poplogfile</b>	function	<b>startererrorlogging</b>	function
<b>poptarget</b>	function	<b>startfilelogging</b>	function
<b>private</b>	table	<b>status</b>	function
F enablepagetiming		<b>stop_page_number</b>	function
F getpagetiming		<b>stoperrorlogging</b>	function
<b>pushlogfile</b>	function	<b>stopfilelogging</b>	function
<b>pushtarget</b>	function	<b>subdirect</b>	function
<b>registerfinalactions</b>	function	<b>subreport</b>	function
<b>report</b>	function	<b>texerrormessage</b>	function
<b>reporter</b>	function	<b>writer</b>	function
<b>resetlogfile</b>	function		

# lpdf (context)

<b>action</b>	function	<b>delayedobject</b>	function
<b>adddocumentcolorspace</b>	function	<b>destinationspecification</b>	function
<b>adddocumenttextgstate</b>	function	<b>dictionary</b>	function
<b>adddocumentpattern</b>	function	<b>docstring</b>	function
<b>adddocumentshade</b>	function	<b>epdf</b>	table
<b>addtocatalog</b>	function	F analyzefonts	
<b>addtoinfo</b>	function	F contenttotext	
<b>addtonames</b>	function	F expanded	
<b>addtopageattributes</b>	function	F getpagecontent	
<b>addtopageresources</b>	function	F getstructure	
<b>addtopagesattributes</b>	function	T image	
<b>addxmpinfo</b>	function	F close	
<b>annotationspecification</b>	function	F copy	
<b>array</b>	function	F new	
<b>attachmentsymbols</b>	function	F open	
<b>boolean</b>	function	F query	
<b>border</b>	function	F load	
<b>checkedkey</b>	function	F objecttype	
<b>checkedvalue</b>	function	F parsecontent	
<b>circularshade</b>	function	F plugin	
<b>cmykcode</b>	function	T resolvers	
<b>collectedresources</b>	function	F destinations	
<b>color</b>	function	F embeddedfiles	
<b>colorspace</b>	function	F javascripts	
<b>colorspaceconstants</b>	data table	F layers	
<b>colorspec</b>	function	F pages	
<b>colorvalue</b>	function	F structure	
<b>colorvalues</b>	function	F widgets	
<b>commentsymbols</b>	function	F stripcontent	
<b>compresslevel</b>	function	F unload	
<b>constant</b>	function	F verboseobject	
<b>copyarray</b>	function	<b>escaped</b>	function
<b>copyboolean</b>	function	<b>finalizedocument</b>	function
<b>copyconstant</b>	function	<b>finalizefonts</b>	function
<b>copydictionary</b>	function	<b>finalizepage</b>	function
<b>copyfloat</b>	function	<b>finishtransparencycode</b>	function
<b>copyinteger</b>	function	<b>flags</b>	table
<b>copynumber</b>	function	T annotations	
<b>copystring</b>	function	N AutoView	
<b>copyunicode</b>	function	N Hidden	
<b>deferredobject</b>	function	N Invisible	

N Locked		<b>fonts</b>	table
N LockedContents		F color_direct	
N NoRotate		F color_indirect	
N NoView		<b>formats</b>	data table
N NoZoom		<b>frombytes</b>	function
N Print		<b>fromeight</b>	function
N Printable		<b>frompdfdoc</b>	function
N ReadOnly		<b>fromsixteen</b>	function
N ToggleNoView		<b>getcatalog</b>	function
N auto		<b>getcompression</b>	function
N hidden		<b>getfontname</b>	function
N printable		<b>getfontobjectnumber</b>	function
T widgets		<b>getinfo</b>	function
N Comb		<b>getmatrix</b>	function
N CommitOnSelChange		<b>getnofpages</b>	function
N DoNotScroll		<b>getpageproperties</b>	function
N DoNotSpellCheck		<b>getpagereference</b>	function
N Edit		<b>getpagetags</b>	function
N FileSelect		<b>getpos</b>	function
N MultiLine		<b>gettrailerid</b>	function
N NoExport		<b>getversion</b>	function
N NoToggleToOff		<b>getxformname</b>	function
N Password		<b>graycode</b>	function
N PopUp		<b>hasmatrix</b>	function
N PushButton		<b>immediateobject</b>	function
N Radio		<b>includeimage</b>	function
N RadiosInUnison		<b>initialize</b>	function
N ReadOnly		<b>injectors</b>	table
N Required		F bitmap	
N RichText		F jp2	
N Sort		F jpg	
N file		F png	
N fixed		<b>injectxmpinfo</b>	function
N nocheck		<b>insertxmpinfo</b>	function
N protected		<b>lastreferredpage</b>	function
N readonly		<b>layerreference</b>	function
N required		<b>limited</b>	function
N sorted		<b>linearshade</b>	function
N unavailable		<b>literal</b>	function
<b>flushfonts</b>	function	<b>majorversion</b>	function
<b>flushgroup</b>	function	<b>makenametree</b>	function
<b>flushobject</b>	function	<b>minorversion</b>	function
<b>flushstreamfileobject</b>	function	<b>nofpages</b>	function
<b>flushstreamobject</b>	function	<b>null</b>	function

<b>number</b>	function	<b>usedcharacters</b>	table
<b>object</b>	function	<b>usedfontnames</b>	table
<b>objectcompresslevel</b>	function	N dejavusansmonoboldttf-1	
<b>pagereference</b>	function	<b>usedfontobjects</b>	table
<b>patternstream</b>	function	N dejavusansmonoboldttf-1	
<b>pdfcolor</b>	function	<b>usedfontstreams</b>	table
<b>pdftimestamp</b>	function	T dejavusansmonoboldttf-1	
<b>print</b>	function	T characters	
<b>procset</b>	function	T descriptions	
<b>protectresources</b>	boolean	T fonts	
<b>rectangle</b>	function	T goodies	
<b>reference</b>	function	S original	
<b>registerannotation</b>	function	T parameters	
<b>registerdestination</b>	function	N ascender	
<b>registerdocumentfinalizer</b>	function	N descender	
<b>registerfont</b>	function	N designsize	
<b>registerinitializer</b>	function	T expansion	
<b>registerpagefinalizer</b>	function	N shrink	
<b>registerpattern</b>	function	N step	
<b>reserveobject</b>	function	N stretch	
<b>rgbcode</b>	function	N extendfactor	
<b>rotationcm</b>	function	N extrafactor	
<b>setcompression</b>	function	N extraspace	
<b>setencryption</b>	function	N factor	
<b>setincludecidset</b>	function	N forcedsize	
<b>setpageorder</b>	function	N hfactor	
<b>setpagestate</b>	function	N mathsize	
<b>setpagetag</b>	function	N maxsize	
<b>setversion</b>	function	N minsize	
<b>sharedobject</b>	function	N mode	
<b>shareobject</b>	function	N quad	
<b>shareobjectreference</b>	function	N scaledpoints	
<b>spotcode</b>	function	N size	
<b>stream</b>	function	N slant	
<b>string</b>	function	N slantfactor	
<b>toeight</b>	function	N space	
<b>topdfdoc</b>	function	N spaceshrink	
<b>tosixteen</b>	function	N spacestretch	
<b>transparency</b>	function	N squeezefactor	
<b>transparencycode</b>	function	N textsize	
<b>transparencygroups</b>	table	N units	
B none		N vfactor	
<b>transparencyvalue</b>	function	N width	
<b>unicode</b>	function	N xheight	



T properties	T arab
S filename	B dflt
B finalized	T gsub
S fontname	T anum
S format	T arab
S fullname	B dflt
S hash	B urd
B hasmath	T camelcasing
N id	T *
S language	B *
S mode	T char-ligatures
S name	T *
S psname	B *
S script	T collapse
S sharedwith	T *
N subfont	B *
S writingmode	T compat-ligatures
T resources	T *
T alreadydone	B *
T classes	T dlig
T duplicates	T latn
T features	B dflt
T gpos	B ism
T mark	B ksm
T arab	B lsm
B dflt	B mol
T cyrl	B nsm
B dflt	B rom
B srb	B sks
T grek	B ssm
B dflt	T locl
T lao	T cyrl
B dflt	B srb
T latn	T latn
B dflt	B ism
B ism	B ksm
B ksm	B lsm
B lsm	B nsm
B mol	B sks
B nsm	B ssm
B rom	T lowercasing
B sks	T *
B ssm	B *
T mkmk	T primes

T *	N Ccircumflex
B *	N Cdotaccent
T tlig	N Chi
T *	N Circumflex
B *	N D
T trep	N Dcaron
T *	N Dcroat
B *	N Delta
T uppercasing	N Dieresis
T *	N E
B *	N Eacute
S filename	N Ebreve
S foundfilename	N Ecaron
T foundtables	N Ecircumflex
T markclasses	N Edieresis
T marks	N Edotaccent
T marksets	N Egrave
N private	N Emacron
T sequences	N Eng
T sublookups	N Eng.alt
T unicodes	N Eogonek
N .null	N Epsilon
N A	N Epsilontonos
N AE	N Eta
N AEacute	N Etatonos
N Aacute	N Eth
N Abreve	N Euro
N Acircumflex	N F
N Acute	N G
N Adieresis	N Gamma
N Agrave	N Gbreve
N Alpha	N Gcaron
N Alphanotos	N Gcircumflex
N Amacron	N Gcommaaccent
N Aogonek	N Gdotaccent
N Aring	N Grave
N Atilde	N H
N B	N Hbar
N Beta	N Hcircumflex
N C	N I
N Cacute	N IJ
N Caron	N Iacute
N Ccaron	N Ibreve
N Ccedilla	N Icircumflex

N Idieresis	N Oslashacute
N Idotaccent	N Otilde
N Igrave	N P
N Imacron	N Phi
N Iogonek	N Pi
N Iota	N Psi
N Iotadieresis	N Q
N Iotatonos	N R
N Itilde	N Racute
N J	N Rcaron
N Jcircumflex	N Rcommaaccent
N K	N Rho
N Kappa	N S
N Kcommaaccent	N Sacute
N L	N Scaron
N Lacute	N Scedilla
N Lambda	N Scircumflex
N Lcaron	N Scommaaccent
N Lcommaaccent	N Sigma
N Ldot	N T
N Lslash	N Tau
N M	N Tbar
N Mu	N Tcaron
N N	N Tcommaaccent
N Nacute	N Theta
N Ncaron	N Thorn
N Ncommaaccent	N Tilde
N Ntilde	N U
N Nu	N Ugrave
N O	N Uhorn
N OE	N Uhungarumlaut
N Oacute	N Umacron
N Obreve	N Uogonek
N Ocircumflex	N Upsilon
N Odieresis	N Upsilon1
N Ograve	N Upsilondieresis
N Ohorn	N Upsilontonos
N Ohungarumlaut	N Uring
N Omacron	N Utilde
N Omega	N V
N Omegatonos	N W
N Omicron	N Wacute
N Omicrontonos	N Wcircumflex
N Oslash	N Wdieresis

N Wgrave	N arrowdblleft
N X	N arrowdblright
N Xi	N arrowdblup
N Y	N arrowdown
N Yacute	N arrowleft
N Ycircumflex	N arrowright
N Ydieresis	N arrowup
N Ygrave	N arrowupdn
N Z	N arrowupdnbse
N Zacute	N asciicircum
N Zcaron	N asciitilde
N Zdotaccent	N asterisk
N Zeta	N asteriskmath
N a	N at
N aacute	N atilde
N abreve	N b
N acircumflex	N backslash
N acute	N bar
N acutecomb	N beta
N adieresis	N block
N ae	N braceleft
N aeacute	N braceright
N agrave	N bracketleft
N alpha	N bracketright
N alphanos	N breve
N amacron	N brokenbar
N ampersand	N bullet
N angle	N c
N anoteleia	N cacute
N aogonek	N caron
N approxequal	N carriagereturn
N arabic_2dots	N ccaron
N arabic_2dots_a	N ccedilla
N arabic_3dots	N ccircumflex
N arabic_3dots_a	N cdotaccent
N arabic_4dots	N cedilla
N arabic_dot	N cent
N arabic_gaf_bar	N chi
N arabic_gaf_bar_a	N circle
N arabic_ring	N circlemultiply
N aring	N circleplus
N arrowboth	N circumflex
N arrowdblboth	N club
N arrowdbldown	N colon

N colonmonetary	N epsilon
N comma	N epsilonontonos
N congruent	N equal
N copyright	N equivalence
N currency	N estimated
N d	N eta
N dagger	N etatonos
N daggerdbl	N eth
N dcaron	N exclam
N dcroat	N exclamdbl
N degree	N exclamdown
N delta	N existential
N diaeresis.symbols	N f
N diamond	N female
N dieresis	N fi
N dieresistonos	N figuredash
N divide	N filledbox
N dkshade	N filledrect
N dLLtcaron	N five
N dnblock	N fiveeighths
N dollar	N fl
N dong	N florin
N dotaccent	N four
N dotbelowcomb	N fractionslash
N dotlessi	N franc
N dotlessj	N g
N dotmath	N gamma
N e	N gbreve
N eacute	N gcaron
N ebreve	N gcircumflex
N ecaron	N gcommaaccent
N ecircumflex	N gdotaccent
N edieresis	N germandbls
N edotaccent	N gradient
N egrave	N grave
N eight	N gravecomb
N element	N greater
N ellipsis	N greaterequal
N emacron	N guillemotleft
N emdash	N guillemotright
N emptyset	N guilsinglleft
N endash	N guilsinglright
N eng	N h
N eogonek	N hbar

N hcircumflex	N lira
N heart	N logicaland
N hookabovecomb	N logicalnot
N house	N logicalor
N hungarumlaut	N longs
N hyphen	N lozenge
N i	N lslash
N iacute	N ltshade
N ibreve	N m
N icircumflex	N macron
N idieresis	N male
N igrave	N minus
N ij	N minute
N imacron	N mu
N infinity	N multiply
N integral	N musicalnote
N integralbt	N musicalnotedbl
N integraltp	N n
N intersection	N nacute
N invbullet	N napostrophe
N invcircle	N ncaron
N invsmileface	N ncommaaccent
N iogonek	N nine
N iota	N nonbreakingspace
N iotadieresis	N nonmarkingreturn
N iotadieresis-tonos	N notdef
N iotatonos	N notelement
N itilde	N notequal
N j	N notsubset
N jcircumflex	N ntilde
N jot	N nu
N k	N numbersign
N kappa	N o
N kcommaaccent	N oacute
N kgreenlandic	N obreve
N l	N ocircumflex
N lacute	N odieresis
N lambda	N oe
N lcaron	N ogonek
N lcommaaccent	N ograve
N ldot	N ohorn
N less	N ohungarumlaut
N lessequal	N omacron
N lfblock	N omega

N omega1	N quotedblright
N omegatonos	N quoteleft
N omicron	N quotereversed
N omicrontonos	N quoteright
N one	N quotesinglbase
N oneeighth	N quotesingle
N onehalf	N r
N onequarter	N racute
N onesuperior	N radical
N onethird	N rcaron
N openbullet	N rcommaaccent
N ordfeminine	N reflexsubset
N ordmasculine	N reflexsuperset
N orthogonal	N registered
N oslash	N revlogicalnot
N oslashacute	N rho
N otilde	N ring
N p	N rtblock
N paragraph	N s
N parenleft	N sacute
N parenright	N scaron
N partialdiff	N scedilla
N percent	N scircumflex
N period	N scommaaccent
N periodcentered	N second
N perpendicular	N section
N perthousand	N semicolon
N peseta	N seven
N phi	N seveneighths
N phil	N sfthyphen
N pi	N shade
N plus	N sigma
N plusminus	N sigma1
N product	N similar
N propersubset	N six
N propersuperset	N slash
N proportional	N smileface
N psi	N space
N q	N spade
N question	N sterling
N questiondown	N suchthat
N quotedbl	N summation
N quotedblbase	N sun
N quotedblleft	N t

N tau  
N tbar  
N tcaron  
N tcommaaccent  
N therefore  
N theta  
N theta1  
N thinquestion  
N thorn  
N three  
N threeeighths  
N threequarters  
N threesuperior  
N tilde  
N tildecomb  
N tonos  
N trademark  
N triagdn  
N triaglf  
N triagrt  
N triagup  
N two  
N twosuperior  
N twothirds  
N u  
N ugrave  
N uhorn  
N uhungarumlaut  
N umacron  
N underbar  
N underbar.small  
N underbar.wide  
N underscore  
N underscoredbl  
N union  
N universal  
N uogonek  
N upblock  
N upsilon  
N upsilondieresis  
N upsilondieresis-tonos  
N upsilontonos  
N uring  
N utilde

N v  
N w  
N wacute  
N wcircumflex  
N wdieresis  
N wgrave  
N x  
N xi  
N y  
N yacute  
N ycircumflex  
N ydieresis  
N yen  
N ygrave  
N z  
N zacute  
N zcaron  
N zdotaccent  
N zero  
N zeta  
S version  
T shared  
T dynamics  
T features  
B analyze  
B checkmarks  
B devanagari  
B dummies  
B extensions  
B extrafeatures  
B extraprivates  
B features  
S indic  
B mathrules  
S mode  
N number  
B spacekern  
B visualspace  
T processes  
T rawdata  
S cache\_uuid  
N cache\_version  
B compacted  
B condensed



S creator	N maxextent
T descriptions	N minbottomsidebearing
B expanded	N mintopsidebearing
S format	N version
T goodies	S weight
T lookuphash	S width
T metadata	N nofglyphs
N ascender	N private
N averagewidth	T properties
T boundingbox	B hascolor
N defaultvheight	B hasitalics
N descender	B hasspacekerns
S family	N size
S familyname	N tableversion
S fontname	N time
N fstyle	T specification
S fullname	S cs
T horizontalmetrics	S detail
N ascender	S fallbacks
N descender	T features
N linegap	T normal
N maxadvanceheight	B features
N maxadvancewidth	S mode
N maxextent	N number
N minbottomsidebearing	S filename
N mintopsidebearing	S forced
N version	S forcedname
N italicangle	B global
B monospaced	S goodies
S panoseweight	S hash
S panosewidth	N id
N pfmweight	S lookup
N pfmwidth	N mathsize
S subfamily	S method
S subfamilyname	S name
N subfontindex	S resolved
N units	N scalemode
S version	N size
T verticalmetrics	S source
N ascender	S specification
N descender	N textsize
N linegap	T unscaled
N maxadvanceheight	N cache_version
N maxadvancewidth	T changed

T characters  
 T descriptions  
 T mathparameters  
 T parameters  
   N ascender  
   N charwidth  
   N descender  
   N designsized  
   N extraspace  
   N italicangle  
   N maxsize  
   N minsize  
   N quad  
   N slant  
   N space  
   N spaceshrink  
   N spacestretch  
   N units  
   N vheight  
   N xheight

T properties  
   S filename  
   S fontname  
   S format  
   S fullname  
   B hasmath  
   N id  
   S mode  
   B monospaced  
   S name  
   N private  
   S psname  
   B setitalics  
   S space  
   N subfont

S writingmode

**usedindices**

T dejavusansmonoboldttf-1

**verbose**

table

function

## lpeg (basic lua)

<b>B</b>	function	<b>firstofsplit</b>	function
<b>C</b>	function	<b>frontstripper</b>	function
<b>Carg</b>	function	<b>instringchecker</b>	function
<b>Cb</b>	function	<b>is_lpeg</b>	function
<b>Cc</b>	function	<b>keeper</b>	function
<b>Cf</b>	function	<b>locale</b>	function
<b>Cg</b>	function	<b>match</b>	function
<b>Cmt</b>	function	<b>oneof</b>	function
<b>Cp</b>	function	<b>patterns</b>	data table
<b>Cs</b>	function	<b>pcode</b>	function
<b>Ct</b>	function	<b>print</b>	function
<b>P</b>	function	<b>ptree</b>	function
<b>R</b>	function	<b>replacer</b>	function
<b>S</b>	function	<b>secondofsplit</b>	function
<b>UP</b>	function	<b>setmaxstack</b>	function
<b>UR</b>	function	<b>setutfcasers</b>	function
<b>US</b>	function	<b>split</b>	function
<b>V</b>	function	<b>splitat</b>	function
<b>afterprefix</b>	function	<b>splitter</b>	function
<b>anywhere</b>	function	<b>stripper</b>	function
<b>append</b>	function	<b>times</b>	function
<b>balancer</b>	function	<b>tsplitat</b>	function
<b>beforesuffix</b>	function	<b>tsplitter</b>	function
<b>checkedsplit</b>	function	<b>type</b>	function
<b>containsws</b>	function	<b>utfchartabletopattern</b>	function
<b>counter</b>	function	<b>utfreplacer</b>	function
<b>endstripper</b>	function	<b>version</b>	function
<b>finder</b>	function		

# lua (basic tex)

<b>bytecode</b>	<b>table</b>	<b>lastbytecode</b>	<b>number</b>
<b>bytedata</b>	<b>data table</b>	<b>macros</b>	<b>table</b>
<b>bytedone</b>	<b>table</b>	<b>B enabled</b>	
<b>callbytecode</b>	<b>function</b>	<b>F loaded</b>	
<b>delay</b>	<b>function</b>	<b>F required</b>	
<b>finalizeinitex</b>	<b>function</b>	<b>F reset</b>	
<b>firstbytecode</b>	<b>number</b>	<b>F resolvestring</b>	
<b>flush</b>	<b>function</b>	<b>F resolving</b>	
<b>flushdelayed</b>	<b>function</b>	<b>F showdefinitions</b>	
<b>get_functions_table</b>	<b>function</b>	<b>messages</b>	<b>data table</b>
<b>getbytecode</b>	<b>function</b>	<b>newindex</b>	<b>function</b>
<b>getcurrenttime</b>	<b>function</b>	<b>newtable</b>	<b>function</b>
<b>getdebuginfo</b>	<b>function</b>	<b>numbers</b>	<b>data table</b>
<b>getexitcode</b>	<b>function</b>	<b>registercode</b>	<b>function</b>
<b>getfunctionstable</b>	<b>overloaded function</b>	<b>registeredcodes</b>	<b>function</b>
<b>getpreciseseconds</b>	<b>function</b>	<b>registerinitexfinalizer</b>	<b>function</b>
<b>getpreciseticks</b>	<b>function</b>	<b>registername</b>	<b>function</b>
<b>getruntime</b>	<b>function</b>	<b>setbytecode</b>	<b>function</b>
<b>getstacktop</b>	<b>function</b>	<b>setexitcode</b>	<b>function</b>
<b>getstartupfile</b>	<b>function</b>	<b>startupfile</b>	<b>string</b>
<b>getversion</b>	<b>function</b>	<b>version</b>	<b>string</b>

## luac (context)

**inspect** function  
**print** function

# luatex (context)

<b>abort</b>	function	F enable	
<b>cleanup</b>	function	F finish	
<b>cleanuptempfiles</b>	function	F pause	
<b>currentfile</b>	function	F popline	
<b>poprunstate</b>	function	F pushline	
<b>pushrunstate</b>	function	F registerdisabler	
<b>registerdumpactions</b>	function	F registerenabler	
<b>registerpageactions</b>	function	F resetfilename	
<b>registerstartactions</b>	function	F resume	
<b>registerstopactions</b>	function	F setfilename	
<b>registertempfile</b>	function	F setup	
<b>starttime</b>	number	F start	
<b>synctex</b>	table	F stop	
F blockfilename		F wrapup	
F collect		<b>wrapup</b>	function
F disable			

# lxml (context)

<b>addindex</b>	function	<b>first</b>	function
<b>all</b>	function	<b>flush</b>	function
<b>applyfunction</b>	function	<b>flushlinewise</b>	function
<b>applyselectors</b>	function	<b>flushsetups</b>	function
<b>att</b>	function	<b>flushspacewise</b>	function
<b>attribute</b>	function	<b>get_id</b>	function
<b>badinclusions</b>	function	<b>getid</b>	function
<b>chainattribute</b>	function	<b>getindex</b>	function
<b>checkindex</b>	function	<b>id</b>	function
<b>collected</b>	function	<b>idsplitter</b>	userdata
<b>command</b>	function	<b>ifatt</b>	function
<b>concat</b>	function	<b>ifattempty</b>	function
<b>concatrange</b>	function	<b>include</b>	function
<b>content</b>	function	<b>inclusion</b>	function
<b>context</b>	function	<b>inclusions</b>	function
<b>convert</b>	function	<b>index</b>	function
<b>count</b>	function	<b>inlineverbatimim</b>	function
<b>delete</b>	function	<b>installsetup</b>	function
<b>depth</b>	function	<b>last</b>	function
<b>direct</b>	function	<b>lastatt</b>	function
<b>directives</b>	table	<b>lastmatch</b>	function
F after		<b>lastpar</b>	function
F before		<b>load</b>	function
F handle		<b>loadbuffer</b>	function
F load		<b>loaddata</b>	function
F setup		<b>loaded</b>	table
<b>displayverbatimim</b>	function	<b>main</b>	function
<b>doif</b>	function	<b>match</b>	function
<b>doifelse</b>	function	<b>name</b>	function
<b>doifelseempty</b>	function	<b>namespace</b>	function
<b>doifelsetext</b>	function	<b>nonspace</b>	function
<b>doifempty</b>	function	<b>par</b>	function
<b>doifnot</b>	function	<b>param</b>	function
<b>doifnotempty</b>	function	<b>parameter</b>	function
<b>doifnottext</b>	function	<b>path</b>	function
<b>doiftext</b>	function	<b>popmatch</b>	function
<b>element</b>	function	<b>pos</b>	function
<b>elements</b>	function	<b>position</b>	function
<b>entities</b>	data table	<b>pure</b>	function
<b>filter</b>	function	<b>pushmatch</b>	function
<b>filterlist</b>	function	<b>raw</b>	function

<b>rawroot</b>	function
<b>rawtex</b>	function
<b>refatt</b>	function
<b>register</b>	function
<b>registerentity</b>	function
<b>removesetup</b>	function
<b>replace</b>	function
<b>resetcdata</b>	function
<b>resetsetups</b>	function
<b>resolvedentity</b>	function
<b>root</b>	function
<b>save</b>	function
<b>serialize</b>	function
<b>setaction</b>	function
<b>setatt</b>	function
<b>setattribute</b>	function
<b>setcdata</b>	function
<b>setcommandtonone</b>	function
<b>setcommandtotext</b>	function
<b>setpar</b>	function
<b>setparam</b>	function
<b>setparameter</b>	function
<b>setsetup</b>	function
<b>snippet</b>	function

<b>sorters</b>	table
F add	
F compare	
F flush	
F reset	
F show	
F sort	
<b>splitid</b>	function
<b>startraw</b>	function
<b>startunesescaped</b>	function
<b>stopraw</b>	function
<b>stopunesescaped</b>	function
<b>store</b>	function
<b>strip</b>	function
<b>stripped</b>	function
<b>tag</b>	function
<b>text</b>	function
<b>tobuffer</b>	function
<b>tofile</b>	function
<b>toparameters</b>	function
<b>toverbatim</b>	function
<b>verbatim</b>	function
<b>withindex</b>	function
<b>xmltexhandler</b>	data table



## math (basic lua)

<b>abs</b>	function	<b>min</b>	function
<b>acos</b>	function	<b>mininteger</b>	number
<b>asin</b>	function	<b>mod</b>	function
<b>atan</b>	function	<b>modf</b>	function
<b>atan2</b>	function	<b>odd</b>	function
<b>ceil</b>	function	<b>pi</b>	number
<b>ceiling</b>	function	<b>pow</b>	function
<b>cos</b>	function	<b>rad</b>	function
<b>cosd</b>	function	<b>random</b>	overloaded function
<b>cosh</b>	function	<b>randomseed</b>	function
<b>deg</b>	function	<b>round</b>	function
<b>div</b>	function	<b>setrandomseedi</b>	function
<b>even</b>	function	<b>sin</b>	function
<b>exp</b>	function	<b>sind</b>	function
<b>floor</b>	function	<b>sinh</b>	function
<b>fmod</b>	function	<b>sqrt</b>	function
<b>huge</b>	number	<b>tan</b>	function
<b>initialseed</b>	number	<b>tand</b>	function
<b>ldexp</b>	function	<b>tanh</b>	function
<b>log</b>	function	<b>tointeger</b>	function
<b>log10</b>	function	<b>type</b>	function
<b>max</b>	function	<b>ult</b>	function
<b>maxinteger</b>	number		

# mathematics (context)

<b>addfallbacks</b>	function	<b>getboth</b>	function
<b>addvariant</b>	function	<b>getitalics</b>	function
<b>alphabets</b>	data table	<b>getstyle</b>	function
<b>alternatives</b>	data table	<b>horizontalcode</b>	function
<b>beforepassingfonttotex</b>	function	<b>initializeparameters</b>	function
<b>big</b>	function	<b>makefont</b>	function
<b>boldmap</b>	data table	<b>mapremap</b>	data table
<b>categories</b>	table	<b>overloadparameters</b>	function
D functions		<b>preset</b>	function
<b>charactersets</b>	data table	<b>presets</b>	table
<b>checkaccentbaseheight</b>	function	T less	
<b>classes</b>	data table	T more	
<b>classnames</b>	data table	T zero	
<b>codes</b>	data table	<b>privatebase</b>	number
<b>collected</b>	function	<b>registerfallbackid</b>	function
<b>define</b>	function	<b>registersimplematrix</b>	function
<b>dictionaries</b>	table	<b>remapalphabets</b>	function
D data		<b>renderings</b>	table
D defaults		D mappings	
D groups		D numbers	
F groupset		D sets	
F groupsetgroup		<b>renderset</b>	function
D names		<b>resetattributes</b>	function
F registercharacter		<b>resetitalics</b>	function
F registergroup		<b>resolvefallbacks</b>	function
F registergroupset		<b>scaleparameters</b>	function
D sets		<b>setitalics</b>	function
D variants		<b>sets</b>	data table
<b>dimensions</b>	function	<b>setsnapping</b>	function
<b>extensiblecode</b>	function	<b>setvariant</b>	function
<b>extensibles</b>	data table	<b>startcollecting</b>	function
<b>extrabase</b>	number	<b>stopcollecting</b>	function
<b>extras</b>	table	<b>styles</b>	data table
F add		<b>syncboth</b>	function
F copy		<b>syncname</b>	function
<b>fallbacks</b>	table	<b>syncstyle</b>	function
F apply		<b>toengineclass</b>	function
F install		<b>toname</b>	function
<b>fallbackstyleattr</b>	function	<b>tostyle</b>	function
<b>finishfallbacks</b>	function	<b>tweakaftercopyingfont</b>	function
<b>gaps</b>	data table	<b>tweakbeforecopyingfont</b>	function

## tweaks

F accentdimensions  
F action  
F addactuarian  
F addarrows  
F addbars  
F addequals  
F addfourier  
F addparts  
F addprivates  
F addrules  
F addscripts  
F checkspacing  
F copyaccents  
F dimensions  
F extendaccents  
F fixaccents  
F fixanchors  
F fixellipses  
F fixprimes  
F fixradicals  
F fixslashes  
F kernpairs  
F kerns  
F margins  
F message  
F replace

## table

F replacements

F staircase

T subsets

T acenorsuvxz

T bhklt

T d

T f

T gjqy

T i

T mw

T p

F substitute

F substitutes

F variant

F variants

F version

F wipeanchors

F wipecues

F wipeitalics

F wipevariants

**utfmathaccent**

**utfmathclass**

**utfmathcommand**

**utfmathfiller**

**utfmathstretch**

**virtualize**

**virtualized**

function

function

function

function

function

function

data table

## md5 (extra lua)

<b>HEX</b>	function
<b>dec</b>	function
<b>hex</b>	function

<b>sum</b>	function
<b>sumHEXA</b>	function
<b>sumhexa</b>	function

# metapost (context)

<b>checkformat</b>	function	N nullary
<b>checktracingonline</b>	function	N numeric
<b>cm</b>	function	N of
<b>codes</b>	table	N ofbinary
N addto		N onlyset
N ampersand		N parametertype
N and		N pathjoin
N assignment		N plusorminus
N atleast		N primarybinary
N begingroup		N primarydef
N btex		N property
N capsule		N protection
N colon		N relax
N comma		N repeatloop
N controls		N rightbrace
N curl		N rightbracket
N cycle		N rightdelimiter
N definedmacro		N runscript
N delimiters		N save
N endgroup		N scantokens
N equals		N secondarybinary
N etex		N secondarydef
N everyjob		N semicolon
N exittest		N setbounds
N expandafter		N shipout
N fiorelse		N show
N if		N slash
N input		N step
N interim		N stop
N internal		N str
N iteration		N string
N leftbrace		N tag
N leftbracket		N tension
N leftdelimiter		N tertiarybinary
N let		N tertiarydef
N macrodef		N thingstoadd
N macrospecial		N to
N maketext		N typename
N message		N unary
N mode		N undefinedcs
N newinternal		N until

N void		<b>gettext</b>	function
N with		<b>gettolerance</b>	function
N within		<b>graphic</b>	function
N write		<b>graphic_base_pass</b>	function
<b>colorinitializer</b>	function	<b>includesvgbuffer</b>	function
<b>convert</b>	function	<b>includesvgfile</b>	function
<b>currentmpx</b>	function	<b>installplugin</b>	function
<b>currentmpxstatus</b>	function	<b>isobject</b>	function
<b>defaultformat</b>	string	<b>knownparameters</b>	table
<b>defaultinstance</b>	string	<b>lastlog</b>	string
<b>defaultmethod</b>	string	<b>load</b>	function
<b>directrun</b>	function	<b>maketext</b>	function
<b>escaped</b>	function	<b>metafonts</b>	table
<b>exectime</b>	table	<b>metafun</b>	table
<b>extensiondata</b>	data table	F interpolate	
<b>filterclippath</b>	function	F topath	
<b>flush</b>	function	<b>mptopdf</b>	table
<b>flushers</b>	table	F convertmpstopdf	
T pdf		N nofconverted	
F flushfigure		<b>n</b>	number
F startfigure		<b>newlogger</b>	function
F stopfigure		<b>nofruns</b>	number
F textfigure		<b>nofscriptruns</b>	function
F tocomment		<b>nvformat</b>	function
<b>flushnormalpath</b>	function	<b>pdfliterals</b>	function
<b>fonts</b>	table	<b>pluginactions</b>	function
F define		<b>popformat</b>	function
<b>format_number</b>	function	<b>popscriptrunner</b>	function
<b>format_string</b>	function	<b>popvariable</b>	function
<b>formatnumber</b>	function	<b>popvariables</b>	function
<b>getbendtolerance</b>	function	<b>preparetexttextsdata</b>	function
<b>getbuffer</b>	function	<b>process</b>	function
<b>getclippath</b>	function	<b>processing</b>	function
<b>getextensions</b>	function	<b>processplugins</b>	function
<b>getextradata</b>	function	<b>properties</b>	table
<b>gethashentries</b>	function	<b>pushformat</b>	function
<b>getinstancenames</b>	function	<b>pushscriptrunner</b>	function
<b>getjobdata</b>	function	<b>pushvariable</b>	function
<b>getmovetolerance</b>	function	<b>pushvariables</b>	function
<b>getparameter</b>	function	<b>reducetogray</b>	boolean
<b>getparameterpreset</b>	function	<b>registerdirect</b>	function
<b>getparameterset</b>	function	<b>registerscript</b>	function
<b>getrecord</b>	function	<b>registertokens</b>	function
<b>getstatistics</b>	function	<b>remappedtext</b>	function

<b>remaptext</b>	function	<b>svgglyphtomp</b>	function
<b>reporterror</b>	function	<b>svgshapestomp</b>	function
<b>reportsvgfonts</b>	function	<b>svgshapestopdf</b>	function
<b>reset</b>	function	<b>svgsplitcolor</b>	function
<b>resetlastlog</b>	function	<b>svgtomp</b>	function
<b>resetplugins</b>	function	<b>svgtopdf</b>	function
<b>run</b>	function	<b>sxsy</b>	function
<b>runinternal</b>	function	<b>tex</b>	table
<b>runscript</b>	function	F get	
<b>scanparameters</b>	function	F reset	
<b>scripterror</b>	function	F set	
<b>scriptindex</b>	function	F setfrombuffer	
<b>setbendtolerance</b>	function	<b>texerrors</b>	boolean
<b>setbuffer</b>	function	<b>texexp</b>	function
<b>setextensions</b>	function	<b>theclippath</b>	function
<b>setlogging</b>	function	<b>tographic</b>	function
<b>setmovetolerance</b>	function	<b>totable</b>	function
<b>setoutercolor</b>	function	<b>types</b>	table
<b>setparameterset</b>	function	N boolean	
<b>setrecord</b>	function	N cmykcolor	
<b>settext</b>	function	N color	
<b>settolerance</b>	function	N dependent	
<b>setvariable</b>	function	N independent	
<b>showlog</b>	boolean	N known	
<b>showsvgpage</b>	function	N nep	
<b>simple</b>	function	N numeric	
<b>splitprescript</b>	function	N pair	
<b>startgraphic</b>	function	N path	
<b>startsvghashing</b>	function	N pen	
<b>stopgraphic</b>	function	N picture	
<b>stopsvghashing</b>	function	N protodependent	
<b>svformat</b>	function	N string	
<b>svgcolorremapper</b>	function	N structured	
<b>svgfactors</b>	table	N suffixedmacro	
N %		N tokenlist	
N bp		N transform	
N cm		N unknownboolean	
N em		N unknownnep	
N ex		N unknownpath	
N in		N unknownpen	
N mm		N unknownpicture	
N pc		N unknownstring	
N pt		N unsuffixedmacro	
N px		N vacuum	

<b>typesvgpage</b>	function	<b>variables</b>	table
<b>unload</b>	function		
<b>untagvariable</b>	function		



## mime (extra lua)

**b64** function

**decode** function

**decodet** table

F base64

F quoted-printable

**dot** function

**encode** function

**encodet** table

F base64

F quoted-printable

**eol** function

**normalize** function

**qp** function

**qpwrp** function

**report** function

**stuff** function

**unb64** function

**unqp** function

**wrap** function

**wrapt** table

F base64

F default

F quoted-printable

F text

**wrp** function

# mp (context)

<b>autoinject</b>	function	<b>fprint</b>	function
<b>aux</b>	function	<b>get</b>	table
F boolean		F hashentry	
F color		<b>graphformat</b>	function
F direct		<b>inject</b>	function
F draw		F boolean	
F fill		F cmykcolor	
F flush		F color	
F fprint		F integer	
F integer		F number	
F number		F numeric	
F numeric		F pair	
F pair		F path	
F pairpoints		F pt	
F path		F quadruplet	
F pathpoints		F string	
F points		F transform	
F print		F triplet	
F quadruple		F whatever	
F quadruplepoints		F whd	
F quoted		F xy	
F size		<b>integer</b>	function
F string		<b>lmt_color_functions</b>	table
F transform		F shade	
F triplet		F step	
F tripletpoints		<b>lmt_contours_bitmap_get</b>	function
F vprint		<b>lmt_contours_bitmap_set</b>	function
<b>boolean</b>	function	<b>lmt_contours_cleanup</b>	function
<b>cleaned</b>	function	<b>lmt_contours_color</b>	function
<b>color</b>	function	<b>lmt_contours_edge_get_band</b>	function
<b>dataset</b>	function	<b>lmt_contours_edge_get_cell</b>	function
<b>datasets</b>	function	<b>lmt_contours_edge_paths</b>	function
F load		<b>lmt_contours_edge_set</b>	function
<b>direct</b>	function	<b>lmt_contours_edge_set_by_band</b>	function
<b>draw</b>	function	<b>lmt_contours_edge_set_by_cell</b>	function
<b>expandtex</b>	function	<b>lmt_contours_format</b>	function
<b>fill</b>	function	<b>lmt_contours_function</b>	function
<b>flatten</b>	function	<b>lmt_contours_maxmean</b>	function
<b>flush</b>	function	<b>lmt_contours_maxz</b>	function
<b>format</b>	function	<b>lmt_contours_minmean</b>	function
<b>formatted</b>	function	<b>lmt_contours_minz</b>	function

<code>lmt_contours_nofvalues</code>	function	<code>n</code>	function
<code>lmt_contours_nx</code>	function	<code>number</code>	function
<code>lmt_contours_ny</code>	function	<code>numeric</code>	function
<code>lmt_contours_range</code>	function	<code>pair</code>	function
<code>lmt_contours_shade_paths</code>	function	<code>pairpoints</code>	function
<code>lmt_contours_shade_set</code>	function	<code>path</code>	function
<code>lmt_contours_shape_paths</code>	function	<code>pathpoints</code>	function
<code>lmt_contours_start</code>	function	<code>points</code>	function
<code>lmt_contours_stop</code>	function	<code>print</code>	function
<code>lmt_contours_value</code>	function	<code>F boolean</code>	
<code>lmt_contours_xrange</code>	function	<code>F color</code>	
<code>lmt_contours_yrange</code>	function	<code>F direct</code>	
<code>lmt_function_x</code>	function	<code>F draw</code>	
<code>lmt_mesh_set</code>	function	<code>F fill</code>	
<code>lmt_mesh_update</code>	function	<code>F flush</code>	
<code>lmt_poisson_generate</code>	function	<code>F fprint</code>	
<code>lmt_surface_do</code>	function	<code>F integer</code>	
<code>lmt_svg_include</code>	function	<code>F number</code>	
<code>mf_blob_add</code>	function	<code>F numeric</code>	
<code>mf_blob_dimensions</code>	function	<code>F pair</code>	
<code>mf_blob_index</code>	function	<code>F pairpoints</code>	
<code>mf_blob_new</code>	function	<code>F path</code>	
<code>mf_blob_raw_content</code>	function	<code>F pathpoints</code>	
<code>mf_blob_raw_dimensions</code>	function	<code>F points</code>	
<code>mf_blob_raw_reset</code>	function	<code>F print</code>	
<code>mf_blob_raw_toutf</code>	function	<code>F quadruple</code>	
<code>mf_blob_raw_wipe</code>	function	<code>F quadruplepoints</code>	
<code>mf_blob_size</code>	function	<code>F quoted</code>	
<code>mf_blob_width</code>	function	<code>F size</code>	
<code>mf_external_figure</code>	function	<code>F string</code>	
<code>mf_finish_saving_data</code>	function	<code>F transform</code>	
<code>mf_formatted_text</code>	function	<code>F triplet</code>	
<code>mf_get_outline_text</code>	function	<code>F tripletpoints</code>	
<code>mf_graphic_text</code>	function	<code>F vprint</code>	
<code>mf_inject_blob</code>	function	<code>processingmode</code>	function
<code>mf_map_move</code>	function	<code>quadruple</code>	function
<code>mf_map_text</code>	function	<code>quadruplepoints</code>	function
<code>mf_named_color</code>	function	<code>quoted</code>	function
<code>mf_outline_text</code>	function	<code>report</code>	function
<code>mf_save_data</code>	function	<code>scan</code>	table
<code>mf_script_index</code>	function	<code>F boolean</code>	
<code>mf_start_saving_data</code>	function	<code>F cmykcolor</code>	
<code>mf_stop_saving_data</code>	function	<code>F color</code>	
<code>mode</code>	function	<code>F expression</code>	

F integer	T typescanners	
F next	F whatever	
F number	<b>set</b>	table
F numeric	<b>size</b>	function
F pair	<b>skip</b>	table
F path	F token	
F pen	<b>solve</b>	function
F property	<b>string</b>	function
F string	<b>systemmode</b>	function
F symbol	<b>transform</b>	function
F token	<b>triplet</b>	function
T tokenscanners	<b>tripletpoints</b>	function
F transform	<b>vprint</b>	function

## mplib (extra tex)

<b>execute</b>	function	<b>injectstring</b>	function
<b>expandtex</b>	function	<b>injecttransform</b>	function
<b>finder</b>	function	<b>injectwhatever</b>	function
<b>finders</b>	table	<b>new</b>	overloaded function
F file		<b>peninfo</b>	function
F mpstemplate		<b>propertycodes</b>	table
<b>finish</b>	function	<b>realtimelogging</b>	boolean
<b>getcallbackstate</b>	function	<b>scanboolean</b>	function
<b>getcodes</b>	function	<b>scanbmykcolor</b>	function
<b>getcolormodels</b>	function	<b>scanbcolor</b>	function
<b>getfields</b>	function	<b>scanexpression</b>	function
<b>gethashentries</b>	function	<b>scaninteger</b>	function
<b>gethashentry</b>	function	<b>scannext</b>	function
<b>getobjecttypes</b>	function	<b>scannumber</b>	function
<b>getstates</b>	function	<b>scannumeric</b>	function
<b>getstatistics</b>	function	<b>scanpair</b>	function
<b>getstatus</b>	function	<b>scanpath</b>	function
<b>gettolerance</b>	function	<b>scanpen</b>	function
<b>gettype</b>	function	<b>scanproperty</b>	function
<b>gettypes</b>	function	<b>scanstring</b>	function
<b>injectboolean</b>	function	<b>scansymbol</b>	function
<b>injectbmykcolor</b>	function	<b>scantoken</b>	function
<b>injectbcolor</b>	function	<b>scantransform</b>	function
<b>injectinteger</b>	function	<b>settolerance</b>	function
<b>injectnumber</b>	function	<b>showcontext</b>	function
<b>injectnumeric</b>	function	<b>skiptoken</b>	function
<b>injectpair</b>	function	<b>solvepath</b>	function
<b>injectpath</b>	function	<b>version</b>	function

# noads (context)

<b>handlers</b>	table		F showtree
F alternates			F snap
F autofences			F suspicious
F classes			F tags
F collapse			F unscript
F dictionaries			F unstack
F export			F variants
F families		<b>process</b>	function
F fixscripts		<b>processnested</b>	function
F italics		<b>processors</b>	table
F kernpairs		T dictionaries	
F makeup		F mlisttohtml	
F normalize		T suspicious	
F relocate		T unscript	
F render		T unstack	
F resize		<b>processouter</b>	function

# node (basic tex)

<b>checkdiscretionaries</b>	function	F getbottom
<b>checkdiscretionary</b>	function	F getbox
<b>copy</b>	function	F getcachestate
<b>copylist</b>	function	F getchar
<b>count</b>	function	F getchardict
<b>currentattributes</b>	function	F getcharspec
<b>dimensions</b>	function	F getchoice
<b>direct</b>	table	F getdata
F addmargins		F getdegree
F addxoffset		F getdelimiter
F addxymargins		F getdenominator
F addyoffset		F getdepth
F appendaftertail		F getdirection
F checkdiscretionaries		F getdisc
F checkdiscretionary		F getdiscpart
F collapsing		F getexpansion
F copy		F getfam
F copylist		F getfield
F copyonly		F getfont
F count		F getgeometry
F currentattributes		F getglue
F dimensions		F getglyphdata
F effectiveglue		F getglyphdimensions
F endofmath		F getheight
F exchange		F getid
F fields		F getindex
F findattribute		F getinputfields
F findattributerange		F getkern
F findnode		F getkerndimension
F firstglyph		F getlanguage
F flattendiscretionaries		F getleader
F flattenleaders		F getleftdelimiter
F flushlist		F getlist
F flushnode		F getnext
F free		F getnodes
F freeze		F getnormalizedline
F getanchors		F getnucleus
F getattribute		F getnumerator
F getattributelist		F getoffsets
F getattributes		F getoptions
F getboth		F getorientation

F getparstate	F ischar
F getpenalty	F isglyph
F getpost	F isnextchar
F getpre	F isnextglyph
F getprev	F isnode
F getprime	F isprevchar
F getpropertystable	F isprevglyph
F getproperty	F isspeciallist
F getreplace	F isvalid
F getrightdelimiter	F iszeroglue
F getscale	F kerning
F getscales	F lastnode
F getscrip	F length
F getshift	F ligaturing
F getspeciallist	F makeextensible
F getstate	F migrate
F getsub	F mlisttohtml
F getsubpre	F naturalhsize
F getsubtype	F naturalwidth
F getsup	F new
F getsuppre	F newmathglyph
F gettop	F newtextglyph
F gettotal	F patchattributes
F getusedattributes	F prependbeforehead
F getwhd	F protectglyph
F getwidth	F protectglyphs
F getwordrange	F protrusionskipable
F getxscale	F rangedimensions
F getxyscales	F remove
F getyscale	F repack
F gluetostring	F reverse
F hasattribute	F serialized
F hasdimensions	F setanchors
F hasfield	F setattribute
F hasgeometry	F setattributelist
F hasglyph	F setattributes
F hasglyphoption	F setboth
F hpack	F setbottom
F hyphenating	F setbox
F id	F setchar
F ignoremathskip	F setchardict
F insertafter	F setchoice
F insertbefore	F setdata
F is_direct	F setdegree



F setdelimiter	F setsubtype	
F setdenominator	F setup	
F setdepth	F setsuppre	
F setdirection	F settop	
F setdisc	F settotal	
F setdiscpart	F setwhd	
F setexpansion	F setwidth	
F setfam	F show	
F setfield	F slide	
F setfont	F softenhyphens	
F setgeometry	F startofpar	
F setglue	F subtypes	
F setglyphdata	F tail	
F setheight	F todirect	
F setindex	F tonode	
F setinputfields	F toString	
F setkern	F tovaliddirect	
F setlanguage	F traverse	
F setleader	F traversechar	
F setleftdelimiter	F traversecontent	
F setlink	F traverseglyph	
F setlist	F traverseid	
F setnext	F traverseleader	
F setnucleus	F traverselist	
F setnumerator	F type	
F setoffsets	F types	
F setoptions	F unprotectglyph	
F setorientation	F unprotectglyphs	
F setpenalty	F unsetattribute	
F setpost	F unsetattributes	
F setpre	F usedlist	
F setprev	F usesfont	
F setprime	F values	
F setproperty	F verticalbreak	
F setreplace	F vpack	
F setrightdelimiter	F write	
F setscales	F xscaled	
F setscript	F yscaled	
F setshift	<b>effectiveglue</b>	function
F setspeciallist	<b>endofmath</b>	function
F setsplit	<b>family_font</b>	function
F setstate	<b>fields</b>	function
F setsub	<b>findattribute</b>	function
F setsubpre	<b>firstglyph</b>	function

<b>flattendiscretionaries</b>	function
<b>flushlist</b>	function
<b>flushnode</b>	function
<b>free</b>	function
<b>getattribute</b>	function
<b>getcachestate</b>	function
<b>getfield</b>	function
<b>getglue</b>	function
<b>getpropertyiestable</b>	function
<b>getproperty</b>	function
<b>gluetostring</b>	function
<b>hasattribute</b>	function
<b>hasfield</b>	function
<b>hasglyph</b>	function
<b>hpack</b>	function
<b>hyphenating</b>	function
<b>id</b>	function
<b>insertafter</b>	function
<b>insertbefore</b>	function
<b>instock</b>	function
<b>inuse</b>	function
<b>isnode</b>	function
<b>iszeroglue</b>	function
<b>kerning</b>	function
<b>lastnode</b>	function
<b>length</b>	function
<b>ligaturing</b>	function
<b>makeextensible</b>	function
<b>mlisttohlist</b>	function

<b>new</b>	function
<b>protectglyph</b>	function
<b>protectglyphs</b>	function
<b>protrusionskipppable</b>	function
<b>rangedimensions</b>	function
<b>remove</b>	function
<b>serialized</b>	function
<b>setattribute</b>	function
<b>setfield</b>	function
<b>setglue</b>	function
<b>setproperty</b>	function
<b>show</b>	function
<b>slide</b>	function
<b>subtypes</b>	function
<b>tail</b>	function
<b>tostring</b>	function
<b>traverse</b>	function
<b>traverseid</b>	function
<b>type</b>	function
<b>types</b>	function
<b>unprotectglyph</b>	function
<b>unprotectglyphs</b>	function
<b>unsetattribute</b>	function
<b>usedlist</b>	function
<b>usesfont</b>	function
<b>values</b>	function
<b>vpack</b>	function
<b>write</b>	function

# nodes (context)

<b>accentcodes</b>	data table	<b>dircodes</b>	data table
<b>adaptive</b>	table	<b>directioncodes</b>	data table
F handlehorizontal		<b>directionvalues</b>	data table
F handlevertical		<b>dirvalues</b>	data table
F set		<b>disccodes</b>	data table
<b>aligned</b>	function	<b>discretionarycodes</b>	data table
<b>append</b>	function	<b>fencecodes</b>	data table
<b>apply</b>	function	<b>fields</b>	function
<b>applyvisuals</b>	function	<b>fieldtypes</b>	table
<b>astable</b>	function	<b>fillcodes</b>	data table
<b>attributecodes</b>	data table	<b>fillvalues</b>	data table
<b>basepoints</b>	function	<b>firstcharacter</b>	function
<b>boundarycodes</b>	data table	<b>firstcharinbox</b>	function
<b>boxes</b>	table	<b>firstdirinbox</b>	function
F count		<b>flush</b>	function
F dimensions		<b>flushlist</b>	function
F direct		<b>flushnode</b>	function
F dispose		<b>fullhpack</b>	function
F found		<b>getattr</b>	function
F prune		<b>getattribute</b>	function
F reset		<b>getboth</b>	function
F restore		<b>getbox</b>	function
F save		<b>getchar</b>	function
F savenode		<b>getfield</b>	function
<b>builders</b>	table	<b>getfont</b>	function
F buildpage_filter		<b>getid</b>	function
F vbox_filter		<b>getleader</b>	function
F vpack_filter		<b>getlist</b>	function
<b>choicecodes</b>	data table	<b>getnext</b>	function
<b>concat</b>	function	<b>getprev</b>	function
<b>copy</b>	function	<b>getproperty</b>	function
<b>copy_node</b>	function	<b>getsubtype</b>	function
<b>copylist</b>	function	<b>gluecodes</b>	data table
<b>countall</b>	function	<b>glyphcodes</b>	data table
<b>currentattributes</b>	function	<b>handlers</b>	table
<b>delete</b>	function	F accessibility	
<b>destinations</b>	table	F adjusters	
N attribute		F aligncharacter	
T done		F backgrounds	
F handler		F backgroundspage	
T stack		F backgroundsvbox	

F characters		F setmove	
F checkglyphs		F setposition	
F checkparcounter		F setspacekerns	
F cleanupbox		<b>insertafter</b>	function
F cleanuppage		<b>insertbefore</b>	function
F export		<b>insertlistafter</b>	function
F finalizebox		<b>installattributehandler</b>	function
F finalizelist		<b>is_display_math</b>	function
F fixmathalign		<b>isnode</b>	function
F flatten		<b>kerncodes</b>	data table
F flattenline		<b>leftmarginwidth</b>	function
F mathmatrixornaments		<b>linefillers</b>	table
F mathmatrixrules		F filler	
F migrate		F handler	
F protectglyphs		F set	
F recolor		<b>lines</b>	table
F show		T boxed	
F showwhyphenation		F addlinenumbers	
F showpreamble		F register	
F stripping		F setup	
F textbackgrounds		D data	
F unprotectglyphs		F finalize	
F visualizehyphenation		F number	
F wipe		<b>link</b>	function
<b>hasattribute</b>	function	<b>linked</b>	function
<b>hasfield</b>	function	<b>list</b>	function
<b>hpack</b>	function	<b>listcodes</b>	data table
<b>idsandsubtypes</b>	function	<b>listtoutf</b>	function
<b>idtostring</b>	function	<b>literalvalues</b>	data table
<b>injections</b>	table	<b>locate</b>	function
F copy		<b>markcodes</b>	data table
F getligaindex		<b>markers</b>	table
F getthreshold		F get	
F handler		<b>mathcodes</b>	data table
F installgetspaceboth		<b>mathvalues</b>	data table
F installnewkern		<b>maxboxwidth</b>	function
F isspace		<b>migrations</b>	table
F keepcounts		F setinserts	
F reset		F setmarks	
F resetcounts		<b>new</b>	function
F setcursive		<b>noadcodes</b>	data table
F setkern		<b>noadoptions</b>	table
F setligaindex		N axis	
F setmark		N exact	

N left  
N middle  
N no\_axis  
N right  
N set  
N unused\_1  
N unused\_2

## nodecodes

## nopts

## nuts

F addmargins  
F addxoffset  
F addxymargins  
F addyoffset  
F append  
F appendaftertail  
F apply  
F applyvisuals  
F checkdiscretionaries  
F checkslide  
F collapsing  
T colors  
F set  
T components  
F copynocomponents  
F copyonlyglyphs  
F count  
F flush  
F get  
F set  
F concat  
F copy  
F copy\_properties  
F copyleft  
F copynode  
F copyonly  
F copyvisual  
F count  
F countall  
F currentattributes  
F delete  
F dimensions  
F dirdimensions  
F effectiveglue

## data table

## function

## table

F endofmath  
F exchange  
F findattribute  
F findnode  
F firstcharacter  
F firstcharinbox  
F firstglyph  
F flattendiscretionaries  
F flattenleaders  
F flush  
F flushlist  
F flushnode  
F free  
F freeze  
F fullhpack  
F getanchors  
F getattr  
F getattribute  
F getattributelist  
F getattributes  
F getattrlist  
F getattrs  
F getboth  
F getbottom  
F getbox  
F getboxglue  
F getchar  
F getchardict  
F getcharspec  
F getchoice  
F getcomponents  
F getdata  
F getdegree  
F getdelimiter  
F getdenominator  
F getdepth  
F getdirection  
F getdisc  
F getdiscpart  
F getdiscretionary  
F getexpansion  
F getfam  
F getfield  
F getfont

F getgeometry  
F getglue  
F getglyphdata  
F getglyphdimensions  
F getheight  
F getid  
F getindex  
F getinputfields  
F getkern  
F getkerndimension  
F getlang  
F getlanguage  
F getleader  
F getleftdelimiter  
F getlist  
F getmiddle  
F getmiddledelimiter  
F getnext  
F getnormalizedline  
F getnucleus  
F getnumerator  
F getoffsets  
F getoptions  
F getorientation  
F getparstate  
F getpenalty  
F getpost  
F getpre  
F getprev  
F getprime  
F getprop  
F getreplace  
F getrightdelimiter  
F getruledata  
F getscale  
F getscales  
F getscrip  
F getshift  
F getspeciallist  
F getstate  
F getsub  
F getsubpre  
F getsubtype  
F getsup

F getsuppre  
F getsurround  
F gettop  
F gettotal  
F getusedattributes  
F getvalue  
F getwhd  
F getwidth  
F getwordrange  
F getxscale  
F getxyscales  
F getsyscale  
F gluetostring  
F hasattribute  
F hasdimensions  
F hasfield  
F hasgeometry  
F hasglyph  
F hasglyphoption  
F hpack  
F hyphenating  
F ignoremathskip  
F insertafter  
F insertbefore  
F insertlistafter  
F is\_display\_math  
F ischar  
F isdone  
F isglyph  
F isnextchar  
F isnextglyph  
F isnode  
F isprevchar  
F isprevglyph  
F iszeroglue  
F kerning  
F lastnode  
F length  
F ligaturing  
F link  
F linked  
F locate  
F migrate  
F mlisttohtml

F naturalhsize	F pageliteral
F naturalwidth	F penalty
F nestedtracedslide	F radical
F new	F rawliteral
F newmathglyph	F register
F openup	F restore
F patchattributes	F righthangskip
T pool	F rightmarginkern
F accent	F rightskip
F baselineskip	F rule
F boundary	F save
F boxrule	F savepos
F choice	F setmatrix
F cleanup	F setstate
F delim	F shrink
F delimiter	F startrotation
F direction	F stock
F directliteral	F stretch
F disc	F strutrue
F emptyrule	F subbox
F fence	F sublist
F fontkern	F temp
F fraction	F usage
F glue	F userdefined
F gluespec	T userids
F glyph	F usernode
F hlist	F userrule
F imagerule	F vlist
F indentskip	F wordboundary
F italickern	F prepend
F kern	F prependbeforehead
F latelua	F processranges
F leader	F processwords
F lefthangskip	F protectglyph
F leftmarginkern	F protectglyphs
F leftskip	F protrusionskipable
F lineskip	F rangedimensions
F literal	F rawprop
F mathchar	F reference
F mathtextchar	F reheapack
F negatedglue	F remove
F noad	F repack
F originliteral	F repackhlist
F outlinerule	F replace

F reverse	F setlang
T rules	F setlanguage
T ruleactions	F setleader
F box	F setleftdelimiter
F draw	F setlink
F fill	F setlist
F mp	F setmiddledelimiter
F stroke	F setnext
F userrule	F setnucleus
F serialized	F setnumerator
F setanchors	F setoffsets
F setattr	F setoptions
F setattribute	F setorientation
F setattributelist	F setparproperty
F setattributes	F setpenalty
F setattrlist	F setpost
F setattrrs	F setpre
F setboth	F setprev
F setbottom	F setprime
F setbox	F setprop
F setboxglue	F setreplace
F setchar	F setrightdelimiter
F setchardict	F setruledata
F setchoice	F setscale
F setcomponents	F setscales
F setdata	F setscript
F setdegree	F setshift
F setdelimiter	F setspeciallist
F setdenominator	F setsplit
F setdepth	F setstate
F setdirection	F setsub
F setdisc	F setsubpre
F setdiscpart	F setsubtype
F setdiscretionary	F setsup
F setexpansion	F setsuppre
F setfam	F setsurround
F setfield	F settop
F setfont	F setvalue
F setgeometry	F setvisual
F setglue	F setvisuals
F setglyphdata	F setwhd
F setheight	F setwidth
F setinputfields	F show
F setkern	F slide



F softenhyphens  
 F somepenalty  
 F somespace  
 F splitbox  
 F startofpar  
 F striprange  
 F tail  
 F takeattr  
 F takebox  
 F takelist  
 F theprop  
 F tonode  
 F tonodes  
 F tonut  
 F tosequence  
 F toString  
 F tracedslide  
 F traverse  
 F traversechar  
 F traversecontent  
 F traverseglyph  
 F traverseid  
 F traverseleader  
 F traverselist  
 T traversers  
   F alignrecord  
   F boundary  
   F char  
   F content  
   F dir  
   F disc  
   F glue  
   F glyph  
   F hlist  
   F leader  
   F list  
   F mark  
   F next  
   F node  
   F rule  
   F unset  
   F vlist  
   F whatsit  
 T treversers

F char  
 F content  
 F glyph  
 F leader  
 F list  
 F node  
 T typesetters  
   F tohbox  
   F tohpack  
   F tonodes  
   F to vbox  
   F tovpack  
 F unprotectglyph  
 F unprotectglyphs  
 F unsetattribute  
 F unsetattributes  
 F untracedslide  
 F usedlist  
 F usesfont  
 F verticalbreak  
 F vianodes  
 F vianuts  
 F vpack  
 F write  
 F xscaled  
 F yscaled

**packlist**  
**parcodes**  
**penaltycodes**  
**plugindata**

F finalizer  
 F initializer  
 S name  
 T namespace  
   N attribute  
   D data  
   F enable  
   F handler  
   F register  
   D registered  
   D values  
 F processor

**points**  
**pool**

function  
 data table  
 data table  
 table

function  
 table

F baselineskip		<b>rulecodes</b>	data table
F cleanup		<b>rules</b>	table
F directliteral		F handler	
F glyph		F process	
F hlist		F set	
F latelua		F userrule	
F leader		<b>serialize</b>	function
F lineskip		<b>serializebox</b>	function
F literal		<b>serialized</b>	function
F originliteral		<b>setattr</b>	function
F register		<b>setattribute</b>	function
F restore		<b>setboth</b>	function
F save		<b>setbox</b>	function
F savepos		<b>setboxtonaturalwd</b>	function
F setmatrix		<b>setchar</b>	function
F stock		<b>setfield</b>	function
F usage		<b>setfont</b>	function
F usernode		<b>setleader</b>	function
F vlist		<b>setlink</b>	function
<b>prepend</b>	function	<b>setlist</b>	function
<b>print</b>	function	<b>setnext</b>	function
<b>processors</b>	table	<b>setprev</b>	function
F alignment_filter		<b>setProperty</b>	function
F append_line_filter		<b>shifts</b>	table
F glyph_run		F handler	
F post_linebreak_filter		F set	
F pre_linebreak_filter		<b>showboxes</b>	function
F trace_glyph_run_a		<b>showlist</b>	function
F trace_glyph_run_b		<b>showsimplelist</b>	function
<b>properties</b>	table	<b>skipcodes</b>	data table
T data		<b>snapshots</b>	table
<b>pts</b>	function	F getsamples	
<b>radicalcodes</b>	data table	F resetsamples	
<b>references</b>	table	F takesample	
N attribute		<b>somepenalty</b>	function
T done		<b>somespace</b>	function
F handler		<b>specialskipcodes</b>	table
T stack		<b>splitbox</b>	function
<b>rehpack</b>	function	<b>startofpar</b>	function
<b>remove</b>	function	<b>stripdiscctionaries</b>	function
<b>repackhlist</b>	function	<b>stripping</b>	table
<b>replace</b>	function	T glyphs	
<b>report</b>	function	F set	
<b>rightmarginwidth</b>	function	<b>subtypes</b>	data table

<b>tail</b>	function	F fontchar	
<b>takeattr</b>	function	T frequencies	
<b>takebox</b>	function	F register	
<b>tasks</b>	table	T pool	
F actions		T nodes	
F appendaction		F rule	
F disableaction		T nuts	
F disablegroup		F rule	
F enableaction		F resetproperties	
F enablegroup		F rule	
F freeze		F setlist	
F freezegroup		F setproperties	
F new		F start	
F prependaction		T steppers	
F removeaction		F check	
F replaceaction		F codes	
F restart		F features	
F setaction		F font	
F showactions		F glyphs	
F table		F message	
<b>tobasepoints</b>	function	F messages	
<b>tocentimeters</b>	function	F nofsteps	
<b>toxiceros</b>	function	F register	
<b>todidots</b>	function	F reset	
<b>todimen</b>	function	F start	
<b>toinches</b>	function	F stop	
<b>tomillimeters</b>	function	F stop	
<b>tonode</b>	function	T transparencies	
<b>tonodes</b>	function	F reset	
<b>tonut</b>	function	F set	
<b>topicas</b>	function	F setlist	
<b>topoints</b>	function	<b>traverse</b>	function
<b>toscaledpoints</b>	function	<b>traverseid</b>	function
<b>tosequence</b>	function	<b>typesetters</b>	table
<b>tostring</b>	function	F hbox	
<b>totable</b>	function	F hpack	
<b>totree</b>	function	F tohbox	
<b>toutf</b>	function	F tohpack	
<b>tracers</b>	table	F tonodes	
T colors		F to vbox	
F reset		F to vpack	
F set		F vpack	
F setlist		<b>unsetattribute</b>	function
F directions		<b>usedlist</b>	function

<b>vianodes</b>	function	N math	
<b>vianuts</b>	function	N mathglue	
<b>visualizebox</b>	function	N mathkern	
<b>visualizers</b>	table	N origin	
F attribute		N par	
T attributes		N penalty	
F box		N simple	
F handler		N simplehbox	
F markfonts		N simplevbox	
T modes		N simplevtop	
N boundary		N space	
N depth		N strut	
N dir		N user	
N discretionary		N vbox	
N expansion		N vtop	
N fontkern		N whatsit	
N glue		F register	
N glyph		F setfont	
N hbox		F setlayer	
N insert		F setruledglyph	
N italic		F setvisual	
N kern		<b>vpack</b>	function
N line		<b>whatsitcodes</b>	data table
N marginkern		<b>write</b>	function
N mark			

## number (context)

	function	<b>tol6dot16</b>	function
<b>basepoints</b>	function	<b>tobasepoints</b>	function
<b>bytetodecimal</b>	function	<b>tobitstring</b>	function
<b>compactfloat</b>	function	<b>tocentimeters</b>	function
<b>decimaltobyte</b>	function	<b>tociceros</b>	function
<b>dimenfactors</b>	data table	<b>tocontext</b>	function
<b>formatted</b>	function	<b>todidots</b>	function
<b>formattedfloat</b>	function	<b>todimen</b>	function
<b>idiv</b>	function	<b>toevenhex</b>	function
<b>maxdimen</b>	number	<b>toinches</b>	function
<b>nopts</b>	function	<b>tomillimeters</b>	function
<b>nubasepoints</b>	function	<b>tonumberf</b>	function
<b>nupoints</b>	function	<b>tonumberg</b>	function
<b>percent</b>	function	<b>topicsas</b>	function
<b>points</b>	function	<b>topoints</b>	function
<b>pts</b>	function	<b>toscaled</b>	function
<b>signed</b>	function	<b>toscaledpoints</b>	function
<b>sparseexponent</b>	function	<b>valid</b>	function
<b>splitdimen</b>	function		

## objects (context)

<b>data</b>	table	<b>page</b>	function
<b>dimensions</b>	function	<b>reference</b>	function
<b>found</b>	function	<b>register</b>	function
<b>n</b>	number	<b>restore</b>	function

# optional (context)

## **curl** table

F escape  
F fetch  
F getversion  
F initialize  
F unescape

## **foreign** table

F abivalues  
F getbuffer  
F initialize  
F load  
F newbuffer  
F totable  
F types

## **ghostscript** table

F execute  
F initialize

## **graphicsmagick** table

F execute  
F initialize

## **hb** table

F getshapers  
F getversion  
F initialize  
F loadfont  
F shapestring

## **imagemagick** table

F execute  
F initialize

## **kpse** table

F expand\_braces  
F expand\_path  
F expand\_var  
F find\_file  
F find\_files  
F get\_file\_types  
F initialize  
F readable\_file  
F set\_program\_name  
F var\_value

## **library** table

F load

## **loaded** table

## **lz4** table

F compress  
F decompresssize  
F framecompress  
F framedecompress  
F initialize

## **lzma** table

F compress  
F decompress  
F initialize

## **lzo** table

F compress  
F decompresssize  
F initialize

## **mujs** table

F dofile  
F execute  
F initialize  
F reset  
F setclosefile  
F setconsole  
F setfindfile  
F setopenfile  
F setreadfile  
F setseekfile

## **mysql** table

F close  
F execute  
F getmessage  
F initialize  
F open

## **postgres** table

F close  
F execute  
F getmessage  
F initialize  
F open

## **sqlite** table

F close

F execute	F initialize	
F getmessage	<b>zstd</b>	table
F initialize	F compress	
F open	F decompress	
<b>zint</b>	F initialize	
F execute		



## os (basic lua)

<code>__getenv__</code>	function	<code>remove</code>	overloaded function
<code>__setenv__</code>	function	<code>rename</code>	overloaded function
<code>binsuffix</code>	string	<code>resultof</code>	function
<code>binsuffixes</code>	table	<code>runtime</code>	function
<code>bits</code>	number	<code>selfarg</code>	table
<code>clock</code>	function	<code>selfbase</code>	string
<code>converttime</code>	function	<code>selfbin</code>	string
<code>date</code>	overloaded function	<code>selfcore</code>	string
<code>difftime</code>	function	<code>selfdir</code>	string
<code>enableansi</code>	function	<code>selfname</code>	string
<code>env</code>	data table	<code>selfpath</code>	string
<code>execute</code>	overloaded function	<code>setenv</code>	overloaded function
<code>exit</code>	overloaded function	<code>setexitcode</code>	function
<code>fulltime</code>	function	<code>setlocale</code>	overloaded function
<code>getcodepage</code>	function	<code>sleep</code>	function
<code>getenv</code>	overloaded function	<code>time</code>	function
<code>gettimeofday</code>	function	<code>timezone</code>	function
<code>isleapyear</code>	function	<code>tmpname</code>	function
<code>launch</code>	function	<code>today</code>	function
<code>libsuffix</code>	string	<code>type</code>	string
<code>localtime</code>	function	<code>uname</code>	function
<code>name</code>	string	<code>uuid</code>	function
<code>newline</code>	string	<code>validdatetime</code>	function
<code>nofdays</code>	function	<code>weekday</code>	function
<code>now</code>	function	<code>where</code>	function
<code>pipeto</code>	function	<code>which</code>	function
<code>platform</code>	string		

## package (basic lua)

<b>config</b>	string	<b>loadlib</b>	function
<b>cpath</b>	string	<b>luapaths</b>	function
<b>extralibpath</b>	function	<b>path</b>	string
<b>extralibpaths</b>	function	<b>poplibpath</b>	function
<b>extralupath</b>	function	<b>popluapath</b>	function
<b>extralupaths</b>	function	<b>preload</b>	table
<b>helpers</b>	table	<b>pushlibpath</b>	function
<b>libpaths</b>	function	<b>pushluapath</b>	function
<b>loaded</b>	table	<b>searchers</b>	table
<b>loaders</b>	table	<b>searchpath</b>	function

# pagebuilders (context)

## columnsets    table

- F add
- F block
- F check
- F currentcolumn
- F define
- F finishflush
- F flushareas
- F flushcolumn
- F flushrest
- F goto
- F noto
- F prepareflush
- F put
- F registerarea
- F reset
- F setarea

- F sethsize
- F sethspace
- F setlines
- F setproperties
- F setstart
- F setvsize

## injections    table

- F flushafter
- F flushbefore
- F save

## mixedcolumns    table

- F cleanup
- F finalize
- F getlist
- F getrest
- F getsplit
- F setsplit

## pdf (basic tex)

`immediateobj` function

## pdfc (extra tex)

<b>arraytotable</b>	function	<b>getnofpages</b>	function
<b>close</b>	function	<b>getnumber</b>	function
<b>closestream</b>	function	<b>getpage</b>	function
<b>dictionarytotable</b>	function	<b>getpages</b>	function
<b>encryptioncodes</b>	data table	<b>getsize</b>	function
<b>getarray</b>	function	<b>getstatus</b>	function
<b>getboolean</b>	function	<b>getstream</b>	function
<b>getbox</b>	function	<b>getstring</b>	function
<b>getcatalag</b>	function	<b>gettrailer</b>	function
<b>getdictionary</b>	function	<b>getversion</b>	function
<b>getfromarray</b>	function	<b>new</b>	function
<b>getfromdictionary</b>	function	<b>objectcodes</b>	data table
<b>getfromobject</b>	function	<b>open</b>	function
<b>getfromreference</b>	function	<b>openfile</b>	function
<b>getfromstream</b>	function	<b>openstream</b>	function
<b>getinfo</b>	function	<b>pagestotable</b>	function
<b>getinteger</b>	function	<b>readfromstream</b>	function
<b>getmemoryusage</b>	function	<b>readwholestream</b>	function
<b>getname</b>	function	<b>type</b>	function
<b>getnofobjects</b>	function	<b>unencrypt</b>	function

# physics (context)

**units** table

F registerunit

D tables

## pngdecode (extra tex)

**applyfilter**    function

**expand**        function

**interlace**    function

**splitmask**    function

**tocmyk**        function

**tomask**        function

# publications (context)

<b>addtexentry</b>	function	<b>concatstate</b>	function
<b>analyze</b>	function	<b>converttoxml</b>	function
<b>anywhere</b>	function	<b>currentspecification</b>	table
<b>authorcache</b>	data table	S author	
<b>authorcollapsers</b>	data table	T categories	
<b>authorhashers</b>	table	T article	
F invertedshort		S category	
F normal		T extra	
F normalinverted		T fields	
F normalshort		S author	
F sequential		S editor	
F sequentialshort		S journal	
F short		S keywords	
<b>authormap</b>	data table	S note	
<b>authortoregister</b>	function	S number	
<b>btx</b>	table	S pages	
<b>casters</b>	table	S title	
F author		S volume	
F keyword		S year	
F pagenumber		T optional	
F range		T required	
<b>checkeddataset</b>	function	T sets	
<b>citevariants</b>	table	T author	
F author		T virtual	
F authornum		T book	
F authoryear		S category	
F authoryears		T extra	
F category		T fields	
F default		S address	
F entry		S author	
F index		S edition	
F keywords		S editor	
F num		S keywords	
F page		S note	
F short		S number	
F tag		S publisher	
F textnum		S subtitle	
F year		S title	
<b>collected</b>	data table	S volume	
<b>components</b>	table	S year	
F author		T optional	



T required	S page	
T sets	S pages	
T author	S volume	
T editionset	S version	
T virtual	D virtual	
T demo-a	T virtualfields	
S category	B authornum	
T extra	B authoryear	
T fields	B authoryears	
S author	B num	
S institution	B suffix	
S organization	<b>datasets</b>	table
S subtitle	<b>detailed</b>	table
S title	<b>endnotes_to_btx</b>	function
S year	<b>enhancer</b>	table
T optional	S arguments	
T required	T askip	
T sets	B dirty	
T author	T gskip	
T virtual	T kind	
T demo-b	T list	
S category	T system	
T extra	T order	
T fields	N steps	
S author	<b>enhancers</b>	table
S institution	F details	
S organization	F order	
S subtitle	F suffixes	
S title	<b>finder</b>	function
S year	<b>firstofrange</b>	function
T optional	<b>found</b>	function
T required	<b>get</b>	function
T sets	<b>getcasted</b>	function
T authors	<b>getdetail</b>	function
T virtual	<b>getdirect</b>	function
S comment	<b>getfaster</b>	function
S copyright	<b>getfield</b>	function
T fields	<b>getfuzzy</b>	function
S name	<b>getindex</b>	function
T types	<b>inspectors</b>	data table
S author	<b>journals</b>	table
S editor	F abbreviated	
S keywords	F add	
S number	F expanded	

F load		F json	
F save		F lua	
<b>lastofrange</b>	function	F refman	
<b>lists</b>	table	F registercleaner	
F collectentries		F xml	
F combiinlist		<b>loadreplacementfile</b>	function
F fetchentries		<b>new</b>	function
F filterall		<b>okay</b>	function
F flushcombi		<b>oneorange</b>	function
F flushentry		<b>parenttag</b>	function
F flushtag		<b>permitted</b>	function
T methods		<b>prerollcmdstring</b>	function
F dataset		<b>refman_to_btx</b>	function
F force		<b>resolvedname</b>	function
F global		<b>save</b>	function
F local		<b>savers</b>	table
F nofregistered		F bib	
F prepareentries		F lua	
F register		F xml	
F sameasprevious		<b>search</b>	function
T sorters		<b>setcategory</b>	function
F cite		<b>setspecification</b>	function
F dataset		<b>singularorplural</b>	function
F default		<b>sortedentries</b>	function
F index		<b>sortmethods</b>	table
F list		T authortitle	
F reference		T sequence	
F short		T authoryear	
F used		T sequence	
F uservariable		T dataset	
<b>listvariants</b>	table	T sequence	
F default		T key	
F index		T sequence	
F num		<b>specifications</b>	table
F short		T default	
F tag		S author	
<b>load</b>	function	S comment	
<b>loadbibdata</b>	function	S copyright	
<b>loaddefinitionfile</b>	function	S name	
<b>loaders</b>	table	S version	
F bbl		D virtual	
F bib		<b>splitauthor</b>	function
F buffer		<b>splitoneauthor</b>	function
F endnote		<b>statistics</b>	table

N nofbytes		F showdatasetfields	
N nofdatasets		F showentry	
N nofdefinitions		F showfields	
N nofshortcuts		F showhashedauthors	
<b>tables</b>	table	F showtables	
D implicits		F showvariants	
D origins		<b>typesetters</b>	table
D privates		F author	
D sets		F string	
D specials		<b>usedataset</b>	function
D types		<b>usedentries</b>	function
D virtuals		<b>writers</b>	table
<b>tags</b>	function	F author	
<b>tracers</b>	table	F keyword	
F showdatasetauthors		F pagenumber	
F showdatasetcompleteness		F range	

## regimes (context)

<b>backmapping</b>	data table
<b>cleanup</b>	function
<b>disable</b>	function
<b>enable</b>	function
<b>fromregime</b>	function
<b>list</b>	function

<b>mapping</b>	data table
<b>pop</b>	function
<b>process</b>	function
<b>push</b>	function
<b>toregime</b>	function
<b>translate</b>	function

# resolvers (context)

<b>allprefixes</b>	function	<b>findfiles</b>	function
<b>appendhash</b>	function	<b>findgivenfile</b>	function
<b>automount</b>	function	<b>findgivenfiles</b>	function
<b>booleanvariable</b>	function	<b>findlib</b>	function
<b>cacheversion</b>	string	<b>findpath</b>	function
<b>checkedvariable</b>	function	<b>findtexfile</b>	function
<b>cleanedpathlist</b>	function	<b>findwildcardfile</b>	function
<b>cleaners</b>	data table	<b>findwildcardfiles</b>	function
<b>cleanpath</b>	function	<b>formatofsuffix</b>	function
<b>cleanpathlist</b>	function	<b>formatofvariable</b>	function
<b>cleanupbinfile</b>	function	<b>formats</b>	data table
<b>concatinators</b>	data table	<b>foundintree</b>	function
<b>configbanner</b>	string	<b>foundintrees</b>	function
<b>configurationfiles</b>	function	<b>generators</b>	data table
<b>dangerous</b>	data table	<b>get_from_content</b>	function
<b>datastate</b>	function	<b>getenv</b>	function
<b>decompressors</b>	table	<b>getextrapaths</b>	function
F register		<b>getfilehashes</b>	function
F unregister		<b>gethashes</b>	function
<b>defaultsuffixes</b>	table	<b>getownpath</b>	function
<b>dirstatus</b>	function	<b>getreadfilename</b>	function
<b>dowithfilesandreport</b>	function	<b>hashers</b>	data table
<b>dowithfilesintree</b>	function	<b>homedir</b>	string
<b>dowithpath</b>	function	<b>initialized</b>	function
<b>dowithvariable</b>	function	<b>installinputfilehandler</b>	function
<b>executers</b>	table	<b>installinputlinehandler</b>	function
<b>expandbraces</b>	function	<b>jobpath</b>	function
<b>expandedpathfromlist</b>	function	<b>jobs</b>	table
<b>expandedpathlist</b>	function	F currentcomponent	
<b>expandedpathlistfromvariable</b>	function	F currentenvironment	
<b>expandpath</b>	function	F currentproduct	
<b>expandpathfromvariable</b>	function	F currentproject	
<b>expansion</b>	function	F justacomponent	
<b>extendtexmfvariable</b>	function	D processors	
<b>filtered_from_content</b>	function	F productcomponent	
<b>find_file</b>	function	F usefile	
<b>find_files</b>	function	<b>joinpath</b>	function
<b>findbinfile</b>	function	<b>knownvariables</b>	function
<b>findctxfile</b>	function	<b>libraries</b>	table
<b>finders</b>	data table	F optionalloaded	
<b>findfile</b>	function	F validoptional	

<b>load</b>	function	<b>renew</b>	function
<b>loadbinfile</b>	function	<b>renewcache</b>	function
<b>loaders</b>	data table	<b>repath</b>	function
<b>loadlualib</b>	function	<b>reset</b>	function
<b>loadtexfile</b>	function	<b>resetextrapaths</b>	function
<b>loadtime</b>	function	<b>resetresolve</b>	function
<b>locateformat</b>	function	<b>resolve</b>	function
<b>locators</b>	data table	<b>savers</b>	data table
<b>luacnffallback</b>	string	<b>scandata</b>	function
<b>luacnfname</b>	string	<b>scanfiles</b>	function
<b>luacnfspec</b>	string	<b>schemes</b>	table
<b>luacnfstate</b>	string		
<b>macros</b>	table	T cleaners	
		F md5	
F convertfile		F none	
F decodecomment		F strip	
F enablecomment		F cleanname	
F encodecomment		F fetchstring	
F preprocessed		F fetchtable	
F processmk		F install	
F processmklx		<b>setdynamic</b>	function
F processmkvi		<b>setenv</b>	function
F version		<b>showpath</b>	function
<b>maxreadlevel</b>	number	<b>simplescanfiles</b>	function
<b>methodhandler</b>	function	<b>splitconfigurationpath</b>	function
<b>openbinfile</b>	function	<b>splitexpansions</b>	function
<b>openers</b>	data table	<b>splitmethod</b>	function
<b>openfile</b>	function	<b>splitpath</b>	function
<b>opentexfile</b>	function	<b>stackpath</b>	function
<b>ownpath</b>	string	<b>starttiming</b>	function
<b>popextrapath</b>	function	<b>stoptiming</b>	function
<b>popinputname</b>	function	<b>suffixes</b>	data table
<b>poppath</b>	function	<b>suffixmap</b>	data table
<b>prefixes</b>	data table	<b>suffixofformat</b>	function
<b>prependhash</b>	function	<b>texdatablob</b>	function
<b>pushextrapath</b>	function	<b>toppath</b>	function
<b>pushinputname</b>	function	<b>tracers</b>	data table
<b>pushpath</b>	function	<b>unexpandedpath</b>	function
<b>registerextrapath</b>	function	<b>unexpandedpathlist</b>	function
<b>registerfile</b>	function	<b>unresolve</b>	function
<b>registerfilehash</b>	function	<b>updaterelations</b>	function
<b>registerintrees</b>	function	<b>updatescript</b>	function
<b>registermethod</b>	function	<b>uselibrary</b>	function
<b>registerzipfile</b>	function	<b>usertypes</b>	data table
<b>relations</b>	data table	<b>usezipfile</b>	function

<b>validatedpath</b>	function	<b>variableofformatorsuffix</b>	function
<b>variable</b>	function	<b>wildcardpattern</b>	function
<b>variableofformat</b>	function		

## sandbox (context)

<b>disablelibraries</b>	function
<b>disablerunners</b>	function
<b>enable</b>	function
<b>filehandlerone</b>	function
<b>filehandlertwo</b>	function
<b>finalizer</b>	function
<b>getrunner</b>	function
<b>initializer</b>	function
<b>iohandler</b>	function
<b>logcalls</b>	function
<b>logfiles</b>	function
<b>original</b>	function
<b>overload</b>	function

<b>possiblepath</b>	function
<b>redefine</b>	function
<b>register</b>	function
<b>registerbinary</b>	function
<b>registerlibrary</b>	function
<b>registerroot</b>	function
<b>registerrunner</b>	function
<b>report</b>	function
<b>setfilenamelogger</b>	function
<b>setlogger</b>	function
<b>setreporter</b>	function
<b>settrace</b>	function
<b>validfilename</b>	function



# scripts (context)

**autofontfeature** table

F disable  
F enable  
F handler

**colors** data table

**decomposehangul** function

**defaults** table

N inter\_char\_half\_shrink\_factor  
N inter\_char\_half\_stretch\_factor  
N inter\_char\_hangul\_penalty  
N inter\_char\_quarter\_shrink\_factor  
N inter\_char\_quarter\_stretch\_factor  
N inter\_char\_shrink\_factor  
N inter\_char\_stretch\_factor  
N inter\_word\_stretch\_factor

**getdata** function

**getinjector** function

**getsplitter** function

**getstatus** function

**handlers** data table

**helpers** data table

**injectors** data table

**inserters** table

F nobreakspace\_after

F nobreakspace\_before

F space\_after

F space\_before

F zerowidthspace\_after

F zerowidthspace\_before

**installdataset** function

**installmethod** function

**numbertodataset** data table

**numbertohandler** data table

**reset** function

**set** function

**setstatus** function

**splitters** data table

## set (context)

**contains**    function

**create**     function

**tolist**     function

**tonumber**   function

**totable**    function

## sha2 (extra lua)

<b>HASH256</b>	function
<b>HASH384</b>	function
<b>HASH512</b>	function
<b>HEX256</b>	function
<b>HEX384</b>	function
<b>HEX512</b>	function
<b>digest256</b>	function
<b>digest384</b>	function
<b>digest512</b>	function

<b>hash256</b>	function
<b>hash384</b>	function
<b>hash512</b>	function
<b>hex256</b>	function
<b>hex384</b>	function
<b>hex512</b>	function
<b>sum256</b>	function
<b>sum384</b>	function
<b>sum512</b>	function

## sio (extra lua)

<b>read2dot14</b>	function
<b>readbytes</b>	function
<b>readbytetable</b>	function
<b>readcardinal1</b>	function
<b>readcardinal1le</b>	function
<b>readcardinal2</b>	function
<b>readcardinal2le</b>	function
<b>readcardinal3</b>	function
<b>readcardinal3le</b>	function
<b>readcardinal4</b>	function
<b>readcardinal4le</b>	function
<b>readcardinaltable</b>	function
<b>readcline</b>	function
<b>readcstring</b>	function
<b>readfixed2</b>	function
<b>readfixed4</b>	function
<b>readinteger1</b>	function

<b>readinteger1le</b>	function
<b>readinteger2</b>	function
<b>readinteger2le</b>	function
<b>readinteger3</b>	function
<b>readinteger3le</b>	function
<b>readinteger4</b>	function
<b>readinteger4le</b>	function
<b>readintegertable</b>	function
<b>tocardinal1</b>	function
<b>tocardinal1le</b>	function
<b>tocardinal2</b>	function
<b>tocardinal2le</b>	function
<b>tocardinal3</b>	function
<b>tocardinal3le</b>	function
<b>tocardinal4</b>	function
<b>tocardinal4le</b>	function

# socket (extra lua)

<b>BLOCKSIZE</b>	number	S content-md5
<b>_DATAGRAMSIZE</b>	number	S content-range
<b>_SETSIZE</b>	number	S content-transfer-encoding
<b>_SOCKETINVALID</b>	number	S content-type
<b>bind</b>	function	S cookie
<b>choose</b>	function	S date
<b>connect</b>	function	S diagnostic-code
<b>connect4</b>	function	S dsn-gateway
<b>connect6</b>	function	S etag
<b>dns</b>	table	S expect
F getaddrinfo		S expires
F gethostname		S final-log-id
F getnameinfo		S final-recipient
F tohostname		S from
F toip		S host
<b>gettime</b>	function	S if-match
<b>headers</b>	table	S if-modified-since
T canonic		S if-none-match
S accept		S if-range
S accept-charset		S if-unmodified-since
S accept-encoding		S in-reply-to
S accept-language		S keywords
S accept-ranges		S last-attempt-date
S action		S last-modified
S age		S location
S allow		S max-forwards
S alternate-recipient		S message-id
S arrival-date		S mime-version
S authorization		S original-envelope-id
S bcc		S original-recipient
S cache-control		S pragma
S cc		S proxy-authenticate
S comments		S proxy-authorization
S connection		S range
S content-description		S received
S content-disposition		S received-from-mta
S content-encoding		S references
S content-id		S referer
S content-language		S remote-mta
S content-length		S reply-to
S content-location		S reporting-mta

S resent-bcc  
 S resent-cc  
 S resent-date  
 S resent-from  
 S resent-message-id  
 S resent-reply-to  
 S resent-sender  
 S resent-to  
 S retry-after  
 S return-path  
 S sender  
 S server  
 S smtp-remote-recipient  
 S status  
 S subject  
 S te  
 S to  
 S trailer  
 S transfer-encoding  
 S upgrade  
 S user-agent  
 S vary  
 S via  
 S warning  
 S will-retry-until  
 S www-authenticate  
 S x-mailer  
 F lower  
 F normalize  
**http** table  
 N TIMEOUT  
 S USERAGENT  
 F genericform  
 F open  
 F request  
**newtry** function

**protect** function  
**report** function  
**select** function  
**sink** function  
**sinkt** table  
 F close-when-done  
 F default  
 F http-chunked  
 F keep-open  
**skip** function  
**sleep** function  
**source** function  
**sourcet** table  
 F by-length  
 F default  
 F http-chunked  
 F until-closed  
**tcp** function  
**tcp4** function  
**tcp6** function  
**tp** table  
 N TIMEOUT  
 F connect  
**try** function  
**udp** function  
**udp4** function  
**udp6** function  
**url** table  
 F absolute  
 F build  
 F build\_path  
 F escape  
 F parse  
 F parse\_path  
 F unescape

# sorters (context)

<b>basicsorter</b>	function		B pm
<b>comparers</b>	table		B uc
F basic			B zc
<b>constants</b>	table		B zm
S defaultdigits		<b>definitions</b>	data table
S defaultlanguage		<b>firstofsplit</b>	function
S defaultmethod		<b>packch</b>	function
N digitmaximum		<b>packuc</b>	function
N digitoffset		<b>replacementlist</b>	function
N ignoredoffset		<b>setlanguage</b>	function
N replacementoffset		<b>sort</b>	function
T validmethods		<b>splitters</b>	table
B ch		F utf	
B mc		<b>strip</b>	function
B mm		<b>tracers</b>	data table
B pc		<b>update</b>	function

## sparse (context)

<b>concat</b>	function
<b>get</b>	function
<b>max</b>	function
<b>min</b>	function
<b>new</b>	function

<b>range</b>	function
<b>restore</b>	function
<b>set</b>	function
<b>traverse</b>	function
<b>wipe</b>	function



## statistics (context)

<b>benchmarktimer</b>	function	<b>resettiming</b>	function
<b>checkfmtstatus</b>	function	<b>runtime</b>	function
<b>currenttime</b>	function	<b>savefmtstatus</b>	function
<b>elapsed</b>	function	<b>show</b>	function
<b>elapsedindeed</b>	function	<b>showmemory</b>	function
<b>elapsedseconds</b>	function	<b>showusage</b>	function
<b>elapsedtime</b>	function	<b>starttiming</b>	function
<b>enable</b>	boolean	<b>stoptiming</b>	function
<b>formatruntime</b>	function	<b>threshold</b>	number
<b>hastiming</b>	function	<b>timed</b>	function
<b>memused</b>	function	<b>tracefunction</b>	function
<b>register</b>	function		

## status (basic tex)

<b>getbufferstate</b>	function	<b>getmarkstate</b>	function
<b>getcallbackstate</b>	function	<b>getneststate</b>	function
<b>getconstants</b>	function	<b>getnodestate</b>	function
<b>geterrorlinestate</b>	function	<b>getparameterstate</b>	function
<b>geterrorstate</b>	function	<b>getpoolstate</b>	function
<b>getexpandstate</b>	function	<b>getreadstate</b>	function
<b>getextrastate</b>	function	<b>getsavestate</b>	function
<b>getfilestate</b>	function	<b>getsparsestate</b>	function
<b>getfontstate</b>	function	<b>getstringstate</b>	function
<b>gethalferrorlinestate</b>	function	<b>gettexstate</b>	function
<b>gethashstate</b>	function	<b>gettokenstate</b>	function
<b>getinputstate</b>	function	<b>getwarningstate</b>	function
<b>getinsertstate</b>	function	<b>iocodes</b>	table
<b>getlanguagestate</b>	function	<b>list</b>	function
<b>getlookupstate</b>	function	<b>resetmessages</b>	function
<b>getluastate</b>	function		

# storage (context)

<b>allocate</b>	function	<b>noftables</b>	number
<b>data</b>	table	<b>register</b>	function
<b>mark</b>	function	<b>shared</b>	data table
<b>marked</b>	function	<b>storedfunctions</b>	data table
<b>max</b>	number	<b>strip</b>	boolean
<b>min</b>	number	<b>tofmodules</b>	number
<b>nofmodules</b>	number	<b>toftables</b>	number

## streams (context)

<b>collect</b>	function
<b>disable</b>	function
<b>enable</b>	function
<b>flush</b>	function
<b>initialize</b>	function

<b>push</b>	function
<b>start</b>	function
<b>stop</b>	function
<b>synchronize</b>	function

## string (basic lua)

<b>autodouble</b>	function	<b>nspaces</b>	table
<b>autosingle</b>	function	<b>optionalquoted</b>	function
<b>booleanstring</b>	function	<b>pack</b>	function
<b>byte</b>	function	<b>packrowscolumns</b>	function
<b>bytepairs</b>	function	<b>packsize</b>	function
<b>bytes</b>	function	<b>quote</b>	function
<b>bytetable</b>	function	<b>quoted</b>	function
<b>char</b>	function	<b>rep</b>	function
<b>characterpairs</b>	function	<b>replacenewlines</b>	function
<b>characters</b>	function	<b>reverse</b>	function
<b>checkedsplit</b>	function	<b>split</b>	function
<b>collapsespaces</b>	function	<b>splitlines</b>	function
<b>containsws</b>	function	<b>splitup</b>	function
<b>count</b>	function	<b>strip</b>	function
<b>dawson</b>	function	<b>sub</b>	function
<b>dump</b>	function	<b>texnewlines</b>	function
<b>erf</b>	function	<b>tformat</b>	function
<b>erfc</b>	function	<b>toHEX</b>	function
<b>erfcx</b>	function	<b>toboollean</b>	function
<b>erfi</b>	function	<b>tobytes</b>	function
<b>escapedpattern</b>	function	<b>tocontext</b>	function
<b>escapedquotes</b>	function	<b>todec</b>	function
<b>explode</b>	function	<b>todimen</b>	function
<b>f6</b>	function	<b>tohex</b>	function
<b>find</b>	function	<b>tonodes</b>	function
<b>format</b>	function	<b>topattern</b>	function
<b>formatter</b>	function	<b>totable</b>	function
<b>formatters</b>	function	<b>tounicode16</b>	function
<b>fullstrip</b>	function	<b>toutf</b>	function
<b>gmatch</b>	function	<b>toutf32</b>	function
<b>gsub</b>	function	<b>toutf8</b>	function
<b>is_boolean</b>	function	<b>tracedchar</b>	function
<b>is_empty</b>	function	<b>tracedchars</b>	table
<b>itself</b>	function	<b>unescapedquotes</b>	function
<b>len</b>	function	<b>unpack</b>	function
<b>limit</b>	function	<b>unquote</b>	function
<b>linetable</b>	function	<b>unquoted</b>	function
<b>longtostring</b>	function	<b>upper</b>	function
<b>lower</b>	function	<b>utfcharacter</b>	function
<b>match</b>	function	<b>utfcharacters</b>	function
<b>nspaces</b>	function	<b>utfcharactertable</b>	function

<b>utflength</b>	function	<b>utfvaluetable</b>	function
<b>utfpadd</b>	function	<b>valid</b>	function
<b>utfpadding</b>	function	<b>voigt</b>	function
<b>utfvalue</b>	function	<b>voigt_hwhm</b>	function
<b>utfvalues</b>	function	<b>wordsplitter</b>	function

# structures (context)

<b>atlocation</b>	function	F last	
<b>blocks</b>	table	F next	
D collected		F prev	
F define		F previous	
F empty		F raw	
F print		F record	
F save		F reset	
F select		F restart	
F setstate		F restore	
D states		F save	
D tobesaved		F set	
F uservariable		F setlevel	
<b>bookmarks</b>	table	F setoffset	
T extras		F setown	
F get		F setstate	
F mergesections		F setvalue	
F register		T specials	
F reset		F userpage	
F tosections		F subs	
F finalize		D tobesaved	
F flatten		F value	
F installhandler		F way	
F merge		<b>currentsectionnumber</b>	function
S method		<b>descriptions</b>	table
F overload		<b>documents</b>	table
F place		D data	
F register		F initialize	
F setopened		F preset	
F setup		F reset	
<b>counters</b>	table	<b>floats</b>	table
F add		<b>formulas</b>	table
F analyze		<b>helpers</b>	table
F check		F analyze	
D collected		F formulanumber	
F compact		F merged	
F converted		F page	
F currentvalue		F pageofinternal	
D data		F prefix	
F define		F prefixlastpage	
F first		F prefixpage	
F get		F simplify	

F title	
F touserdata	
<b>inserts</b>	<b>table</b>
D data	
F define	
F getdata	
F getlocation	
F getname	
F getnumber	
F setlocation	
F setup	
D stored	
<b>itemgroups</b>	<b>table</b>
<b>lists</b>	<b>table</b>
F addto	
F analyze	
B autoreorder	
D cached	
D collected	
F discard	
F enhance	
T enhancers	
F filter	
F formulainumber	
F getresult	
F groupindex	
F hasnumberdata	
F haspagedata	
F hastitledata	
F iscached	
D kinds	
F label	
F location	
D names	
F number	
D ordered	
F page	
F popnesting	
F prefix	
F prefixednumber	
F prefixedpage	
F process	
D pushed	
F pushnesting	

F rawnumber	
F realpage	
F reordered	
T result	
F savedlistnumber	
F savedlistprefixednumber	
F savedlisttitle	
D sectionblocks	
F sectionnumber	
F size	
F title	
D tobesaved	
F userdata	
F uservalue	
<b>marks</b>	<b>table</b>
F number	
F title	
<b>notes</b>	<b>table</b>
F check_spacing	
F checkpagechange	
F define	
F doifonsamepageasprevious	
F get	
F getdeltapage	
F getinternal	
F getn	
F getstate	
F hascontent	
F internal	
F internalid	
F listindex	
D numbers	
F ordered	
F postpone	
F resetpostponed	
F restore	
F save	
F setstate	
D states	
F store	
<b>pages</b>	<b>table</b>
F allmarked	
F analyze	
D collected	



- F fraction
- F in\_body
- F is\_odd
- F mark
- F marked
- F markedlist
- N nopages
- F number
- F on\_right
- F save
- D tobosaved
- F toranges

## references

- F analyze
- F checked
- F checkedfile
- F checkedfileorurl
- F checkedprogram
- F checkedrealpage
- F checkedurl
- D collected
- U componentsplitter
- F currentmetadata
- F currentorder
- D currentset
- F define
- D defined
- D derived
- F enhance
- D executers
- F export
- T files
- T data
- F define
- F found
- F get
- F filter
- F filterdefault
- D filters
- D flaginternals
- F from
- D functions
- F get
- F getcurrentmetadata

## table

- F getcurrentprefixspec
- F getinnermethod
- F getinternalcachedlistreference
- F getinternallistreference
- F getinternalreference
- F getoutermethod
- D handlers
- F identify
- F import
- F inject
- F injectcurrentset
- S innermethod
- D internals
- F load
- F loadpresets
- F mark
- S outermethod
- D pages
- U prefixsplitter
- D productdata
- T programs
- T data
- F define
- F get
- F realpageofpage
- U referencesplitter
- D referred
- F referredpage
- F registerfinalizer
- F registerinitializer
- F registerpage
- F reset
- D runners
- F set
- F setandgetattribute
- F setcomponent
- F setinternalreference
- F setlinkmethod
- F setnextinternal
- F setnextorder
- F setreferencerealpage
- D specials
- F splitcomponent
- F splitprefix

- F splitreference
- F synchronizepage
- T testrunners
  - F inner
  - F special
  - F special operation
  - F special operation with arguments
- T testspecials
  - F deltapage
  - F i
  - F internal
  - F page
  - F realpage
  - F section
  - F userpage
- D tobereferred
- D tobesaved
- D tracedpages
- T urls
  - T data
  - F define
  - F found
  - F get
  - F untex
- D usedinternals
- D usedviews
- F valid

## registers

- F analyze
- D collected
- F compare
- F define
- F enhance
- F extend
- F filter
- F filtercollected
- F finalize
- F findinternal
- F flush
- F get
- F prepare
- F process
- F setmethod
- F sort

## table

- F store
- D tobesaved
- F unique
- F userdata

## sections

## table

- F autodepth
- F cct
- D collected
- F current
- F currentblock
- F currentid
- F currentlevel
- F currentsectionindex
- F depthnumber
- F finddata
- F findnumber
- F fullnumber
- F getcurrentlevel
- F getlevel
- F getnumber
- F internalreference
- D levelmap
- D levels
- F matchingtilldepth
- F numberatdepth
- F numbers
- F popblock
- F prefixedconverted
- F pushblock
- F register
- D registered
- F reportstructure
- F save
- T sectionblockdata
  - T bodypart
    - S bookmark
- F set
- F setblock
- F setchecker
- F setentry
- F setinitialblock
- F setlevel
- F setnumber
- F showstructure

F structuredata		F margintext
F title		F math
D tobesaved		F mrow
F typesetnumber		F mtable
F userdata		T destinationhash
B verbose		T extras
<b>sets</b>	table	F adddestination
F define		F addimplicit
F get		F addinternal
F getall		F addreference
D setlist		F combination
<b>specials</b>	table	F delimitedsymbol
D collected		F description
F retrieve		F descriptionsymbol
F store		F document
D tobesaved		F float
<b>synonyms</b>	table	F formulacontent
F analyzed		F image
D collected		F item
F compare		F itemgroup
F define		F link
F filter		F listitem
F finalize		F mi
F flush		F msub
F isshown		F msup
F isused		F paragraph
F meaning		F publication
F prepare		F reference
F process		F registerlocation
F register		F registerpages
F registershown		F registerseparator
F registerused		F section
F reset		F sorting
F resetall		F subsentencesymbol
F resetlist		F synonym
F resetshown		F tablecell
F resetused		F tabulate
F sort		F tabulatecell
F synonym		T finalizers
D tobesaved		F descriptions
<b>tags</b>	table	T fixes
T backend		F linenumber
T checks		T listdata
F marginanchor		T referencehash

F setattribute	F setattributefunction
T usedimages	F setcombination
T image	F setconstruct
T usedstyles	F setfigure
T construct	F setfloat
T highlight	F setformulacontent
F current	F sethighlight
F elementtag	F setitem
F enabled	F setitemgroup
F exportbox	F setlist
F finishexport	F setnotation
F getextradata	F setnotationsymbol
F getid	F setparagraph
F getmetadata	F setproperty
F gettablecell	F setpublication
F gettabulatecell	F setregister
F handler	F setsorting
F initializeexport	F setsynonym
D labels	F settablecell
F last	F settabulatecell
F lastinchain	F settagdelimitedsymbol
F localexport	F settagsubsentencesymbol
F locatedtag	F setupexport
T patterns	F setuserproperties
U splitter	D specifications
D properties	F start
F registerextradata	F stop
F registermetadata	F strip
F restart	D taglist
F setaspect	T usewithcare

## table (basic lua)

<b>allkeys</b>	function	<b>orderedhash</b>	function
<b>append</b>	function	<b>pack</b>	function
<b>are_equal</b>	function	<b>prepend</b>	function
<b>collapsed</b>	function	<b>print</b>	function
<b>collapsedhash</b>	function	<b>remove</b>	function
<b>combine</b>	function	<b>reverse</b>	function
<b>compact</b>	function	<b>reversed</b>	function
<b>concat</b>	function	<b>save</b>	function
<b>contains</b>	function	<b>sequenced</b>	function
<b>copy</b>	function	<b>serialize</b>	function
<b>count</b>	function	<b>setmetatablecall</b>	function
<b>derive</b>	function	<b>setmetatableindex</b>	function
<b>deserialize</b>	function	<b>setmetatableindices</b>	function
<b>drop</b>	function	<b>setmetatablekey</b>	function
<b>fastcopy</b>	function	<b>setmetatablenewindex</b>	function
<b>fastserialize</b>	function	<b>sort</b>	function
<b>filtered</b>	function	<b>sorted</b>	function
<b>flattened</b>	function	<b>sortedhash</b>	function
<b>fromhash</b>	function	<b>sortedhashkeys</b>	function
<b>getmetatablekey</b>	function	<b>sortedhashonly</b>	function
<b>getn</b>	function	<b>sortedindexonly</b>	function
<b>has_one_entry</b>	function	<b>sortedkeys</b>	function
<b>hashed</b>	function	<b>sortedpairs</b>	function
<b>identical</b>	function	<b>sparse</b>	function
<b>imerge</b>	function	<b>strip</b>	function
<b>imerged</b>	function	<b>sub</b>	function
<b>insert</b>	function	<b>swapped</b>	function
<b>is_empty</b>	function	<b>tocontext</b>	function
<b>is_simple_table</b>	function	<b>tocsv</b>	function
<b>keys</b>	function	<b>tofile</b>	function
<b>load</b>	function	<b>tohandle</b>	function
<b>loweredkeys</b>	function	<b>tohash</b>	function
<b>makewweak</b>	function	<b>toxml</b>	function
<b>merge</b>	function	<b>twowaymapper</b>	function
<b>merged</b>	function	<b>unique</b>	function
<b>mirrored</b>	function	<b>unnest</b>	function
<b>move</b>	function	<b>unpack</b>	function
<b>ordered</b>	function	<b>values</b>	function

# tex (basic tex)

<b>attribute</b>	table	<b>forceinputstateline</b>	function
<b>automigrationcodes</b>	data table	<b>fprint</b>	function
<b>badness</b>	function	<b>frozenparcodes</b>	data table
<b>boundaries</b>	table	<b>get</b>	function
D names		<b>getalignmentcontextvalues</b>	function
D numbers		<b>getappendlinecontextvalues</b>	function
F system		<b>getattribute</b>	function
<b>box</b>	table	<b>getautomigrationvalues</b>	function
<b>boxresources</b>	table	<b>getbox</b>	function
F getbox		<b>getboxdir</b>	function
F getdimensions		<b>getboxresourcebox</b>	function
F save		<b>getboxresourcedimensions</b>	function
F use		<b>getcatcode</b>	function
<b>catcode</b>	table	<b>getcount</b>	function
<b>chardef</b>	function	<b>getdelcode</b>	function
<b>classoptioncodes</b>	data table	<b>getdelcodes</b>	function
<b>codes</b>	table	<b>getdimen</b>	function
<b>conditionals</b>	data table	<b>getdimensionvalue</b>	function
<b>constants</b>	data table	<b>getdiscoptionvalues</b>	function
<b>count</b>	table	<b>getdiscstatevalues</b>	function
<b>cprint</b>	function	<b>geterrorvalues</b>	function
<b>ctdcatcodes</b>	number	<b>getflagvalues</b>	function
<b>ctxcatcodes</b>	number	<b>getfontoffamily</b>	function
<b>definefont</b>	function	<b>getfrozenparvalues</b>	function
<b>delcode</b>	table	<b>getglue</b>	function
<b>dimen</b>	table	<b>getglyphdata</b>	function
<b>dimensiondef</b>	function	<b>getglyphoptionvalues</b>	function
<b>directives</b>	data table	<b>getglyphscales</b>	function
<b>discoptioncodes</b>	data table	<b>getglyphscript</b>	function
<b>dontcomplain</b>	function	<b>getglyphstate</b>	function
<b>enableprimitives</b>	function	<b>getgroupvalues</b>	function
<b>error</b>	function	<b>gethccode</b>	function
<b>expandasvalue</b>	function	<b>gethelptext</b>	function
<b>experiments</b>	data table	<b>gethmcode</b>	function
<b>extraprimitives</b>	function	<b>gethyphenationvalues</b>	function
<b>fatalerror</b>	function	<b>getinputstatefile</b>	function
<b>flagcodes</b>	data table	<b>getinputstateline</b>	function
<b>fontidentifier</b>	function	<b>getinputstatemode</b>	function
<b>fontname</b>	function	<b>getinsertcontent</b>	function
<b>forcehmode</b>	function	<b>getinsertdepth</b>	function
<b>forceinputstatefile</b>	function	<b>getinsertdistance</b>	function

<b>getinsertheight</b>	function	<b>getprimitiveorigins</b>	function
<b>getinsertlimit</b>	function	<b>getregisterindex</b>	function
<b>getinsertmultiplier</b>	function	<b>getrunstatevalues</b>	function
<b>getinsertwidth</b>	function	<b>getsfcode</b>	function
<b>getintegervalue</b>	function	<b>getshapingpenaltiesvalues</b>	function
<b>getinteraction</b>	function	<b>getskip</b>	function
<b>getiovalues</b>	function	<b>getspecialmathclassvalues</b>	function
<b>getlargestusedmark</b>	function	<b>gettextcontrolvalues</b>	function
<b>getlccode</b>	function	<b>gettextdir</b>	function
<b>getlinedir</b>	function	<b>gettoks</b>	function
<b>getlist</b>	function	<b>getuccode</b>	function
<b>getlistanchorvalues</b>	function	<b>glue</b>	table
<b>getlistgeometryvalues</b>	function	<b>glyphoptioncodes</b>	data table
<b>getlistsignvalues</b>	function	<b>groupcodes</b>	data table
<b>getlocalbox</b>	function	<b>hashtokens</b>	function
<b>getlocallevel</b>	function	<b>hccode</b>	table
<b>getmark</b>	function	<b>hmcode</b>	table
<b>getmath</b>	function	<b>hyphenationcodes</b>	data table
<b>getmathclassoptionvalues</b>	function	<b>ifs</b>	data table
<b>getmathcode</b>	function	<b>inimatcodes</b>	number
<b>getmathcodes</b>	function	<b>integerdef</b>	function
<b>getmathcontrolvalues</b>	function	<b>isattribute</b>	function
<b>getmathdir</b>	function	<b>isbox</b>	function
<b>getmathparametervalues</b>	function	<b>iscount</b>	overloaded function
<b>getmathstylenamevalues</b>	function	<b>isdefined</b>	function
<b>getmathstylevalues</b>	function	<b>isdimen</b>	overloaded function
<b>getmathvariantvalues</b>	function	<b>isglue</b>	function
<b>getmode</b>	function	<b>ismuglue</b>	function
<b>getmodevalues</b>	function	<b>ismuskip</b>	overloaded function
<b>getmuglue</b>	function	<b>isprintable</b>	function
<b>getmuskip</b>	function	<b>isskip</b>	overloaded function
<b>getnest</b>	function	<b>istoken</b>	function
<b>getnoadoptoptionvalues</b>	function	<b>istoks</b>	function
<b>getnormalizelinevalues</b>	function	<b>lastnodetype</b>	function
<b>getnormalizeparvalues</b>	function	<b>lccode</b>	table
<b>getoutputactive</b>	function	<b>linebreak</b>	function
<b>getpacktypevalues</b>	function	<b>listanchorcodes</b>	data table
<b>getpagecontextvalues</b>	function	<b>lists</b>	table
<b>getpagestate</b>	function	<b>listsigncodes</b>	data table
<b>getparbeginvalues</b>	function	<b>luacatcodes</b>	number
<b>getparcontextvalues</b>	function	<b>magicconstants</b>	table
<b>getpardir</b>	function		
<b>getparmodevalues</b>	function		
<b>getparstate</b>	function		

N assumedmathcontrol

N awfulbad

N decentcriterion

N defaultcatcodetable	N maxnoflanguages	
N defaultdeadcycles	N maxnofmarks	
N defaulteqnogapstep	N maxnofmathfamilies	
N defaulthangafter	N maxquarterword	
N defaultoutputbox	N maxsizeofword	
N defaultpredisplaygap	N maxspacefactor	
N defaultrule	N maxtoksregisterindex	
N defaultspacefactor	N mincardinal	
N defaulttolerance	N mindatavalue	
N deplorable	N mindimen	
N ejectpenalty	N minhalfword	
N ignoredepth	N mininfinity	
N infinitebad	N mininteger	
N infinitepenalty	N minquarterword	
N infinity	N minspacefactor	
N largewidthexcess	N nocatcodetable	
N loosecriterium	N null	
N mathbeginclass	N nullflag	
N mathendclass	N nullfont	
N maxattributeregisterindex	N onebp	
N maxboxregisterindex	N presetrulethickness	
N maxbytecodeindex	N runningrule	
N maxcardinal	N smallstretchability	
N maxcategorycode	N texeqtbsize	
N maxcharactercode	N texhashprime	
N maxcharcode	N texhashsize	
N maxdatavalue	N two	
N maxdimen	N undefinedmathparameter	
N maxdimenregisterindex	N unity	
N maxfunctionreference	N unusedattributevalue	
N maxglueregisterindex	N unusedmathfamily	
N maxhalfvalue	N unusedmathstyle	
N maxhalfword	N unusedscriptvalue	
N maxinteger	N unusedstatevalue	
N maxintregisterindex	N zeroglu	
N maxlimitedscale	<b>mathchardef</b>	function
N maxmarkindex	<b>mathcode</b>	table
N maxmathclasscode	<b>mathcontrolcodes</b>	data table
N maxmathfamilyindex	<b>modelevels</b>	table
N maxmuglueregisterindex	N horizontal	
N maxnewlinecharacter	N math	
N maxnofbytecodes	N unset	
N maxnofcatcodetables	N vertical	
N maxnoffonts	<b>modes</b>	data table



<b>mprint</b>	function	<b>sethccode</b>	function
<b>muglue</b>	table	<b>sethmcodes</b>	function
<b>muskip</b>	table	<b>setinputstatefile</b>	function
<b>nest</b>	table	<b>setinputstateline</b>	function
<b>nilcatcodes</b>	number	<b>setinputstatemode</b>	function
<b>noadoptioncodes</b>	data table	<b>setinsertcontent</b>	function
<b>normalizelinecodes</b>	data table	<b>setinsertdistance</b>	function
<b>normalizeparcodes</b>	data table	<b>setinsertlimit</b>	function
<b>notcatcodes</b>	number	<b>setinsertmultiplier</b>	function
<b>number</b>	function	<b>setintegervalue</b>	function
<b>parcontextcodes</b>	data table	<b>setinteraction</b>	function
<b>poplocal</b>	function	<b>setlccode</b>	function
<b>popsavelevel</b>	function	<b>setlinedir</b>	function
<b>preparelinebreak</b>	function	<b>setlist</b>	function
<b>primitives</b>	function	<b>setlocalbox</b>	function
<b>print</b>	function	<b>setmath</b>	function
<b>prtcategories</b>	number	<b>setmathcode</b>	function
<b>pushlocal</b>	function	<b>setmathdir</b>	function
<b>pushsavelevel</b>	function	<b>setmuglue</b>	function
<b>quitlocal</b>	function	<b>setmuskip</b>	function
<b>quittoks</b>	function	<b>setnest</b>	function
<b>resetparagraph</b>	function	<b>setpardir</b>	function
<b>rlncatcodes</b>	number	<b>setrunstate</b>	overloaded function
<b>romannumeral</b>	function	<b>setsfcode</b>	function
<b>round</b>	function	<b>setskip</b>	function
<b>runlocal</b>	function	<b>settetdir</b>	function
<b>runstring</b>	function	<b>settoks</b>	function
<b>runtoks</b>	function	<b>setuccode</b>	function
<b>saveboxresource</b>	function	<b>sfcode</b>	table
<b>scale</b>	function	<b>shiftparshape</b>	function
<b>scantoks</b>	function	<b>shipout</b>	function
<b>set</b>	function	<b>showcontext</b>	function
<b>setattribute</b>	function	<b>skip</b>	table
<b>setbox</b>	function	<b>snapshotpar</b>	function
<b>setboxdir</b>	function	<b>sp</b>	function
<b>setcatcode</b>	function	<b>specialmathclasscodes</b>	data table
<b>setcount</b>	function	<b>splitbox</b>	function
<b>setdelcode</b>	function	<b>sprint</b>	function
<b>setdimen</b>	function	<b>stringtocodesbitmap</b>	function
<b>setdimensionvalue</b>	function	<b>systemmodes</b>	data table
<b>setglue</b>	function	<b>takebox</b>	function
<b>setglyphdata</b>	function	<b>texcatcodes</b>	number
<b>setglyphscript</b>	function	<b>textcontrolcodes</b>	data table
<b>setglyphstate</b>	function	<b>toks</b>	table

<b>tonumber</b>	function	<b>txtcatcodes</b>	number
<b>toscaled</b>	function	<b>type</b>	function
<b>tpacatcodes</b>	number	<b>uccode</b>	<b>table</b>
<b>tpbcatcodes</b>	number	<b>uprint</b>	function
<b>tprint</b>	function	<b>useboxresource</b>	function
<b>trackers</b>	data table	<b>vrbcatcodes</b>	number
<b>triggerbuildpage</b>	function	<b>write</b>	function

# texconfig (basic tex)

<b>firstline</b>	string		N step
<b>formatname</b>	string	<b>propertyssize</b>	number
<b>functionsize</b>	number	<b>shell_escape</b>	string
<b>init</b>	overloaded function	<b>tokensize</b>	table
<b>kpse_init</b>	boolean		N size
<b>nodesize</b>	table		N step
	N size		

## texio (basic tex)

**closeinput**

function

**setlogfile**

function

**terminal**

function

**write**

function

**write\_nl**

function

**writeln**

function

**writeselector**

function

**writeselectorlf**

function

**writeselectornl**

function

## token (basic tex)

<b>create</b>	function	<b>getexpandable</b>	function
<b>expand</b>	function	<b>getexpansion</b>	function
<b>expand_macro</b>	function	<b>getfields</b>	function
<b>expandmacro</b>	function	<b>getflags</b>	function
<b>future_expand</b>	function	<b>getfrozen</b>	function
<b>futureexpand</b>	function	<b>getfunctionvalues</b>	function
<b>get_active</b>	function	<b>getid</b>	function
<b>get_cmdchrscs</b>	function	<b>getimmutable</b>	function
<b>get_cmdname</b>	function	<b>getindex</b>	function
<b>get_command</b>	function	<b>getinstance</b>	function
<b>get_csname</b>	function	<b>getinteger</b>	function
<b>get_cstoken</b>	function	<b>getmacro</b>	function
<b>get_dimension</b>	function	<b>getmeaning</b>	function
<b>get_expandable</b>	function	<b>getnoaligned</b>	function
<b>get_fields</b>	function	<b>getparameters</b>	function
<b>get_flags</b>	function	<b>getpermanent</b>	function
<b>get_frozen</b>	function	<b>getprimitive</b>	function
<b>get_id</b>	function	<b>getprimitives</b>	function
<b>get_immutable</b>	function	<b>getprotected</b>	function
<b>get_index</b>	function	<b>getrange</b>	function
<b>get_instance</b>	function	<b>gettok</b>	function
<b>get_integer</b>	function	<b>gettolerant</b>	function
<b>get_macro</b>	function	<b>gobble</b>	function
<b>get_meaning</b>	function	<b>gobble_dimen</b>	function
<b>get_noaligned</b>	function	<b>gobble_integer</b>	function
<b>get_parameters</b>	function	<b>gobbledimen</b>	function
<b>get_permanent</b>	function	<b>gobbleinteger</b>	function
<b>get_primitive</b>	function	<b>grab</b>	function
<b>get_protected</b>	function	<b>is_defined</b>	function
<b>get_range</b>	function	<b>is_next_char</b>	function
<b>get_tok</b>	function	<b>is_token</b>	function
<b>get_tolerant</b>	function	<b>isdefined</b>	function
<b>getactive</b>	function	<b>isnextchar</b>	function
<b>getcmtchrscs</b>	function	<b>istoken</b>	function
<b>getcmtname</b>	function	<b>new</b>	function
<b>getcommand</b>	function	<b>peek_next</b>	function
<b>getcommandid</b>	function	<b>peek_next_char</b>	function
<b>getcommandvalues</b>	function	<b>peek_next_expanded</b>	function
<b>getcsname</b>	function	<b>peeknext</b>	function
<b>getcstoken</b>	function	<b>peeknextchar</b>	function
<b>getdimension</b>	function	<b>peeknextexpanded</b>	function

<code>pop_macro</code>	<code>function</code>	<code>scan_word</code>	<code>function</code>
<code>popmacro</code>	<code>function</code>	<code>scanargument</code>	<code>function</code>
<code>push_macro</code>	<code>function</code>	<code>scanbox</code>	<code>function</code>
<code>pushmacro</code>	<code>function</code>	<code>scancardinal</code>	<code>function</code>
<code>put_back</code>	<code>function</code>	<code>scanchar</code>	<code>function</code>
<code>put_next</code>	<code>function</code>	<code>scancmdchr</code>	<code>function</code>
<code>putback</code>	<code>function</code>	<code>scancmdchrexploded</code>	<code>function</code>
<code>putnext</code>	<code>function</code>	<code>scancode</code>	<code>function</code>
<code>save_lua</code>	<code>function</code>	<code>scancsname</code>	<code>function</code>
<code>savelua</code>	<code>function</code>	<code>scandelimited</code>	<code>function</code>
<code>scan_argument</code>	<code>function</code>	<code>scandimen</code>	<code>function</code>
<code>scan_box</code>	<code>function</code>	<code>scandimenargument</code>	<code>function</code>
<code>scan_cardinal</code>	<code>function</code>	<code>scanfloat</code>	<code>function</code>
<code>scan_char</code>	<code>function</code>	<code>scan glue</code>	<code>function</code>
<code>scan_cmdchr</code>	<code>function</code>	<code>scaninteger</code>	<code>function</code>
<code>scan_cmdchr_expanded</code>	<code>function</code>	<code>scanintegerargument</code>	<code>function</code>
<code>scan_code</code>	<code>function</code>	<code>scankey</code>	<code>function</code>
<code>scan_csname</code>	<code>function</code>	<code>scankeyword</code>	<code>function</code>
<code>scan_delimited</code>	<code>function</code>	<code>scankeywordcs</code>	<code>function</code>
<code>scan_dimen</code>	<code>function</code>	<code>scanletters</code>	<code>function</code>
<code>scan_dimen_argument</code>	<code>function</code>	<code>scanluacardinal</code>	<code>function</code>
<code>scan_float</code>	<code>function</code>	<code>scanluainteger</code>	<code>function</code>
<code>scan_glue</code>	<code>function</code>	<code>scanluanumber</code>	<code>function</code>
<code>scan_integer</code>	<code>function</code>	<code>scannext</code>	<code>function</code>
<code>scan_integer_argument</code>	<code>function</code>	<code>scannextchar</code>	<code>function</code>
<code>scan_key</code>	<code>function</code>	<code>scannextexploded</code>	<code>function</code>
<code>scan_keyword</code>	<code>function</code>	<code>scanreal</code>	<code>function</code>
<code>scan_keyword_cs</code>	<code>function</code>	<code>scanscale</code>	<code>function</code>
<code>scan_letters</code>	<code>function</code>	<code>scanskip</code>	<code>function</code>
<code>scan_luacardinal</code>	<code>function</code>	<code>scanstring</code>	<code>function</code>
<code>scan_luainteger</code>	<code>function</code>	<code>scantoken</code>	<code>function</code>
<code>scan_luanumber</code>	<code>function</code>	<code>scantokencode</code>	<code>function</code>
<code>scan_next</code>	<code>function</code>	<code>scantokenlist</code>	<code>function</code>
<code>scan_next_char</code>	<code>function</code>	<code>scantoks</code>	<code>function</code>
<code>scan_next_expanded</code>	<code>function</code>	<code>scanvalue</code>	<code>function</code>
<code>scan_real</code>	<code>function</code>	<code>scanword</code>	<code>function</code>
<code>scan_scale</code>	<code>function</code>	<code>serialize</code>	<code>function</code>
<code>scan_skip</code>	<code>function</code>	<code>set_char</code>	<code>function</code>
<code>scan_string</code>	<code>function</code>	<code>set_dimension</code>	<code>function</code>
<code>scan_token</code>	<code>function</code>	<code>set_integer</code>	<code>function</code>
<code>scan_token_code</code>	<code>function</code>	<code>set_lua</code>	<code>function</code>
<code>scan_tokenlist</code>	<code>function</code>	<code>set_macro</code>	<code>function</code>
<code>scan_toks</code>	<code>function</code>	<code>setchar</code>	<code>function</code>
<code>scan_value</code>	<code>function</code>	<code>setdimension</code>	<code>function</code>

<b>setinteger</b>	function	<b>skipnext</b>	function
<b>setlua</b>	function	<b>skipnextexpanded</b>	function
<b>setmacro</b>	function	<b>type</b>	function
<b>skip_next</b>	function	<b>undefine_macro</b>	function
<b>skip_next_expanded</b>	function	<b>undefinemacro</b>	function

# tokens (context)

## accessors table

- F active
- F cmd
- F cmdchrcs
- F cmdname
- F command
- F csname
- F expandable
- F frozen
- F index
- F name
- F protected
- F range

## astable function

## bits table

- N active
- N alignment
- N begingroup
- N character
- N close
- N comment
- N endgroup
- N endoffline
- N escape
- N ignore
- N invalid
- N letter
- N mathshift
- N open
- N other
- N parameter
- N space
- N subscript
- N superscript
- N whitespace

## cache table

- U NC
- U NR
- U bf
- U buff\_finish
- U c\_font\_compact

- U color
- U colordefalc
- U colordefflc
- U colordefflt
- U colordefrlt
- U dofinishreference
- U dostarttext
- U finishjob
- U firstofoneargument
- U firstoftwoarguments
- U gobbleoneargument
- U goto
- U iftrue
- U input
- U loadfoundtypescriptfile
- U resetctxscanner
- U rlap
- U secondoftwoarguments
- U setfalsevalue
- U setsectionblock
- U setupsystem
- U startcolumns
- U starttabulate
- U starttitle
- U startxtitle
- U stopcolumns
- U stoptabulate
- U stoptitle
- U stopxtitle
- U texsetup
- U xmlw

## commands data table

## compile function

## constant function

## converters table

- S toboolean
- S todimen
- S toglue
- S tonumber
- S tostring

## create function



<b>defined</b>	function	F cmdchrexanded
<b>flags</b>	function	F code
<b>getinteger</b>	function	F conditional
<b>getters</b>	table	F count
F box		F csname
F count		F csnameunchecked
F cstoken		F delimited
F dimen		F dimen
F glue		F dimenargument
F macro		F dimension
F meaning		F float
F skip		F glue
F token		F gluespec
<b>gobble</b>	function	F gluevalues
<b>isdefined</b>	function	F hash
<b>istoken</b>	function	F hbox
<b>new</b>	function	F integer
<b>pickup</b>	function	F integerargument
<b>popmacro</b>	function	F ischar
<b>presets</b>	table	F key
T 1 argument		F keyword
T 1 string		F keywordcs
T 2 arguments		F letters
T 2 strings		F list
T 3 arguments		F luacardinal
T 3 strings		F luainteger
T 4 arguments		F luanumber
T 4 strings		F lxmlid
T 5 strings		F next
T 6 strings		F nextchar
T 7 strings		F nextexpanded
T 8 strings		F number
<b>pushmacro</b>	function	F optional
<b>scanners</b>	table	F peek
F argument		F peekchar
F argumentasis		F peekexpanded
F array		F real
F boolean		F scanclose
F box		F scanopen
F bracketed		F skip
F bracketedasis		F skipexpanded
F cardinal		F string
F char		F table
F cmdchr		F token

- F tokencode
- F tokenlist
- F tokens
- F toks
- F value
- F vbox
- F verbatim
- F vtop
- F whd
- F word
- setinteger** function
- setters** table

- F box
- F char
- F count
- F dimen
- F glue
- F lua
- F macro
- F skip

- shortcuts** table

- T bits
  - N active
  - N alignment
  - N begingroup
  - N character
  - N close
  - N comment
  - N endgroup
  - N endofline
  - N escape
  - N ignore
  - N invalid
  - N letter
  - N mathshift
  - N open
  - N other
  - N parameter
  - N space
  - N subscript
  - N superscript
  - N whitespace
- N close
- F inspect

- N open
- F report
- F scanargument
- F scanargumentasis
- F scanarray
- F scanboolean
- F scanbox
- F scanbracketed
- F scanbracketedasis
- F scancardinal
- F scanclose
- F scancode
- F scanconditional
- F scanscsname
- F scanscsnameunchecked
- F scandelimited
- F scandimen
- F scandimenargument
- F scandimension
- F scanglue
- F scangluespec
- F scangluevalues
- F scanhash
- F scanhbox
- F scaninteger
- F scanintegerargument
- F scankeyword
- F scankeywordcs
- F scanletters
- F scanlist
- T scanners
  - F argument
  - F argumentasis
  - F array
  - F boolean
  - F box
  - F bracketed
  - F bracketedasis
  - F cardinal
  - F char
  - F cmdchr
  - F cmdchrexplanded
  - F code
  - F conditional

F count	F toks
F csname	F value
F csnameunchecked	F vbox
F delimited	F verbatim
F dimen	F vtop
F dimenargument	F whd
F dimension	F word
F float	F scannumber
F glue	F scanopen
F gluespec	F scanoptional
F gluevalues	F scanstring
F hash	F scantable
F hbox	F scantokenlist
F integer	F scantoks
F integerargument	F scanvbox
F ischar	F scanverbatim
F key	F scanvtop
F keyword	F scanword
F keywordcs	F toboolean
F letters	F todimen
F list	T tokens
F luacardinal	T accessors
F luainteger	F active
F luanumber	F cmd
F lxmlid	F cmdchrsc
F next	F cmdname
F nextchar	F command
F nextexpanded	F csname
F number	F expandable
F optional	F frozen
F peek	F index
F peekchar	F name
F peekexpanded	F protected
F real	F range
F scanclose	F astable
F scanopen	T cache
F skip	U NC
F skipexpanded	U NR
F string	U bf
F table	U buff_finish
F token	U c_font_compact
F tokencode	U color
F tokenlist	U colordefalc
F tokens	U colordefflc

U colordefflt	F cstoken
U colordefrlt	F dimen
U dofinishreference	F glue
U dostarttext	F macro
U finishjob	F meaning
U firstofoneargument	F skip
U firstoftwoarguments	F token
U gobbleoneargument	F gobble
U goto	F isdefined
U iftrue	F istoken
U input	F new
U loadfoundtypescriptfile	F pickup
U resetctxscanner	F popmacro
U rlap	T presets
U secondoftwoarguments	F pushmacro
U setfalsevalue	F setinteger
U setsectionblock	T setters
U setupsystem	F box
U startcolumns	F char
U starttabulate	F count
U starttitle	F dimen
U startxtitle	F glue
U stopcolumns	F lua
U stoptabulate	F macro
U stoptitle	F skip
U stopxtitle	T shortcuts
U texsetup	N close
U xmlw	F inspect
D commands	N open
F compile	F report
F constant	F scanargument
T converters	F scanargumentasis
S toboolean	F scanarray
S todimen	F scanboolean
S toglue	F scanbox
S tonumber	F scanbracketed
S tostring	F scanbracketedasis
F create	F scancardinal
F defined	F scanclose
F flags	F scancode
F getinteger	F scanconditional
T getters	F scansname
F box	F scansnameunchecked
F count	F scandalimited

F scandimen	F scanstring
F scandimenargument	F scantable
F scandimension	F scantokenlist
F scanglue	F scantoks
F scangluespec	F scanvbox
F scangluevalues	F scanverbatim
F scanhash	F scanvtop
F scanhbox	F scanword
F scaninteger	F tobboolean
F scanintegerargument	F todimen
F scankeyword	F tonumber
F scankeywordcs	F tostring
F scanletters	D values
F scanlist	F tonumber
F scannumber	F tostring
F scanopen	<b>values</b> data table
F scanoptional	

## tracers (context)

**printerror**    function  
**printwarning**    function

**showlines**    function

## trackers (context)

<b>data</b>	data table	<b>register</b>	function
<b>default</b>	function	<b>report</b>	function
<b>disable</b>	function	<b>reset</b>	function
<b>done</b>	table	<b>savehash</b>	function
<b>dumphashtofile</b>	function	<b>show</b>	function
<b>enable</b>	function	<b>value</b>	function
<b>list</b>	function	<b>values</b>	function
<b>name</b>	string		

# typesetters (context)

<b>alignments</b>	table				T handlers
F handler					F installhandler
F set					F processmath
<b>breakpoints</b>	table				F set
F define					F setcolor
F handler					F setmath
D mapping					F tomode
T methods				<b>firstlines</b>	table
T numbers				T actions	
F set				F default	
F setreplacement				F line	
<b>cases</b>	table			F word	
T actions				F handler	
F handler				F set	
F register				<b>fontkerns</b>	table
F set				F handler	
<b>characteralign</b>	table			<b>initials</b>	table
F handler				T actions	
F resetcharacteralign				F default	
F setcharacteralign				F handler	
<b>characters</b>	table			F set	
F handler				<b>injectors</b>	table
T methods				F check	
F replacensp				T list	
F replacenspaces				F mark	
<b>checkers</b>	table			F reset	
F handler				F set	
F reset				F show	
F set				<b>italics</b>	table
<b>cleaners</b>	table			F enablemath	
F handler				F enabletext	
F set				F forcevariant	
<b>digits</b>	table			F handler	
T actions				F reset	
F handler				F set	
F set				<b>kerns</b>	table
<b>directions</b>	table			D factors	
F getfences				F handler	
F getglobal				F keepligature	
F getmethod				D mapping	
F handler				F set	



**localboxes**            table

F handler

**manipulators**        table

F apply

F applyspecification

T methods

F Word

F Words

F abbreviatedjournal

F expandedjournal

F lowercase

F stripperperiod

F uppercase

T patterns

U list

U pair

F splitspecification

**margins**            table

F finalhandler

F globalhandler

F localhandler

F save

**marksuspects**        function

**paragraphs**        table

F addanchortoline

F addtoline

F calculatedelta

F checkline

F moveinline

**periodkerns**        table

D factors

F handler

D mapping

F set

**processors**        table

F apply

F register

F reset

F split

F startapply

F stopapply

F stripped

F toString

**rubies**            table

F attach

F check

**showsuspects**        function

**spacings**            table

F define

F handler

D mapping

T numbers

T frenchpunctuation

T characters

S name

N number

F reset

F set

F setup

**synchronize**        table

F handler

**wrappers**            table

F handler

**xtables**            table

F cleanup

F construct

F create

F finish\_row

F flush

F initialize\_construct

F initialize\_reflow\_height

F initialize\_reflow\_width

F next\_row

F reflow\_height

F reflow\_width

F set\_construct

F set\_reflow\_height

F set\_reflow\_width

## updaters (context)

**apply**      function  
**register**   function

## url (context)

<b>addscheme</b>	function
<b>barepath</b>	function
<b>construct</b>	function
<b>decode</b>	function
<b>encode</b>	function
<b>escape</b>	function
<b>filename</b>	function

<b>hashed</b>	function
<b>hasscheme</b>	function
<b>query</b>	function
<b>split</b>	function
<b>toquery</b>	function
<b>unescape</b>	function
<b>unescapeget</b>	function

## utf8 (basic lua)

**char**            function  
**charpattern**   string  
**codepoint**     function

**codes**          function  
**len**            function  
**offset**         function

# utilities (context)

## **debugger**            table

F disable  
F enable  
F savestats  
F showstats  
F showtraceback

## **files**                table

F close  
F getposition  
F getsize  
F look  
F open  
F read2dot14  
F readbyte  
F readbytes  
F readbytetable  
F readcardinal  
F readcardinal1  
F readcardinal1le  
F readcardinal2  
F readcardinal2le  
F readcardinal3  
F readcardinal3le  
F readcardinal4  
F readcardinal4le  
F readcardinaltable  
F readchar  
F readcline  
F readcstring  
F readfixed2  
F readfixed4  
F readinteger  
F readinteger1  
F readinteger1le  
F readinteger2  
F readinteger2le  
F readinteger3  
F readinteger3le  
F readinteger4  
F readinteger4le  
F readintegertable

F readsignedbyte  
F readstring  
F readtag  
F setposition  
F size  
F skip  
F skiplong  
F skipposition  
F skipshort  
F writebyte  
F writecardinal1  
F writecardinal1le  
F writecardinal2  
F writecardinal2le  
F writecardinal3  
F writecardinal3le  
F writecardinal4  
F writecardinal4le  
F writeinteger1  
F writeinteger1le  
F writeinteger2  
F writeinteger2le  
F writeinteger3  
F writeinteger3le  
F writeinteger4  
F writeinteger4le  
F writestring

## **formatters**           table

F formatcolumns  
F list  
F stripzeros

## **ghostscript**           table

F convert  
F statistics

## **graphicmagick**        table

F convert  
F statistics

## **graphicsmagick**      table

F convert  
F statistics

## **lua**                    table

- B alwaysstripcode
- F checkmemory
- F compile
- F loadedluacode
- F loadstring
- F loadstripped
- N nofstrippedbytes
- N nofstrippedchunks
- F registerfinalizer
- B stripcode
- T strippedchunks
- F strippedloadstring
- T suffixes
  - S lua
  - S luc
  - S lui
  - S luj
  - S luv
  - S tma
  - S tmc
  - S tua
  - S tuc

## packers table

- F hashed
- F new
- F pack
- F simplehashed
- F strip
- F unpack
- N version

## parsers table

- F add\_settings\_to\_array
- F arguments\_to\_table
- F array\_to\_string
- F csvsplitter
- F getparameters
- F groupedsplitat
- F hash\_to\_string
- T hashes
  - T settings\_to\_set
    - T text,hidden,paper,page,leftpage,rightpage
      - B hidden
      - B leftpage
      - B page

- B paper
- B rightpage
- B text
- F iterator
- F keq\_to\_hash
- F listitem
- F make\_settings\_to\_hash\_pattern
- F mergehashes
- F options\_to\_array
- F options\_to\_hash
- T patterns
  - U settings\_to\_array
  - U settings\_to\_hash\_a
  - U settings\_to\_hash\_b
  - U settings\_to\_hash\_c
  - U settings\_to\_hash\_d
  - U unittotex
- F process\_stripped\_settings
- F rfc4180splitter
- F runtime
- F settings\_to\_array
- F settings\_to\_array\_obey\_fences
- F settings\_to\_array\_with\_repeat
- F settings\_to\_hash
- F settings\_to\_hash\_colon\_too
- F settings\_to\_hash\_strict
- F settings\_to\_hash\_tolerant
- F settings\_to\_numbers
- F settings\_to\_set
- F simple\_hash\_to\_string
- F splitmethod
- F splitthousands
- F stepper
- F stripped\_settings\_to\_array
- F totime
- F unittotex
- F unittoxml

## randomizer table

- F get
- F getnumber
- F getrepeatable
- F getrepeatableseed
- F getseed
- F newrepeatable

F popseed		F sparse	
F pushseed		<b>streams</b>	table
F repeatable		F close	
F reuseseed		F getposition	
F setseed		F getsize	
F setseedi		F getstring	
<b>randomizers</b>	table	F look	
F poisson		F open	
<b>sequencers</b>	table	F openstring	
F appendaction		F read2dot14	
F appendgroup		F readbyte	
F compile		F readbytes	
F disableaction		F readbytetable	
F disablegroup		F readcardinal	
F enableaction		F readcardinal1	
F enablegroup		F readcardinal11e	
D functions		F readcardinal2	
F localize		F readcardinal21e	
F new		F readcardinal3	
F nodeprocessor		F readcardinal31e	
F prependaction		F readcardinal4	
F prependgroup		F readcardinal41e	
F removeaction		F readcardinaltable	
F replaceaction		F readchar	
F setkind		F readcline	
F tostring		F readcstring	
<b>setters</b>	table	F readfixed2	
F disable		F readfixed4	
F enable		F readinteger	
F initialize		F readinteger1	
F list		F readinteger11e	
F new		F readinteger2	
F register		F readinteger21e	
F report		F readinteger3	
F reset		F readinteger31e	
F show		F readinteger4	
<b>stacker</b>	table	F readinteger41e	
F new		F readintegertable	
<b>storage</b>	table	F readsignedbyte	
F allocate		F readstring	
F checked		F setposition	
F mark		F size	
F marked		F skip	
F setinitializer		F skipbytes	

F skiplong	F removevalue	
F skipshort	F replacevalue	
F tocardinal1	<b>tar</b>	<b>table</b>
F tocardinal1le	T archives	
F tocardinal2	F closearchive	
F tocardinal2le	T files	
F tocardinal3	F fetch	
F tocardinal3le	F hash	
F tocardinal4	F list	
F tocardinal4le	F pack	
<b>strings</b>	F unpack	
F collapse	F openarchive	
F collapsecrlf	T registeredfiles	
T formatters	T streams	
F add	F fetch	
F new	F hash	
F newcollector	F list	
F newrepeater	F pack	
F nice	F unpack	
T striplinepatterns	T strings	
U collapse	F fetch	
U prune	F hash	
U prune and collapse	F list	
U prune and no empty	F pack	
U prune and to space	F unpack	
U retain	<b>templates</b>	<b>table</b>
U retain and collapse	F load	
U retain and no empty	F replace	
F striplines	F replacer	
F striplong	F resolve	
F tabtospace	<b>zipfiles</b>	<b>table</b>
T tracers	F close	
<b>tables</b>	F found	
F accesstable	F hash	
F definedtable	F list	
F definetable	F open	
F encapsulate	F unzip	
F insertaftervalue	F unzipdir	
F insertbeforevalue	F zipdir	
F migratetable		



## visualizers (context)

<b>escapepatterns</b>	data table	<b>signal</b>	string
<b>getspecification</b>	function	<b>signalpattern</b>	userdata
<b>getvisualizer</b>	function	<b>specifications</b>	data table
<b>load</b>	function	<b>visualize</b>	function
<b>makenested</b>	function	<b>visualizebuffer</b>	function
<b>makepattern</b>	function	<b>visualizefile</b>	function
<b>newgrammar</b>	function	<b>visualizestring</b>	function
<b>newhandler</b>	function	<b>write</b>	function
<b>parsedxml</b>	function	<b>writeargument</b>	function
<b>pattern</b>	function	<b>writedefault</b>	function
<b>register</b>	function	<b>writeemptyline</b>	function
<b>registerescapecommand</b>	function	<b>writenewline</b>	function
<b>registerescapepline</b>	function	<b>writespace</b>	function
<b>registerescapepattern</b>	function		

# xcomplex (extra lua)

<b>I</b>	function	F sqrt	
<b>__add</b>	function	F tan	
<b>__div</b>	function	F tanh	
<b>__eq</b>	function	F topair	
<b>__index</b>	table	F tostring	
F I		F totable	
F __add		F __mul	
F __div		S __name	
F __eq		F __pow	
T __index		F __sub	
F I		F __tostring	
F __add		F __unm	
F __div		F abs	
F __eq		F acos	
F __mul		F acosh	
S __name		F arg	
F __pow		F asin	
F __sub		F asinh	
F __tostring		F atan	
F __unm		F atanh	
F abs		F conj	
F acos		F cos	
F acosh		F cosh	
F arg		F exp	
F asin		F i	
F asinh		F imag	
F atan		F log	
F atanh		F new	
F conj		F pow	
F cos		F proj	
F cosh		F real	
F exp		F sin	
F i		F sinh	
F imag		F sqrt	
F log		F tan	
F new		F tanh	
F pow		F topair	
F proj		F tostring	
F real		F totable	
F sin		<b>__mul</b>	function
F sinh		<b>__name</b>	string

<b>__pow</b>	function	<b>i</b>	function
<b>__sub</b>	function	<b>imag</b>	function
<b>__tostring</b>	function	<b>log</b>	function
<b>__unm</b>	function	<b>new</b>	function
<b>abs</b>	function	<b>pow</b>	function
<b>acos</b>	function	<b>proj</b>	function
<b>acosh</b>	function	<b>real</b>	function
<b>arg</b>	function	<b>sin</b>	function
<b>asin</b>	function	<b>sinh</b>	function
<b>asinh</b>	function	<b>sqrt</b>	function
<b>atan</b>	function	<b>tan</b>	function
<b>atanh</b>	function	<b>tanh</b>	function
<b>conj</b>	function	<b>topair</b>	function
<b>cos</b>	function	<b>tostring</b>	function
<b>cosh</b>	function	<b>totable</b>	function
<b>exp</b>	function		

## xdecimal (extra lua)

<b>__add</b>	function	F getprecision
<b>__band</b>	function	F ln
<b>__bor</b>	function	F log
<b>__bxor</b>	function	F max
<b>__div</b>	function	F min
<b>__eq</b>	function	F minus
<b>__idiv</b>	function	F new
<b>__index</b>	table	F plus
F __add		F pow
F __band		F rotate
F __bor		F setprecision
F __bxor		F shift
F __div		F sqrt
F __eq		F toengstring
F __idiv		F tonumber
T __index		F tostring
F __add		F trim
F __band		F __le
F __bor		F __lt
F __bxor		F __mod
F __div		F __mul
F __eq		S __name
F __idiv		F __pow
F __le		F __shl
F __lt		F __shr
F __mod		F __sub
F __mul		F __tostring
S __name		F __unm
F __pow		F abs
F __shl		F band
F __shr		F bor
F __sub		F bxor
F __tostring		F conj
F __unm		F copy
F abs		F exp
F band		F getprecision
F bor		F ln
F bxor		F log
F conj		F max
F copy		F min
F exp		F minus

F new		<b>band</b>	function
F plus		<b>bor</b>	function
F pow		<b>bxor</b>	function
F rotate		<b>conj</b>	function
F setprecision		<b>copy</b>	function
F shift		<b>exp</b>	function
F sqrt		<b>getprecision</b>	function
F toengstring		<b>ln</b>	function
F tonumber		<b>log</b>	function
F tostring		<b>max</b>	function
F trim		<b>min</b>	function
<b>__le</b>	function	<b>minus</b>	function
<b>__lt</b>	function	<b>new</b>	function
<b>__mod</b>	function	<b>plus</b>	function
<b>__mul</b>	function	<b>pow</b>	function
<b>__name</b>	string	<b>rotate</b>	function
<b>__pow</b>	function	<b>setprecision</b>	function
<b>__shl</b>	function	<b>shift</b>	function
<b>__shr</b>	function	<b>sqrt</b>	function
<b>__sub</b>	function	<b>toengstring</b>	function
<b>__tostring</b>	function	<b>tonumber</b>	function
<b>__unm</b>	function	<b>tostring</b>	function
<b>abs</b>	function	<b>trim</b>	function

## xmath (extra lua)

<b>acos</b>	function
<b>acosh</b>	function
<b>asin</b>	function
<b>asinh</b>	function
<b>atan</b>	function
<b>atan2</b>	function
<b>atanh</b>	function
<b>cbrt</b>	function
<b>ceil</b>	function
<b>copysign</b>	function
<b>cos</b>	function
<b>cosh</b>	function
<b>deg</b>	function
<b>erf</b>	function
<b>erfc</b>	function
<b>exp</b>	function
<b>exp2</b>	function
<b>expm1</b>	function
<b>fabs</b>	function
<b>fdim</b>	function
<b>floor</b>	function
<b>fma</b>	function
<b>fmax</b>	function
<b>fmin</b>	function
<b>fmod</b>	function
<b>frexp</b>	function
<b>gamma</b>	function
<b>hypot</b>	function
<b>inf</b>	number
<b>isfinite</b>	function
<b>isinf</b>	function
<b>isnan</b>	function

<b>isnormal</b>	function
<b>j0</b>	function
<b>j1</b>	function
<b>jn</b>	function
<b>ldexp</b>	function
<b>lgamma</b>	function
<b>log</b>	function
<b>log10</b>	function
<b>log1p</b>	function
<b>log2</b>	function
<b>logb</b>	function
<b>modf</b>	function
<b>nan</b>	number
<b>nearbyint</b>	function
<b>nextafter</b>	function
<b>pi</b>	number
<b>pow</b>	function
<b>rad</b>	function
<b>remainder</b>	function
<b>remquo</b>	function
<b>round</b>	function
<b>scalbn</b>	function
<b>sin</b>	function
<b>sinh</b>	function
<b>sqrt</b>	function
<b>tan</b>	function
<b>tanh</b>	function
<b>tgamma</b>	function
<b>trunc</b>	function
<b>y0</b>	function
<b>y1</b>	function
<b>yn</b>	function

# xml (context)

<b>addentitiesdoctype</b>	function	F family	
<b>addspecialcode</b>	function	F fontspecification	
<b>after</b>	function	F mappedstylevalue	
<b>all</b>	function	F padding	
<b>applylpath</b>	function	F size	
<b>applyselector</b>	function	F style	
<b>assign</b>	function	F stylevalue	
<b>attribute</b>	function	F todimension	
<b>badinclusions</b>	function	F variant	
<b>before</b>	function	F weight	
<b>body</b>	function	<b>defaulthandlers</b>	table
<b>builtinentities</b>	table	D file	
B amp		D parsedxml	
B apos		D string	
B gt		D tex	
B lt		D texline	
B quot		D texspace	
<b>CDATA</b>	function	D verbose	
<b>CDATATOTEXT</b>	function	<b>defaultprotocol</b>	string
<b>checkbom</b>	function	<b>delete</b>	function
<b>checkedempty</b>	function	<del>delete_element</del>	function
<b>checkerror</b>	function	<b>despecialized</b>	function
<b>checknamespace</b>	function	<b>each</b>	function
<b>checkns</b>	function	<del>each_element</del>	function
<b>cleansed</b>	function	<b>elements</b>	function
<b>collect</b>	function	<b>elementtocdata</b>	function
<del>collect_elements</del>	function	<b>empty</b>	function
<b>collect_tags</b>	function	<b>entities</b>	data table
<del>collect_texts</del>	function	<b>erase</b>	function
<b>collected</b>	function	<b>errorhandler</b>	function
<b>collecttexts</b>	function	<b>escaped</b>	function
<b>compactelement</b>	function	<b>expand</b>	function
<b>content</b>	function	<b>expressions</b>	table
<b>convert</b>	function	F attribute	
<b>copy</b>	function	F boolean	
<b>count</b>	function	F child	
<b>cprint</b>	function	F contains	
<b>CSS</b>	table	F count	
F applyselector		F error	
F colorspecification		F find	
F dimension		F hasclass	

F idstring		F text	
F lower		F upper	
F name		F upperall	
F number		F xml	
F oneof		T xml	
F print		F all	
F quit		F att	
F tag		F attribute	
F text		F attributes	
F undefined		F cdata	
F upper		F chainattribute	
<b>fillin</b>	function	F count	
<b>filter</b>	function	F default	
<b>finalizers</b>	table	F elements	
F paragraphs		F empty	
T tex		F first	
F all		F function	
F attribute		F index	
F chainattribute		F last	
F chainpath		F lowerall	
F command		F match	
F concat		F name	
F concatrange		F position	
F context		F reverse	
F count		F table	
F ctxtext		F tag	
F default		F tags	
F depth		F text	
F first		F texts	
F function		F upperall	
F index		<b>first</b>	function
F last		<b>found</b>	function
F lettered		<b>functions</b>	table
F lower		F classes	
F lowerall		F hasclass	
F match		<b>getbuffer</b>	function
F name		<b>gethandlers</b>	function
F param		<b>gethandlersfunction</b>	function
F parameter		<b>helpers</b>	table
F position		F recursetext	
F reverse		<b>include</b>	function
F stripped		<b>inclusion</b>	function
F tag		<b>inclusions</b>	function
F tags		<b>index</b>	function



<b>inheritattributes</b>	function	<b>privatecodes</b>	table
<b>inheritedconvert</b>	function	<b>privatetoken</b>	function
<b>inject</b>	function	<b>process</b>	function
<b>inject_element</b>	function	<b>process_attributes</b>	function
<b>inject_element_after</b>	function	<b>process_elements</b>	function
<b>inject_element_before</b>	function	<b>processattributes</b>	function
<b>injectafter</b>	function	<b>profiled</b>	table
<b>injectbefore</b>	function	<b>pure</b>	function
<b>insert</b>	function	<b>pushmatch</b>	function
<b>insert_element</b>	function	<b>raw</b>	function
<b>insert_element_after</b>	function	<b>registerentity</b>	function
<b>insert_element_before</b>	function	<b>registerns</b>	function
<b>insertafter</b>	function	<b>reindex</b>	function
<b>insertbefore</b>	function	<b>remap_name</b>	function
<b>insertcdata</b>	function	<b>remap_namespace</b>	function
<b>insertcomment</b>	function	<b>remap_tag</b>	function
<b>inspect</b>	function	<b>remapname</b>	function
<b>is_valid</b>	function	<b>remapnamespace</b>	function
<b>kind</b>	function	<b>remaptag</b>	function
<b>last</b>	function	<b>rename</b>	function
<b>lastmatch</b>	function	<b>renamespace</b>	function
<b>load</b>	function	<b>reparsedentitylpeg</b>	userdata
<b>lpath</b>	function	<b>replace</b>	function
<b>lpathcached</b>	function	<b>replace_element</b>	function
<b>lpathcalls</b>	function	<b>resetinjectors</b>	function
<b>lshow</b>	function	<b>resolvns</b>	function
<b>makestandalone</b>	function	<b>root</b>	function
<b>match</b>	function	<b>save</b>	function
<b>name</b>	function	<b>selection</b>	function
<b>newhandlers</b>	function	<b>separate</b>	function
<b>nodesettostring</b>	function	<b>serialize</b>	function
<b>originalload</b>	function	<b>serializetotext</b>	function
<b>package</b>	function	<b>setcdata</b>	function
<b>parent</b>	function	<b>setcomment</b>	function
<b>parsedentitylpeg</b>	userdata	<b>sethandlersfunction</b>	function
<b>pihandlers</b>	table	<b>setinjectors</b>	function
F injector		<b>setproperty</b>	function
F tex		<b>settings</b>	function
<b>placeholders</b>	table	<b>specialcodes</b>	table
F unknown_any_entity		S "	
F unknown_dec_entity		S #	
F unknown_hex_entity		S \$	
<b>popmatch</b>	function	S %	
<b>position</b>	function	S &	

<code>S '</code>		<code>texttocdata</code>	function
<code>S &lt;</code>		<code>tocdata</code>	function
<code>S &gt;</code>		<code>toelement</code>	function
<code>S \</code>		<code>tostring</code>	function
<code>S {</code>		<code>totable</code>	function
<code>S  </code>		<code>toxml</code>	function
<code>S }</code>		<code>tprint</code>	function
<code>S ~</code>		<code>traverse</code>	function
<code>specialhandler</code>	table	<code>unescaped</code>	function
<code>sprint</code>	function	<code>unescapedentitylpeg</code>	userdata
<code>string</code>	function	<code>unprivatized</code>	function
<code>strip</code>	function	<code>unspecialized</code>	function
<code>strip_whitespace</code>	function	<code>wipe</code>	function
<code>stripelement</code>	function	<code>withelement</code>	function
<code>stripleadingspaces</code>	function	<code>withelements</code>	function
<code>table</code>	function	<code>wrap</code>	function
<code>text</code>	function	<code>xmlns</code>	table
<code>textonly</code>	function		

## xzip (extra lua)

**adler32**           function  
**compress**        function  
**compresssize**    function

**crc32**            function  
**decompress**      function  
**decompresssize** function

## zip (extra lua)

**archives**

table

**closearchive**

function

**openarchive**

function

**registeredfiles**

table

## zlib (extra lua)

**adler32**           function  
**compress**        function  
**compresssize**   function

**crc32**           function  
**decompress**      function  
**decompresssize** function