

MP attributes backends bit **bit32** blobs  
boolean buffers builders caches **callback**  
callbacks catcodes characters chemistry  
commands containers context converters  
**coroutine** ctxrunner **debug** dir directives  
document documentdata environment **epdf**  
experiments figures **file** floats **font**  
**fontloader** fonts functions global graphics  
**gzip** **img** interactions interfaces **io** jit job  
**lang** languages layouts **lfs** libraries lmx  
logs lpdf **lpeg** **ltn12** **lua** luatex lxml **math**  
mathematics mbox **md5** metapost **mime**  
moduledata modules mp **mplib** noads **node**  
nodes number **os** **package** pagebuilders  
parametersets pattern **pdf** pdfscanner  
physics **profiler** publications regimes  
resolvers scripts set **socket** sorters  
statistics **status** storage streams **string**  
structures **table** **tex** **texconfig** **texio**  
thirddata **token** tokens tracers trackers  
typesetters **unicode** url userdata utilities  
vf visualizers xml **zip** **zlib**

# ConTEXT MkIV

# global (alias: \_G)

|                            |          |                 |          |
|----------------------------|----------|-----------------|----------|
| MP                         | table    | environment     | table    |
| _LUAVERSION                | number   | epdf            | table    |
| _MAJORVERSION              | number   | error           | function |
| _MINORVERSION              | number   | experiments     | table    |
| _cldo_                     | function | figures         | table    |
| arg                        | table    | file            | table    |
| assert                     | function | floats          | table    |
| attributes                 | table    | font            | table    |
| backends                   | table    | fontloader      | table    |
| beginpage                  | function | fonts           | table    |
| bit                        | table    | format_n        | function |
| bit32                      | table    | frozen          | boolean  |
| blobs                      | table    | functions       | table    |
| boolean                    | table    | gcinfo          | function |
| border_set                 | boolean  | getfenv         | function |
| buffers                    | table    | getmetatable    | function |
| builders                   | table    | getpos          | function |
| caches                     | table    | getreadfilename | function |
| callback                   | table    | getvpos         | function |
| callbacks                  | table    | global          | table    |
| catcodes                   | table    | graphics        | table    |
| characters                 | table    | gzip            | table    |
| chemistry                  | table    | img             | table    |
| collectgarbage             | function | inspect         | function |
| commands                   | table    | interactions    | table    |
| containers                 | table    | interfaces      | table    |
| context                    | function | io              | table    |
| context_applyprocessor     | function | ipairs          | function |
| context_firstofoneargument | function | jit             | table    |
| converters                 | table    | job             | table    |
| coroutine                  | table    | lang            | table    |
| ctxrunner                  | table    | languages       | table    |
| debug                      | table    | layouts         | table    |
| delta                      | number   | lfs             | table    |
| dimen                      | function | libraries       | table    |
| dir                        | table    | lmx             | table    |
| directives                 | table    | lmxconvert      | function |
| document                   | table    | lmxnew          | function |
| documentdata               | table    | load            | function |
| dofile                     | function | loadfile        | function |
| endpage                    | function | loadstring      | function |

|                 |          |                   |          |
|-----------------|----------|-------------------|----------|
| logs            | table    | publications      | table    |
| lp_fastpos_n    | userdata | rawequal          | function |
| lp_fastpos_p    | userdata | rawget            | function |
| lpdf            | table    | rawlen            | function |
| lpeg            | table    | rawset            | function |
| ltn12           | table    | regimes           | table    |
| lua             | table    | report_characters | function |
| luatex          | table    | require           | function |
| lxml            | table    | resolve_fences    | function |
| marknocite      | function | resolvers         | table    |
| math            | table    | scripts           | table    |
| mathematics     | table    | select            | function |
| mbox            | table    | set               | table    |
| md5             | table    | setcharacteralign | function |
| metapost        | table    | setfenv           | function |
| mime            | table    | setinspector      | function |
| module          | function | setmetatable      | function |
| moduledata      | table    | socket            | table    |
| modules         | table    | sorters           | table    |
| mp              | table    | statistics        | table    |
| mplib           | table    | status            | table    |
| newline         | function | storage           | table    |
| newproxy        | function | streams           | table    |
| next            | function | string            | table    |
| noads           | table    | stripmath         | function |
| node            | table    | structures        | table    |
| nodes           | table    | swiglib           | function |
| number          | table    | table             | table    |
| optionalrequire | function | tex               | table    |
| os              | table    | texconfig         | table    |
| outputpagestree | function | texio             | table    |
| package         | table    | thirddata         | table    |
| pagebuilders    | table    | toboolean         | function |
| pairs           | function | token             | table    |
| parametersets   | table    | tokens            | table    |
| pattern         | table    | tonumber          | function |
| pcall           | function | tostring          | function |
| pdf             | table    | trace_characters  | boolean  |
| pdfborder       | function | tracers           | table    |
| pdfscanner      | table    | trackers          | table    |
| physics         | table    | type              | function |
| print           | function | typesetters       | table    |
| profiler        | table    | unicode           | table    |
| protect         | function | unpack            | function |

|                          |          |
|--------------------------|----------|
| <code>url</code>         | table    |
| <code>userdata</code>    | table    |
| <code>utf</code>         | table    |
| <code>utilities</code>   | table    |
| <code>vf</code>          | table    |
| <code>visualizers</code> | table    |
| <code>xml</code>         | table    |
| <code>xmlconvert</code>  | function |
| <code>xpcall</code>      | function |
| <code>zip</code>         | table    |
| <code>zlib</code>        | table    |

# attributes (context)

## colorintents table

- N attribute
- D data
- F enable
- F handler
- F register
- D registered

## colors table

- N attribute
- F cmyk
- F cmyktogray
- F cmyktorgb
- F colorcomponents
- B couple
- D data
- N default
- F defineintermediatecolor
- F definemixcolor
- F definemultitonecolor
- F defineprocesscolor
- F definesimplegray
- F definespotcolor
- F definetransparency
- F enable
- F filter
- F forcedmodel
- F forcesupport
- F formatcolor
- F formatgray
- F gray
- F graytohsv
- F handler
- F hsvtorgay
- F hsvtorgb
- F iccprofile
- F isblack
- N main
- S model
- D models
- F mpcolor
- F mpnamedcolor

- F mpoptions
- U none
- F popset
- F processcolorcomponents
- F pushset
- F register
- D registered
- F registerspotcolor
- F rgb
- F rgbtocmyk
- F rgbtorgay
- F rgbtohsv
- N selector
- F setlist
- F setmodel
- D sets
- F spec
- F spot
- F spotcolorname
- F spotcolorparent
- F spotcolorvalue
- B supported
- F transparencycomponents
- B triggering
- F usecolors
- F value
- D values
- B weightgray

## define function effects table

- N attribute
- D data
- F enable
- F handler
- F register
- D registered
- D values

## handlers table list data table names data table negatives table

|                       |            |                 |
|-----------------------|------------|-----------------|
| N attribute           |            | F register      |
| D data                |            | D registered    |
| F enable              |            | F resolve_begin |
| F handler             |            | F resolve_end   |
| F register            |            | F resolve_step  |
| D registered          |            | D scopes        |
| <b>numbers</b>        | data table | F setfeatures   |
| <b>ofnode</b>         | function   | F start         |
| <b>private</b>        | function   | F stop          |
| <b>public</b>         | function   | B supported     |
| <b>showcurrent</b>    | function   | D values        |
| <b>states</b>         | table      |                 |
| F disabletriggering   |            |                 |
| F enabletriggering    |            |                 |
| F finalize            |            |                 |
| F initialize          |            |                 |
| F process             |            |                 |
| F selective           |            |                 |
| F stacked             |            |                 |
| F stacker             |            |                 |
| <b>system</b>         | function   |                 |
| <b>transparencies</b> | table      |                 |
| N attribute           |            |                 |
| D data                |            |                 |
| F enable              |            |                 |
| F forcesupport        |            |                 |
| F handler             |            |                 |
| U none                |            |                 |
| F register            |            |                 |
| D registered          |            |                 |
| B supported           |            |                 |
| B triggering          |            |                 |
| F value               |            |                 |
| D values              |            |                 |
| <b>unsetvalue</b>     | number     |                 |
| <b>viewerlayers</b>   | table      |                 |
| N attribute           |            |                 |
| D data                |            |                 |
| F define              |            |                 |
| F enable              |            |                 |
| F forcesupport        |            |                 |
| F handler             |            |                 |
| B hasorder            |            |                 |
| D listwise            |            |                 |

# backends (context)

**codeinjections** table

F synchronizecolormodel

**current** string

**defaults** table

T codeinjections

F gethpos

F getmatrix

F getpos

F getvpos

F hasmatrix

T nodeinjections

T registrations

D tables

**install** function

**nodeinjections** table

F restore

F save

F transform

**nothing** function

**pdf** table

T codeinjections

F addbookmarks

F attachmentid

F clonefield

F definefield

F definefieldset

F defineviewerlayer

F embedfile

F enabletags

F exportformdata

F getdefaultfieldvalue

F getfieldcategory

F getfieldset

F getformatoption

F gethpos

F getmatrix

F getoutputfilename

F getpos

F getpreviewfigure

F getvpos

F hasmatrix

F insertrenderingwindow

F mergereferences

F mergeviewerlayers

F prerollreference

F presetsymbol

F presetsymbollist

F processrendering

F registerdocumentcloseaction

F registerdocumentopenaction

F registeredsymbol

F registerpagecloseaction

F registerpageopenaction

F registersymbol

F setfieldcalculationset

F setfigurealternative

F setfigurecolorspace

F setfiguremask

F setformat

F setformsmethod

F setpagetransition

F setupcanvas

F setupidentity

F setxmpfile

F startlayer

F stoplayer

F supportedformats

F unicodetoactualtext

F useviewerlayer

F validfield

F validfieldcategory

F validfieldset

S comment

T nodeinjections

F addtags

F annotation

F attachfile

F changestackedlayer

F cmykcolor

F comment

F destination

F effect

- F graycolor
- F injectbitmap
- F insertmovie
- F insertsound
- F insertswf
- F insertu3d
- F knockout
- F negative
- F overprint
- F positive
- F reference
- F rgbcolor
- F spotcolor
- F startlayer
- F startstackedlayer
- F stoplayer
- F stopstackedlayer
- F transparency
- F typesetfield
- T registrations
  - F cmykindexcolor
  - F cmykspotcolor
  - F getspotcolorreference
  - F grayindexcolor
  - F grayspotcolor
  - F rgbindexcolor
  - F rgbspotcolor
  - F spotcolorname
  - F transparency

- T tables

- D vfspecials

**registrations**      table

**tables**              table



## bit (context)

|                |          |
|----------------|----------|
| <b>arshift</b> | function |
| <b>band</b>    | function |
| <b>bnot</b>    | function |
| <b>bor</b>     | function |
| <b>bswap</b>   | function |
| <b>bxor</b>    | function |
| <b>lshift</b>  | function |
| <b>rol</b>     | function |
| <b>ror</b>     | function |
| <b>rshift</b>  | function |
| <b>tobit</b>   | function |
| <b>tohex</b>   | function |

## bit32 (basic lua)

|                |          |
|----------------|----------|
| <b>arshift</b> | function |
| <b>band</b>    | function |
| <b>bnot</b>    | function |
| <b>bor</b>     | function |
| <b>btest</b>   | function |
| <b>bxor</b>    | function |
| <b>extract</b> | function |
| <b>lrotate</b> | function |
| <b>lshift</b>  | function |
| <b>replace</b> | function |
| <b>rrotate</b> | function |
| <b>rshift</b>  | function |

## blobs (context)

|                    |          |
|--------------------|----------|
| <b>append</b>      | function |
| <b>dimensions</b>  | function |
| <b>dispose</b>     | function |
| <b>new</b>         | function |
| <b>pack</b>        | function |
| <b>strdp</b>       | function |
| <b>strhd</b>       | function |
| <b>strht</b>       | function |
| <b>strwd</b>       | function |
| <b>tohpack</b>     | function |
| <b>tohpackfast</b> | function |
| <b>tonodes</b>     | function |
| <b>tovpack</b>     | function |
| <b>tovpackfast</b> | function |
| <b>write</b>       | function |

## boolean (context)

**tocontext** function

**tonumber** function

## buffers (context)

|                       |          |
|-----------------------|----------|
| <b>append</b>         | function |
| <b>assign</b>         | function |
| <b>collectcontent</b> | function |
| <b>erase</b>          | function |
| <b>exists</b>         | function |
| <b>getcontent</b>     | function |
| <b>getlines</b>       | function |
| <b>loadcontent</b>    | function |
| <b>parallel</b>       | table    |
| F define              |          |
| F hassomecontent      |          |
| F next                |          |
| F place               |          |
| F reset               |          |
| F save                |          |
| <b>prepend</b>        | function |
| <b>raw</b>            | function |

# builders (context)

## **kernel**      table

- F hyphenation
- F kerning
- F ligaturing
- F mlist\_to\_hlist

## **paragraphs**   table

- T constructors
  - N attribute
  - F define
  - F disable
  - F enable
  - F handler
- T methods
  - F basic
  - F default
  - F oneline

- D names

- D numbers

- F set

- F start

- F stop

- T expansion

- F trace

- F kepttogether

- F registertogether

- T solutions

- T splitters

- F define

- F optimize

- T registered

- F reset

- F set

- F split

- F start

- F stop

- F tag

## **vspacing**      table

- F analyze

- D categories

- F collapsevbox

- T data

- D map

- D skip

- D snapmethods

- F definesnapmethod

- B fixed

- F pagehandler

- F resetprevdepth

- F setmap

- F setskip

- F snapbox

- F tocategories

- F tocategory

- F vboxhandler

## caches (context)

|   |          |
|---|----------|
| <b>ask</b>                                | boolean  |
| <b>base</b>                               | string   |
| <b>collapsecontent</b>                    | function |
| <b>configfiles</b>                        | function |
| <b>contentstate</b>                       | function |
| <b>defaults</b>                           | table    |
| <b>define</b>                             | function |
| <b>direct</b>                             | boolean  |
| <b>force</b>                              | boolean  |
| <b>getfirstreadablefile</b>               | function |
| <b>getfirstreadablefile_TEST_ME_FIRST</b> | function |
| <b>getreadablepaths</b>                   | function |
| <b>getwritablepath</b>                    | function |
| <b>hashed</b>                             | function |
| <b>is_writable</b>                        | function |
| <b>loadcontent</b>                        | function |
| <b>loaddata</b>                           | function |
| <b>more</b>                               | string   |
| <b>relocate</b>                           | boolean  |
| <b>savecontent</b>                        | function |
| <b>savedata</b>                           | function |
| <b>setfirstwritablefile</b>               | function |
| <b>setluanames</b>                        | function |
| <b>tree</b>                               | string   |
| <b>treehash</b>                           | function |
| <b>usedpaths</b>                          | function |

## callback (basic tex)

**find**        function

**list**        function

**register**   overloaded function



## callbacks (context)

|                 |            |
|-----------------|------------|
| <b>freeze</b>   | function   |
| <b>known</b>    | function   |
| <b>list</b>     | data table |
| <b>pop</b>      | function   |
| <b>push</b>     | function   |
| <b>register</b> | function   |
| <b>report</b>   | function   |

## catcodes (context)

|                 |            |
|-----------------|------------|
| <b>names</b>    | data table |
| <b>numbers</b>  | data table |
| <b>register</b> | function   |

# characters (context)

|                       |            |     |
|-----------------------|------------|-----|
| <b>activeoffset</b>   | number     | S B |
| <b>adobename</b>      | function   | S C |
| <b>bidirectional</b>  | data table | S D |
| <b>blockrange</b>     | function   | S E |
| <b>blocks</b>         | data table | S F |
| <b>casemap</b>        | table      | S G |
| <b>categories</b>     | data table | S H |
| <b>category</b>       | function   | S I |
| <b>categorytags</b>   | data table | S J |
| <b>collapsed</b>      | data table | S K |
| <b>combined</b>       | data table | S L |
| <b>contextname</b>    | function   | S M |
| <b>data</b>           | data table | S N |
| <b>decomposed</b>     | data table | S O |
| <b>define</b>         | function   | S P |
| <b>description</b>    | function   | S Q |
| <b>descriptions</b>   | data table | S R |
| <b>directions</b>     | table      | S S |
| <b>encodes</b>        | data table | S T |
| <b>entities</b>       | data table | S U |
| <b>fallbacks</b>      | data table | S V |
| <b>filters</b>        | data table | S W |
| <b>fromnumber</b>     | function   | S X |
| <b>fschars</b>        | data table | S Y |
| <b>fscodes</b>        | data table | S Z |
| <b>getrange</b>       | function   | S Å |
| <b>graphemes</b>      | data table | S Á |
| <b>hangul</b>         | data table | S Â |
| <b>initialize</b>     | function   | S Ã |
| <b>is_character</b>   | data table | S Ä |
| <b>is_command</b>     | data table | S Å |
| <b>is_letter</b>      | data table | S Æ |
| <b>is_mark</b>        | data table | S Ç |
| <b>is_punctuation</b> | data table | S È |
| <b>is_spacing</b>     | data table | S É |
| <b>lcchars</b>        | data table | S Ê |
| <b>lccode</b>         | function   | S Ë |
| <b>lccodes</b>        | data table | S Ì |
| <b>lettered</b>       | function   | S Í |
| <b>lhash</b>          | table      | S Î |
| <b>S A</b>            |            | S Ï |



S Ķ  
 S Q  
 S Ū  
 S Ź  
 S  
 S Ģ  
 S H  
 S  
 S Ņ  
 S  
 S Ē  
 S Ō  
 S Ā  
 S Ā  
 S Ē  
 S Ī  
 S Ī  
 S Ō  
 S Ō  
 S Ŗ  
 S Ŗ  
 S Ū  
 S Ū  
 S Š  
 S Ţ  
 S 3  
 S H  
 S Ņ  
 S  
 S Z  
 S Ā  
 S Ē  
 S Ō  
 S Ō  
 S Ō  
 S Ū  
 S Ā  
 S Ē  
 S Ē  
 S Ē

|     |      |
|-----|------|
| S B | S ʁ  |
| S H | S ŋ  |
| S ʌ | S    |
| S   | S    |
| S   | S    |
| S   | S    |
| S R | S    |
| S   | S    |
| S A | S    |
| S E | S θ  |
| S H | S p  |
| S I | S c  |
| S D | S m  |
| S Y | S ɔ  |
| S ɒ | S ɕ  |
| S A | S ɔ̃ |
| S B | S ě  |
| S ɾ | S ě  |
| S Δ | S ħ  |
| S E | S ġ  |
| S Z | S €  |
| S H | S s  |
| S θ | S i  |
| S I | S ĭ  |
| S K | S j  |
| S ʌ | S ʅ  |
| S M | S ħ  |
| S N | S ɦ  |
| S Ɛ | S k  |
| S O | S ŋ  |
| S Π | S ŷ  |
| S P | S ɥ  |
| S Σ | S A  |
| S T | S Б  |
| S Y | S В  |
| S Φ | S ɾ  |
| S X | S Д  |
| S Ψ | S E  |
| S Ω | S Ж  |
| S Ĩ | S 3  |
| S Ỳ | S И  |
| S Q | S Й  |
| S Ç | S K  |
| S F | S Л  |

|     |     |
|-----|-----|
| S M | S 3 |
| S H | S K |
| S O | S   |
| S П | S   |
| S P | S   |
| S C | S H |
| S T | S H |
| S Y | S   |
| S Ø | S   |
| S X | S Ç |
| S Ц | S Т |
| S Ч | S Y |
| S Ш | S ʏ |
| S Щ | S X |
| S Ъ | S   |
| S Ы | S   |
| S Ь | S   |
| S Э | S h |
| S Ю | S   |
| S Я | S   |
| S   | S I |
| S Ъ | S ǰ |
| S   | S ȝ |
| S   | S   |
| S   | S H |
| S   | S   |
| S   | S ʏ |
| S   | S   |
| S   | S Ā |
| S Ø | S Ā |
| S   | S Æ |
| S   | S Ē |
| S   | S ə |
| S   | S ǝ |
| S   | S ǰ |
| S   | S 3 |
| S   | S 3 |
| S   | S Ï |
| S   | S Ï |
| S   | S Ō |
| S Ґ | S Ө |
| S F | S Ө |
| S Ѓ | S 3 |
| S Ж | S ʏ |

|      |     |
|------|-----|
| S Ÿ  | S 2 |
| S Ÿ  | S ņ |
| S ı  | S U |
| S ĸ  | S 4 |
| S 6l | S S |
| S    | S ĩ |
| S    | S 8 |
| S    | S ĩ |
| S    | S 0 |
| S    | S 0 |
| S    | S 0 |
| S    | S   |
| S    | S   |
| S    | S   |
| S    | S   |
| S E  | S   |
| S    | S   |
| S U  | S   |
| S P  | S   |
| S q  | S   |
| S 7  | S   |
| S t  | S   |
| S 2  | S   |
| S t  | S   |
| S 2  | S   |
| S 0  | S   |
| S d  | S   |
| S ĩ  | S   |
| S L  | S   |
| S hu | S   |
| S 0  | S   |
| S 4  | S   |
| S 2  | S   |
| S 2  | S   |
| S 7  | S   |
| S x  | S   |
| S U  | S   |
| S 3  | S   |
| S 7  | S   |
| S 0  | S   |
| S 2  | S   |
| S 7  | S   |



|      |      |
|------|------|
| S    | S Ő  |
| S    | S    |
| S    | S    |
| S    | S    |
| S    | S P  |
| S    | S P  |
| S Å  | S R  |
| S B̂ | S R  |
| S B̃ | S Ṙ |
| S B̄ | S R̈ |
| S B̅ | S R̉ |
| S Ç  | S Ṡ |
| S Đ  | S Ş  |
| S Ð  | S    |
| S ð  | S    |
| S ò  | S Š  |
| S Q  | S Ṫ |
| S    | S T̈ |
| S    | S T̊ |
| S Ē  | S T̋ |
| S Ė | S U̇ |
| S Ę  | S Ü |
| S Ė  | S Ủ |
| S Ğ  | S Ó  |
| S Ḣ | S    |
| S Ḧ | S V̇ |
| S Ĥ  | S V̈ |
| S H̊ | S Ẇ |
| S H̋ | S Ẅ |
| S İ | S W̊ |
| S    | S W̋ |
| S K̇ | S W̌ |
| S K̈ | S Ẋ |
| S K̊ | S Ẍ |
| S L̇ | S Ẏ |
| S L̈ | S Ž  |
| S L̊ | S Ż |
| S L̋ | S Z̈ |
| S Ṁ | S Ȧ |
| S M̈ | S    |
| S M̊ | S    |
| S Ṅ | S    |
| S N̈ | S    |
| S N̊ | S    |
| S N̋ | S Â  |

S Å  
S Å  
S E  
S E  
S E  
S E  
S E  
S H  
S H  
S H  
S H  
S H  
S H  
S I  
S I  
S I  
S I  
S I  
S I  
S I  
S I  
S I  
S O  
S O  
S O  
S O  
S O  
S O  
S Y  
S Y  
S Y  
S Y  
S N  
S N  
S N  
S N  
S N  
S N  
S N  
S A  
S A

[illegible]





|                   |              |                             |              |
|-------------------|--------------|-----------------------------|--------------|
| <b>linebreaks</b> | <b>table</b> | <b>mirrors</b>              | <b>table</b> |
| S ai              |              | <b>otfscripts</b>           | data table   |
| S al              |              | <b>ranges</b>               | data table   |
| S b2              |              | <b>registerentities</b>     | function     |
| S ba              |              | <b>remap_hangul_syllabe</b> | function     |
| S bb              |              | <b>setcodes</b>             | function     |
| S bk              |              | <b>shape</b>                | function     |
| S cb              |              | <b>shaped</b>               | function     |
| S cj              |              | <b>shash</b>                | table        |
| S cl              |              | S Å                         |              |
| S cm              |              | S Á                         |              |
| S cp              |              | S Ă                         |              |
| S cr              |              | S Ą                         |              |
| S ex              |              | S Ǻ                         |              |
| S gl              |              | S Ǻ                         |              |
| S h2              |              | S Æ                         |              |
| S h3              |              | S Ç                         |              |
| S hl              |              | S È                         |              |
| S hy              |              | S É                         |              |
| S id              |              | S Ê                         |              |
| S in              |              | S Ë                         |              |
| S is              |              | S Ĩ                         |              |
| S jl              |              | S Í                         |              |
| S jt              |              | S Î                         |              |
| S jv              |              | S Ī                         |              |
| S lf              |              | S Ñ                         |              |
| S nl              |              | S Ò                         |              |
| S ns              |              | S Ó                         |              |
| S nu              |              | S Ô                         |              |
| S op              |              | S Õ                         |              |
| S po              |              | S Ö                         |              |
| S pr              |              | S Ø                         |              |
| S qu              |              | S Ù                         |              |
| S ri              |              | S Ú                         |              |
| S sa              |              | S Û                         |              |
| S sg              |              | S Ü                         |              |
| S sp              |              | S Ý                         |              |
| S sy              |              | S ß                         |              |
| S wj              |              | S à                         |              |
| S xx              |              | S á                         |              |
| S zw              |              | S â                         |              |
| <b>lower</b>      | function     | S ă                         |              |
| <b>math</b>       | table        | S ä                         |              |
| <b>mathpairs</b>  | data table   | S å                         |              |

|     |      |
|-----|------|
| S æ | S ẽ  |
| S ç | S Ě  |
| S è | S é  |
| S é | S Ě  |
| S ê | S ę  |
| S ẽ | S Ě  |
| S ì | S ẽ  |
| S í | S Ğ  |
| S î | S ô  |
| S ï | S Ğ  |
| S ñ | S õ  |
| S ò | S Ğ  |
| S ó | S ô  |
| S ô | S ç  |
| S õ | S ó  |
| S ö | S Ĥ  |
| S ø | S ĥ  |
| S ù | S Ħ  |
| S ú | S ħ  |
| S û | S Ĩ  |
| S ü | S i  |
| S ý | S Ĩ  |
| S ÿ | S i  |
| S Ā | S Ĩ  |
| S ā | S i  |
| S Ă | S Į  |
| S ă | S į  |
| S A | S Ĩ  |
| S a | S ı  |
| S Ć | S ij |
| S ć | S j  |
| S Ĉ | S j  |
| S ĉ | S Ƶ  |
| S Ċ | S ƶ  |
| S ċ | S Ĺ  |
| S Č | S ł  |
| S č | S Ț  |
| S Ď | S Ț  |
| S đ | S Ľ  |
| S ð | S ʟ  |
| S đ | S ʟ  |
| S Ē | S ʟ  |
| S ē | S Ł  |
| S Ĕ | S ʟ  |

S Ū  
S ū  
S Ŵ  
S ŵ  
S Ŷ  
S ŷ  
S Ÿ  
S Ž  
S ž  
S Ż  
S ż  
S Ĺ  
S ĺ  
S Ł  
S ł  
S Ą  
S ą  
S Ƀ  
S ɔ̃  
S Ȣ  
S ȣ  
S Ɔ  
S ɕ  
S Ծ  
Տ  
Տա  
Տբ  
Տգ  
Տդ  
Տե  
Տզ  
Տէ  
Տթ  
Տր  
Տս  
Տտ  
Տւ  
Տօ  
Տֆ  
Տ֊  
Տղ  
Տը  
Տթ  
Տր  
Տս  
Տտ



|      |     |
|------|-----|
| S y  | S Ȯ |
| S Z  | S Š |
| S z  | S š |
| S ž  | S j |
| S    | S   |
| S    | S Ġ |
| S    | S ġ |
| S    | S Ñ |
| S    | S ñ |
| S    | S   |
| S    | S   |
| S    | S Æ |
| S    | S æ |
| S Ä  | S Ø |
| S ä  | S ø |
| S Ī  | S Ā |
| S ī  | S ā |
| S Ō  | S Ā |
| S ō  | S ā |
| S Ū  | S Ē |
| S ū  | S ē |
| S Ū  | S Ê |
| S ū  | S ê |
| S Ū  | S Ī |
| S ū  | S ī |
| S Ū  | S Ī |
| S ū  | S ī |
| S Ū  | S Ō |
| S ū  | S ō |
| S Ä  | S Ō |
| S ä  | S ō |
| S Ā  | S Ĥ |
| S ā  | S ĥ |
| S Æ  | S Ĥ |
| S æ  | S ĥ |
| S    | S Ū |
| S    | S ū |
| S Ġ  | S Ū |
| S ġ  | S ū |
| S Ĥ  | S Ş |
| S ĥ  | S ş |
| S Q  | S Ț |
| S q  | S ț |
| S Q̄ | S Ħ |

[illegible]

|   |   |   |   |
|---|---|---|---|
| Ѕ | Й | Ѕ | Ѓ |
| Ѕ |   | Ѕ |   |
| Ѕ |   | Ѕ |   |
| Ѕ |   | Ѕ |   |
| Ѕ |   | Ѕ |   |
| Ѕ |   | Ѕ | Ă |
| Ѕ |   | Ѕ | ă |
| Ѕ | Г | Ѕ | Ā |
| Ѕ | г | Ѕ | ā |
| Ѕ | Ɔ | Ѕ | Ē |
| Ѕ | Ɔ | Ѕ | ē |
| Ѕ | Ђ | Ѕ | Ė |
| Ѕ | ђ | Ѕ | ė |
| Ѕ | Ж | Ѕ | Ĵ |
| Ѕ | ж | Ѕ | ĵ |
| Ѕ | З | Ѕ | Š |
| Ѕ | з | Ѕ | š |
| Ѕ | Қ | Ѕ | Й |
| Ѕ | қ | Ѕ | й |
| Ѕ |   | Ѕ | Й |
| Ѕ |   | Ѕ | й |
| Ѕ |   | Ѕ | Ō |
| Ѕ |   | Ѕ | ō |
| Ѕ | Ң | Ѕ | Š |
| Ѕ | ң | Ѕ | š |
| Ѕ |   | Ѕ | Ÿ |
| Ѕ |   | Ѕ | ÿ |
| Ѕ | Ç | Ѕ | Ÿ |
| Ѕ | ç | Ѕ | ÿ |
| Ѕ | Ƨ | Ѕ | Ÿ |
| Ѕ | Ƨ | Ѕ | ÿ |
| Ѕ | Х | Ѕ | Ч |
| Ѕ | х | Ѕ | č |
| Ѕ |   | Ѕ | Г |
| Ѕ |   | Ѕ | г |
| Ѕ |   | Ѕ | Ы |
| Ѕ |   | Ѕ | ы |
| Ѕ | Ж | Ѕ |   |
| Ѕ | ж | Ѕ |   |
| Ѕ | Қ | Ѕ |   |
| Ѕ | қ | Ѕ |   |
| Ѕ |   | Ѕ |   |
| Ѕ |   | Ѕ |   |
| Ѕ |   | Ѕ |   |

§

§

S

S

S

S

§

S

S

§

§

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

S

§

S

§

S

S

S

S

§

S

|     |      |
|-----|------|
| S   | S    |
| S   | S    |
| S   | S    |
| S   | S Å  |
| S   | S ą  |
| S   | S ß  |
| S   | S b  |
| S   | S B  |
| S   | S ḃ |
| S   | S Ḃ |
| S   | S b̈ |
| S   | S Ç  |
| S   | S Ć  |
| S   | S Ď  |
| S   | S d  |
| S   | S D  |
| S   | S ḋ |
| S   | S Ḋ |
| S   | S d̈ |
| S   | S D̈ |
| S   | S d̊ |
| S   | S D̊ |
| S   | S d̋ |
| S   | S    |
| S   | S    |
| S   | S    |
| S   | S    |
| S   | S Ē  |
| S Ļ | S ē  |
| S   | S Ē̇ |
| S   | S ē̇ |
| S   | S Ē̈ |
| S   | S ē̈ |
| S   | S Ē̊ |
| S   | S ē̊ |
| S   | S Ē̋ |
| S   | S Ĕ  |
| S   | S ĕ  |
| S   | S Ğ  |
| S   | S ğ  |
| S   | S Ĥ  |
| S   | S ĥ  |
| S   | S Ħ  |
| S   | S ĩ  |
| S   | S Ĩ  |
| S   | S ĩ̇ |
| S   | S Ĩ̇ |
| S   | S ĩ̈ |
| S   | S Ĩ̈ |
| S   | S ĩ̊ |
| S   | S Ĩ̊ |
| S   | S ĩ̋ |
| S   | S Ĩ̋ |

S š  
S Š  
S š  
S Š  
S Ŗ  
S r̃  
S R̄  
S ṙ  
S R̈  
S r̆  
S R̆  
S r̅  
S R̅  
S r̂  
S Š  
S š  
S Ě  
S ě  
S Ṫ  
S ṫ  
S T̈  
S ẗ  
S T̉  
S t̉  
S T̊  
S t̊  
S U̇  
S u̇  
S Ü  
S ü  
S Ủ  
S ủ  
S Ů  
S ů  
S  
S  
S V̇  
S v̇  
S V̈  
S v̈  
S Ẇ

[illegible]





S ŋ  
S ɲ  
S ì  
S í  
S ò  
S ó  
S ù  
S ú  
S ÷  
S ω  
S ǎ  
S ǎ̃  
S ǎ̄  
S ǎ̅  
S ǎ̆  
S ǎ̇  
S ǎ̈  
S ǎ̉  
S ǎ̊  
S ǎ̋  
S ǎ̌  
S ǎ̍  
S ǎ̎  
S ǎ̏  
S ǎ̐  
S ǎ̑  
S ǎ̒  
S ǎ̓  
S ǎ̔  
S ǎ̕  
S ǎ̖  
S ǎ̗  
S ǎ̘  
S ǎ̙  
S ǎ̚  
S ǎ̛  
S ǎ̜  
S ǎ̝  
S ǎ̞  
S ǎ̟  
S ǎ̠  
S ǎ̡  
S ǎ̢  
S ạ̌  
S ǎ̤  
S ḁ̌  
S ǎ̦  
S ǎ̧  
S ą̌  
S ǎ̩  
S ǎ̪  
S ǎ̫  
S ǎ̬  
S ǎ̭  
S ǎ̮  
S ǎ̯  
S ǎ̰  
S ǎ̱  
S ǎ̲  
S ǎ̳  
S ǎ̴  
S ǎ̵  
S ǎ̶  
S ǎ̷  
S ǎ̸  
S ǎ̹  
S ǎ̺  
S ǎ̻  
S ǎ̼  
S ǎ̽  
S ǎ̾  
S ǎ̿

S T  
S T  
S ũ  
S ū  
S ù  
S ú  
S ő  
S ő  
S ü  
S ü  
S ý  
S ý  
S ý  
S ý  
S þ  
S ð  
S ø  
S œ  
S œ  
S ò  
S ò  
S ï  
S ï  
S q̇  
S  
S  
S  
S  
S R  
S  
S  
S  
S  
S  
S  
S  
S  
S fi  
S fl  
S  
S  
S

|     |                     |            |
|-----|---------------------|------------|
| S   | S j                 |            |
| S   | S i                 |            |
| S   | <b>shchars</b>      | data table |
| S   | <b>shcodes</b>      | data table |
| S   | <b>showstring</b>   | function   |
| S   | <b>specialchars</b> | data table |
| S   | <b>specials</b>     | data table |
| S   | <b>subscripts</b>   | table      |
| S   | <b>superscripts</b> | table      |
| S   | <b>synonyms</b>     | data table |
| S   | <b>tex</b>          | table      |
| S   | D accentmapping     |            |
| S   | D commandmapping    |            |
| S   | F defineaccents     |            |
| S   | F safechar          |            |
| S   | F toutf             |            |
| S   | F toutfpattern      |            |
| S   | <b>textclasses</b>  | table      |
| S   | <b>tonumber</b>     | function   |
| S   | <b>ucchars</b>      | data table |
| S   | <b>uccode</b>       | function   |
| S   | <b>uccodes</b>      | data table |
| S   | <b>uhash</b>        | table      |
| S   | S a                 |            |
| S   | S b                 |            |
| S   | S c                 |            |
| S   | S d                 |            |
| S   | S e                 |            |
| S   | S f                 |            |
| S   | S g                 |            |
| S   | S h                 |            |
| S   | S i                 |            |
| S   | S j                 |            |
| S   | S k                 |            |
| S   | S l                 |            |
| S Ā | S m                 |            |
| S Ą | S n                 |            |
| S ĩ | S o                 |            |
| S Ĭ | S p                 |            |
| S ǃ | S q                 |            |
| S ǂ | S r                 |            |
| S ǃ | S s                 |            |
| S Ǆ | S t                 |            |
| S ǅ | S u                 |            |

|     |     |
|-----|-----|
| S v | S ě |
| S w | S đ |
| S x | S đ |
| S y | S ě |
| S z | S ě |
| S μ | S è |
| S ß | S ę |
| S à | S ě |
| S á | S ô |
| S â | S õ |
| S ã | S ô |
| S ä | S ô |
| S å | S ô |
| S æ | S ħ |
| S ç | S ĭ |
| S è | S ĭ |
| S é | S ĭ |
| S ê | S ĭ |
| S ë | S ĭ |
| S ì | S ĭ |
| S í | S ĭ |
| S î | S ĭ |
| S ï | S ĭ |
| S ð | S ĭ |
| S ñ | S ĭ |
| S ò | S ĭ |
| S ó | S ĭ |
| S ô | S ĭ |
| S õ | S ĭ |
| S ö | S ĭ |
| S ø | S ĭ |
| S ù | S ĭ |
| S ú | S ĭ |
| S û | S ĭ |
| S ü | S ĭ |
| S ý | S ĭ |
| S þ | S ĭ |
| S ÿ | S ĭ |
| S ā | S ĭ |
| S ă | S ĭ |
| S ą | S ĭ |
| S ć | S ĭ |
| S ċ | S ĭ |
| S č | S ĭ |

|     |     |
|-----|-----|
| S Ƨ | S ù |
| S ũ | S ə |
| S ů | S ǎ |
| S ű | S ǻ |
| S Ű | S æ |
| S Ų | S   |
| S Ʃ | S ğ |
| S Ŵ | S ƙ |
| S Ŷ | S ƚ |
| S Ẑ | S ȯ |
| S Ẓ | S ǰ |
| S Ẕ | S   |
| S ƚ | S ȳ |
| S Ƨ | S ñ |
| S Ƨ | S   |
| S Ƨ | S á |
| S Ƨ | S ø |
| S Ƨ | S ǎ |
| S Ƨ | S ă |
| S Ƨ | S ë |
| S Ƨ | S ê |
| S Ƨ | S ï |
| S Ƨ | S î |
| S Ƨ | S ð |
| S Ƨ | S ô |
| S Ƨ | S ř |
| S Ƨ | S ƣ |
| S Ƨ | S ù |
| S Ƨ | S ũ |
| S Ƨ | S Ț |
| S Ƨ | S ȝ |
| S Ƨ | S ħ |
| S Ƨ | S   |
| S Ƨ | S ȝ |
| S Ƨ | S à |
| S Ƨ | S ę |
| S Ƨ | S ȯ |
| S Ƨ | S ȯ |
| S Ƨ | S ò |
| S Ƨ | S ȯ |
| S Ƨ | S ȳ |
| S Ƨ | S ƣ |
| S Ƨ | S   |

|     |     |
|-----|-----|
| S   | S ı |
| S   | S κ |
| S   | S λ |
| S ₣ | S μ |
| S   | S ν |
| S 6 | S ξ |
| S ı | S o |
| S d | S π |
| S d | S ρ |
| S ə | S ς |
| S ε | S σ |
| S đ | S τ |
| S ʒ | S υ |
| S ð | S φ |
| S ı | S χ |
| S Ƨ | S ψ |
| S Ƨ | S ω |
| S Ƨ | S ĩ |
| S Ƨ | S ü |
| S Ƨ | S ó |
| S Ƨ | S ú |
| S Ƨ | S ȳ |
| S Ƨ | S 8 |
| S Ƨ | S 0 |
| S Ƨ | S ϕ |
| S Ƨ | S 𐀀 |
| S Ƨ | S ϱ |
| S Ƨ | S ς |
| S   | S f |
| S   | S 4 |
| S   | S λ |
| S   | S   |
| S á | S   |
| S é | S   |
| S ĩ | S   |
| S í | S   |
| S α | S   |
| S β | S   |
| S γ | S x |
| S 6 | S q |
| S ε | S c |
| S ζ | S € |
| S η | S þ |
| S θ | S m |

|      |      |
|------|------|
| Ѕ а  | Ѕ к  |
| Ѕ б  | Ѕ й  |
| Ѕ в  | Ѕ ъ  |
| Ѕ г  | Ѕ ы  |
| Ѕ д  | Ѕ    |
| Ѕ е  | Ѕ ъ  |
| Ѕ ж  | Ѕ    |
| Ѕ з  | Ѕ    |
| Ѕ и  | Ѕ    |
| Ѕ й  | Ѕ    |
| Ѕ к  | Ѕ    |
| Ѕ л  | Ѕ    |
| Ѕ м  | Ѕ    |
| Ѕ н  | Ѕ ъ  |
| Ѕ о  | Ѕ    |
| Ѕ п  | Ѕ    |
| Ѕ р  | Ѕ    |
| Ѕ с  | Ѕ    |
| Ѕ т  | Ѕ    |
| Ѕ у  | Ѕ    |
| Ѕ ф  | Ѕ    |
| Ѕ х  | Ѕ    |
| Ѕ ц  | Ѕ    |
| Ѕ ч  | Ѕ    |
| Ѕ ш  | Ѕ г' |
| Ѕ щ  | Ѕ ф  |
| Ѕ ъ  | Ѕ ъ  |
| Ѕ ы  | Ѕ ж  |
| Ѕ ъ  | Ѕ э  |
| Ѕ э  | Ѕ к  |
| Ѕ ю  | Ѕ    |
| Ѕ я  | Ѕ    |
| Ѕ ё  | Ѕ    |
| Ѕ ё  | Ѕ н  |
| Ѕ ъ  | Ѕ н  |
| Ѕ г' | Ѕ    |
| Ѕ е  | Ѕ    |
| Ѕ с  | Ѕ с  |
| Ѕ і  | Ѕ т  |
| Ѕ і  | Ѕ ы  |
| Ѕ ј  | Ѕ ы  |
| Ѕ ъ  | Ѕ х  |
| Ѕ ъ  | Ѕ    |
| Ѕ ъ  | Ѕ    |

|     |      |
|-----|------|
| S   | S ε  |
| S h | S    |
| S   | S w  |
| S   | S p  |
| S ж | S q  |
| S к | S η  |
| S   | S t  |
| S н | S q  |
| S   | S t  |
| S ч | S n  |
| S   | S p  |
| S l | S d  |
| S ä | S h  |
| S ä | S L  |
| S æ | S hu |
| S ě | S b  |
| S ə | S ı  |
| S ö | S h  |
| S ж | S d  |
| S ă | S η  |
| S 3 | S ó  |
| S й | S ı  |
| S й | S J  |
| S ö | S u  |
| S ø | S 2  |
| S ö | S n  |
| S ă | S z  |
| S ŷ | S w  |
| S ŷ | S 2  |
| S ŷ | S n  |
| S č | S u  |
| S r | S ı  |
| S ъ | S m  |
| S   | S n  |
| S   | S g  |
| S   | S L  |
| S   | S ψ  |
| S   | S p  |
| S   | S o  |
| S   | S f  |
| S   | S    |
| S   | S a  |
| S   | S b  |
| S   | S b  |



S ŀ  
S ś  
S ș  
S  
S  
S ș  
S ț  
S ț  
S ț  
S ț  
S ũ  
S ū  
S ū  
S ũ  
S  
S v̇  
S ȳ  
S ẇ  
S ẇ  
S w̄  
S w̄  
S ẋ  
S ẏ  
S ž  
S ż  
S ř  
S ṛ  
S  
S  
S  
S  
S â  
S  
S à  
S  
S  
S ă  
S ę  
S  
S ě

S ħ  
S ħ̇  
S ħ̈  
S ħ̊  
S ħ̋  
S ħ̌  
S ħ̍  
S ħ̎  
S ħ̏  
S ĭ  
S ï  
S ı̇  
S ı̈  
S Ń  
S Ņ  
S ņ  
S ő  
S ő̇  
S ő̈  
S ő̊  
S ő̋  
S ő̌  
S ő̍  
S ő̎  
S ő̏  
S Ő  
S Ű  
S ŷ  
S Ź  
S ž  
S ȁ  
S ȡ  
S Ȣ  
S ȣ  
S Ȥ  
S ȥ  
S Ȧ  
S ȧ  
S Ȩ  
S ȩ  
S Ȫ  
S ȫ  
S Ȭ  
S ȭ  
S Ȯ  
S Ȱ  
S ȱ  
S Ȳ  
S ȳ  
S ȴ  
S ȵ  
S ȶ  
S ȷ  
S ȸ  
S ȹ  
S Ⱥ  
S Ȼ  
S ȼ  
S Ƚ  
S Ⱦ  
S ȿ  
S ̀  
S ́  
S ͂  
S ̓  
S ̈́  
S ͅ  
S ͆  
S ͇  
S ͈  
S ͉  
S ͊  
S ͋  
S ͌  
S ͍  
S ͎  
S ͏  
S ͐  
S ͑  
S ͒  
S ͓  
S ͔  
S ͕  
S ͖  
S ͗  
S ͘  
S ͙  
S ͚  
S ͛  
S ͜  
S ͝  
S ͞  
S ͟  
S ͠  
S ͡  
S ͢  
S ͣ  
S ͤ  
S ͥ  
S ͦ  
S ͧ  
S ͨ  
S ͩ  
S ͪ  
S ͫ  
S ͬ  
S ͭ  
S ͮ  
S ͯ  
S Ͱ  
S ͱ  
S Ͳ  
S ͳ  
S ʹ  
S ͵  
S Ͷ  
S ͷ  
S ͸  
S ͹  
S ͺ  
S ͻ  
S ͼ  
S ͽ  
S Ϳ  
S ͽ  
S Ϳ



[illegible]



|                    |          |
|--------------------|----------|
| <b>unicodechar</b> | function |
| <b>upper</b>       | function |

[previous](#) 53 [next](#)

## chemistry (context)

|                       |            |
|-----------------------|------------|
| <b>component</b>      | function   |
| <b>define</b>         | function   |
| <b>definitions</b>    | data table |
| <b>format</b>         | string     |
| <b>instance</b>       | string     |
| <b>molecule</b>       | function   |
| <b>moleculeparser</b> | userdata   |
| <b>start</b>          | function   |
| <b>stop</b>           | function   |
| <b>structures</b>     | number     |
| <b>undefine</b>       | function   |

## commands (context)

|                                |          |                                  |          |
|--------------------------------|----------|----------------------------------|----------|
| <b>Alphabetic</b>              | function | <b>assignbuffer</b>              | function |
| <b>Character</b>               | function | <b>attachproperty</b>            | function |
| <b>Characters</b>              | function | <b>autofinishstructurelevels</b> | function |
| <b>MPc</b>                     | function | <b>autonextspace</b>             | function |
| <b>MPd</b>                     | function | <b>autonextstructurelevel</b>    | function |
| <b>MPh</b>                     | function | <b>autosetups</b>                | function |
| <b>MPll</b>                    | function | <b>autostarttext</b>             | function |
| <b>MPlr</b>                    | function | <b>autostoptext</b>              | function |
| <b>MPls</b>                    | function | <b>averagecharwidth</b>          | function |
| <b>MPn</b>                     | function | <b>bcolumn</b>                   | function |
| <b>MPp</b>                     | function | <b>boolcase</b>                  | function |
| <b>MPpardata</b>               | function | <b>boxtostring</b>               | function |
| <b>MPplus</b>                  | function | <b>btx_a_f</b>                   | function |
| <b>MPpos</b>                   | function | <b>btx_a_i</b>                   | function |
| <b>MPposset</b>                | function | <b>btx_a_j</b>                   | function |
| <b>MPr</b>                     | function | <b>btx_a_s</b>                   | function |
| <b>MPrest</b>                  | function | <b>btx_a_v</b>                   | function |
| <b>MPrs</b>                    | function | <b>btxabbreviatedjournal</b>     | function |
| <b>MPul</b>                    | function | <b>btxaddfield</b>               | function |
| <b>MPur</b>                    | function | <b>btxaddjournal</b>             | function |
| <b>MPw</b>                     | function | <b>btxauthor</b>                 | function |
| <b>MPx</b>                     | function | <b>btxauthorfield</b>            | function |
| <b>MPxy</b>                    | function | <b>btxcollectlistentries</b>     | function |
| <b>MPxywhd</b>                 | function | <b>btxdetail</b>                 | function |
| <b>MPy</b>                     | function | <b>btxdoif</b>                   | function |
| <b>Romannumerals</b>           | function | <b>btxdoifelse</b>               | function |
| <b>abjadnodotnumerals</b>      | function | <b>btxdoifnot</b>                | function |
| <b>abjadnumerals</b>           | function | <b>btxexpandedjournal</b>        | function |
| <b>addbtxentry</b>             | function | <b>btxfetchlistentries</b>       | function |
| <b>addcounter</b>              | function | <b>btxfield</b>                  | function |
| <b>addlinklistelement</b>      | function | <b>btxflush</b>                  | function |
| <b>addreplacements</b>         | function | <b>btxflushlistentries</b>       | function |
| <b>addtojavascriptpreamble</b> | function | <b>btxhandlecite</b>             | function |
| <b>addtolist</b>               | function | <b>btxhandlenocite</b>           | function |
| <b>allinputpaths</b>           | function | <b>btxlistvariant</b>            | function |
| <b>alphabetic</b>              | function | <b>btxloadjournallist</b>        | function |
| <b>analysefloatmethod</b>      | function | <b>btxpreparelistentries</b>     | function |
| <b>analyzelist</b>             | function | <b>btxsavejournallist</b>        | function |
| <b>applytochars</b>            | function | <b>btxsingularorplural</b>       | function |
| <b>applytofirstcharacter</b>   | function | <b>buildtextaccent</b>           | function |
| <b>applytowords</b>            | function | <b>character</b>                 | function |



|                                |          |                                |          |
|--------------------------------|----------|--------------------------------|----------|
| <b>characters</b>              | function | <b>definecharacterspacing</b>  | function |
| <b>chardescription</b>         | function | <b>definechemical</b>          | function |
| <b>checkcharactersinfo</b>     | function | <b>defineconversion</b>        | function |
| <b>checkcountersetup</b>       | function | <b>definecounter</b>           | function |
| <b>checkedconversion</b>       | function | <b>definedviewerlayer</b>      | function |
| <b>checkedpagefloat</b>        | function | <b>definefallbackfamily</b>    | function |
| <b>checktwopassdata</b>        | function | <b>definefield</b>             | function |
| <b>chemicalcomponent</b>       | function | <b>definefieldset</b>          | function |
| <b>chineseallnumerals</b>      | function | <b>definefilefallback</b>      | function |
| <b>chinesecapnumerals</b>      | function | <b>definefilesynonym</b>       | function |
| <b>chinesenumerals</b>         | function | <b>definefont_one</b>          | function |
| <b>cleanfontname</b>           | function | <b>definefont_two</b>          | function |
| <b>cleanupbox</b>              | function | <b>definefontfamily</b>        | function |
| <b>cleanuplayers</b>           | function | <b>definefontfeature</b>       | function |
| <b>clonefield</b>              | function | <b>definefontsolution</b>      | function |
| <b>collectfloat</b>            | function | <b>defineinsertion</b>         | function |
| <b>collecthelp</b>             | function | <b>defineintermediatecolor</b> | function |
| <b>colorcomponents</b>         | function | <b>definelabels</b>            | function |
| <b>concatcommalist</b>         | function | <b>definelanguage</b>          | function |
| <b>consultfloat</b>            | function | <b>definelinkedlist</b>        | function |
| <b>convertbtbxdatasettoxml</b> | function | <b>definemarking</b>           | function |
| <b>converteddimen</b>          | function | <b>definemetafont</b>          | function |
| <b>copyposition</b>            | function | <b>definemultitonecolor</b>    | function |
| <b>cos</b>                     | function | <b>definernote</b>             | function |
| <b>cosd</b>                    | function | <b>defineparallel</b>          | function |
| <b>countervalue</b>            | function | <b>defineparbuilder</b>        | function |
| <b>counttwopassdata</b>        | function | <b>defineprocesscolor</b>      | function |
| <b>ctxfunction</b>             | function | <b>defineprogram</b>           | function |
| <b>currentcomponent</b>        | function | <b>definereference</b>         | function |
| <b>currentdate</b>             | function | <b>defineregister</b>          | function |
| <b>currentenvironment</b>      | function | <b>definesectionlevels</b>     | function |
| <b>currentproduct</b>          | function | <b>defineselectfont</b>        | function |
| <b>currentproject</b>          | function | <b>definesnapmethod</b>        | function |
| <b>currentreferencedefault</b> | function | <b>definespotcolor</b>         | function |
| <b>currentreferenceorder</b>   | function | <b>definestructureblock</b>    | function |
| <b>currentregime</b>           | function | <b>definestructureset</b>      | function |
| <b>currentsectiontolist</b>    | function | <b>definetransparency</b>      | function |
| <b>datasetvariable</b>         | function | <b>definetwopasslist</b>       | function |
| <b>dayname</b>                 | function | <b>defineviewerlayer</b>       | function |
| <b>deferredproperty</b>        | function | <b>defrostrandomseed</b>       | function |
| <b>defineattribute</b>         | function | <b>depthnumber</b>             | function |
| <b>definebreakpoint</b>        | function | <b>digits</b>                  | function |
| <b>definebreakpoints</b>       | function | <b>disableautofontscript</b>   | function |
| <b>definecatcodetable</b>      | function | <b>disableparbuilder</b>       | function |

|                                      |          |                                     |          |
|--------------------------------------|----------|-------------------------------------|----------|
| <b>disableregime</b>                 | function | <b>doifnotcounter</b>               | function |
| <b>disablespellchecking</b>          | function | <b>doifnotecontent</b>              | function |
| <b>discardfromlist</b>               | function | <b>doifnoteonsamepageasprevious</b> | function |
| <b>doanalyzeframedbox</b>            | function | <b>doifobjectreferencefoundelse</b> | function |
| <b>doif</b>                          | function | <b>doifolderverversionelse</b>      | function |
| <b>doifblackelse</b>                 | function | <b>doifoverlappingelse</b>          | function |
| <b>doifcommonelse</b>                | function | <b>doifparentfileelse</b>           | function |
| <b>doifcounter</b>                   | function | <b>doifpathexistelse</b>            | function |
| <b>doifdimenstringelse</b>           | function | <b>doifposition</b>                 | function |
| <b>doifdrawingblackelse</b>          | function | <b>doifpositionelse</b>             | function |
| <b>doifelse</b>                      | function | <b>doifpositiononpage</b>           | function |
| <b>doifelsebuffer</b>                | function | <b>doifpositionsonsamepageelse</b>  | function |
| <b>doifelsecontinuewithfile</b>      | function | <b>doifpositionsonthispageelse</b>  | function |
| <b>doifelsecounter</b>               | function | <b>doifurldefinedelse</b>           | function |
| <b>doifelsecurrentfonthasfeature</b> | function | <b>doprocесstypescriptfile</b>      | function |
| <b>doifelseintwopassdata</b>         | function | <b>doreshapeframedbox</b>           | function |
| <b>doifelsemarking</b>               | function | <b>dostarttextfile</b>              | function |
| <b>doifelsemessage</b>               | function | <b>dostoptextfile</b>               | function |
| <b>doifelsemultipar</b>              | function | <b>ecolumn</b>                      | function |
| <b>doifelseparallel</b>              | function | <b>elapsedtime</b>                  | function |
| <b>doifelsepositionsused</b>         | function | <b>enableautofontscript</b>         | function |
| <b>doifelserangeonpage</b>           | function | <b>enablecolor</b>                  | function |
| <b>doifelserereference</b>           | function | <b>enablecolorintents</b>           | function |
| <b>doifelsesavedfloat</b>            | function | <b>enablefontcolorschemas</b>       | function |
| <b>doifelsespaces</b>                | function | <b>enableparbuilder</b>             | function |
| <b>doifelseutfmathabove</b>          | function | <b>enableregime</b>                 | function |
| <b>doifelseutfmathaccent</b>         | function | <b>enablespellchecking</b>          | function |
| <b>doifelseutfmathbelow</b>          | function | <b>enabletransparency</b>           | function |
| <b>doifelsevisualizer</b>            | function | <b>enhancelinkedlist</b>            | function |
| <b>doiffielddcategoryelse</b>        | function | <b>enhancelist</b>                  | function |
| <b>doiffielddelse</b>                | function | <b>enhancereference</b>             | function |
| <b>doiffielddsetelse</b>             | function | <b>enhanceregister</b>              | function |
| <b>doiffiledefinedelse</b>           | function | <b>erasebuffer</b>                  | function |
| <b>doiffileexistelse</b>             | function | <b>expandcurrentreference</b>       | function |
| <b>doiffirstcharelse</b>             | function | <b>exportformdata</b>               | function |
| <b>doifinputfileelse</b>             | function | <b>exportreferences</b>             | function |
| <b>doifinsetelse</b>                 | function | <b>extendregister</b>               | function |
| <b>doifleapyearelse</b>              | function | <b>extensiblecode</b>               | function |
| <b>doiflisthasentry</b>              | function | <b>feature</b>                      | function |
| <b>doiflisthasnumberelse</b>         | function | <b>featureattribute</b>             | function |
| <b>doiflisthaspageelse</b>           | function | <b>featurelist</b>                  | function |
| <b>doiflisthastitleelse</b>          | function | <b>feedback</b>                     | function |
| <b>doiflocfileelse</b>               | function | <b>fetchhallmarks</b>               | function |
| <b>doifnot</b>                       | function | <b>fetchmultipar</b>                | function |

|                                |                 |                                    |                 |
|--------------------------------|-----------------|------------------------------------|-----------------|
| <b>fetchmultishape</b>         | <b>function</b> | <b>getbufferctxlua</b>             | <b>function</b> |
| <b>fetchonemark</b>            | <b>function</b> | <b>getbuffermkvi</b>               | <b>function</b> |
| <b>fetchposboxes</b>           | <b>function</b> | <b>getcommandline</b>              | <b>function</b> |
| <b>fetchtwomarks</b>           | <b>function</b> | <b>getctxfile</b>                  | <b>function</b> |
| <b>figurefilename</b>          | <b>function</b> | <b>getcurrentprefixspec</b>        | <b>function</b> |
| <b>figurefilepath</b>          | <b>function</b> | <b>getcurrentreferencemetadata</b> | <b>function</b> |
| <b>figurefiletype</b>          | <b>function</b> | <b>getcurrentsectionlevel</b>      | <b>function</b> |
| <b>figurerequest</b>           | <b>function</b> | <b>getdefaultfieldvalue</b>        | <b>function</b> |
| <b>figurestatus</b>            | <b>function</b> | <b>getelementtag</b>               | <b>function</b> |
| <b>figureused</b>              | <b>function</b> | <b>getfieldcategory</b>            | <b>function</b> |
| <b>figurevariable</b>          | <b>function</b> | <b>getfirstcharacter</b>           | <b>function</b> |
| <b>filterdefaultreference</b>  | <b>function</b> | <b>getfirsttwopassdata</b>         | <b>function</b> |
| <b>filterreference</b>         | <b>function</b> | <b>getfloatvariable</b>            | <b>function</b> |
| <b>finalizebox</b>             | <b>function</b> | <b>getfullsectionnumber</b>        | <b>function</b> |
| <b>findtwopassdata</b>         | <b>function</b> | <b>getinternallistreference</b>    | <b>function</b> |
| <b>firstcountervalue</b>       | <b>function</b> | <b>getinternalreference</b>        | <b>function</b> |
| <b>firstinrange</b>            | <b>function</b> | <b>getlasttwopassdata</b>          | <b>function</b> |
| <b>firstinset</b>              | <b>function</b> | <b>getmarking</b>                  | <b>function</b> |
| <b>flushfloat</b>              | <b>function</b> | <b>getmessage</b>                  | <b>function</b> |
| <b>flushmarked</b>             | <b>function</b> | <b>getmpextensions</b>             | <b>function</b> |
| <b>flushnotes</b>              | <b>function</b> | <b>getnotestate</b>                | <b>function</b> |
| <b>flushpostponedblocks</b>    | <b>function</b> | <b>getplaceholderchar</b>          | <b>function</b> |
| <b>flushpostponednotes</b>     | <b>function</b> | <b>getprivatechar</b>              | <b>function</b> |
| <b>fontchar</b>                | <b>function</b> | <b>getprogram</b>                  | <b>function</b> |
| <b>fontcharbyindex</b>         | <b>function</b> | <b>getrandomcounta</b>             | <b>function</b> |
| <b>fontcollectionclone</b>     | <b>function</b> | <b>getrandomcountb</b>             | <b>function</b> |
| <b>fontcollectiondefine</b>    | <b>function</b> | <b>getrandomseed</b>               | <b>function</b> |
| <b>fontcollectionprepare</b>   | <b>function</b> | <b>getreadfilename</b>             | <b>function</b> |
| <b>fontcollectionregister</b>  | <b>function</b> | <b>getsectionnumber</b>            | <b>function</b> |
| <b>fontcollectionreport</b>    | <b>function</b> | <b>getstructuredata</b>            | <b>function</b> |
| <b>fontcollectionreset</b>     | <b>function</b> | <b>getsubstring</b>                | <b>function</b> |
| <b>fontlookupgetkey</b>        | <b>function</b> | <b>gettexbuffer</b>                | <b>function</b> |
| <b>fontlookupgetkeyofindex</b> | <b>function</b> | <b>gettwopassdata</b>              | <b>function</b> |
| <b>fontlookupinitialize</b>    | <b>function</b> | <b>gettwopassdatalist</b>          | <b>function</b> |
| <b>fontlookupnofound</b>       | <b>function</b> | <b>geturl</b>                      | <b>function</b> |
| <b>forceendjob</b>             | <b>function</b> | <b>grabbuffer</b>                  | <b>function</b> |
| <b>forcequitjob</b>            | <b>function</b> | <b>hboxtovbox</b>                  | <b>function</b> |
| <b>format</b>                  | <b>function</b> | <b>helpaction</b>                  | <b>function</b> |
| <b>formatcolor</b>             | <b>function</b> | <b>helpreference</b>               | <b>function</b> |
| <b>formatgray</b>              | <b>function</b> | <b>hexstringtonumber</b>           | <b>function</b> |
| <b>freezerandomseed</b>        | <b>function</b> | <b>horizontalcode</b>              | <b>function</b> |
| <b>from</b>                    | <b>function</b> | <b>hour</b>                        | <b>function</b> |
| <b>getbidimode</b>             | <b>function</b> | <b>hyphenatedlist</b>              | <b>function</b> |
| <b>getbuffer</b>               | <b>function</b> | <b>hyphenatedurl</b>               | <b>function</b> |

|                                |          |                            |          |
|--------------------------------|----------|----------------------------|----------|
| D characters                   |          | locfilename                | function |
| N lefthyphenmin                |          | lower                      | function |
| D mapping                      |          | makeactive                 | function |
| N righthyphenmin               |          | manipulated                | function |
| F setcharacters                |          | markfonts                  | function |
| <b>immediateproperty</b>       | function | markingnumber              | function |
| <b>incrementedcounter</b>      | function | markingtitle               | function |
| <b>initializetexdirectives</b> | function | markregionbox              | function |
| <b>initializetextrackers</b>   | function | math_frac                  | function |
| <b>injectcurrentreference</b>  | function | mathrenderset              | function |
| <b>injectreference</b>         | function | maxitemwidth               | function |
| <b>inlinechemical</b>          | function | minute                     | function |
| <b>insertattachment</b>        | function | mixcleanup                 | function |
| <b>insertcomment</b>           | function | mixfinalize                | function |
| <b>insertfield</b>             | function | mixflushlist               | function |
| <b>insertionnumber</b>         | function | mixflushrest               | function |
| <b>insertrenderingwindow</b>   | function | mixgetsplit                | function |
| <b>insertsoundclip</b>         | function | mixsetsplit                | function |
| <b>installedlanguages</b>      | function | mixstate                   | function |
| <b>installtexdirective</b>     | function | molecule                   | function |
| <b>installtextracker</b>       | function | month                      | function |
| <b>languagenumber</b>          | function | monthmnem                  | function |
| <b>lastcountervalue</b>        | function | monthname                  | function |
| <b>lchexnumber</b>             | function | mpcolor                    | function |
| <b>lchexnumbers</b>            | function | mpoptions                  | function |
| <b>leapyear</b>                | function | mprunvar                   | function |
| <b>linenumbersstageone</b>     | function | namedstructureuservariable | function |
| <b>linenumbersstagetwo</b>     | function | namedstructurevariable     | function |
| <b>listgroupindex</b>          | function | nbfs                       | function |
| <b>listlabel</b>               | function | nextcountervalue           | function |
| <b>listlocation</b>            | function | nextparallel               | function |
| <b>listprefixednumber</b>      | function | nofdays                    | function |
| <b>listprefixedpage</b>        | function | nofitems                   | function |
| <b>listrealpage</b>            | function | nofstackedfloats           | function |
| <b>listsize</b>                | function | notedeltapage              | function |
| <b>listtitle</b>               | function | notelistindex              | function |
| <b>listuserdata</b>            | function | notenumberpage             | function |
| <b>loadbtxdefinitionfile</b>   | function | noteprefixednumber         | function |
| <b>loadexamodes</b>            | function | notesymbolpage             | function |
| <b>loadfontgoodies</b>         | function | notetitle                  | function |
| <b>loadspellchecklist</b>      | function | ntimes                     | function |
| <b>loadtypescriptfile</b>      | function | number                     | function |
| <b>loadvisualizer</b>          | function | F C                        |          |
| <b>locatefilepath</b>          | function | F FL                       |          |

|                                |                           |
|--------------------------------|---------------------------|
| F HL                           | F XmlSnippetBoundary      |
| F L                            | F XmlSnippetCdata         |
| F LL                           | F XmlSnippetComment       |
| F LuaSnippet                   | F XmlSnippetEntity        |
| F LuaSnippetBoundary           | F XmlSnippetEqual         |
| F LuaSnippetComment            | F XmlSnippetKey           |
| F LuaSnippetName               | F XmlSnippetName          |
| F LuaSnippetNameBase           | F XmlSnippetString        |
| F LuaSnippetNameCore           | F __flush                 |
| F LuaSnippetNameLibraries      | F __flushdirect           |
| F LuaSnippetQuote              | F __flushlines            |
| F LuaSnippetSpecial            | F a                       |
| F LuaSnippetString             | F addaskedblankskip       |
| F ML                           | F addpredefinedblankskip  |
| F MPLIBsetCtext                | F applyprocessor          |
| F MPLIBsetNtext                | F b                       |
| F MPcolor                      | F beginhbox               |
| F MetapostSnippet              | F beginvbox               |
| F MetapostSnippetBoundary      | F bf                      |
| F MetapostSnippetComment       | F bgroup                  |
| F MetapostSnippetConstructor   | F blank                   |
| F MetapostSnippetName          | F bold                    |
| F MetapostSnippetNameMetafun   | F btxchecklistcombi       |
| F MetapostSnippetNamePlain     | F btxchecklistentry       |
| F MetapostSnippetNamePrimitive | F btxciteauthorsetup      |
| F MetapostSnippetQuote         | F btxcitesetup            |
| F MetapostSnippetSpecial       | F btxcitevariantparameter |
| F MetapostSnippetString        | F btxdirectlink           |
| F NC                           | F btxhandlelistentry      |
| F NR                           | F btxlistauthorsetup      |
| F ParsedXmlSnippetCdata        | F btxlistparameter        |
| F ParsedXmlSnippetComment      | F btxlistsetup            |
| F ParsedXmlSnippetDoctype      | F btxlistvariantparameter |
| F ParsedXmlSnippetElement      | F btxmissing              |
| F ParsedXmlSnippetInstruction  | F btxsetauthorindex       |
| F ParsedXmlSnippetKey          | F btxsetauthorvariant     |
| F ParsedXmlSnippetValue        | F btxsetbacklink          |
| F TexSnippet                   | F btxsetbacktrace         |
| F TexSnippetBoundary           | F btxsetcategory          |
| F TexSnippetComment            | F btxsetcitereference     |
| F TexSnippetGroup              | F btxsetcombis            |
| F TexSnippetName               | F btxsetconcat            |
| F TexSnippetSpecial            | F btxsetcount             |
| F XmlSnippet                   | F btxsetdataset           |

|                       |                               |
|-----------------------|-------------------------------|
| F btxsetfirst         | F convertnumber               |
| F btxsetfirstnames    | F ctxreport                   |
| F btxsetinitials      | F d                           |
| F btxsetinternal      | F darkblue                    |
| F btxsetjuniors       | F darkgreen                   |
| F btxsetlanguage      | F darkred                     |
| F btxsetlefttext      | F definefontsynonym           |
| F btxsetlistreference | T delayed                     |
| F btxsetnumber        | F digitsdigit                 |
| F btxsetoverflow      | F digitsfinalcomma            |
| F btxsetrighttext     | F digitsfinalperiod           |
| F btxsetsecond        | F digitshighspace             |
| F btxsetsurnames      | F digitsintermediatecomma     |
| F btxsettag           | F digitsintermediateperiod    |
| F btxsetthird         | F digitsminus                 |
| F btxsetvons          | F digitsnegative              |
| F btxstartauthor      | F digitsplus                  |
| F btxstartcite        | F digitspositive              |
| F btxstartciteauthor  | F digitspower                 |
| F btxstartsubcite     | F digitspowerminus            |
| F btxstopauthor       | F digitspowerplus             |
| F btxstopcite         | F digitseparatorspace         |
| F btxstopciteauthor   | F digitssignspace             |
| F btxstopsubcite      | F digitsspace                 |
| F c                   | F digitszeropadding           |
| F callfunctiononce    | F direct                      |
| F char                | F dodisplayverbatimbeginline  |
| F chardef             | F dodisplayverbatimemptyline  |
| F color               | F dodisplayverbatiminitialize |
| F colordefagc         | F dodisplayverbatimnewline    |
| F colordefagt         | F dodisplayverbatimstart      |
| F colordefalc         | F dodisplayverbatimstop       |
| F colordefalt         | F dofastdefinetypeface        |
| F colordeffgc         | F dofinishsomereference       |
| F colordeffgt         | F dofromfiledescription       |
| F colordefflc         | F dofromfileliteral           |
| F colordefflt         | F dofromurldescription        |
| F colordefrgc         | F dofromurlliteral            |
| F colordefrgt         | F doinlineverbatimbeginline   |
| F colordefrlc         | F doinlineverbatimemptyline   |
| F colordefrlt         | F doinlineverbatimnewline     |
| F concat              | F doinlineverbatimstart       |
| F constructcs         | F doinlineverbatimstop        |
| F constructcsonly     | F donestedtypingstart         |

- F donestedtypingstop
- F dostarttext
- F doverbatimspace
- F egroup
- F emptyreference
- F enablemode
- F endhbox
- F endvbox
- F environment
- F expandreferencearguments
- F expandreferenceoperation
- F finalizeautostructurelevel
- F finishjob
- F firstofoneargument
- F firstoftwoarguments
- F fixedblankskip
- F flexibleblankskip
- F flushblankhandling
- F flushboxregister
- F flushnode
- F fntsetdefname
- F fntsetnopsiz
- F fntsetsomename
- F fntsetsomesize
- T formatted
- F fprint
- T generics
  - S starttabulate
  - S stoptabulate
- F getlogger
- F getreferencestructureprefix
- F getvalue
- F glyph
- F gobbleoneargument
- F goto
- F hrule
- F input
- T knownfunctions
- F l
- F lateluafunction
- F letvaluerelax
- F llap
- F loadfile
- F loadfoundtypescriptfile

- F luasetup
- F m
- F makelinenumber
- T metafun
  - F color
  - T delayed
  - F start
  - F stop
- T nested
  - F markingcommand
  - F markingseparator
- F newbox
- F newcount
- F newdimen
- F newindexer
- F newmuskip
- F newskip
- F newtexthandler
- F newtoks
- F newverbosehandler
- F nointerlineskip
- F normalatop
- F normalover
- F overstrike
- F par
- F pdfliteral
- F popcatcodes
- F poplogger
- F printlines
- F processfilemany
- F processfilenone
- F processfileonce
- F protect
- T puretext
- F pushcatcodes
- F pushlogger
- F registerentry
- F registerfunction
- F registeronepage
- F registerpagerange
- F registerseeword
- F reservefunction
- F rlap
- F rotate

|                          |                         |
|--------------------------|-------------------------|
| F runfile                | F stopLuaSnippet        |
| F secondoftwoarguments   | F stopMetapostSnippet   |
| F setblankcategory       | F stopParsedXmlSnippet  |
| F setblankorder          | F stopTexSnippet        |
| F setblankpenalty        | F stopXmlSnippet        |
| F setconditional         | F stopblankhandling     |
| F setfalsevalue          | F stopcolumns           |
| F sethboxregister        | F stopcomponentindeed   |
| F setsomevalue           | F stopenvironmentindeed |
| F settabulateentry       | F stopfontclass         |
| F settabulatelastentry   | F stophboxregister      |
| F settracing             | F stopproductindeed     |
| F setupsystem            | F stopprojectindeed     |
| F setupwithargument      | F stopreadingfile       |
| F setvalue               | F stopregisterentries   |
| F setvboxregister        | F stopregisterentry     |
| F setxvalue              | F stopregisteroutput    |
| F space                  | F stopregisterpages     |
| F sprint                 | F stopregistersection   |
| F startLuaSnippet        | F stopregisterseewords  |
| F startMetapostSnippet   | F stoptabulate          |
| F startParsedXmlSnippet  | F stoptext              |
| F startTexSnippet        | F stoptitle             |
| F startXmlSnippet        | F stopvboxregister      |
| F startblankhandling     | F stopxtitle            |
| F startcolumns           | F storenode             |
| F startcomponentindeed   | F synonymentry          |
| F startenvironmentindeed | F tabulaterow           |
| F startfontclass         | F tabulaterowbold       |
| F starthboxregister      | F tabulaterowtyp        |
| F startproductindeed     | F tabulaterowtype       |
| F startprojectindeed     | F template              |
| F startreadingfile       | T templates             |
| F startregisterentries   | F texsetup              |
| F startregisterentry     | F tobuffer              |
| F startregisteroutput    | F tocontext             |
| F startregisterpages     | F tolines               |
| F startregistersection   | F unitsC                |
| F startregisterseewords  | F unitsN                |
| F starttabulate          | F unitsNspace           |
| F starttext              | F unitsNstart           |
| F starttitle             | F unitsNstop            |
| F startvboxregister      | F units0                |
| F startxtitle            | F unitsP                |



|                                |                                |                 |
|--------------------------------|--------------------------------|-----------------|
| F unitsPS                      | F XmlSnippetEntity             |                 |
| F unitsPU                      | F XmlSnippetEqual              |                 |
| F unitsPUS                     | F XmlSnippetKey                |                 |
| F unitsQ                       | F XmlSnippetName               |                 |
| F unitsS                       | F XmlSnippetString             |                 |
| F unitsU                       | F ctxreport                    |                 |
| F unitsUS                      | F viafile                      |                 |
| F unprotect                    | F vrule                        |                 |
| F unregisterfunction           | F xmldataaafter                |                 |
| F usemodule                    | F xmldatabefore                |                 |
| F utfchar                      | F xmldataobeyedline            |                 |
| T verbatim                     | F xmldataobeyedspace           |                 |
| F LuaSnippetBoundary           | F xmlprocessbuffer             |                 |
| F LuaSnippetComment            | F xmlsetup                     |                 |
| F LuaSnippetName               | <b>numbers</b>                 | <b>function</b> |
| F LuaSnippetNameBase           | F C                            |                 |
| F LuaSnippetNameCore           | F FL                           |                 |
| F LuaSnippetNameLibraries      | F HL                           |                 |
| F LuaSnippetQuote              | F L                            |                 |
| F LuaSnippetSpecial            | F LL                           |                 |
| F LuaSnippetString             | F LuaSnippet                   |                 |
| F MetapostSnippetBoundary      | F LuaSnippetBoundary           |                 |
| F MetapostSnippetComment       | F LuaSnippetComment            |                 |
| F MetapostSnippetConstructor   | F LuaSnippetName               |                 |
| F MetapostSnippetName          | F LuaSnippetNameBase           |                 |
| F MetapostSnippetNameMetafun   | F LuaSnippetNameCore           |                 |
| F MetapostSnippetNamePlain     | F LuaSnippetNameLibraries      |                 |
| F MetapostSnippetNamePrimitive | F LuaSnippetQuote              |                 |
| F MetapostSnippetQuote         | F LuaSnippetSpecial            |                 |
| F MetapostSnippetSpecial       | F LuaSnippetString             |                 |
| F MetapostSnippetString        | F ML                           |                 |
| F ParsedXmlSnippetCdata        | F MPLIBsetCtext                |                 |
| F ParsedXmlSnippetComment      | F MPLIBsetNtext                |                 |
| F ParsedXmlSnippetDoctype      | F MPcolor                      |                 |
| F ParsedXmlSnippetElement      | F MetapostSnippet              |                 |
| F ParsedXmlSnippetInstruction  | F MetapostSnippetBoundary      |                 |
| F TexSnippetBoundary           | F MetapostSnippetComment       |                 |
| F TexSnippetComment            | F MetapostSnippetConstructor   |                 |
| F TexSnippetGroup              | F MetapostSnippetName          |                 |
| F TexSnippetName               | F MetapostSnippetNameMetafun   |                 |
| F TexSnippetSpecial            | F MetapostSnippetNamePlain     |                 |
| F XmlSnippetBoundary           | F MetapostSnippetNamePrimitive |                 |
| F XmlSnippetCdata              | F MetapostSnippetQuote         |                 |
| F XmlSnippetComment            | F MetapostSnippetSpecial       |                 |

|                               |                           |
|-------------------------------|---------------------------|
| F MetapostSnippetString       | F btxdirectlink           |
| F NC                          | F btxhandlelistentry      |
| F NR                          | F btxlistauthorsetup      |
| F ParsedXmlSnippetCdata       | F btxlistparameter        |
| F ParsedXmlSnippetComment     | F btxlistsetup            |
| F ParsedXmlSnippetDoctype     | F btxlistvariantparameter |
| F ParsedXmlSnippetElement     | F btxmissing              |
| F ParsedXmlSnippetInstruction | F btxsetauthorindex       |
| F ParsedXmlSnippetKey         | F btxsetauthorvariant     |
| F ParsedXmlSnippetValue       | F btxsetbacklink          |
| F TexSnippet                  | F btxsetbacktrace         |
| F TexSnippetBoundary          | F btxsetcategory          |
| F TexSnippetComment           | F btxsetcitereference     |
| F TexSnippetGroup             | F btxsetcombis            |
| F TexSnippetName              | F btxsetconcat            |
| F TexSnippetSpecial           | F btxsetcount             |
| F XmlSnippet                  | F btxsetdataset           |
| F XmlSnippetBoundary          | F btxsetfirst             |
| F XmlSnippetCdata             | F btxsetfirstnames        |
| F XmlSnippetComment           | F btxsetinitials          |
| F XmlSnippetEntity            | F btxsetinternal          |
| F XmlSnippetEqual             | F btxsetjuniors           |
| F XmlSnippetKey               | F btxsetlanguage          |
| F XmlSnippetName              | F btxsetlefttext          |
| F XmlSnippetString            | F btxsetlistreference     |
| F __flush                     | F btxsetnumber            |
| F __flushdirect               | F btxsetoverflow          |
| F __flushlines                | F btxsetrighttext         |
| F a                           | F btxsetsecond            |
| F addaskedblankskip           | F btxsetsurnames          |
| F addpredefinedblankskip      | F btxsettag               |
| F applyprocessor              | F btxsetthird             |
| F b                           | F btxsetvons              |
| F beginhbox                   | F btxstartauthor          |
| F beginvbox                   | F btxstartcite            |
| F bf                          | F btxstartciteauthor      |
| F bgroup                      | F btxstartsubcite         |
| F blank                       | F btxstopauthor           |
| F bold                        | F btxstopcite             |
| F btxchecklistcombi           | F btxstopciteauthor       |
| F btxchecklistentry           | F btxstopsubcite          |
| F btxciteauthorsetup          | F c                       |
| F btxcitesetup                | F callfunctiononce        |
| F btxcitevariantparameter     | F char                    |

|                              |                               |
|------------------------------|-------------------------------|
| F chardef                    | F dodisplayverbatimemptyline  |
| F color                      | F dodisplayverbatiminitialize |
| F colordefagc                | F dodisplayverbatimnewline    |
| F colordefagt                | F dodisplayverbatimstart      |
| F colordefalc                | F dodisplayverbatimstop       |
| F colordefault               | F dofastdefinetypeface        |
| F colordeffgc                | F dofinishsomereference       |
| F colordeffgt                | F dofromfiledescription       |
| F colordefflc                | F dofromfileliteral           |
| F colordefflt                | F dofromurldescription        |
| F colordefrgc                | F dofromurlliteral            |
| F colordefrgt                | F doinlineverbatimbeginline   |
| F colordefrlc                | F doinlineverbatimemptyline   |
| F colordefrlt                | F doinlineverbatimnewline     |
| F concat                     | F doinlineverbatimstart       |
| F constructcs                | F doinlineverbatimstop        |
| F constructcsonly            | F donestedtypingstart         |
| F convertnumber              | F donestedtypingstop          |
| F ctxreport                  | F dostarttext                 |
| F d                          | F doverbatimspace             |
| F darkblue                   | F egroup                      |
| F darkgreen                  | F emptyreference              |
| F darkred                    | F enablemode                  |
| F definefontsynonym          | F endhbox                     |
| T delayed                    | F endvbox                     |
| F digitsdigit                | F environment                 |
| F digitsfinalcomma           | F expandreferencearguments    |
| F digitsfinalperiod          | F expandreferenceoperation    |
| F digitshighspace            | F finalizeautostructurelevel  |
| F digitsintermediatecomma    | F finishjob                   |
| F digitsintermediateperiod   | F firstofoneargument          |
| F digitsminus                | F firstoftwoarguments         |
| F digitsnegative             | F fixedblankskip              |
| F digitsplus                 | F flexibleblankskip           |
| F digitspositive             | F flushblankhandling          |
| F digitspower                | F flushboxregister            |
| F digitspowerminus           | F flushnode                   |
| F digitspowerplus            | F fntsetdefname               |
| F digitsseparatorspace       | F fntsetnopsiz                |
| F digitssignspace            | F fntsetsomename              |
| F digitsspace                | F fntsetsomesize              |
| F digitsszeropadding         | T formatted                   |
| F direct                     | F fprint                      |
| F dodisplayverbatimbeginline | T generics                    |

|                               |                         |
|-------------------------------|-------------------------|
| S starttabulate               | F poplogger             |
| S stoptabulate                | F printlines            |
| F getlogger                   | F processfilemany       |
| F getreferencestructureprefix | F processfilenone       |
| F getvalue                    | F processfileonce       |
| F glyph                       | F protect               |
| F gobbleoneargument           | T puretext              |
| F goto                        | F pushcatcodes          |
| F hrule                       | F pushlogger            |
| F input                       | F registerentry         |
| T knownfunctions              | F registerfunction      |
| F l                           | F registeronepage       |
| F lateluafunction             | F registerpagerange     |
| F letvaluerelax               | F registerseeword       |
| F llap                        | F reservefunction       |
| F loadfile                    | F rlap                  |
| F loadfoundtypescriptfile     | F rotate                |
| F luasetup                    | F runfile               |
| F m                           | F secondoftwoarguments  |
| F makelinenumber              | F setblankcategory      |
| T metafun                     | F setblankorder         |
| F color                       | F setblankpenalty       |
| T delayed                     | F setconditional        |
| F start                       | F setfalsevalue         |
| F stop                        | F sethboxregister       |
| T nested                      | F setsomevalue          |
| F markingcommand              | F settabulateentry      |
| F markingseparator            | F settabulatelastentry  |
| F newbox                      | F settracing            |
| F newcount                    | F setupsystem           |
| F newdimen                    | F setupwithargument     |
| F newindexer                  | F setvalue              |
| F newmuskup                   | F setvboxregister       |
| F newskip                     | F setxvalue             |
| F newtexthandler              | F space                 |
| F newtoks                     | F sprint                |
| F newverbosehandler           | F startLuaSnippet       |
| F nointerlineskip             | F startMetapostSnippet  |
| F normalatop                  | F startParsedXmlSnippet |
| F normalover                  | F startTexSnippet       |
| F overstrike                  | F startXmlSnippet       |
| F par                         | F startblankhandling    |
| F pdfliteral                  | F startcolumns          |
| F popcatcodes                 | F startcomponentindeed  |

|                          |                              |
|--------------------------|------------------------------|
| F startenvironmentindeed | F tabulaterow                |
| F startfontclass         | F tabulaterowbold            |
| F starthboxregister      | F tabulaterowtyp             |
| F startproductindeed     | F tabulaterowtype            |
| F startprojectindeed     | F template                   |
| F startreadingfile       | T templates                  |
| F startregisterentries   | F texsetup                   |
| F startregisterentry     | F tobuffer                   |
| F startregisteroutput    | F tocontext                  |
| F startregisterpages     | F tolines                    |
| F startregistersection   | F unitsC                     |
| F startregisterseewords  | F unitsN                     |
| F starttabulate          | F unitsNspace                |
| F starttext              | F unitsNstart                |
| F starttitle             | F unitsNstop                 |
| F startvboxregister      | F unitsO                     |
| F startxtitle            | F unitsP                     |
| F stopLuaSnippet         | F unitsPS                    |
| F stopMetapostSnippet    | F unitsPU                    |
| F stopParsedXmlSnippet   | F unitsPUS                   |
| F stopTexSnippet         | F unitsQ                     |
| F stopXmlSnippet         | F unitsS                     |
| F stopblankhandling      | F unitsU                     |
| F stopcolumns            | F unitsUS                    |
| F stopcomponentindeed    | F unprotect                  |
| F stopenvironmentindeed  | F unregisterfunction         |
| F stopfontclass          | F usemodule                  |
| F stophboxregister       | F utfchar                    |
| F stopproductindeed      | T verbatim                   |
| F stopprojectindeed      | F LuaSnippetBoundary         |
| F stopreadingfile        | F LuaSnippetComment          |
| F stopregisterentries    | F LuaSnippetName             |
| F stopregisterentry      | F LuaSnippetNameBase         |
| F stopregisteroutput     | F LuaSnippetNameCore         |
| F stopregisterpages      | F LuaSnippetNameLibraries    |
| F stopregistersection    | F LuaSnippetQuote            |
| F stopregisterseewords   | F LuaSnippetSpecial          |
| F stoptabulate           | F LuaSnippetString           |
| F stoptext               | F MetapostSnippetBoundary    |
| F stoptitle              | F MetapostSnippetComment     |
| F stopvboxregister       | F MetapostSnippetConstructor |
| F stopxtitle             | F MetapostSnippetName        |
| F storenode              | F MetapostSnippetNameMetafun |
| F synonymentry           | F MetapostSnippetNamePlain   |

|                                |          |                        |          |
|--------------------------------|----------|------------------------|----------|
| F MetapostSnippetNamePrimitive |          | pdfstartmatrix         | function |
| F MetapostSnippetQuote         |          | pdfstartmirroring      | function |
| F MetapostSnippetSpecial       |          | pdfstartrotation       | function |
| F MetapostSnippetString        |          | pdfstartscaling        | function |
| F ParsedXmlSnippetCdata        |          | pdfstopmatrix          | function |
| F ParsedXmlSnippetComment      |          | pdfstopmirroring       | function |
| F ParsedXmlSnippetDoctype      |          | pdfstoprotation        | function |
| F ParsedXmlSnippetElement      |          | pdfstopscaling         | function |
| F ParsedXmlSnippetInstruction  |          | percentageof           | function |
| F TexSnippetBoundary           |          | pgfxcolorspec          | function |
| F TexSnippetComment            |          | placeparallel          | function |
| F TexSnippetGroup              |          | popfloat               | function |
| F TexSnippetName               |          | popitaliccorrection    | function |
| F TexSnippetSpecial            |          | poplist                | function |
| F XmlSnippetBoundary           |          | popreferenceprefix     | function |
| F XmlSnippetCdata              |          | popregime              | function |
| F XmlSnippetComment            |          | popsectionblock        | function |
| F XmlSnippetEntity             |          | pos                    | function |
| F XmlSnippetEqual              |          | posplus                | function |
| F XmlSnippetKey                |          | posstrut               | function |
| F XmlSnippetName               |          | postponenotes          | function |
| F XmlSnippetString             |          | poswhd                 | function |
| F ctxreport                    |          | posxy                  | function |
| F viafile                      |          | prefixedconverted      | function |
| F vrule                        |          | prepareMPvariable      | function |
| F xmlcdataafter                |          | preparedfile           | function |
| F xmlcdatabefore               |          | presetsymbolist        | function |
| F xmlcdataobeyedline           |          | presettabulate         | function |
| F xmlcdataobeyedspace          |          | prevcountervalue       | function |
| F xmlprocessbuffer             |          | processbuffer          | function |
| F xmlsetup                     |          | processcolorcomponents | function |
| objectnumber                   | function | processedfile          | function |
| objectpage                     | function | processedfiles         | function |
| octnumber                      | function | processfile            | function |
| octstringtonumber              | function | processfilemany        | function |
| oneorange                      | function | processfilenone        | function |
| ordinal                        | function | processfileonce        | function |
| overloadbookmark               | function | processlist            | function |
| page_injections_flush_after    | function | processregister        | function |
| page_injections_flush_before   | function | processsplit           | function |
| page_injections_save           | function | processsynonyms        | function |
| pagestaterealpage              | function | purefontname           | function |
| parpos                         | function | pushfloat              | function |
| pdfrotation                    | function | pushitaliccorrection   | function |

|                                   |          |                                 |          |
|-----------------------------------|----------|---------------------------------|----------|
| <b>pushlist</b>                   | function | <b>resetmarking</b>             | function |
| <b>pushreferenceprefix</b>        | function | <b>resetmathattributes</b>      | function |
| <b>pushregime</b>                 | function | <b>resetmathitalics</b>         | function |
| <b>pushsectionblock</b>           | function | <b>resetnullfont</b>            | function |
| <b>rawcharacter</b>               | function | <b>resetparallel</b>            | function |
| <b>rawcountervalue</b>            | function | <b>resetprevdepth</b>           | function |
| <b>rawdate</b>                    | function | <b>resetreference</b>           | function |
| <b>referencepagestate</b>         | function | <b>resetstructureprocessor</b>  | function |
| <b>referencecerealpage</b>        | function | <b>resettimer</b>               | function |
| <b>registerattachment</b>         | function | <b>restartcounter</b>           | function |
| <b>registerbookmark</b>           | function | <b>restorecounter</b>           | function |
| <b>registerbuttons</b>            | function | <b>restorecurrentattributes</b> | function |
| <b>registercatcodetable</b>       | function | <b>restorenote</b>              | function |
| <b>registercolor</b>              | function | <b>romannumerals</b>            | function |
| <b>registercolorintent</b>        | function | <b>runbuffer</b>                | function |
| <b>registeredviewerlayer</b>      | function | <b>safechar</b>                 | function |
| <b>registerhelp</b>               | function | <b>savebuffer</b>               | function |
| <b>registeritemgroup</b>          | function | <b>savecounter</b>              | function |
| <b>registerlanguagefeatures</b>   | function | <b>savecurrentattributes</b>    | function |
| <b>registerlinenumbering</b>      | function | <b>savedlistnumber</b>          | function |
| <b>registermaintextcolor</b>      | function | <b>savedlistprefixednumber</b>  | function |
| <b>registernamespace</b>          | function | <b>savedlisttitle</b>           | function |
| <b>registerpostponedblock</b>     | function | <b>savefloat</b>                | function |
| <b>registerrendering</b>          | function | <b>savemargindata</b>           | function |
| <b>registersection</b>            | function | <b>savenote</b>                 | function |
| <b>registersoundclip</b>          | function | <b>saveobject</b>               | function |
| <b>registerstructureprocessor</b> | function | <b>savepagedata</b>             | function |
| <b>registersynonym</b>            | function | <b>saveparallel</b>             | function |
| <b>registertransparency</b>       | function | <b>savestructureblock</b>       | function |
| <b>registerunit</b>               | function | <b>savetaggedtwopassdata</b>    | function |
| <b>registerusedsynonym</b>        | function | <b>save twopassdata</b>         | function |
| <b>registeruserdata</b>           | function | <b>savevariable</b>             | function |
| <b>relatemarking</b>              | function | <b>second</b>                   | function |
| <b>remapentity</b>                | function | <b>selectstructureblock</b>     | function |
| <b>removemissingcharacters</b>    | function | <b>setbreakpoints</b>           | function |
| <b>renderingvar</b>               | function | <b>setbtxdataset</b>            | function |
| <b>replacemissingcharacters</b>   | function | <b>setbtxentry</b>              | function |
| <b>replacepospxywhd</b>           | function | <b>setcharacteralign</b>        | function |
| <b>reportstructure</b>            | function | <b>setcharactercasing</b>       | function |
| <b>resavefloat</b>                | function | <b>setcharactercleaning</b>     | function |
| <b>resetcharacteralign</b>        | function | <b>setcharactercodes</b>        | function |
| <b>resetcounter</b>               | function | <b>setcharacterkerning</b>      | function |
| <b>resetfontfeature</b>           | function | <b>setcharacterspacing</b>      | function |
| <b>resetfontsolution</b>          | function | <b>setcharacterstripping</b>    | function |

|                                 |          |                                |          |
|---------------------------------|----------|--------------------------------|----------|
| <b>setclosedocumentaction</b>   | function | <b>setopenpageaction</b>       | function |
| <b>setclosepageaction</b>       | function | <b>setowncounter</b>           | function |
| <b>setcolormodel</b>            | function | <b>setpagestate</b>            | function |
| <b>setcounter</b>               | function | <b>setpagestaterealpageno</b>  | function |
| <b>setdataset</b>               | function | <b>setpagetransition</b>       | function |
| <b>setdigitsmanipulation</b>    | function | <b>setparbuilder</b>           | function |
| <b>setdirection</b>             | function | <b>setpos</b>                  | function |
| <b>setdocumentenvironments</b>  | function | <b>setrandomseed</b>           | function |
| <b>setdocumentfilenames</b>     | function | <b>setrealign</b>              | function |
| <b>setdocumentmodes</b>         | function | <b>setrealspaces</b>           | function |
| <b>setdocumentmodules</b>       | function | <b>setreferencearguments</b>   | function |
| <b>setelementuserproperties</b> | function | <b>setreferenceattribute</b>   | function |
| <b>setfigurelookuporder</b>     | function | <b>setreferenceoperation</b>   | function |
| <b>setfirstline</b>             | function | <b>setregistermethod</b>       | function |
| <b>setfontfeature</b>           | function | <b>setreplacements</b>         | function |
| <b>setfontofid</b>              | function | <b>setsectionblock</b>         | function |
| <b>setfontsolution</b>          | function | <b>setsectionentry</b>         | function |
| <b>setformat</b>                | function | <b>setsectionlevel</b>         | function |
| <b>setformsmethod</b>           | function | <b>setsectionnumber</b>        | function |
| <b>setinitial</b>               | function | <b>setstructureblockstate</b>  | function |
| <b>setinsertionlocation</b>     | function | <b>settagcombination</b>       | function |
| <b>setinterfaceconstant</b>     | function | <b>settagdescription</b>       | function |
| <b>setinterfaceelement</b>      | function | <b>settagdescriptionsymbol</b> | function |
| <b>setinterfacemessage</b>      | function | <b>settagfigure</b>            | function |
| <b>setinterfacemessages</b>     | function | <b>settaghighlight</b>         | function |
| <b>setinterfacevariable</b>     | function | <b>settagitemgroup</b>         | function |
| <b>setinternalreference</b>     | function | <b>settaglist</b>              | function |
| <b>setjobcomment</b>            | function | <b>settagproperty</b>          | function |
| <b>setlanguageexceptions</b>    | function | <b>settagregister</b>          | function |
| <b>setlanguagesynonym</b>       | function | <b>settagsorting</b>           | function |
| <b>setlayer</b>                 | function | <b>settagsynonym</b>           | function |
| <b>setmarking</b>               | function | <b>settagtablecell</b>         | function |
| <b>setmathalphabet</b>          | function | <b>settagtabulatecell</b>      | function |
| <b>setmathalternate</b>         | function | <b>setupbookmarks</b>          | function |
| <b>setmathattribute</b>         | function | <b>setupcanvas</b>             | function |
| <b>setmathdirection</b>         | function | <b>setupcharacterspacing</b>   | function |
| <b>setmathitalics</b>           | function | <b>setupexport</b>             | function |
| <b>setmathstyle</b>             | function | <b>setupfontexpansion</b>      | function |
| <b>setnextinternalreference</b> | function | <b>setupfontprotrusion</b>     | function |
| <b>setnextreferenceorder</b>    | function | <b>setupidentity</b>           | function |
| <b>setnotestate</b>             | function | <b>setupinsertion</b>          | function |
| <b>setnotesymbolpage</b>        | function | <b>setupitaliccorrection</b>   | function |
| <b>setobject</b>                | function | <b>setuplinenumbering</b>      | function |
| <b>setopendocumentaction</b>    | function | <b>setvisual</b>               | function |



|                                   |          |                                  |          |
|-----------------------------------|----------|----------------------------------|----------|
| <b>setxmpfile</b>                 | function | <b>stoptag</b>                   | function |
| <b>showassignerror</b>            | function | <b>stoptext</b>                  | function |
| <b>showattributes</b>             | function | <b>stopviewerlayer</b>           | function |
| <b>showbtxdatasetcompleteness</b> | function | <b>storejavascriptcode</b>       | function |
| <b>showbtxdatasetfields</b>       | function | <b>storejavascriptpreamble</b>   | function |
| <b>showbtxfields</b>              | function | <b>storenote</b>                 | function |
| <b>showcallbacks</b>              | function | <b>storeregister</b>             | function |
| <b>showchardata</b>               | function | <b>strdp</b>                     | function |
| <b>showcounter</b>                | function | <b>strhd</b>                     | function |
| <b>showfontparameters</b>         | function | <b>strht</b>                     | function |
| <b>showhyphenatedinlist</b>       | function | <b>strip</b>                     | function |
| <b>showjustification</b>          | function | <b>structureautocatcodedget</b>  | function |
| <b>showmessage</b>                | function | <b>structurecatcodedget</b>      | function |
| <b>sin</b>                        | function | <b>structuregivencatcodedget</b> | function |
| <b>sind</b>                       | function | <b>structurenumber</b>           | function |
| <b>splitfilename</b>              | function | <b>structuretitle</b>            | function |
| <b>spotcolorname</b>              | function | <b>structureuservariable</b>     | function |
| <b>spotcolorparent</b>            | function | <b>structurevariable</b>         | function |
| <b>spotcolorvalue</b>             | function | <b>strwd</b>                     | function |
| <b>startactualtext</b>            | function | <b>subcountervalues</b>          | function |
| <b>startchemical</b>              | function | <b>synchronizecolormodel</b>     | function |
| <b>startcolorset</b>              | function | <b>synchronizemarking</b>        | function |
| <b>startcomponent</b>             | function | <b>synonymmeaning</b>            | function |
| <b>startenvironment</b>           | function | <b>synonymname</b>               | function |
| <b>startfontsolution</b>          | function | <b>taggedmathfunction</b>        | function |
| <b>startparbuilder</b>            | function | <b>tan</b>                       | function |
| <b>startproduct</b>               | function | <b>tand</b>                      | function |
| <b>startproject</b>               | function | <b>testcase</b>                  | function |
| <b>startregime</b>                | function | <b>textime</b>                   | function |
| <b>startsectionlevel</b>          | function | <b>thefirstcharacter</b>         | function |
| <b>starttag</b>                   | function | <b>theremainingcharacters</b>    | function |
| <b>starttext</b>                  | function | <b>thetexdefinition</b>          | function |
| <b>startviewerlayer</b>           | function | <b>transparencycomponents</b>    | function |
| <b>stopactualtext</b>             | function | <b>triggereffect</b>             | function |
| <b>stopchemical</b>               | function | <b>triggernegative</b>           | function |
| <b>stopcolorset</b>               | function | <b>truefilename</b>              | function |
| <b>stopcomponent</b>              | function | <b>typebuffer</b>                | function |
| <b>stopenvironment</b>            | function | <b>typefile</b>                  | function |
| <b>stopfontsolution</b>           | function | <b>typestring</b>                | function |
| <b>stopparbuilder</b>             | function | <b>uchexnumber</b>               | function |
| <b>stopproduct</b>                | function | <b>uchexnumbers</b>              | function |
| <b>stopproject</b>                | function | <b>undefinechemical</b>          | function |
| <b>stopregime</b>                 | function | <b>unicodechar</b>               | function |
| <b>stopsectionlevel</b>           | function | <b>unit</b>                      | function |

|                              |          |                                   |          |
|------------------------------|----------|-----------------------------------|----------|
| <b>unloadlanguage</b>        | function | <b>x_table_c</b>                  | function |
| <b>upper</b>                 | function | <b>x_table_cleanup</b>            | function |
| <b>useMPLibrary</b>          | function | <b>x_table_construct</b>          | function |
| <b>useanyfile</b>            | function | <b>x_table_create</b>             | function |
| <b>usebtxdataset</b>         | function | <b>x_table_flush</b>              | function |
| <b>usecldfile</b>            | function | <b>x_table_init_construct</b>     | function |
| <b>usecolors</b>             | function | <b>x_table_init_reflow_height</b> | function |
| <b>usecomponent</b>          | function | <b>x_table_init_reflow_width</b>  | function |
| <b>useenvironment</b>        | function | <b>x_table_next_row</b>           | function |
| <b>usefile</b>               | function | <b>x_table_r</b>                  | function |
| <b>usejavascriptpreamble</b> | function | <b>x_table_reflow_height</b>      | function |
| <b>usejavascriptscripts</b>  | function | <b>x_table_reflow_width</b>       | function |
| <b>uselibrary</b>            | function | <b>x_table_set_construct</b>      | function |
| <b>useluafile</b>            | function | <b>x_table_set_reflow_height</b>  | function |
| <b>uselua module</b>         | function | <b>x_table_set_reflow_width</b>   | function |
| <b>usemodules</b>            | function | <b>year</b>                       | function |
| <b>usepath</b>               | function |                                   |          |
| <b>useproduct</b>            | function |                                   |          |
| <b>useproject</b>            | function |                                   |          |
| <b>usesubpath</b>            | function |                                   |          |
| <b>usesymbols</b>            | function |                                   |          |
| <b>usetexfile</b>            | function |                                   |          |
| <b>useurl</b>                | function |                                   |          |
| <b>usexmlfile</b>            | function |                                   |          |
| <b>usezipfile</b>            | function |                                   |          |
| <b>utfchar</b>               | function |                                   |          |
| <b>utfmathclass</b>          | function |                                   |          |
| <b>utfmathcommand</b>        | function |                                   |          |
| <b>utfmathcommandabove</b>   | function |                                   |          |
| <b>utfmathcommandbelow</b>   | function |                                   |          |
| <b>utfmathfiller</b>         | function |                                   |          |
| <b>utfmathstretch</b>        | function |                                   |          |
| <b>vboxlisttohbox</b>        | function |                                   |          |
| <b>verbose</b>               | function |                                   |          |
| <b>visual</b>                | function |                                   |          |
| <b>vspacing</b>              | function |                                   |          |
| <b>vspacingcollapse</b>      | function |                                   |          |
| <b>vspacingdefine</b>        | function |                                   |          |
| <b>vspacingsetamount</b>     | function |                                   |          |
| <b>vspacingsnap</b>          | function |                                   |          |
| <b>way</b>                   | function |                                   |          |
| <b>weekday</b>               | function |                                   |          |
| <b>weekdayname</b>           | function |                                   |          |
| <b>writestatus</b>           | function |                                   |          |

## containers (context)

|                   |          |
|-------------------|----------|
| <b>cleannname</b> | function |
| <b>content</b>    | function |
| <b>define</b>     | function |
| <b>is_usable</b>  | function |
| <b>is_valid</b>   | function |
| <b>read</b>       | function |
| <b>usecache</b>   | boolean  |
| <b>write</b>      | function |

## converters (context)

|                           |          |                          |            |
|---------------------------|----------|--------------------------|------------|
| <b>A</b>                  | function | <b>octstringtonumber</b> | function   |
| <b>AK</b>                 | function | <b>ordinal</b>           | function   |
| <b>Alphabetic</b>         | function | <b>r</b>                 | function   |
| <b>Character</b>          | function | <b>rawcharacter</b>      | function   |
| <b>Characters</b>         | function | <b>romannumerals</b>     | function   |
| <b>I</b>                  | function | <b>second</b>            | function   |
| <b>KA</b>                 | function | <b>sequences</b>         | data table |
| <b>KR</b>                 | function | <b>textime</b>           | function   |
| <b>R</b>                  | function | <b>toabjad</b>           | function   |
| <b>RK</b>                 | function | <b>tochinese</b>         | function   |
| <b>Romannumerals</b>      | function | <b>toroman</b>           | function   |
| <b>Word</b>               | function | <b>upper</b>             | function   |
| <b>Words</b>              | function | <b>verbose</b>           | table      |
| <b>a</b>                  | function | D data                   |            |
| <b>abjadnodotnumerals</b> | function | F translate              |            |
| <b>abjadnumerals</b>      | function | <b>weekday</b>           | function   |
| <b>alphabetic</b>         | function | <b>word</b>              | function   |
| <b>character</b>          | function | <b>words</b>             | function   |
| <b>characters</b>         | function | <b>year</b>              | function   |
| <b>chineseallnumerals</b> | function |                          |            |
| <b>chineseapnumerals</b>  | function |                          |            |
| <b>chinesenumerals</b>    | function |                          |            |
| <b>chr</b>                | function |                          |            |
| <b>chrs</b>               | function |                          |            |
| <b>cn</b>                 | function |                          |            |
| <b>cn-a</b>               | function |                          |            |
| <b>cn-c</b>               | function |                          |            |
| <b>convert</b>            | function |                          |            |
| <b>define</b>             | function |                          |            |
| <b>hexstringtonumber</b>  | function |                          |            |
| <b>hour</b>               | function |                          |            |
| <b>i</b>                  | function |                          |            |
| <b>isleapyear</b>         | function |                          |            |
| <b>leapyear</b>           | function |                          |            |
| <b>lower</b>              | function |                          |            |
| <b>maxchrs</b>            | function |                          |            |
| <b>minute</b>             | function |                          |            |
| <b>month</b>              | function |                          |            |
| <b>nofdays</b>            | function |                          |            |
| <b>number</b>             | function |                          |            |
| <b>numbers</b>            | function |                          |            |

## coroutine (basic lua)

|                |          |
|----------------|----------|
| <b>create</b>  | function |
| <b>resume</b>  | function |
| <b>running</b> | function |
| <b>status</b>  | function |
| <b>wrap</b>    | function |
| <b>yield</b>   | function |

## ctxrunner (context)

|                  |            |
|------------------|------------|
| <b>load</b>      | function   |
| <b>prepfiles</b> | data table |
| <b>resolve</b>   | function   |

## debug (basic lua)

|                     |          |
|---------------------|----------|
| <b>debug</b>        | function |
| <b>getfenv</b>      | function |
| <b>gethook</b>      | function |
| <b>getinfo</b>      | function |
| <b>getlocal</b>     | function |
| <b>getmetatable</b> | function |
| <b>getregistry</b>  | function |
| <b>getupvalue</b>   | function |
| <b>getuservalue</b> | function |
| <b>setfenv</b>      | function |
| <b>sethook</b>      | function |
| <b>setlocal</b>     | function |
| <b>setmetatable</b> | function |
| <b>setupvalue</b>   | function |
| <b>setuservalue</b> | function |
| <b>traceback</b>    | function |
| <b>upvalueid</b>    | function |
| <b>upvaluejoin</b>  | function |

## dir (context)

|                       |          |
|-----------------------|----------|
| <b>collectpattern</b> | function |
| <b>current</b>        | function |
| <b>expandname</b>     | function |
| <b>found</b>          | function |
| <b>glob</b>           | function |
| <b>globfiles</b>      | function |
| <b>globpattern</b>    | function |
| <b>ls</b>             | function |
| <b>makedirs</b>       | function |
| <b>mkdirs</b>         | function |
| <b>pop</b>            | function |
| <b>push</b>           | function |



## directives (context)

|                 |            |
|-----------------|------------|
| <b>data</b>     | data table |
| <b>default</b>  | function   |
| <b>disable</b>  | function   |
| <b>enable</b>   | function   |
| <b>list</b>     | function   |
| <b>name</b>     | string     |
| <b>register</b> | function   |
| <b>report</b>   | function   |
| <b>show</b>     | function   |
| <b>value</b>    | function   |

# document (context)

|                           |            |
|---------------------------|------------|
| <b>arguments</b>          | data table |
| <b>files</b>              | table      |
| <b>getargument</b>        | function   |
| <b>getfilename</b>        | function   |
| <b>options</b>            | table      |
| T cmdline                 |            |
| D environments            |            |
| D modes                   |            |
| D modules                 |            |
| T ctxfile                 |            |
| D environments            |            |
| D modes                   |            |
| D modules                 |            |
| <b>setargument</b>        | function   |
| <b>setdefaultargument</b> | function   |
| <b>setfilename</b>        | function   |
| <b>variables</b>          | data table |

## environment (context)

|                               |            |                     |            |
|-------------------------------|------------|---------------------|------------|
| <b>argument</b>               | function   | <b>texroot</b>      | string     |
| <b>arguments</b>              | data table | <b>truefilename</b> | function   |
| <b>basicengines</b>           | data table | <b>validengines</b> | data table |
| <b>currentrun</b>             | number     |                     |            |
| <b>default_texmfcnf</b>       | string     |                     |            |
| <b>engineflags</b>            | data table |                     |            |
| <b>filename</b>               | string     |                     |            |
| <b>files</b>                  | table      |                     |            |
| <b>filesynonyms</b>           | data table |                     |            |
| <b>forcedruns</b>             | number     |                     |            |
| <b>getargument</b>            | function   |                     |            |
| <b>homedir</b>                | string     |                     |            |
| <b>initex</b>                 | boolean    |                     |            |
| <b>initializearguments</b>    | function   |                     |            |
| <b>initializefilenames</b>    | function   |                     |            |
| <b>inputfilebarename</b>      | string     |                     |            |
| <b>inputfilename</b>          | string     |                     |            |
| <b>inputfilesuffix</b>        | string     |                     |            |
| <b>jobfilename</b>            | string     |                     |            |
| <b>jobfilesuffix</b>          | string     |                     |            |
| <b>kindofrun</b>              | number     |                     |            |
| <b>loadluafile</b>            | function   |                     |            |
| <b>luafile</b>                | function   |                     |            |
| <b>luafilechunk</b>           | function   |                     |            |
| <b>maxnofruns</b>             | number     |                     |            |
| <b>originalarguments</b>      | data table |                     |            |
| <b>outputfilename</b>         | string     |                     |            |
| <b>ownbin</b>                 | string     |                     |            |
| <b>ownmain</b>                | string     |                     |            |
| <b>ownname</b>                | string     |                     |            |
| <b>ownpath</b>                | string     |                     |            |
| <b>prerollrun</b>             | boolean    |                     |            |
| <b>rawarguments</b>           | data table |                     |            |
| <b>reconstructcommandline</b> | function   |                     |            |
| <b>relativepath</b>           | function   |                     |            |
| <b>setargument</b>            | function   |                     |            |
| <b>splitarguments</b>         | function   |                     |            |
| <b>suffix</b>                 | string     |                     |            |
| <b>texfile</b>                | function   |                     |            |
| <b>texmfos</b>                | string     |                     |            |
| <b>texos</b>                  | string     |                     |            |

## epdf (extra tex)

|                     |          |
|---------------------|----------|
| <b>Array</b>        | function |
| <b>Dict</b>         | function |
| <b>Object</b>       | function |
| <b>PDFRectangle</b> | function |
| <b>open</b>         | function |
| <b>type</b>         | function |

## experiments (context)

|                 |            |
|-----------------|------------|
| <b>data</b>     | data table |
| <b>default</b>  | function   |
| <b>disable</b>  | function   |
| <b>enable</b>   | function   |
| <b>list</b>     | function   |
| <b>name</b>     | string     |
| <b>register</b> | function   |
| <b>report</b>   | function   |
| <b>show</b>     | function   |
| <b>value</b>    | function   |

# figures (context)

|                      |            |
|----------------------|------------|
| <b>applyratio</b>    | function   |
| <b>badname</b>       | function   |
| <b>bases</b>         | data table |
| <b>bitmapimage</b>   | function   |
| <b>boxnumber</b>     | number     |
| <b>cachepaths</b>    | data table |
| <b>check</b>         | function   |
| <b>checkers</b>      | data table |
| <b>converters</b>    | data table |
| <b>current</b>       | function   |
| <b>defaultdepth</b>  | number     |
| <b>defaultheight</b> | number     |
| <b>defaultsearch</b> | boolean    |
| <b>defaultwidth</b>  | number     |
| <b>done</b>          | function   |
| <b>dummy</b>         | function   |
| <b>exists</b>        | data table |
| <b>exists</b>        | function   |
| <b>formats</b>       | data table |
| <b>found</b>         | data table |
| <b>get</b>           | function   |
| <b>guess</b>         | function   |
| <b>hash</b>          | function   |
| <b>identifiers</b>   | data table |
| <b>identify</b>      | function   |
| <b>images</b>        | table      |

- F boxes
- F check
- F checksize
- F clone
- F copy
- F immediatewrite
- F keys
- F new
- F node
- F ofindex
- F package
- F print
- F scan
- F serialize
- F totable

|                         |            |
|-------------------------|------------|
| F types                 |            |
| F write                 |            |
| <b>include</b>          | function   |
| <b>includers</b>        | data table |
| <b>initialize</b>       | function   |
| <b>loaded</b>           | data table |
| <b>localpaths</b>       | data table |
| <b>magics</b>           | data table |
| <b>mergegoodies</b>     | function   |
| <b>nofprocessed</b>     | number     |
| <b>order</b>            | data table |
| <b>paths</b>            | data table |
| <b>patterns</b>         | data table |
| <b>pop</b>              | function   |
| <b>preferquality</b>    | boolean    |
| <b>programs</b>         | data table |
| <b>push</b>             | function   |
| <b>registerpattern</b>  | function   |
| <b>registerresource</b> | function   |
| <b>registersuffix</b>   | function   |
| <b>resources</b>        | data table |
| <b>scale</b>            | function   |
| <b>setlookups</b>       | function   |
| <b>setorder</b>         | function   |
| <b>setpaths</b>         | function   |
| <b>suffixes</b>         | data table |
| <b>used</b>             | data table |

## file (basic lua)

|                          |          |
|--------------------------|----------|
| <b>addsuffix</b>         | function |
| <b>basename</b>          | function |
| <b>checksum</b>          | function |
| <b>collapsepath</b>      | function |
| <b>copy</b>              | function |
| <b>dirname</b>           | function |
| <b>expandname</b>        | function |
| <b>extname</b>           | function |
| <b>is_qualified_path</b> | function |
| <b>is_readable</b>       | function |
| <b>is_rootbased_path</b> | function |
| <b>is_writable</b>       | function |
| <b>isreadable</b>        | function |
| <b>iswritable</b>        | function |
| <b>join</b>              | function |
| <b>joinpath</b>          | function |
| <b>loadchecksum</b>      | function |
| <b>nameonly</b>          | function |
| <b>nametotable</b>       | function |
| <b>needs Updating</b>    | function |
| <b>needsupdating</b>     | function |
| <b>pathpart</b>          | function |
| <b>readdata</b>          | function |
| <b>removesuffix</b>      | function |
| <b>replacesuffix</b>     | function |
| <b>reslash</b>           | function |
| <b>robustname</b>        | function |
| <b>savechecksum</b>      | function |
| <b>savedata</b>          | function |
| <b>size</b>              | function |
| <b>splitbase</b>         | function |
| <b>splitname</b>         | function |
| <b>splitpath</b>         | function |
| <b>strip</b>             | function |
| <b>suffix</b>            | function |
| <b>suffixes</b>          | function |
| <b>suffixesonly</b>      | function |
| <b>suffixonly</b>        | function |
| <b>syncmtimes</b>        | function |

## floats (context)

|                         |          |
|-------------------------|----------|
| <b>analysemethod</b>    | function |
| <b>checkedpagefloat</b> | function |
| <b>collect</b>          | function |
| <b>consult</b>          | function |
| <b>flush</b>            | function |
| <b>getvariable</b>      | function |
| <b>nofstacked</b>       | function |
| <b>pop</b>              | function |
| <b>push</b>             | function |
| <b>resave</b>           | function |
| <b>save</b>             | function |
| <b>stacked</b>          | function |



## font (basic tex)

|                 |                     |
|-----------------|---------------------|
| <b>current</b>  | function            |
| <b>define</b>   | function            |
| <b>each</b>     | function            |
| <b>fonts</b>    | table               |
| <b>frozen</b>   | function            |
| <b>getfont</b>  | overloaded function |
| <b>id</b>       | function            |
| <b>max</b>      | function            |
| <b>nextid</b>   | function            |
| <b>read_tfm</b> | function            |
| <b>read_vf</b>  | function            |
| <b>setfont</b>  | function            |

## fontloader (extra tex)

|                          |          |
|--------------------------|----------|
| <b>apply_afmfile</b>     | function |
| <b>apply_featurefile</b> | function |
| <b>close</b>             | function |
| <b>fields</b>            | function |
| <b>fullinfo</b>          | function |
| <b>info</b>              | function |
| <b>open</b>              | function |
| <b>to_table</b>          | function |
| <b>totable</b>           | function |

# fonts (context)

|                    |       |                           |           |
|--------------------|-------|---------------------------|-----------|
| <b>analyzers</b>   | table |                           | F report  |
| T features         |       |                           | F reset   |
| N blwf             |       |                           | T vectors |
| N fina             |       | <b>constructors</b>       | table     |
| N half             |       | F aftercopyingcharacters  |           |
| N init             |       | F applymanipulators       |           |
| N isol             |       | F assignmathparameters    |           |
| N medi             |       | B autocleanup             |           |
| N pref             |       | F beforecopyingcharacters |           |
| N pstf             |       | D cache                   |           |
| N rphf             |       | F calculatyscale          |           |
| D initializers     |       | F checkedfeatures         |           |
| D methods          |       | F checkedfilename         |           |
| F setstate         |       | F checkvirtualids         |           |
| T states           |       | F cleanupable             |           |
| N blwf             |       | F collectprocessors       |           |
| N fina             |       | D designsizes             |           |
| N half             |       | D dontembed               |           |
| N init             |       | F enhanceparameters       |           |
| N isol             |       | N factor                  |           |
| N mark             |       | F finalize                |           |
| N medi             |       | F getfeatureaction        |           |
| N pref             |       | F hashfeatures            |           |
| N pstf             |       | F hashinstance            |           |
| N rest             |       | T hashmethods             |           |
| N rphf             |       | F normal                  |           |
| B useunicodemarks  |       | F virtual                 |           |
| <b>checkers</b>    | table | F initializefeatures      |           |
| F getmissing       |       | T keys                    |           |
| F missing          |       | T character               |           |
| <b>cid</b>         | table | S depth                   |           |
| F getmap           |       | S height                  |           |
| F loadfile         |       | S italic                  |           |
| <b>collections</b> | table | S width                   |           |
| F checkenabled     |       | T description             |           |
| F clonevector      |       | T boundingbox             |           |
| F define           |       | S depth                   |           |
| T definitions      |       | S height                  |           |
| F prepare          |       | S width                   |           |
| F process          |       | T parameters              |           |
| F registermain     |       | S ascender                |           |

|                          |                       |          |
|--------------------------|-----------------------|----------|
| S descender              | S encodingbytes       |          |
| S designsize             | S filename            |          |
| T expansion              | S finalized           |          |
| S auto                   | S fontname            |          |
| S shrink                 | S format              |          |
| S step                   | S fullname            |          |
| S stretch                | S hasitalics          |          |
| S extendfactor           | S hasmath             |          |
| S factor                 | S mathitalics         |          |
| S hfactor                | S mode                |          |
| S mathsize               | S name                |          |
| T protrusion             | S noglyphnames        |          |
| S auto                   | S nostackmath         |          |
| S quad                   | S psname              |          |
| S scaledpoints           | S textitalics         |          |
| S scriptpercentage       | S virtualized         |          |
| S scriptscriptpercentage | D loadedfonts         |          |
| S size                   | S namemode            |          |
| S slantfactor            | F newfeatures         |          |
| S slantperpoint          | F newhandler          |          |
| T spacing                | N noffontsloaded      |          |
| S extra                  | N nofsharedfonts      |          |
| S shrink                 | N nofsharedhashes     |          |
| S stretch                | N nofsharedvectors    |          |
| S width                  | N privateoffset       |          |
| T synonyms               | F readanddefine       |          |
| S em                     | F registerfeature     |          |
| S ex                     | B resolvevirtualtoo   |          |
| S extra_space            | F scale               |          |
| S extraspace             | F scaled              |          |
| S slant                  | F setfactor           |          |
| S space                  | F setname             |          |
| S space_shrink           | B sharefonts          |          |
| S space_stretch          | F trytosharefont      |          |
| S spaceshrink            | N version             |          |
| S spacestretch           | <b>current</b>        | function |
| S x_height               | <b>currentid</b>      | function |
| S units                  | <b>definers</b>       | table    |
| S vfactor                | F addlookup           |          |
| S xheight                | F analyze             |          |
| T properties             | F applypostprocessors |          |
| S autoitalicamount       | F checkedmode         |          |
| T cidinfo                | F checkedscript       |          |
| S embedding              | F current             |          |

- S defaultlookup
- F define
- F getspecification
- F internal
- F loadfont
- F makespecification
- T methods
  - F install
  - D variants
- F read
- F register
- F registered
- F registersplit
- F resetnullfont
- F resolve
- T resolvers
  - F file
  - F name
  - F spec

**definetypeface**    function

**encodings**        table

- T agl
- D cache
- F is\_known
- D known
- F load
- F make\_unicode\_vector
- D math
- N version

**expansions**        data table

**formats**           data table

**goodies**           table

- D colorschemes
- D data
- D designsizes
- D filenames
- F getcompositions
- T list
  - F compositions
  - F designsizes
  - F expansions
  - F featureset
  - F filenames
  - F files

- F mathematics
- F protrusions
- F solutions
- F treatments
- F typefaces
- F load
- F prepare\_features
- F register
- F registerpostprocessor
- F report

**handlers**           table

- T afm
  - B addkerns
  - B addligatures
  - B addtexligatures
  - B autoprefixed
  - D cache
  - D features
  - T helpdata
    - D bothkerned
    - D leftkerned
    - D ligatures
    - D rightkerned
    - D texligatures
  - F load
  - F setfeatures
  - B syncspace
  - N version
- T otf
  - F addfeature
  - D cache
  - T chainhandlers
    - F normal
    - F verbose
  - F collectlookups
  - F dataset
  - S defaultbasealternate
  - S defaultnodealternate
  - D enhancers
  - D features
  - F fileformat
  - F getalternate
  - T glists
  - T handlers

|   |                      |              |
|---|----------------------|--------------|
| F contextchain                                      | D math               |              |
| F devanagari_remove_joiners                         | D predefined         |              |
| F devanagari_reorder_matras                         | D whatever           |              |
| F devanagari_reorder_pre_base_reordering_consonants | <b>hashes</b>        | <b>table</b> |
| F devanagari_reorder_reph                           | D characters         |              |
| F gpos_context                                      | D csnames            |              |
| F gpos_contextchain                                 | D descriptions       |              |
| F gpos_cursive                                      | D dynamics           |              |
| F gpos_mark2base                                    | D emwidths           |              |
| F gpos_mark2ligature                                | D exheights          |              |
| F gpos_mark2mark                                    | D extensibles        |              |
| F gpos_pair   | D features           |              |
| F gpos_single                                       | D identifiers        |              |
| F gsub_alternate                                    | D italics            |              |
| F gsub_context                                      | D lastmathids        |              |
| F gsub_contextchain                                 | D marks              |              |
| F gsub_ligature                                     | D parameters         |              |
| F gsub_multiple                                     | T processes          |              |
| F gsub_reversecontextchain                          | D properties         |              |
| F gsub_single                                       | D quads              |              |
| F load  | D resources          |              |
| F scriptandlanguage                                 | T setdynamics        |              |
| F setcontextchain                                   | D spaces             |              |
| F setdynamics                                       | D spacings           |              |
| F setfeatures                                       | D unicodes           |              |
| T statistics  | D xheights           |              |
| D usedfeatures                                      | <b>helpers</b>       | <b>table</b> |
| T tables  | F addprivate         |              |
| D baselines   | F dimenfactor        |              |
| D features  | F expandglyph        |              |
| D languages   | F fontpatternhassize |              |
| D scripts   | F getdigitwidth      |              |
| N version   | F getparameters      |              |
| T pfb   | F getprivatenode     |              |
| T tfm   | F hasprivate         |              |
| D features  | F indextoslot        |              |
| F setfeatures                                       | F name               |              |
| T vf  | F nametoslot         |              |
| T combinations                                      | F setdigitwidth      |              |
| F combine   | F splitfontpattern   |              |
| T combiner  | <b>iterators</b>     | <b>table</b> |
| D commands  | F characters         |              |
| F find  | F descriptions       |              |
| D helpers   | F glyphs             |              |

## loggers table

F add\_placeholders  
T category\_to\_placeholder  
S ll  
S lm  
S lo  
S lt  
S lu  
S mc  
S me  
S mn  
S nd  
S nl  
S no  
S pc  
S pd  
S pe  
S pf  
S pi  
S po  
S ps  
S sc  
S sk  
S sm  
S so  
F format  
F onetimemessage  
F register  
F reportdefinedfonts  
F reportusedfeatures

## mappings table

F addtounicode  
F fromunicode16  
F loadfile  
F loadline  
F loadlumtable  
F makenameparser  
F reset  
F tounicode16  
F tounicode16sequence

## mp table

D cache  
B inline  
N version

## names data table

## nulldata data table

## protrusions data table

## readers table

F afm  
F check\_lua  
F check\_tfm  
F dfont  
F lua  
F opentype  
F otf  
F pfb  
D sequence  
F tfm  
F ttc  
F ttf

## select table

T data  
F definetypeface  
T fallbacks  
F filterinput  
T methods  
F default  
F features  
F file  
F goodies  
F name  
F selectfont  
F simplefonts  
F spec  
F style  
F registerfallback  
F searchfiles

## specifiers table

D contextmerged  
F contextnumber  
D contextnumbers  
D contextsetups  
F contexttostring  
F definecontext  
F mergecontext  
F presetcontext  
F registercontext  
F showcontext

F splitcontext  
D synonyms  
D variants  
**symbols** table  
F uselibrary  
**tables** table  
**tracers** table  
**treatments** table  
F applyfixes  
D data  
S filename  
F ignoredfile  
F report  
F trace  
**typefaces** data table



# functions (context)

**dummy** function

# graphics (context)

## **backgrounds** table

F calculatemultipar

F fetchmultipar

F pair

F path

F point

## gzip (extra lua)

|               |          |
|---------------|----------|
| <b>close</b>  | function |
| <b>lines</b>  | function |
| <b>load</b>   | function |
| <b>open</b>   | function |
| <b>save</b>   | function |
| <b>suffix</b> | function |

## img (basic tex)

|                       |          |
|-----------------------|----------|
| <b>boxes</b>          | function |
| <b>check</b>          | function |
| <b>checksize</b>      | function |
| <b>clone</b>          | function |
| <b>copy</b>           | function |
| <b>immediatewrite</b> | function |
| <b>keys</b>           | function |
| <b>new</b>            | function |
| <b>node</b>           | function |
| <b>ofindex</b>        | function |
| <b>package</b>        | function |
| <b>print</b>          | function |
| <b>scan</b>           | function |
| <b>serialize</b>      | function |
| <b>totable</b>        | function |
| <b>types</b>          | function |
| <b>write</b>          | function |

# interactions (context)

**attachments** data table

**fields** table

F clone

F define

F defineset

F insert

**general** table

F getidentity

F setupidentity

**help** table

F collect

F reference

F register

**javascripts** table

F addtopreamble

F code

D codes

F flushpreambles

D functions

D preambles

F setpreamble

F storecode

F storepreamble

F usepreamblenow

F usescripts

**linkedlists** data table

**pages** table

F setpagetransition

F setupcanvas

**references** table

F setclosedocument

F setclosepage

F setopendocument

F setopenpage

**renderings** data table

**soundclips** data table

# interfaces (context)

|                             |            |
|-----------------------------|------------|
| <b>addvalidkeys</b>         | function   |
| <b>cachedsetups</b>         | data table |
| <b>cachesetup</b>           | function   |
| <b>checkedspecification</b> | function   |
| <b>complete</b>             | data table |
| <b>constants</b>            | data table |
| <b>corenamespaces</b>       | data table |
| <b>definecommand</b>        | function   |
| <b>doifelsemessage</b>      | function   |
| <b>elements</b>             | data table |
| <b>formats</b>              | data table |
| <b>getcheckedparameters</b> | function   |
| <b>getmessage</b>           | function   |
| <b>hashedsetups</b>         | data table |
| <b>interfacedcommand</b>    | function   |
| <b>interfaces</b>           | table      |
| <b>invalidkey</b>           | function   |
| <b>is_command</b>           | function   |
| <b>namespaces</b>           | table      |
| F define                    |            |
| F list                      |            |
| <b>registernamespace</b>    | function   |
| <b>setconstant</b>          | function   |
| <b>setelement</b>           | function   |
| <b>setformat</b>            | function   |
| <b>setmessage</b>           | function   |
| <b>setmessages</b>          | function   |
| <b>settranslation</b>       | function   |
| <b>setuserinterface</b>     | function   |
| <b>setvalidkeys</b>         | function   |
| <b>setvariable</b>          | function   |
| <b>showmessage</b>          | function   |
| <b>syntax</b>               | data table |
| <b>tolist</b>               | function   |
| <b>translations</b>         | data table |
| <b>variables</b>            | data table |

## io (basic lua)

|                      |                     |
|----------------------|---------------------|
| <b>ask</b>           | function            |
| <b>bytes</b>         | function            |
| <b>characters</b>    | function            |
| <b>close</b>         | function            |
| <b>exists</b>        | function            |
| <b>fileseparator</b> | string              |
| <b>flush</b>         | function            |
| <b>i_limiter</b>     | function            |
| <b>i_limiters</b>    | table               |
| T paranoid           |                     |
| <b>input</b>         | function            |
| <b>limiter</b>       | function            |
| <b>lines</b>         | function            |
| <b>loadchunk</b>     | function            |
| <b>loaddata</b>      | function            |
| <b>loadlines</b>     | function            |
| <b>noflines</b>      | function            |
| <b>o_limiter</b>     | function            |
| <b>o_limiters</b>    | table               |
| T paranoid           |                     |
| <b>open</b>          | overloaded function |
| <b>output</b>        | function            |
| <b>pathseparator</b> | string              |
| <b>popen</b>         | overloaded function |
| <b>read</b>          | function            |
| <b>readall</b>       | function            |
| <b>readnumber</b>    | function            |
| <b>readstring</b>    | function            |
| <b>savedata</b>      | function            |
| <b>size</b>          | function            |
| <b>stderr</b>        | userdata            |
| <b>stdin</b>         | userdata            |
| <b>stdout</b>        | userdata            |
| <b>tmpfile</b>       | function            |
| <b>type</b>          | function            |
| <b>write</b>         | function            |

# jit (context)

|               |          |
|---------------|----------|
| <b>arch</b>   | string   |
| <b>attach</b> | function |
| <b>flush</b>  | function |
| <b>off</b>    | function |
| <b>on</b>     | function |
| <b>opt</b>    | table    |
| F start       |          |
| <b>os</b>     | string   |
| <b>status</b> | function |
| <b>util</b>   | table    |

|                 |
|-----------------|
| F funcbc        |
| F funcinfo      |
| F funcn         |
| F funcuvname    |
| F ircalladdr    |
| F traceexitstub |
| F traceinfo     |
| F traceir       |
| F tracek        |
| F tracemc       |
| F tracesnap     |

|                    |        |
|--------------------|--------|
| <b>version</b>     | string |
| <b>version_num</b> | number |



# job (context)

**comment** function

**datasets** table

D collected

F extend

F getdata

F setdata

D tobesaved

**disablesave** function

**files** table

D collected

F context

B forcerun

F run

D tobesaved

**initialize** function

**load** function

**loadother** function

**objects** table

D collected

F get

F number

F page

F save

F set

D tobesaved

**pack** boolean

**packversion** number

**pagestates** table

D collected

F extend

F realpage

F setstate

D tobesaved

**passes** table

F check

D collected

F count

F define

F find

F first

F get

F getcollected

F getdata

F getfield

F gettobesaved

F inlist

F last

F list

F save

F savetagged

D tobesaved

**positions** table

F b\_col

F b\_region

F c

D collected

F column

F copy

F depth

F e\_col

F e\_region

F enhance

F extra

F get

F getreserved

F hangafter

F hangindent

F height

F hsize

F leftskip

F lowerleft

F lowerright

F markregionbox

F n

F onsamepage

F overlapping

F p

F page

F paragraph

F parindent

F position

F r

- F region
- F replace
- F rightskip
- F set
- F setall
- F setdim
- D tobesaved
- F upperleft
- F upperright
- S used
- F width
- F x
- F xy
- F y
- register**        function
- save**            function
- structure**      table
- D collected
- T components
- T tobesaved
- T branches
- S name
- S type
- variables**      table
- D checksums
- D collected
- F getchecksum
- F makechecksum
- F restore
- F save
- F setchecksum
- D tobesaved
- version**        number

## lang (basic tex)

|                          |          |
|--------------------------|----------|
| <b>clean</b>             | function |
| <b>clear_hyphenation</b> | function |
| <b>clear_patterns</b>    | function |
| <b>exceptions</b>        | function |
| <b>hyphenate</b>         | function |
| <b>hyphenation</b>       | function |
| <b>id</b>                | function |
| <b>new</b>               | function |
| <b>patterns</b>          | function |
| <b>postexhyphenchar</b>  | function |
| <b>posthyphenchar</b>    | function |
| <b>preexhyphenchar</b>   | function |
| <b>prehyphenchar</b>     | function |

# languages (context)

|                       |            |             |
|-----------------------|------------|-------------|
| <b>associate</b>      | function   | B enables   |
| <b>associated</b>     | data table | F found     |
| <b>association</b>    | function   | F load      |
| <b>counters</b>       | data table | T methods   |
| <b>current</b>        | function   | N threshold |
| <b>data</b>           | data table |             |
| <b>define</b>         | function   |             |
| <b>frequencies</b>    | table      |             |
| F averagecharwidth    |            |             |
| F getdata             |            |             |
| <b>getdata</b>        | function   |             |
| <b>getnumber</b>      | function   |             |
| <b>hyphenate</b>      | function   |             |
| <b>installed</b>      | function   |             |
| <b>labels</b>         | table      |             |
| F define              |            |             |
| F split               |            |             |
| <b>lefthyphenmin</b>  | function   |             |
| <b>loadable</b>       | function   |             |
| <b>loadwords</b>      | function   |             |
| <b>logger</b>         | table      |             |
| F report              |            |             |
| <b>numbers</b>        | data table |             |
| <b>posthyphenchar</b> | function   |             |
| <b>prehyphenchar</b>  | function   |             |
| <b>registered</b>     | data table |             |
| <b>replacements</b>   | table      |             |
| F add                 |            |             |
| F handler             |            |             |
| F set                 |            |             |
| <b>righthyphenmin</b> | function   |             |
| <b>setexceptions</b>  | function   |             |
| <b>setsynonym</b>     | function   |             |
| <b>unload</b>         | function   |             |
| <b>version</b>        | number     |             |
| <b>words</b>          | table      |             |
| F check               |            |             |
| T data                |            |             |
| F disable             |            |             |
| F enable              |            |             |
| T enablers            |            |             |

# layouts (context)

**status** table

F isleftpage

F leftorrightpagection

## lfs (extra lua)

|                          |                     |
|--------------------------|---------------------|
| <b>attributes</b>        | function            |
| <b>chdir</b>             | function            |
| <b>currentdir</b>        | function            |
| <b>dir</b>               | function            |
| <b>isdir</b>             | overloaded function |
| <b>isfile</b>            | overloaded function |
| <b>lock</b>              | function            |
| <b>lock_dir</b>          | function            |
| <b>mkdir</b>             | function            |
| <b>mkdirs</b>            | function            |
| <b>readlink</b>          | function            |
| <b>rmdir</b>             | function            |
| <b>setmode</b>           | function            |
| <b>shortname</b>         | function            |
| <b>symlinkattributes</b> | function            |
| <b>touch</b>             | function            |
| <b>unlock</b>            | function            |

## libraries (context)

|                  |            |
|------------------|------------|
| <b>basiclua</b>  | data table |
| <b>basictex</b>  | data table |
| <b>builtin</b>   | data table |
| <b>extralua</b>  | data table |
| <b>extratex</b>  | data table |
| <b>functions</b> | data table |
| <b>globals</b>   | data table |

# lmx (context)

**color** function  
**convert** function  
**convertfile** function  
**convertstring** function  
**einject** function  
**eprint** function  
**escape** function  
**finalized** function  
**finject** function  
**fprint** function  
**get** function  
**getvariables** function  
**htmfile** function  
**html** table

F a

F td

F th

**include** function  
**inherited** table

S color-background-four

S color-background-one

S color-background-three

S color-background-two

S title

**initialize** function  
**inject** function  
**lmxfile** function  
**loadedfile** function  
**new** function  
**overloaderror** function  
**popupfile** function  
**print** function  
**pv** function  
**report** function  
**reset** function  
**result** function  
**set** function  
**show** function  
**showdebuginfo** function  
**showerror** function  
**stripcss** function

**tv** function  
**type** function  
**urlescape** function  
**variable** function  
**variables** table

S color-background-blue

S color-background-body

S color-background-green

S color-background-main

S color-background-purple

S color-background-yellow

S title-default



# logs (context)

|                        |          |
|------------------------|----------|
| <b>application</b>     | function |
| <b>categories</b>      | function |
| <b>direct</b>          | function |
| <b>disable</b>         | function |
| <b>enable</b>          | function |
| <b>exporters</b>       | table    |
| <b>extendbanner</b>    | function |
| <b>flush</b>           | function |
| <b>help</b>            | function |
| <b>messenger</b>       | function |
| <b>new</b>             | function |
| <b>newline</b>         | function |
| <b>poptarget</b>       | function |
| <b>pushtarget</b>      | function |
| <b>report</b>          | function |
| <b>reportbanner</b>    | function |
| <b>reporter</b>        | function |
| <b>reporters</b>       | table    |
| F banner               |          |
| F export               |          |
| F help                 |          |
| F info                 |          |
| F lines                |          |
| F version              |          |
| <b>reportline</b>      | function |
| <b>reportlines</b>     | function |
| <b>setformats</b>      | function |
| <b>setformatters</b>   | function |
| <b>setlogfile</b>      | function |
| <b>setmessenger</b>    | function |
| <b>setprocessor</b>    | function |
| <b>setprogram</b>      | function |
| <b>settarget</b>       | function |
| <b>settimedlog</b>     | function |
| <b>settranslations</b> | function |
| <b>show</b>            | function |
| <b>show_close</b>      | function |
| <b>show_load</b>       | function |
| <b>show_open</b>       | function |
| <b>simple</b>          | function |
| <b>simpleline</b>      | function |

|                          |          |
|--------------------------|----------|
| <b>simplelines</b>       | function |
| <b>start_page_number</b> | function |
| <b>status</b>            | function |
| <b>stop_page_number</b>  | function |
| <b>subdirect</b>         | function |
| <b>subreport</b>         | function |
| <b>system</b>            | function |
| <b>texerrormessage</b>   | function |
| <b>writer</b>            | function |

# lpdf (context)

|                                 |            |                                  |            |
|---------------------------------|------------|----------------------------------|------------|
| <b>action</b>                   | function   | <b>gethpos</b>                   | function   |
| <b>adddocumentcolorspace</b>    | function   | <b>getmatrix</b>                 | function   |
| <b>adddocumenttextgstate</b>    | function   | <b>getpos</b>                    | function   |
| <b>adddocumentpattern</b>       | function   | <b>getvpos</b>                   | function   |
| <b>adddocumentshade</b>         | function   | <b>graycode</b>                  | function   |
| <b>addtocatalog</b>             | function   | <b>hasmatrix</b>                 | function   |
| <b>addtoinfo</b>                | function   | <b>id</b>                        | function   |
| <b>addtonames</b>               | function   | <b>injectxmpinfo</b>             | function   |
| <b>addtopageattributes</b>      | function   | <b>insertxmpinfo</b>             | function   |
| <b>addtopageresources</b>       | function   | <b>layerreference</b>            | function   |
| <b>addtopagesattributes</b>     | function   | <b>limited</b>                   | function   |
| <b>addxmpinfo</b>               | function   | <b>linearshade</b>               | function   |
| <b>annotationspecification</b>  | function   | <b>nametree</b>                  | function   |
| <b>array</b>                    | function   | <b>null</b>                      | function   |
| <b>boolean</b>                  | function   | <b>number</b>                    | function   |
| <b>border</b>                   | function   | <b>pagedestinations</b>          | data table |
| <b>checkedkey</b>               | function   | <b>pagereference</b>             | function   |
| <b>checkedvalue</b>             | function   | <b>pagereferences</b>            | data table |
| <b>circularshade</b>            | function   | <b>pdfcolor</b>                  | function   |
| <b>cmykcode</b>                 | function   | <b>pdftimestamp</b>              | function   |
| <b>collectedresources</b>       | function   | <b>protectresources</b>          | boolean    |
| <b>color</b>                    | function   | <b>rectangle</b>                 | function   |
| <b>colorspace</b>               | function   | <b>reference</b>                 | function   |
| <b>colorspaceconstants</b>      | data table | <b>registerannotation</b>        | function   |
| <b>colorspec</b>                | function   | <b>registerdestination</b>       | function   |
| <b>colorvalue</b>               | function   | <b>registerdocumentfinalizer</b> | function   |
| <b>colorvalues</b>              | function   | <b>registerpagefinalizer</b>     | function   |
| <b>constant</b>                 | function   | <b>reserveobject</b>             | function   |
| <b>delayedobject</b>            | function   | <b>rgbcode</b>                   | function   |
| <b>destinationspecification</b> | function   | <b>rotationcm</b>                | function   |
| <b>dictionary</b>               | function   | <b>shareobject</b>               | function   |
| <b>epdf</b>                     | table      | <b>shareobjectreference</b>      | function   |
| F expand                        |            | <b>spotcode</b>                  | function   |
| F load                          |            | <b>stream</b>                    | function   |
| <b>finalizeddocument</b>        | function   | <b>string</b>                    | function   |
| <b>finalizepage</b>             | function   | <b>timestamp</b>                 | function   |
| <b>finishtransparencycode</b>   | function   | <b>toeight</b>                   | function   |
| <b>flushobject</b>              | function   | <b>tosixteen</b>                 | function   |
| <b>flushstreamfileobject</b>    | function   | <b>transform</b>                 | function   |
| <b>flushstreamobject</b>        | function   | <b>transparency</b>              | function   |
| <b>formats</b>                  | data table | <b>transparencycode</b>          | function   |

**transparencygroups**

B none

**transparencyvalue**

**unicode**

**verbose**

table

function

function

function

## lpeg (basic lua)

|                        |            |                              |          |
|------------------------|------------|------------------------------|----------|
| <b>B</b>               | function   | <b>setmaxstack</b>           | function |
| <b>C</b>               | function   | <b>split</b>                 | function |
| <b>Carg</b>            | function   | <b>splitat</b>               | function |
| <b>Cb</b>              | function   | <b>splitter</b>              | function |
| <b>Cc</b>              | function   | <b>stripper</b>              | function |
| <b>Cf</b>              | function   | <b>times</b>                 | function |
| <b>Cg</b>              | function   | <b>tsplitat</b>              | function |
| <b>Cmt</b>             | function   | <b>tsplitter</b>             | function |
| <b>Cp</b>              | function   | <b>type</b>                  | function |
| <b>Cs</b>              | function   | <b>utfchartabletopattern</b> | function |
| <b>Ct</b>              | function   | <b>version</b>               | function |
| <b>P</b>               | function   |                              |          |
| <b>R</b>               | function   |                              |          |
| <b>S</b>               | function   |                              |          |
| <b>UP</b>              | function   |                              |          |
| <b>UR</b>              | function   |                              |          |
| <b>US</b>              | function   |                              |          |
| <b>V</b>               | function   |                              |          |
| <b>afterprefix</b>     | function   |                              |          |
| <b>anywhere</b>        | function   |                              |          |
| <b>append</b>          | function   |                              |          |
| <b>balancer</b>        | function   |                              |          |
| <b>beforesuffix</b>    | function   |                              |          |
| <b>checkedsplit</b>    | function   |                              |          |
| <b>counter</b>         | function   |                              |          |
| <b>endstripper</b>     | function   |                              |          |
| <b>finder</b>          | function   |                              |          |
| <b>firstofsplit</b>    | function   |                              |          |
| <b>frontstripper</b>   | function   |                              |          |
| <b>instringchecker</b> | function   |                              |          |
| <b>is_lpeg</b>         | function   |                              |          |
| <b>keeper</b>          | function   |                              |          |
| <b>locale</b>          | function   |                              |          |
| <b>match</b>           | function   |                              |          |
| <b>oneof</b>           | function   |                              |          |
| <b>patterns</b>        | data table |                              |          |
| <b>pcode</b>           | function   |                              |          |
| <b>print</b>           | function   |                              |          |
| <b>ptree</b>           | function   |                              |          |
| <b>replacer</b>        | function   |                              |          |
| <b>secondofsplit</b>   | function   |                              |          |

# ltn12 (extra lua)

**BLOCKSIZE** number

**filter** table

F chain

F cycle

**pump** table

F all

F step

**sink** table

F chain

F error

F file

F null

F simplify

F table

**source** table

F cat

F chain

F empty

F error

F file

F rewind

F simplify

F string

## lua (basic tex)

|                            |            |
|----------------------------|------------|
| <b>bytecode</b>            | table      |
| <b>bytedata</b>            | data table |
| <b>bytdone</b>             | table      |
| <b>collectgarbage</b>      | function   |
| <b>delay</b>               | function   |
| <b>finalize</b>            | function   |
| <b>firstbytecode</b>       | number     |
| <b>flush</b>               | function   |
| <b>flushdelayed</b>        | function   |
| <b>get_functions_table</b> | function   |
| <b>getbytecode</b>         | function   |
| <b>getluaname</b>          | function   |
| <b>lastbytecode</b>        | number     |
| <b>mask</b>                | string     |
| <b>messages</b>            | data table |
| <b>name</b>                | table      |
| <b>numbers</b>             | data table |
| <b>registercode</b>        | function   |
| <b>registeredcodes</b>     | function   |
| <b>registerfinalizer</b>   | function   |
| <b>registername</b>        | function   |
| <b>setbytecode</b>         | function   |
| <b>setluaname</b>          | function   |
| <b>startupfile</b>         | string     |
| <b>version</b>             | string     |

## luatex (context)

|                             |          |
|-----------------------------|----------|
| <b>cleanuptempfiles</b>     | function |
| <b>registerstartactions</b> | function |
| <b>registerstopactions</b>  | function |
| <b>registertempfile</b>     | function |
| <b>starttime</b>            | number   |

# lxml (context)

|                        |            |                         |          |
|------------------------|------------|-------------------------|----------|
| <b>addindex</b>        | function   | <b>getid</b>            | function |
| <b>all</b>             | function   | <b>getindex</b>         | function |
| <b>applyfunction</b>   | function   | <b>id</b>               | function |
| <b>att</b>             | function   | <b>idsplitter</b>       | userdata |
| <b>attribute</b>       | function   | <b>include</b>          | function |
| <b>chainattribute</b>  | function   | <b>inclusion</b>        | function |
| <b>checkindex</b>      | function   | <b>inclusions</b>       | function |
| <b>collected</b>       | function   | <b>index</b>            | function |
| <b>command</b>         | function   | <b>info</b>             | function |
| <b>concat</b>          | function   | <b>inlineverbatim</b>   | function |
| <b>concatrange</b>     | function   | <b>installsetup</b>     | function |
| <b>content</b>         | function   | <b>last</b>             | function |
| <b>context</b>         | function   | <b>load</b>             | function |
| <b>convert</b>         | function   | <b>loadbuffer</b>       | function |
| <b>count</b>           | function   | <b>loaddata</b>         | function |
| <b>delete</b>          | function   | <b>loaded</b>           | table    |
| <b>direct</b>          | function   | <b>loadregistered</b>   | function |
| <b>directives</b>      | table      | <b>main</b>             | function |
| F after                |            | <b>match</b>            | function |
| F before               |            | <b>name</b>             | function |
| F handle               |            | <b>namespace</b>        | function |
| F load                 |            | <b>nonspace</b>         | function |
| F setup                |            | <b>pos</b>              | function |
| <b>displayverbatim</b> | function   | <b>position</b>         | function |
| <b>doif</b>            | function   | <b>raw</b>              | function |
| <b>doifelse</b>        | function   | <b>rawroot</b>          | function |
| <b>doifelsetext</b>    | function   | <b>register</b>         | function |
| <b>doifnot</b>         | function   | <b>registerentity</b>   | function |
| <b>doifnottext</b>     | function   | <b>removesetup</b>      | function |
| <b>doiftext</b>        | function   | <b>resetcdata</b>       | function |
| <b>element</b>         | function   | <b>resetsetups</b>      | function |
| <b>elements</b>        | function   | <b>resolvedentity</b>   | function |
| <b>entities</b>        | data table | <b>root</b>             | function |
| <b>filter</b>          | function   | <b>save</b>             | function |
| <b>filterlist</b>      | function   | <b>serialize</b>        | function |
| <b>first</b>           | function   | <b>setaction</b>        | function |
| <b>flush</b>           | function   | <b>setcdata</b>         | function |
| <b>flushlinewise</b>   | function   | <b>setcommandtonone</b> | function |
| <b>flushsetups</b>     | function   | <b>setcommandtotext</b> | function |
| <b>flushspacewise</b>  | function   | <b>setsetup</b>         | function |
| <b>get_id</b>          | function   | <b>snippet</b>          | function |



|                      |            |
|----------------------|------------|
| <b>sorters</b>       | table      |
| F add                |            |
| F compare            |            |
| F flush              |            |
| F reset              |            |
| F show               |            |
| F sort               |            |
| <b>splitid</b>       | function   |
| <b>startraw</b>      | function   |
| <b>stopraw</b>       | function   |
| <b>store</b>         | function   |
| <b>strip</b>         | function   |
| <b>stripped</b>      | function   |
| <b>tag</b>           | function   |
| <b>text</b>          | function   |
| <b>tofile</b>        | function   |
| <b>toparameters</b>  | function   |
| <b>toverbatim</b>    | function   |
| <b>verbatim</b>      | function   |
| <b>withindex</b>     | function   |
| <b>xmltexhandler</b> | data table |

## math (basic lua)

|                       |          |
|-----------------------|----------|
| <b>abs</b>            | function |
| <b>acos</b>           | function |
| <b>asin</b>           | function |
| <b>atan</b>           | function |
| <b>atan2</b>          | function |
| <b>ceil</b>           | function |
| <b>cos</b>            | function |
| <b>cosd</b>           | function |
| <b>cosh</b>           | function |
| <b>deg</b>            | function |
| <b>div</b>            | function |
| <b>even</b>           | function |
| <b>exp</b>            | function |
| <b>floor</b>          | function |
| <b>fmod</b>           | function |
| <b>frexp</b>          | function |
| <b>huge</b>           | number   |
| <b>initialseed</b>    | number   |
| <b>ldexp</b>          | function |
| <b>log</b>            | function |
| <b>log10</b>          | function |
| <b>max</b>            | function |
| <b>min</b>            | function |
| <b>mod</b>            | function |
| <b>modf</b>           | function |
| <b>odd</b>            | function |
| <b>pi</b>             | number   |
| <b>pow</b>            | function |
| <b>rad</b>            | function |
| <b>random</b>         | function |
| <b>randomseed</b>     | function |
| <b>round</b>          | function |
| <b>setrandomseedi</b> | function |
| <b>sin</b>            | function |
| <b>sind</b>           | function |
| <b>sinh</b>           | function |
| <b>sqrt</b>           | function |
| <b>tan</b>            | function |
| <b>tand</b>           | function |
| <b>tanh</b>           | function |

# mathematics (context)

|                               |            |                               |            |
|-------------------------------|------------|-------------------------------|------------|
| <b>addfallbacks</b>           | function   | <b>resetitalics</b>           | function   |
| <b>alphabets</b>              | data table | <b>scaleparameters</b>        | function   |
| <b>alternatives</b>           | data table | <b>setalternate</b>           | function   |
| <b>big</b>                    | function   | <b>setitalics</b>             | function   |
| <b>boldmap</b>                | data table | <b>sets</b>                   | data table |
| <b>categories</b>             | table      | <b>styles</b>                 | data table |
| D functions                   |            | <b>syncboth</b>               | function   |
| <b>charactersets</b>          | data table | <b>syncname</b>               | function   |
| <b>checkaccentbaseheight</b>  | function   | <b>syncstyle</b>              | function   |
| <b>checkprivateparameters</b> | function   | <b>toname</b>                 | function   |
| <b>classes</b>                | data table | <b>tostyle</b>                | function   |
| <b>codes</b>                  | data table | <b>tweakaftercopyingfont</b>  | function   |
| <b>define</b>                 | function   | <b>tweakbeforecopyingfont</b> | function   |
| <b>dimensions</b>             | function   | <b>tweaks</b>                 | table      |
| <b>extensiblecode</b>         | function   | <b>utfmathaccent</b>          | function   |
| <b>extensibles</b>            | data table | <b>utfmathclass</b>           | function   |
| <b>extrabase</b>              | number     | <b>utfmathcommand</b>         | function   |
| <b>extras</b>                 | table      | <b>utfmathfiller</b>          | function   |
| F add                         |            | <b>utfmathstretch</b>         | function   |
| F copy                        |            |                               |            |
| <b>fallbacks</b>              | table      |                               |            |
| F apply                       |            |                               |            |
| F install                     |            |                               |            |
| <b>fallbackstyleattr</b>      | function   |                               |            |
| <b>families</b>               | data table |                               |            |
| <b>gaps</b>                   | data table |                               |            |
| <b>getboth</b>                | function   |                               |            |
| <b>getstyle</b>               | function   |                               |            |
| <b>initializeparameters</b>   | function   |                               |            |
| <b>injectfallbacks</b>        | function   |                               |            |
| <b>makefont</b>               | function   |                               |            |
| <b>mapremap</b>               | data table |                               |            |
| <b>overloaddimensions</b>     | function   |                               |            |
| <b>overloadparameters</b>     | function   |                               |            |
| <b>privatebase</b>            | number     |                               |            |
| <b>remapalphabets</b>         | function   |                               |            |
| <b>renderings</b>             | table      |                               |            |
| D mappings                    |            |                               |            |
| D numbers                     |            |                               |            |
| D sets                        |            |                               |            |
| <b>renderset</b>              | function   |                               |            |

## mbox (context)

|                      |          |
|----------------------|----------|
| <b>parse</b>         | function |
| <b>parse_from</b>    | function |
| <b>parse_header</b>  | function |
| <b>parse_headers</b> | function |
| <b>parse_message</b> | function |
| <b>split_headers</b> | function |
| <b>split_mbox</b>    | function |
| <b>split_message</b> | function |

## md5 (extra lua)

|                |          |
|----------------|----------|
| <b>HEX</b>     | function |
| <b>crypt</b>   | function |
| <b>dec</b>     | function |
| <b>decrypt</b> | function |
| <b>exor</b>    | function |
| <b>hex</b>     | function |
| <b>sum</b>     | function |
| <b>sumhexa</b> | function |

# metapost (context)

|                         |            |                               |          |
|-------------------------|------------|-------------------------------|----------|
| <b>analyzeplugins</b>   | function   | <b>getstatistics</b>          | function |
| <b>checkformat</b>      | function   | <b>gettext</b>                | function |
| <b>checktexts</b>       | function   | <b>graphic</b>                | function |
| <b>collapse</b>         | boolean    | <b>graphic_base_pass</b>      | function |
| <b>colorinitializer</b> | function   | <b>initializescriptrunner</b> | function |
| <b>convert</b>          | function   | <b>instance</b>               | function |
| <b>defaultformat</b>    | string     | <b>intermediate</b>           | table    |
| <b>defaultinstance</b>  | string     | T actions                     |          |
| <b>defaultmethod</b>    | string     | F makemyp                     |          |
| <b>directrun</b>        | function   | <b>lastlog</b>                | string   |
| <b>edefsxsy</b>         | function   | <b>load</b>                   | function |
| <b>escaped</b>          | function   | <b>makemyp</b>                | table    |
| <b>exectime</b>         | table      | N nofconverted                |          |
| <b>extensiondata</b>    | data table | F processgraphics             |          |
| <b>filterclippath</b>   | function   | F registerfile                |          |
| <b>finder</b>           | function   | <b>metafun</b>                | table    |
| <b>flush</b>            | function   | F interpolate                 |          |
| <b>flushers</b>         | table      | F topath                      |          |
| T pdf                   |            | <b>method</b>                 | number   |
| F comment               |            | <b>mptopdf</b>                | table    |
| F flushfigure           |            | F convertmptstopdf            |          |
| F startfigure           |            | N nofconverted                |          |
| F stopfigure            |            | <b>n</b>                      | number   |
| F textfigure            |            | <b>nvformat</b>               | function |
| <b>flushliteral</b>     | function   | <b>optimize</b>               | boolean  |
| <b>flushnormalpath</b>  | function   | <b>parse</b>                  | function |
| <b>flushreset</b>       | function   | <b>pdf literals</b>           | function |
| <b>fonts</b>            | table      | <b>pluginactions</b>          | function |
| F define                |            | <b>process</b>                | function |
| T flusher               |            | <b>processplugins</b>         | function |
| F flushfigure           |            | <b>processspecial</b>         | function |
| F startfigure           |            | <b>properties</b>             | table    |
| F stopfigure            |            | <b>quickanddirty</b>          | function |
| N instances             |            | <b>reducetogray</b>           | boolean  |
| F process               |            | <b>reporterror</b>            | function |
| <b>format</b>           | function   | <b>reset</b>                  | function |
| <b>format_number</b>    | function   | <b>resetlastlog</b>           | function |
| <b>format_string</b>    | function   | <b>resetplugins</b>           | function |
| <b>formatnumber</b>     | function   | <b>runscript</b>              | function |
| <b>getclippath</b>      | function   | <b>scripterror</b>            | function |
| <b>getextensions</b>    | function   | <b>setextensions</b>          | function |

|                      |          |
|----------------------|----------|
| <b>setoutercolor</b> | function |
| <b>settext</b>       | function |
| <b>showlog</b>       | boolean  |
| <b>svformat</b>      | function |
| <b>tex</b>           | table    |
| F get                |          |
| F reset              |          |
| F set                |          |
| <b>texerrors</b>     | boolean  |
| <b>textextsdata</b>  | function |
| <b>theclippath</b>   | function |
| <b>totable</b>       | function |
| <b>unload</b>        | function |
| <b>untagvariable</b> | function |
| <b>variables</b>     | table    |

## mime (extra lua)

**b64** function

**decode** function

**decodet** table

F base64

F quoted-printable

**dot** function

**encode** function

**encodet** table

F base64

F quoted-printable

**eol** function

**normalize** function

**qp** function

**qpwrp** function

**stuff** function

**unb64** function

**unqp** function

**wrap** function

**wrapt** table

F base64

F default

F quoted-printable

F text

**wrp** function



## mp (context)

|                  |          |
|------------------|----------|
| <b>_f_</b>       | function |
| <b>boolean</b>   | function |
| <b>format</b>    | function |
| <b>number</b>    | function |
| <b>numeric</b>   | function |
| <b>pair</b>      | function |
| <b>print</b>     | function |
| <b>quadruple</b> | function |
| <b>quoted</b>    | function |
| <b>string</b>    | function |
| <b>triplet</b>   | function |

## mplib (extra tex)

|                     |          |
|---------------------|----------|
| <b>fields</b>       | function |
| <b>finders</b>      | table    |
| F file              |          |
| <b>get_boolean</b>  | function |
| <b>get_number</b>   | function |
| <b>get_numeric</b>  | function |
| <b>get_string</b>   | function |
| <b>new</b>          | function |
| <b>pen_info</b>     | function |
| <b>preprocessed</b> | function |
| <b>version</b>      | function |

# noads (context)

## **handlers**      table

- F check
- F classes
- F collapse
- F families
- F italics
- F relocate
- F render
- F resize
- F showtree
- F tags
- F unscript
- F variants

## **process**          function

## **processors**      table

- T collapse
- F mlist\_to\_hlist
- T relocate
- T render
- T resize
- T unscript

## node (basic tex)

|                          |          |                               |          |
|--------------------------|----------|-------------------------------|----------|
| <b>copy</b>              | function | F protect_glyphs              |          |
| <b>copy_list</b>         | function | F protrusion_skippable        |          |
| <b>count</b>             | function | F remove                      |          |
| <b>current_attr</b>      | function | F set_attribute               |          |
| <b>dimensions</b>        | function | F set_properties_mode         |          |
| <b>direct</b>            | table    | F setbox                      |          |
| F copy                   |          | F setfield                    |          |
| F copy_list              |          | F setproperty                 |          |
| F count                  |          | F slide                       |          |
| F current_attr           |          | F tail                        |          |
| F dimensions             |          | F todirect                    |          |
| F do_ligature_n          |          | F tonode                      |          |
| F end_of_math            |          | F toString                    |          |
| F first_glyph            |          | F traverse                    |          |
| F flush_list             |          | F traverse_id                 |          |
| F flush_node             |          | F unprotect_glyphs            |          |
| F flush_properties_table |          | F unset_attribute             |          |
| F free                   |          | F usedlist                    |          |
| F get_properties_table   |          | F vpack                       |          |
| F getbox                 |          | F write                       |          |
| F getchar                |          | <b>do_ligature_n</b>          | function |
| F getfield               |          | <b>end_of_math</b>            | function |
| F getfont                |          | <b>family_font</b>            | function |
| F getid                  |          | <b>fields</b>                 | function |
| F getleader              |          | <b>first_character</b>        | function |
| F getlist                |          | <b>first_glyph</b>            | function |
| F getnext                |          | <b>flush_list</b>             | function |
| F getprev                |          | <b>flush_node</b>             | function |
| F getproperty            |          | <b>flush_properties_table</b> | function |
| F getsubtype             |          | <b>free</b>                   | function |
| F has_attribute          |          | <b>get_properties_table</b>   | function |
| F has_field              |          | <b>getchar</b>                | function |
| F has_glyph              |          | <b>getfield</b>               | function |
| F hpack                  |          | <b>getfont</b>                | function |
| F insert_after           |          | <b>getid</b>                  | function |
| F insert_before          |          | <b>getleader</b>              | function |
| F is_direct              |          | <b>getlist</b>                | function |
| F is_node                |          | <b>getnext</b>                | function |
| F last_node              |          | <b>getprev</b>                | function |
| F length                 |          | <b>getproperty</b>            | function |
| F new                    |          | <b>getsubtype</b>             | function |

|                             |          |
|-----------------------------|----------|
| <b>has_attribute</b>        | function |
| <b>has_field</b>            | function |
| <b>has_glyph</b>            | function |
| <b>hpack</b>                | function |
| <b>id</b>                   | function |
| <b>insert_after</b>         | function |
| <b>insert_before</b>        | function |
| <b>is_node</b>              | function |
| <b>kerning</b>              | function |
| <b>last_node</b>            | function |
| <b>length</b>               | function |
| <b>ligaturing</b>           | function |
| <b>mlist_to_hlist</b>       | function |
| <b>new</b>                  | function |
| <b>next</b>                 | function |
| <b>prev</b>                 | function |
| <b>protect_glyphs</b>       | function |
| <b>protrusion_skippable</b> | function |
| <b>remove</b>               | function |
| <b>set_attribute</b>        | function |
| <b>set_properties_mode</b>  | function |
| <b>setfield</b>             | function |
| <b>setProperty</b>          | function |
| <b>slide</b>                | function |
| <b>subtype</b>              | function |
| <b>tail</b>                 | function |
| <b>tostring</b>             | function |
| <b>traverse</b>             | function |
| <b>traverse_id</b>          | function |
| <b>type</b>                 | function |
| <b>types</b>                | function |
| <b>unprotect_glyphs</b>     | function |
| <b>unset_attribute</b>      | function |
| <b>usedlist</b>             | function |
| <b>vpack</b>                | function |
| <b>whatsits</b>             | function |
| <b>write</b>                | function |

## nodes (context)

|                           |            |                               |            |
|---------------------------|------------|-------------------------------|------------|
| <b>accentcodes</b>        | data table | <b>free_spec</b>              | function   |
| <b>aligned</b>            | function   | <b>getattr</b>                | function   |
| <b>append</b>             | function   | <b>getattribute</b>           | function   |
| <b>astable</b>            | function   | <b>getbox</b>                 | function   |
| <b>basepoints</b>         | function   | <b>getchar</b>                | function   |
| <b>builders</b>           | table      | <b>getfield</b>               | function   |
| F buildpage_filter        |            | <b>getfont</b>                | function   |
| F vpack_filter            |            | <b>getid</b>                  | function   |
| <b>codes</b>              | data table | <b>getleader</b>              | function   |
| <b>concat</b>             | function   | <b>getlist</b>                | function   |
| <b>copy</b>               | function   | <b>getnext</b>                | function   |
| <b>copy_list</b>          | function   | <b>getprev</b>                | function   |
| <b>copy_spec</b>          | function   | <b>getskip</b>                | function   |
| <b>count</b>              | function   | <b>getsubtype</b>             | function   |
| <b>current_attr</b>       | function   | <b>gluecodes</b>              | data table |
| <b>delete</b>             | function   | <b>glyphcodes</b>             | data table |
| <b>destinations</b>       | table      | <b>glyphdir_is_equal</b>      | data table |
| N attribute               |            | <b>glyphdir_is_opposite</b>   | data table |
| T done                    |            | <b>glyphdir_is_orthogonal</b> | data table |
| F handler                 |            | <b>gonuts</b>                 | boolean    |
| T stack                   |            | <b>handlers</b>               | table      |
| <b>dimensionfields</b>    | data table | F accessibility               |            |
| <b>dimensions</b>         | function   | F alignbackgrounds            |            |
| <b>dir_is_pop</b>         | data table | F backgrounds                 |            |
| <b>dir_negation</b>       | data table | F characters                  |            |
| <b>disccodes</b>          | data table | F checkforleaks               |            |
| <b>discretionarycodes</b> | data table | F checkglyphs                 |            |
| <b>do_ligature_n</b>      | function   | F cleanupbox                  |            |
| <b>end_of_math</b>        | function   | F cleanuppage                 |            |
| <b>fasthpack</b>          | function   | F export                      |            |
| <b>fencecodes</b>         | data table | F finalize                    |            |
| <b>fields</b>             | function   | F migrate                     |            |
| <b>fillcodes</b>          | data table | F protectglyphs               |            |
| <b>first_character</b>    | function   | F stripping                   |            |
| <b>first_glyph</b>        | function   | F unprotectglyphs             |            |
| <b>firstcharacter</b>     | function   | <b>has_attribute</b>          | function   |
| <b>firstcharinbox</b>     | function   | <b>has_field</b>              | function   |
| <b>firstglyph</b>         | function   | <b>has_glyph</b>              | function   |
| <b>flush_list</b>         | function   | <b>hpack</b>                  | function   |
| <b>flush_node</b>         | function   | <b>idstosting</b>             | function   |
| <b>free</b>               | function   | <b>ignorablefields</b>        | data table |

|                                |            |                       |            |
|--------------------------------|------------|-----------------------|------------|
| <b>injections</b>              | table      | <b>load</b>           | function   |
| F getligaindex                 |            | <b>locate</b>         | function   |
| F handler                      |            | <b>margincodes</b>    | data table |
| F installnewkern               |            | <b>markers</b>        | table      |
| F reset                        |            | F get                 |            |
| F setcursive                   |            | <b>mathcodes</b>      | data table |
| F setkern                      |            | <b>maxboxwidth</b>    | function   |
| F setligaindex                 |            | <b>mlist_to_hlist</b> | function   |
| F setmark                      |            | <b>new</b>            | function   |
| F setpair                      |            | <b>noadcodes</b>      | data table |
| <b>insert_after</b>            | function   | <b>nodecodes</b>      | data table |
| <b>insert_before</b>           | function   | <b>nopts</b>          | function   |
| <b>insert_list_after</b>       | function   | <b>nuts</b>           | table      |
| <b>installattributehandler</b> | function   | F append              |            |
| <b>is_direct</b>               | function   | F concat              |            |
| <b>is_display_math</b>         | function   | F copy                |            |
| <b>is_mirrored</b>             | data table | F copy_list           |            |
| <b>is_node</b>                 | function   | F count               |            |
| <b>is_nut</b>                  | function   | F current_attr        |            |
| <b>is_rotated</b>              | data table | F delete              |            |
| <b>kerncodes</b>               | data table | F dimensions          |            |
| <b>kerining</b>                | function   | F do_ligature_n       |            |
| <b>keys</b>                    | table      | F end_of_math         |            |
| T whatsit                      |            | F fasthpack           |            |
| <b>last_node</b>               | function   | F first_glyph         |            |
| <b>leftmarginwidth</b>         | function   | F firstcharacter      |            |
| <b>ligaturing</b>              | function   | F firstcharinbox      |            |
| <b>lines</b>                   | table      | F firstglyph          |            |
| T boxed                        |            | F flush_list          |            |
| F register                     |            | F flush_node          |            |
| F setup                        |            | F free                |            |
| F stage_one                    |            | F getattr             |            |
| F stage_two                    |            | F getattribute        |            |
| F stage_zero                   |            | F getbox              |            |
| D data                         |            | F getchar             |            |
| F finalize                     |            | F getfield            |            |
| F number                       |            | F getfont             |            |
| N scratchbox                   |            | F getid               |            |
| <b>link</b>                    | function   | F getleader           |            |
| <b>linked</b>                  | function   | F getlist             |            |
| <b>list</b>                    | function   | F getnext             |            |
| <b>listablefields</b>          | data table | F getprev             |            |
| <b>listcodes</b>               | data table | F getprop             |            |
| <b>listtoutf</b>               | function   | F getskip             |            |

|                     |                        |
|---------------------|------------------------|
| F getsubtype        | F pdfsave              |
| F has_attribute     | F pdfsetmatrix         |
| F has_field         | F penalty              |
| F has_glyph         | F register             |
| F hpack             | F rightmarginkern      |
| F insert_after      | F rightskip            |
| F insert_before     | F rule                 |
| F insert_list_after | F shrink               |
| F is_direct         | F special              |
| F is_display_math   | F stretch              |
| F is_node           | F temp                 |
| F is_nut            | F textdir              |
| F kerning           | F usage                |
| F last_node         | T userids              |
| F leftmarginwidth   | N margins.inline       |
| F ligaturing        | N property             |
| F link              | N splitters.one        |
| F linked            | N splitters.two        |
| F locate            | F userlist             |
| F mlist_to_hlist    | F usernumber           |
| F nestedtracedslide | F userstring           |
| F new               | F usertokens           |
| T pool              | F vlist                |
| F baselineskip      | F zeroglue             |
| F cleanup           | F prepend              |
| F disc              | F protect_glyphs       |
| F fontkern          | F protrusion_skippable |
| F glue              | F reference            |
| F gluespec          | F remove               |
| F glyph             | F repackhlist          |
| F hlist             | F replace              |
| F kern              | F rightmarginwidth     |
| F latelua           | F set_attribute        |
| F lateluafunction   | F setattr              |
| F leftmarginkern    | F setattrtribute       |
| F leftskip          | F setattrtributes      |
| F lineskip          | F setbox               |
| F negatedglue       | F setfield             |
| F noad              | F setprop              |
| F pdfannotation     | F setunsetattributes   |
| F pdfdestination    | F slide                |
| F pdfdirect         | F somepenalty          |
| F pdfliteral        | F somespace            |
| F pdfrestore        | F tail                 |



|                            |            |                         |          |
|----------------------------|------------|-------------------------|----------|
| F takebox                  |            | F register              |          |
| F tonode                   |            | D registered            |          |
| F tonodes                  |            | D values                |          |
| F tonut                    |            | F processor             |          |
| F tosequence               |            | <b>points</b>           | function |
| F tostring                 |            | <b>pool</b>             | table    |
| F tracedslide              |            | F baselineskip          |          |
| F traverse                 |            | F cleanup               |          |
| F traverse_id              |            | F glyph                 |          |
| T typesetters              |            | F kern                  |          |
| F fast_hpack               |            | F latelua               |          |
| F hpack                    |            | F lateluafunction       |          |
| F tohpack                  |            | F lineskip              |          |
| F tohpackfast              |            | F pdfdirect             |          |
| F tonodes                  |            | F pdfliteral            |          |
| F tovpack                  |            | F pdfrestore            |          |
| F tovpackfast              |            | F pdfsave               |          |
| F vpack                    |            | F pdfsetmatrix          |          |
| F unprotect_glyphs         |            | F register              |          |
| F unset_attribute          |            | F rule                  |          |
| F unsetattribute           |            | F special               |          |
| F unsetattributes          |            | F usage                 |          |
| F untracedslide            |            | T userids               |          |
| F usedlist                 |            | N margins.inline        |          |
| F vianodes                 |            | N property              |          |
| F vianuts                  |            | N splitters.one         |          |
| F vpack                    |            | N splitters.two         |          |
| F writable_spec            |            | F usernumber            |          |
| F write                    |            | <b>prepend</b>          | function |
| <b>packlist</b>            | function   | <b>print</b>            | function |
| <b>pardir_is_equal</b>     | data table | <b>processors</b>       | table    |
| <b>pardir_is_opposite</b>  | data table | B enabled               |          |
| <b>pardir_is_parallel</b>  | data table | F hpack_filter          |          |
| <b>partextdir_is_equal</b> | data table | F post_linebreak_filter |          |
| <b>penaltycodes</b>        | data table | F pre_linebreak_filter  |          |
| <b>plugindata</b>          | table      | F tracer                |          |
| F finalizer                |            | <b>processwords</b>     | function |
| F initializer              |            | <b>properties</b>       | table    |
| S name                     |            | T actions               |          |
| T namespace                |            | F delayed               |          |
| N attribute                |            | F fdelayed              |          |
| D data                     |            | F immediate             |          |
| F enable                   |            | F attach                |          |
| F handler                  |            | T data                  |          |

|                             |            |                            |            |
|-----------------------------|------------|----------------------------|------------|
| F delayed                   |            | F getsamples               |            |
| <b>protect_glyphs</b>       | function   | F resetsamples             |            |
| <b>protrusion_skippable</b> | function   | F takesample               |            |
| <b>pts</b>                  | function   | <b>somepenalty</b>         | function   |
| <b>reference</b>            | function   | <b>somespace</b>           | function   |
| <b>references</b>           | table      | <b>stripping</b>           | table      |
| N attribute                 |            | T glyphs                   |            |
| T done                      |            | F set                      |            |
| F handler                   |            | <b>striprange</b>          | function   |
| T stack                     |            | <b>tail</b>                | function   |
| <b>remove</b>               | function   | <b>takebox</b>             | function   |
| <b>repackhlist</b>          | function   | <b>tasks</b>               | table      |
| <b>replace</b>              | function   | F actions                  |            |
| <b>report</b>               | function   | F appendaction             |            |
| <b>rightmarginwidth</b>     | function   | F disableaction            |            |
| <b>rules</b>                | table      | F disablegroup             |            |
| D data                      |            | F enableaction             |            |
| F define                    |            | F enablegroup              |            |
| F enable                    |            | F freeze                   |            |
| F handler                   |            | F freezegroup              |            |
| <b>save</b>                 | function   | F new                      |            |
| <b>serialize</b>            | function   | F prependaction            |            |
| <b>serializebox</b>         | function   | F removeaction             |            |
| <b>set_attribute</b>        | function   | F replaceaction            |            |
| <b>setattr</b>              | function   | F restart                  |            |
| <b>setattribute</b>         | function   | F setaction                |            |
| <b>setattributes</b>        | function   | F showactions              |            |
| <b>setbox</b>               | function   | F table                    |            |
| <b>setfield</b>             | function   | <b>texmdir_is_equal</b>    | data table |
| <b>setunsetattributes</b>   | function   | <b>texmdir_is_is</b>       | data table |
| <b>shifts</b>               | table      | <b>texmdir_is_opposite</b> | data table |
| D data                      |            | <b>texmdir_is_parallel</b> | data table |
| F define                    |            | <b>tobasepoints</b>        | function   |
| F enable                    |            | <b>tocentimeters</b>       | function   |
| F handler                   |            | <b>tociceros</b>           | function   |
| <b>show</b>                 | function   | <b>todidots</b>            | function   |
| <b>showboxes</b>            | function   | <b>todimen</b>             | function   |
| <b>showcodes</b>            | function   | <b>toinches</b>            | function   |
| <b>showlist</b>             | function   | <b>tomillimeters</b>       | function   |
| <b>showsimplelist</b>       | function   | <b>tonewciceros</b>        | function   |
| <b>skipcodes</b>            | data table | <b>tonewdidots</b>         | function   |
| <b>slide</b>                | function   | <b>tonode</b>              | function   |
| <b>snapshots</b>            | table      | <b>tonodes</b>             | function   |
| F getparameters             |            | <b>tonut</b>               | function   |

|                       |          |                         |            |
|-----------------------|----------|-------------------------|------------|
| <b>topics</b>         | function | F stop                  |            |
| <b>topoints</b>       | function | F stop                  |            |
| <b>toscaledpoints</b> | function | T transparencies        |            |
| <b>tosequence</b>     | function | F reset                 |            |
| <b>tostring</b>       | function | F set                   |            |
| <b>totable</b>        | function | F setlist               |            |
| <b>totree</b>         | function | <b>traverse</b>         | function   |
| <b>toutf</b>          | function | <b>traverse_id</b>      | function   |
| <b>tracers</b>        | table    | <b>typesetters</b>      | table      |
| T characters          |          | F hpack                 |            |
| F collect             |          | F tohpack               |            |
| F equal               |          | F tohpackfast           |            |
| F start               |          | F tonodes               |            |
| F string              |          | F tovpack               |            |
| F unicodes            |          | F tovpackfast           |            |
| T colors              |          | F vpack                 |            |
| F reset               |          | <b>unprotect_glyphs</b> | function   |
| F set                 |          | <b>unset_attribute</b>  | function   |
| F setlist             |          | <b>unsetattribute</b>   | function   |
| F fontchar            |          | <b>unsetattributes</b>  | function   |
| T frequencies         |          | <b>usedlist</b>         | function   |
| F register            |          | <b>vianodes</b>         | function   |
| T pool                |          | <b>vianuts</b>          | function   |
| T nodes               |          | <b>visualizebox</b>     | function   |
| F rule                |          | <b>visualizers</b>      | table      |
| T nuts                |          | F box                   |            |
| F rule                |          | F handler               |            |
| F resetproperties     |          | F markfonts             |            |
| F rule                |          | F setfont               |            |
| F setlist             |          | F setlayer              |            |
| F setproperties       |          | F setvisual             |            |
| F start               |          | <b>vpack</b>            | function   |
| T steppers            |          | <b>whatcodes</b>        | data table |
| F check               |          | <b>whatsitcodes</b>     | data table |
| F codes               |          | <b>writable_spec</b>    | function   |
| F features            |          | <b>write</b>            | function   |
| F font                |          |                         |            |
| F glyphs              |          |                         |            |
| F message             |          |                         |            |
| F messages            |          |                         |            |
| F nofsteps            |          |                         |            |
| F register            |          |                         |            |
| F reset               |          |                         |            |
| F start               |          |                         |            |

## number (context)

|                       |            |
|-----------------------|------------|
|                       | function   |
| <b>basepoints</b>     | function   |
| <b>bit</b>            | function   |
| <b>bits</b>           | function   |
| <b>clearbit</b>       | function   |
| <b>dimenfactors</b>   | data table |
| <b>formatted</b>      | function   |
| <b>hasbit</b>         | function   |
| <b>maxdimen</b>       | number     |
| <b>nopts</b>          | function   |
| <b>percent</b>        | function   |
| <b>points</b>         | function   |
| <b>pts</b>            | function   |
| <b>setbit</b>         | function   |
| <b>signed</b>         | function   |
| <b>sparseexponent</b> | function   |
| <b>splitdimen</b>     | function   |
| <b>tobasepoints</b>   | function   |
| <b>tobitstring</b>    | function   |
| <b>tocentimeters</b>  | function   |
| <b>toxiceros</b>      | function   |
| <b>todidots</b>       | function   |
| <b>todimen</b>        | function   |
| <b>toevenhex</b>      | function   |
| <b>toinches</b>       | function   |
| <b>tomillimeters</b>  | function   |
| <b>tonewciceros</b>   | function   |
| <b>tonewdidots</b>    | function   |
| <b>tonumberf</b>      | function   |
| <b>tonumberg</b>      | function   |
| <b>topics</b>         | function   |
| <b>topoints</b>       | function   |
| <b>toscaled</b>       | function   |
| <b>toscaledpoints</b> | function   |
| <b>toset</b>          | function   |
| <b>valid</b>          | function   |

## os (basic lua)

|                     |                     |                      |          |
|---------------------|---------------------|----------------------|----------|
| <b>__getenv__</b>   | function            | <b>uname</b>         | function |
| <b>__setenv__</b>   | function            | <b>uuid</b>          | function |
| <b>binsuffix</b>    | string              | <b>validdatetime</b> | function |
| <b>binsuffixes</b>  | table               | <b>weekday</b>       | function |
| <b>clock</b>        | function            | <b>where</b>         | function |
| <b>converttime</b>  | function            | <b>which</b>         | function |
| <b>date</b>         | function            |                      |          |
| <b>difftime</b>     | function            |                      |          |
| <b>env</b>          | data table          |                      |          |
| <b>exec</b>         | overloaded function |                      |          |
| <b>execute</b>      | overloaded function |                      |          |
| <b>exit</b>         | function            |                      |          |
| <b>fulltime</b>     | function            |                      |          |
| <b>getenv</b>       | overloaded function |                      |          |
| <b>gettimeofday</b> | function            |                      |          |
| <b>isleapyear</b>   | function            |                      |          |
| <b>launch</b>       | function            |                      |          |
| <b>libsuffix</b>    | string              |                      |          |
| <b>localtime</b>    | function            |                      |          |
| <b>name</b>         | string              |                      |          |
| <b>nofdays</b>      | function            |                      |          |
| <b>now</b>          | function            |                      |          |
| <b>platform</b>     | string              |                      |          |
| <b>remove</b>       | function            |                      |          |
| <b>rename</b>       | function            |                      |          |
| <b>resolvers</b>    | table               |                      |          |
| F bits              |                     |                      |          |
| <b>resultof</b>     | function            |                      |          |
| <b>runtime</b>      | function            |                      |          |
| <b>selfdir</b>      | string              |                      |          |
| <b>setenv</b>       | overloaded function |                      |          |
| <b>setlocale</b>    | overloaded function |                      |          |
| <b>sleep</b>        | function            |                      |          |
| <b>spawn</b>        | overloaded function |                      |          |
| <b>time</b>         | function            |                      |          |
| <b>times</b>        | function            |                      |          |
| <b>timezone</b>     | function            |                      |          |
| <b>tmpdir</b>       | function            |                      |          |
| <b>tmpname</b>      | function            |                      |          |
| <b>today</b>        | function            |                      |          |
| <b>type</b>         | string              |                      |          |

## package (basic lua)

|                      |          |
|----------------------|----------|
| <b>config</b>        | string   |
| <b>cpath</b>         | string   |
| <b>extralibpath</b>  | function |
| <b>extralibpaths</b> | function |
| <b>extralupath</b>   | function |
| <b>extralupaths</b>  | function |
| <b>helpers</b>       | table    |
| <b>libpaths</b>      | function |
| <b>loaded</b>        | table    |
| <b>loaders</b>       | table    |
| <b>loadlib</b>       | function |
| <b>luapaths</b>      | function |
| <b>path</b>          | string   |
| <b>preload</b>       | table    |
| <b>searchpath</b>    | function |
| <b>seeall</b>        | function |

# pagebuilders (context)

## **injections**    table

F flushafter  
F flushbefore  
F save

## **mixedcolumns**    table

F cleanup  
F finalize  
F getlist  
F getrest  
F getsplit  
F setsplit

## pattern (context)

- 1 userdata
- 2 userdata
- 3 userdata



## pdf (basic tex)

|                           |                     |
|---------------------------|---------------------|
| <b>getcatalog</b>         | function            |
| <b>gethpos</b>            | function            |
| <b>getinfo</b>            | function            |
| <b>getmatrix</b>          | function            |
| <b>getnames</b>           | function            |
| <b>getpageattributes</b>  | function            |
| <b>getpageresources</b>   | function            |
| <b>getpagesattributes</b> | function            |
| <b>getpos</b>             | function            |
| <b>gettrailer</b>         | function            |
| <b>getvpos</b>            | function            |
| <b>hasmatrix</b>          | function            |
| <b>immediateobj</b>       | function            |
| <b>mapfile</b>            | function            |
| <b>mapline</b>            | function            |
| <b>maxobjnum</b>          | function            |
| <b>obj</b>                | function            |
| <b>objtype</b>            | function            |
| <b>pageref</b>            | function            |
| <b>print</b>              | function            |
| <b>refobj</b>             | function            |
| <b>registerannot</b>      | overloaded function |
| <b>reserveobj</b>         | function            |
| <b>setcatalog</b>         | overloaded function |
| <b>setinfo</b>            | overloaded function |
| <b>setnames</b>           | overloaded function |
| <b>setpageattributes</b>  | overloaded function |
| <b>setpageresources</b>   | overloaded function |
| <b>setpagesattributes</b> | overloaded function |
| <b>settrailer</b>         | overloaded function |

# pdfscanner (context)

**scan** function

# physics (context)

**units** table

D tables

## profiler (extra lua)

**pause**    function  
**resume**   function  
**start**    function  
**stop**     function

# publications (context)

|                        |            |                         |          |
|------------------------|------------|-------------------------|----------|
| <b>addtexentry</b>     | function   | F filterall             |          |
| <b>analyze</b>         | function   | F flushentries          |          |
| <b>authors</b>         | table      | T methods               |          |
| F sorted               |            | F dataset               |          |
| T sorters              |            | F force                 |          |
| F author               |            | F global                |          |
| F writer               |            | F local                 |          |
| F splitstring          |            | F nofregistered         |          |
| <b>citevariants</b>    | table      | F prepareentries        |          |
| F author               |            | F register              |          |
| F authornum            |            | T sorters               |          |
| F authoryear           |            | F author                |          |
| F authoryears          |            | F dataset               |          |
| F category             |            | F default               |          |
| F default              |            | F reference             |          |
| F index                |            | F short                 |          |
| F key                  |            | <b>listvariants</b>     | table    |
| F num                  |            | F bib                   |          |
| F page                 |            | F default               |          |
| F serial               |            | F num                   |          |
| F short                |            | F page                  |          |
| F tag                  |            | F short                 |          |
| F type                 |            | F yes                   |          |
| F year                 |            | <b>load</b>             | function |
| <b>collected</b>       | data table | <b>loadbibdata</b>      | function |
| <b>concatstate</b>     | function   | <b>loaders</b>          | table    |
| <b>converttoxml</b>    | function   | F bib                   |          |
| <b>datasets</b>        | table      | F buffer                |          |
| <b>endnotes_to_btx</b> | function   | F endnote               |          |
| <b>enhance</b>         | function   | F lua                   |          |
| <b>finder</b>          | function   | F refman                |          |
| <b>getindex</b>        | function   | F xml                   |          |
| <b>journals</b>        | table      | <b>markasupdated</b>    | function |
| F abbreviated          |            | <b>new</b>              | function |
| F add                  |            | <b>parenttag</b>        | function |
| F expanded             |            | <b>refman_to_btx</b>    | function |
| F load                 |            | <b>resolvedname</b>     | function |
| F save                 |            | <b>search</b>           | function |
| <b>lists</b>           | table      | <b>singularorplural</b> | function |
| F collectentries       |            | <b>statistics</b>       | table    |
| F fetchentries         |            | N nofbytes              |          |

|                  |              |                           |              |
|------------------|--------------|---------------------------|--------------|
| N nofdatasets    |              | T required                |              |
| N nofdefinitions |              | T unpublished             |              |
| N nofshortcuts   |              | T optional                |              |
| <b>tracers</b>   | <b>table</b> | T required                |              |
| F addfield       |              | T citevariants            |              |
| T categories     |              | T fields                  |              |
| T article        |              | T listvariants            |              |
| T optional       |              | F showdatasetcompleteness |              |
| T required       |              | F showdatasetfields       |              |
| T book           |              | F showfields              |              |
| T optional       |              | <b>writers</b>            | <b>table</b> |
| T required       |              | F author                  |              |
| T booklet        |              |                           |              |
| T optional       |              |                           |              |
| T required       |              |                           |              |
| T inbook         |              |                           |              |
| T optional       |              |                           |              |
| T required       |              |                           |              |
| T incollection   |              |                           |              |
| T optional       |              |                           |              |
| T required       |              |                           |              |
| T inproceedings  |              |                           |              |
| T optional       |              |                           |              |
| T required       |              |                           |              |
| T manual         |              |                           |              |
| T optional       |              |                           |              |
| T required       |              |                           |              |
| T mastersthesis  |              |                           |              |
| T optional       |              |                           |              |
| T required       |              |                           |              |
| T misc           |              |                           |              |
| T optional       |              |                           |              |
| T required       |              |                           |              |
| T patent         |              |                           |              |
| T optional       |              |                           |              |
| T required       |              |                           |              |
| T phdthesis      |              |                           |              |
| T optional       |              |                           |              |
| T required       |              |                           |              |
| T proceedings    |              |                           |              |
| T optional       |              |                           |              |
| T required       |              |                           |              |
| T techreport     |              |                           |              |
| T optional       |              |                           |              |

## regimes (context)

|                  |          |
|------------------|----------|
| <b>cleanup</b>   | function |
| <b>disable</b>   | function |
| <b>enable</b>    | function |
| <b>pop</b>       | function |
| <b>process</b>   | function |
| <b>push</b>      | function |
| <b>toregime</b>  | function |
| <b>translate</b> | function |

# resolvers (context)

|                                     |            |                                |            |
|-------------------------------------|------------|--------------------------------|------------|
| <b>allprefixes</b>                  | function   | <b>finders</b>                 | data table |
| <b>appendhash</b>                   | function   | <b>findfile</b>                | function   |
| <b>automount</b>                    | function   | <b>findfiles</b>               | function   |
| <b>automounted</b>                  | table      | <b>findgivenfile</b>           | function   |
| <b>booleanvariable</b>              | function   | <b>findgivenfiles</b>          | function   |
| <b>cacheversion</b>                 | string     | <b>findpath</b>                | function   |
| <b>checkedvariable</b>              | function   | <b>findtexfile</b>             | function   |
| <b>cleanpath</b>                    | function   | <b>findwildcardfile</b>        | function   |
| <b>cleanpathlist</b>                | function   | <b>findwildcardfiles</b>       | function   |
| <b>concatinators</b>                | data table | <b>formatofsuffix</b>          | function   |
| <b>configbanner</b>                 | string     | <b>formatofvariable</b>        | function   |
| <b>criticalvars</b>                 | data table | <b>formats</b>                 | data table |
| <b>dangerous</b>                    | data table | <b>generators</b>              | data table |
| <b>datastate</b>                    | function   | <b>get_from_content</b>        | function   |
| <b>defaultsuffixes</b>              | table      | <b>getenv</b>                  | function   |
| <b>dowithfilesandreport</b>         | function   | <b>getownpath</b>              | function   |
| <b>dowithfilesintree</b>            | function   | <b>getreadfilename</b>         | function   |
| <b>dowithpath</b>                   | function   | <b>hashers</b>                 | data table |
| <b>dowithvariable</b>               | function   | <b>homedir</b>                 | string     |
| <b>env</b>                          | function   | <b>inputstack</b>              | table      |
| <b>executers</b>                    | table      | <b>installinputfilehandler</b> | function   |
| F check                             |            | <b>installinputlinehandler</b> | function   |
| F exec                              |            | <b>instance</b>                | table      |
| F execute                           |            | D data                         |            |
| F finalize                          |            | B diskcache                    |            |
| F popen                             |            | D environment                  |            |
| F register                          |            | D expansions                   |            |
| F spawn                             |            | D fakepaths                    |            |
| <b>expandbraces</b>                 | function   | D files                        |            |
| <b>expandedpathfromlist</b>         | function   | B force_suffixes               |            |
| <b>expandedpathlist</b>             | function   | D found                        |            |
| <b>expandedpathlistfromvariable</b> | function   | D foundintrees                 |            |
| <b>expandpath</b>                   | function   | D hashed                       |            |
| <b>expandpathfromvariable</b>       | function   | D hashes                       |            |
| <b>expansion</b>                    | function   | D lists                        |            |
| <b>extendtexmfvariable</b>          | function   | B loadererror                  |            |
| <b>filtered_from_content</b>        | function   | D order                        |            |
| <b>find_file</b>                    | function   | T pathstack                    |            |
| <b>find_files</b>                   | function   | B remember                     |            |
| <b>findbinfile</b>                  | function   | B renewcache                   |            |
| <b>findctxfile</b>                  | function   | B renewtree                    |            |



|                      |            |                               |            |
|----------------------|------------|-------------------------------|------------|
| B savelists          |            | prefixes                      | data table |
| D setups             |            | prependhash                   | function   |
| D specification      |            | pushpath                      | function   |
| D variables          |            | registerextrapath             | function   |
| <b>jobpath</b>       | function   | registerfile                  | function   |
| <b>jobs</b>          | table      | registerfilehash              | function   |
| F currentcomponent   |            | registerintrees               | function   |
| F currentenvironment |            | registermethod                | function   |
| F currentproduct     |            | registerzipfile               | function   |
| F currentproject     |            | relations                     | data table |
| F justacomponent     |            | renew                         | function   |
| D processors         |            | repath                        | function   |
| F productcomponent   |            | reset                         | function   |
| F usefile            |            | resetextrapath                | function   |
| <b>joinpath</b>      | function   | resetresolve                  | function   |
| <b>load</b>          | function   | resolve                       | function   |
| <b>loadbinfile</b>   | function   | savers                        | data table |
| <b>loaders</b>       | data table | scandata                      | function   |
| <b>loadlualib</b>    | function   | scanfiles                     | function   |
| <b>loadtexfile</b>   | function   | schemes                       | table      |
| <b>loadtime</b>      | function   | T cleaners                    |            |
| <b>locateformat</b>  | function   | F md5                         |            |
| <b>locators</b>      | data table | F none                        |            |
| <b>luacnfname</b>    | string     | F strip                       |            |
| <b>luacnfspec</b>    | string     | F cleanname                   |            |
| <b>luacnfstate</b>   | string     | F fetchstring                 |            |
| <b>macros</b>        | table      | F fetchtable                  |            |
| F convertfile        |            | F install                     |            |
| F decodecomment      |            | <b>setdynamic</b>             | function   |
| F enablecomment      |            | <b>setenv</b>                 | function   |
| F encodecomment      |            | <b>setinstance</b>            | function   |
| F preprocessed       |            | <b>showpath</b>               | function   |
| F processmk          |            | <b>simplescanfiles</b>        | function   |
| F processmkvi        |            | <b>splitconfigurationpath</b> | function   |
| F version            |            | <b>splitexpansions</b>        | function   |
| <b>maxreadlevel</b>  | number     | <b>splitmethod</b>            | function   |
| <b>methodhandler</b> | function   | <b>splitpath</b>              | function   |
| <b>newinstance</b>   | function   | <b>stackpath</b>              | function   |
| <b>openbinfile</b>   | function   | <b>suffixes</b>               | data table |
| <b>openers</b>       | data table | <b>suffixmap</b>              | data table |
| <b>openfile</b>      | function   | <b>suffixofformat</b>         | function   |
| <b>opentexfile</b>   | function   | <b>texdatablob</b>            | function   |
| <b>ownpath</b>       | string     | <b>toppath</b>                | function   |
| <b>poppath</b>       | function   | <b>unexpandedpath</b>         | function   |

|                                 |            |
|---------------------------------|------------|
| <b>unexpandedpathlist</b>       | function   |
| <b>unresolve</b>                | function   |
| <b>updaterelations</b>          | function   |
| <b>updatescript</b>             | function   |
| <b>usertypes</b>                | data table |
| <b>usezipfile</b>               | function   |
| <b>validatedpath</b>            | function   |
| <b>variable</b>                 | function   |
| <b>variableofformat</b>         | function   |
| <b>variableofformatorsuffix</b> | function   |
| <b>wildcardpattern</b>          | function   |

# scripts (context)

**autofontfeature**    table  
    F disable  
    F enable  
    F handler

**categorytonumber** data table

**colors**            data table

**decomposehangul**    function

**defaults**           table  
    N inter\_char\_half\_shrink\_factor  
    N inter\_char\_half\_stretch\_factor  
    N inter\_char\_hangul\_penalty  
    N inter\_char\_quarter\_shrink\_factor  
    N inter\_char\_quarter\_stretch\_factor  
    N inter\_char\_shrink\_factor  
    N inter\_char\_stretch\_factor  
    N inter\_word\_stretch\_factor

**handlers**           data table

**hash**                table

**injectors**           data table

**installdataset**     function

**installmethod**      function

**numbertocategory**   data table

**numbertodataset**    data table

**numbertohandler**    data table

**reset**                function

**set**                  function

**splitters**           data table

## set (context)

**contains** function  
**create** function  
**tolist** function  
**tonumber** function  
**totable** function

# socket (extra lua)

|                       |          |                             |
|-----------------------|----------|-----------------------------|
| <b>BLOCKSIZE</b>      | number   | S connection                |
| <b>_DEBUG</b>         | boolean  | S content-description       |
| <b>_SETSIZE</b>       | number   | S content-disposition       |
| <b>bind</b>           | function | S content-encoding          |
| <b>choose</b>         | function | S content-id                |
| <b>connect</b>        | function | S content-language          |
| <b>connect4</b>       | function | S content-length            |
| <b>connect6</b>       | function | S content-location          |
| <b>dns</b>            | table    | S content-md5               |
| F getaddrinfo         |          | S content-range             |
| F gethostname         |          | S content-transfer-encoding |
| F getnameinfo         |          | S content-type              |
| F tohostname          |          | S date                      |
| F toip                |          | S diagnostic-code           |
| <b>ftp</b>            | table    | S dsn-gateway               |
| S PASSWORD            |          | S etag                      |
| N PORT                |          | S expect                    |
| N TIMEOUT             |          | S expires                   |
| S USER                |          | S final-log-id              |
| F command             |          | S final-recipient           |
| F get                 |          | S from                      |
| F open                |          | S host                      |
| F put                 |          | S if-match                  |
| <b>gettime</b>        | function | S if-modified-since         |
| <b>headers</b>        | table    | S if-none-match             |
| T canonic             |          | S if-range                  |
| S accept              |          | S if-unmodified-since       |
| S accept-charset      |          | S in-reply-to               |
| S accept-encoding     |          | S keywords                  |
| S accept-language     |          | S last-attempt-date         |
| S accept-ranges       |          | S last-modified             |
| S action              |          | S location                  |
| S age                 |          | S max-forwards              |
| S allow               |          | S message-id                |
| S alternate-recipient |          | S mime-version              |
| S arrival-date        |          | S original-envelope-id      |
| S authorization       |          | S original-recipient        |
| S bcc                 |          | S pragma                    |
| S cache-control       |          | S proxy-authenticate        |
| S cc                  |          | S proxy-authorization       |
| S comments            |          | S range                     |

S received  
 S received-from-mta  
 S references  
 S referer  
 S remote-mta  
 S reply-to  
 S reporting-mta  
 S resent-bcc  
 S resent-cc  
 S resent-date  
 S resent-from  
 S resent-message-id  
 S resent-reply-to  
 S resent-sender  
 S resent-to  
 S retry-after  
 S return-path  
 S sender  
 S server  
 S smtp-remote-recipient  
 S status  
 S subject  
 S te  
 S to  
 S trailer  
 S transfer-encoding  
 S upgrade  
 S user-agent  
 S vary  
 S via  
 S warning  
 S will-retry-until  
 S www-authenticate  
 S x-mailer

## http table

N PORT  
 N TIMEOUT  
 S USERAGENT  
 F open  
 F request

**newtry** function  
**protect** function  
**select** function  
**sink** function

## sinkt table

F close-when-done  
 F default  
 F http-chunked  
 F keep-open

## skip function

## sleep function

## smtp table

S DOMAIN  
 N PORT  
 S SERVER  
 N TIMEOUT  
 S ZONE  
 F message  
 F open  
 F send

## source function

## sourcet table

F by-length  
 F default  
 F http-chunked  
 F until-closed

## tcp function

## tcp6 function

## tp table

N TIMEOUT  
 F connect

## try function

## udp function

## udp6 function

## url table

F absolute  
 F build  
 F build\_path  
 F escape  
 F parse  
 F parse\_path  
 F unescape

# sorters (context)

**basicsorter**      function

**comparers**        table

    F basic

**constants**        table

    S defaultdigits

    S defaultlanguage

    S defaultmethod

    N digitsoffset

    N ignoredoffset

    N replacementoffset

    T validmethods

        B ch

        B mc

        B mm

        B pc

        B pm

        B uc

        B zc

        B zm

**definitions**      data table

**firstofsplit**     function

**setlanguage**      function

**sort**              function

**splitters**        table

    F utf

**strip**             function

**tracers**          data table

**update**           function

## statistics (context)

|                       |          |
|-----------------------|----------|
| <b>checkfmtstatus</b> | function |
| <b>elapsed</b>        | function |
| <b>elapsedindeed</b>  | function |
| <b>elapsedseconds</b> | function |
| <b>elapsedtime</b>    | function |
| <b>enable</b>         | boolean  |
| <b>formatruntime</b>  | function |
| <b>hastiming</b>      | function |
| <b>memused</b>        | function |
| <b>register</b>       | function |
| <b>resettiming</b>    | function |
| <b>runtime</b>        | function |
| <b>savefmtstatus</b>  | function |
| <b>show</b>           | function |
| <b>starttiming</b>    | function |
| <b>stoptiming</b>     | function |
| <b>threshold</b>      | number   |
| <b>timed</b>          | function |
| <b>tracefunction</b>  | function |



status (basic tex)

**list** function

## storage (context)

|                   |            |
|-------------------|------------|
| <b>allocate</b>   | function   |
| <b>data</b>       | table      |
| <b>mark</b>       | function   |
| <b>marked</b>     | function   |
| <b>max</b>        | number     |
| <b>min</b>        | number     |
| <b>nofmodules</b> | number     |
| <b>noftables</b>  | number     |
| <b>register</b>   | function   |
| <b>shared</b>     | data table |
| <b>strip</b>      | boolean    |
| <b>tofmodules</b> | number     |
| <b>toftables</b>  | number     |

## streams (context)

|                    |          |
|--------------------|----------|
| <b>collect</b>     | function |
| <b>disable</b>     | function |
| <b>enable</b>      | function |
| <b>flush</b>       | function |
| <b>initialize</b>  | function |
| <b>push</b>        | function |
| <b>start</b>       | function |
| <b>stop</b>        | function |
| <b>synchronize</b> | function |

## string (basic lua)

|                       |          |                      |          |
|-----------------------|----------|----------------------|----------|
| <b>autodouble</b>     | function | <b>tformat</b>       | function |
| <b>autosingle</b>     | function | <b>toboolean</b>     | function |
| <b>booleanstring</b>  | function | <b>tocontext</b>     | function |
| <b>byte</b>           | function | <b>todimen</b>       | function |
| <b>bytepairs</b>      | function | <b>tonodes</b>       | function |
| <b>bytes</b>          | function | <b>topattern</b>     | function |
| <b>char</b>           | function | <b>totable</b>       | function |
| <b>characterpairs</b> | function | <b>toutf</b>         | function |
| <b>characters</b>     | function | <b>tracedchar</b>    | function |
| <b>checkedsplit</b>   | function | <b>tracedchars</b>   | table    |
| <b>collapsespaces</b> | function | <b>unquote</b>       | function |
| <b>count</b>          | function | <b>unquoted</b>      | function |
| <b>dump</b>           | function | <b>upper</b>         | function |
| <b>escapedpattern</b> | function | <b>utfcharacters</b> | function |
| <b>explode</b>        | function | <b>utfvalues</b>     | function |
| <b>find</b>           | function | <b>valid</b>         | function |
| <b>format</b>         | function |                      |          |
| <b>formatter</b>      | function |                      |          |
| <b>formatters</b>     | function |                      |          |
| <b>fullstrip</b>      | function |                      |          |
| <b>gmatch</b>         | function |                      |          |
| <b>gsub</b>           | function |                      |          |
| <b>is_boolean</b>     | function |                      |          |
| <b>is_empty</b>       | function |                      |          |
| <b>itself</b>         | function |                      |          |
| <b>len</b>            | function |                      |          |
| <b>limit</b>          | function |                      |          |
| <b>longtostring</b>   | function |                      |          |
| <b>lower</b>          | function |                      |          |
| <b>match</b>          | function |                      |          |
| <b>nspaces</b>        | table    |                      |          |
| <b>optionalquoted</b> | function |                      |          |
| <b>quote</b>          | function |                      |          |
| <b>quoted</b>         | function |                      |          |
| <b>rep</b>            | function |                      |          |
| <b>reverse</b>        | function |                      |          |
| <b>split</b>          | function |                      |          |
| <b>splitlines</b>     | function |                      |          |
| <b>splitup</b>        | function |                      |          |
| <b>strip</b>          | function |                      |          |
| <b>sub</b>            | function |                      |          |

# structures (context)

|                   |          |                             |          |
|-------------------|----------|-----------------------------|----------|
| <b>atlocation</b> | function | F setlevel                  |          |
| <b>blocks</b>     | table    | F setoffset                 |          |
| D collected       |          | F setown                    |          |
| F define          |          | F setstate                  |          |
| F print           |          | F setvalue                  |          |
| F save            |          | T specials                  |          |
| F select          |          | F userpage                  |          |
| F setstate        |          | F subs                      |          |
| D states          |          | D tobesaved                 |          |
| D tobesaved       |          | F value                     |          |
| <b>bookmarks</b>  | table    | <b>currentsectionnumber</b> | function |
| F finalize        |          | <b>descriptions</b>         | table    |
| F flatten         |          | <b>documents</b>            | table    |
| S method          |          | D data                      |          |
| F overload        |          | F initialize                |          |
| F place           |          | F preset                    |          |
| F register        |          | F reset                     |          |
| F setup           |          | <b>floats</b>               | table    |
| <b>counters</b>   | table    | <b>formulas</b>             | table    |
| F add             |          | F current                   |          |
| F analyze         |          | F simplify                  |          |
| F check           |          | F store                     |          |
| D collected       |          | <b>helpers</b>              | table    |
| F compact         |          | F analyze                   |          |
| F converted       |          | F formulanumber             |          |
| F currentvalue    |          | F merged                    |          |
| D data            |          | F page                      |          |
| F define          |          | F prefix                    |          |
| F first           |          | F prefixlastpage            |          |
| F get             |          | F prefixpage                |          |
| F last            |          | F simplify                  |          |
| F next            |          | F title                     |          |
| F prev            |          | F touserdata                |          |
| F previous        |          | <b>inserts</b>              | table    |
| F raw             |          | D data                      |          |
| F record          |          | F define                    |          |
| F reset           |          | F getdata                   |          |
| F restart         |          | F getlocation               |          |
| F restore         |          | F getname                   |          |
| F save            |          | F getnumber                 |          |
| F set             |          | F setlocation               |          |

|                   |              |                            |              |
|-------------------|--------------|----------------------------|--------------|
| F setup           |              | F userdata                 |              |
| D stored          |              | F uservalue                |              |
| <b>itemgroups</b> | <b>table</b> | <b>marks</b>               | <b>table</b> |
| F maxwidth        |              | D data                     |              |
| F nofitems        |              | F define                   |              |
| F register        |              | F exists                   |              |
| <b>lists</b>      | <b>table</b> | F fetch                    |              |
| F addto           |              | F fetchallmarks            |              |
| F analyze         |              | F fetched                  |              |
| B autoreorder     |              | F fetchonemark             |              |
| D cached          |              | F fetchtwomarks            |              |
| D collected       |              | F get                      |              |
| F discard         |              | F number                   |              |
| F enhance         |              | F relate                   |              |
| T enhancers       |              | F reset                    |              |
| F filter          |              | F set                      |              |
| F filtercollected |              | F show                     |              |
| F formulainumber  |              | F synchronize              |              |
| F getresult       |              | F title                    |              |
| F groupindex      |              | T tracers                  |              |
| F hasnumberdata   |              | F showtable                |              |
| F haspagedata     |              | <b>notes</b>               | <b>table</b> |
| F hastitledata    |              | F checkpagechange          |              |
| F iscached        |              | F define                   |              |
| F label           |              | F doifonsamepageasprevious |              |
| F location        |              | F get                      |              |
| F number          |              | F getdeltapage             |              |
| D ordered         |              | F getn                     |              |
| F page            |              | F getnumberpage            |              |
| F popnesting      |              | F getstate                 |              |
| F prefix          |              | F getsymbolpage            |              |
| F prefixednumber  |              | F hascontent               |              |
| F prefixedpage    |              | F internal                 |              |
| F process         |              | F internalid               |              |
| D pushed          |              | F listindex                |              |
| F pushnesting     |              | F ordered                  |              |
| F realpage        |              | F postpone                 |              |
| F reordered       |              | F resetpostponed           |              |
| T result          |              | F restore                  |              |
| D sectionblocks   |              | F save                     |              |
| F sectionnumber   |              | F setstate                 |              |
| F size            |              | F setsymbolpage            |              |
| F title           |              | D states                   |              |
| D tobesaved       |              | F store                    |              |

## pages

F analyze  
D collected  
F is\_odd  
N nopages  
F number  
F save  
D tobesaved

## table

## references

F analyze  
F checkedfile  
F checkedfileorurl  
F checkedprogram  
F checkedrealpage  
F checkedurl  
D collected  
U componentsplitter  
F currentmetadata  
F currentorder  
D currentset  
F define  
D defined  
D derived  
F enableinteraction  
F enhance  
D executors  
F expandcurrent  
F export  
T files  
T data  
F define  
F get  
F filter  
F filterdefault  
D filters  
D flaginternals  
F from  
F get  
F getcurrentmetadata  
F getcurrentprefixspec  
F getinnermethod  
F getinternallistreference  
F getinternalreference  
D handlers

F identify  
F import  
F inject  
F injectcurrentset  
S innermethod  
D internals  
F load  
F loadpresets  
F mark  
D pages  
U prefixsplitter  
D productdata  
T programs  
T data  
F define  
F get  
F realpageofpage  
U referencesplitter  
D referred  
F referredpage  
F registerfinalizer  
F registerinitializer  
F registerpage  
F reportproblems  
F reset  
D runners  
F set  
F setandgetattribute  
F setcomponent  
F setinnermethod  
F setinternalreference  
F setnextinternal  
F setnextorder  
D specials  
F splitcomponent  
F splitprefix  
F splitreference  
F synchronizepage  
T testrunners  
F inner  
F special  
F special operation  
F special operation with arguments  
T testspecials

|                   |              |                     |              |
|-------------------|--------------|---------------------|--------------|
| F deltapage       |              | F currentlevel      |              |
| F i               |              | F depthnumber       |              |
| F internal        |              | F finddata          |              |
| F page            |              | F findnumber        |              |
| F realpage        |              | F fullnumber        |              |
| F section         |              | F getcurrentlevel   |              |
| F userpage        |              | F getlevel          |              |
| D tobereferred    |              | F getnumber         |              |
| D tobesaved       |              | F internalreference |              |
| T urls            |              | D levelmap          |              |
| T data            |              | D levels            |              |
| F define          |              | F load              |              |
| F get             |              | F matchingtilldepth |              |
| D usedinternals   |              | F numberatdepth     |              |
| D usedviews       |              | F numbers           |              |
| F valid           |              | F popblock          |              |
| F whatfrom        |              | F prefixedconverted |              |
| <b>registers</b>  | <b>table</b> | F pushblock         |              |
| F analyze         |              | F register          |              |
| D collected       |              | D registered        |              |
| F compare         |              | F reportstructure   |              |
| F define          |              | F save              |              |
| F enhance         |              | T sectionblockdata  |              |
| F extend          |              | T bodypart          |              |
| F filter          |              | S bookmark          |              |
| F filtercollected |              | F set               |              |
| F finalize        |              | F setblock          |              |
| F flush           |              | F setchecker        |              |
| F get             |              | F setentry          |              |
| F prepare         |              | F setlevel          |              |
| F process         |              | F setnumber         |              |
| F setmethod       |              | F structuredata     |              |
| F sort            |              | F title             |              |
| F store           |              | D tobesaved         |              |
| D tobesaved       |              | F typesetnumber     |              |
| F unique          |              | F userdata          |              |
| F userdata        |              | B verbose           |              |
| <b>sections</b>   | <b>table</b> | <b>sets</b>         | <b>table</b> |
| F autodepth       |              | F define            |              |
| F cct             |              | F get               |              |
| D collected       |              | F getall            |              |
| F current         |              | D setlist           |              |
| F currentblock    |              | <b>specials</b>     | <b>table</b> |
| F currentid       |              | D collected         |              |



F retrieve  
F store  
D tobesaved

## **synonyms**

F analyzed  
D collected  
F compare  
F define  
F filter  
F finalize  
F flush  
F meaning  
F prepare  
F process  
F register  
F registerused  
F sort  
F synonym  
D tobesaved

## **table**

F settablecell  
F settabulatecell  
F setuserproperties  
F start  
F stop  
D taglist  
T userdata  
D userproperties

## **tags**

T data  
F detailedtag  
F getid  
F handler  
D labels  
F last  
F lastinchain  
T metadata  
D properties  
F registerdata  
F registermetadata  
F restart  
F setattributehash  
F setcombination  
F setdescription  
F setdescriptionsymbol  
F setfigure  
F sethighlight  
F setitemgroup  
F setlist  
F setproperty  
F setregister  
F setsorting  
F setsynonym

## **table**

## table (basic lua)

|                        |          |                             |          |
|------------------------|----------|-----------------------------|----------|
| <b>allkeys</b>         | function | <b>sequenced</b>            | function |
| <b>append</b>          | function | <b>serialize</b>            | function |
| <b>are_equal</b>       | function | <b>setmetatablecall</b>     | function |
| <b>autokey</b>         | function | <b>setmetatableindex</b>    | function |
| <b>compact</b>         | function | <b>setmetatablekey</b>      | function |
| <b>concat</b>          | function | <b>setmetatablenewindex</b> | function |
| <b>contains</b>        | function | <b>sort</b>                 | function |
| <b>copy</b>            | function | <b>sorted</b>               | function |
| <b>count</b>           | function | <b>sortedhash</b>           | function |
| <b>derive</b>          | function | <b>sortedhashkeys</b>       | function |
| <b>deserialize</b>     | function | <b>sortedhashonly</b>       | function |
| <b>drop</b>            | function | <b>sortedindexonly</b>      | function |
| <b>fastcopy</b>        | function | <b>sortedkeys</b>           | function |
| <b>fastserialize</b>   | function | <b>sortedpairs</b>          | function |
| <b>filtered</b>        | function | <b>sparse</b>               | function |
| <b>flattened</b>       | function | <b>strip</b>                | function |
| <b>foreach</b>         | function | <b>sub</b>                  | function |
| <b>foreachi</b>        | function | <b>swapped</b>              | function |
| <b>fromhash</b>        | function | <b>tocontext</b>            | function |
| <b>getmetatablekey</b> | function | <b>tocsv</b>                | function |
| <b>getn</b>            | function | <b>tofile</b>               | function |
| <b>has_one_entry</b>   | function | <b>tohandle</b>             | function |
| <b>identical</b>       | function | <b>tohash</b>               | function |
| <b>imerge</b>          | function | <b>toxml</b>                | function |
| <b>imerged</b>         | function | <b>twowaymapper</b>         | function |
| <b>insert</b>          | function | <b>unique</b>               | function |
| <b>is_empty</b>        | function | <b>unnest</b>               | function |
| <b>keys</b>            | function | <b>unpack</b>               | function |
| <b>load</b>            | function | <b>values</b>               | function |
| <b>loweredkeys</b>     | function |                             |          |
| <b>maxn</b>            | function |                             |          |
| <b>merge</b>           | function |                             |          |
| <b>merged</b>          | function |                             |          |
| <b>mirrored</b>        | function |                             |          |
| <b>pack</b>            | function |                             |          |
| <b>prepend</b>         | function |                             |          |
| <b>print</b>           | function |                             |          |
| <b>remove</b>          | function |                             |          |
| <b>reverse</b>         | function |                             |          |
| <b>reversed</b>        | function |                             |          |
| <b>save</b>            | function |                             |          |

## tex (basic tex)

|                         |            |                              |            |
|-------------------------|------------|------------------------------|------------|
| <b>attribute</b>        | table      | <b>isdefined</b>             | data table |
| <b>badness</b>          | function   | <b>isdimen</b>               | function   |
| <b>box</b>              | table      | <b>isskip</b>                | function   |
| <b>catcode</b>          | table      | <b>istoken</b>               | function   |
| <b>conditionals</b>     | data table | <b>lccode</b>                | table      |
| <b>constants</b>        | data table | <b>linebreak</b>             | function   |
| <b>count</b>            | table      | <b>lists</b>                 | table      |
| <b>ctdcatcodes</b>      | number     | <b>lua_math_random</b>       | function   |
| <b>ctxcatcodes</b>      | number     | <b>lua_math_randomseed</b>   | function   |
| <b>definefont</b>       | function   | <b>luacatcodes</b>           | number     |
| <b>delcode</b>          | table      | <b>mathcode</b>              | table      |
| <b>dimen</b>            | table      | <b>modes</b>                 | data table |
| <b>directives</b>       | data table | <b>nest</b>                  | table      |
| <b>enableprimitives</b> | function   | <b>nilcatcodes</b>           | number     |
| <b>error</b>            | function   | <b>normal_rand</b>           | function   |
| <b>extraprimitives</b>  | function   | <b>notcatcodes</b>           | number     |
| <b>finish</b>           | function   | <b>number</b>                | function   |
| <b>fontidentifier</b>   | function   | <b>pdffontname</b>           | function   |
| <b>fontname</b>         | function   | <b>pdffontobjnum</b>         | function   |
| <b>fprint</b>           | function   | <b>pdffontsize</b>           | function   |
| <b>get</b>              | function   | <b>pdfpageref</b>            | function   |
| <b>getattribute</b>     | function   | <b>pdfxformname</b>          | function   |
| <b>getbox</b>           | function   | <b>primitives</b>            | function   |
| <b>getcatcode</b>       | function   | <b>print</b>                 | function   |
| <b>getcount</b>         | function   | <b>printlist</b>             | function   |
| <b>getdelcode</b>       | function   | <b>prtcatcodes</b>           | number     |
| <b>getdimen</b>         | function   | <b>romannumeral</b>          | function   |
| <b>getlccode</b>        | function   | <b>round</b>                 | function   |
| <b>getlist</b>          | function   | <b>run</b>                   | function   |
| <b>getmath</b>          | function   | <b>scale</b>                 | function   |
| <b>getmathcode</b>      | function   | <b>set</b>                   | function   |
| <b>getnest</b>          | function   | <b>set_experimental_code</b> | function   |
| <b>getsfcode</b>        | function   | <b>setattribute</b>          | function   |
| <b>getskip</b>          | function   | <b>setbox</b>                | function   |
| <b>gettoks</b>          | function   | <b>setcatcode</b>            | function   |
| <b>getuccode</b>        | function   | <b>setcount</b>              | function   |
| <b>hashtokens</b>       | function   | <b>setdelcode</b>            | function   |
| <b>ifs</b>              | data table | <b>setdimen</b>              | function   |
| <b>inicatcodes</b>      | number     | <b>setlccode</b>             | function   |
| <b>init_rand</b>        | function   | <b>setlist</b>               | function   |
| <b>iscount</b>          | function   | <b>setmath</b>               | function   |

|                       |            |
|-----------------------|------------|
| <b>setmathcode</b>    | function   |
| <b>setnest</b>        | function   |
| <b>setsfcode</b>      | function   |
| <b>setskip</b>        | function   |
| <b>settoks</b>        | function   |
| <b>setuccode</b>      | function   |
| <b>sfcode</b>         | table      |
| <b>shipout</b>        | function   |
| <b>show_context</b>   | function   |
| <b>skip</b>           | table      |
| <b>sp</b>             | function   |
| <b>sprint</b>         | function   |
| <b>systemmodes</b>    | data table |
| <b>takebox</b>        | function   |
| <b>texcatcodes</b>    | number     |
| <b>toks</b>           | table      |
| <b>tpacatcodes</b>    | number     |
| <b>tpbcatcodes</b>    | number     |
| <b>tprint</b>         | function   |
| <b>trackers</b>       | data table |
| <b>txtcatcodes</b>    | number     |
| <b>type</b>           | function   |
| <b>uccode</b>         | table      |
| <b>uniform_rand</b>   | function   |
| <b>uniformdeviate</b> | function   |
| <b>uprint</b>         | function   |
| <b>vrbcacodes</b>     | number     |
| <b>write</b>          | function   |

## texconfig (basic tex)

|                        |                     |
|------------------------|---------------------|
| <b>error_line</b>      | number              |
| <b>expand_depth</b>    | number              |
| <b>formatname</b>      | string              |
| <b>half_error_line</b> | number              |
| <b>hash_extra</b>      | number              |
| <b>init</b>            | overloaded function |
| <b>kpse_init</b>       | boolean             |
| <b>max_in_open</b>     | number              |
| <b>max_print_line</b>  | number              |
| <b>max_strings</b>     | number              |
| <b>nest_size</b>       | number              |
| <b>param_size</b>      | number              |
| <b>save_size</b>       | number              |
| <b>shell_escape</b>    | string              |
| <b>stack_size</b>      | overloaded number   |

## texio (basic tex)

`write`      function

`write_nl`   function

## token (basic tex)

|                      |          |
|----------------------|----------|
| <b>command_id</b>    | function |
| <b>command_name</b>  | function |
| <b>create</b>        | function |
| <b>csname_id</b>     | function |
| <b>csname_name</b>   | function |
| <b>expand</b>        | function |
| <b>get_next</b>      | function |
| <b>is_activechar</b> | function |
| <b>is_expandable</b> | function |
| <b>is_protected</b>  | function |
| <b>lookup</b>        | function |

# tokens (context)

**bgroup**        table

**collectors** table

  T data

  F defaultwords

  F dowithwords

  F flush

  F handle

  F install

  F register

  T registered

  T remapper

    F convert

    T data

    F store

  F show

  T show\_methods

    F a

    F b

    F c

  F showtoken

  F test

  F trace

**egroup**        table

**hbox**          table

**letter**        function

**letters**       function

**other**         function

**vbox**          table

**vtop**          table



# tracers (context)

|                  |          |
|------------------|----------|
| <b>count</b>     | function |
| <b>cs</b>        | function |
| <b>dimen</b>     | function |
| <b>knownlist</b> | function |
| <b>lists</b>     | table    |

T context

T internals

T scratch

|                  |          |
|------------------|----------|
| <b>name</b>      | function |
| <b>primitive</b> | function |
| <b>prnterror</b> | function |
| <b>showlines</b> | function |
| <b>strings</b>   | table    |

S undefined

|             |          |
|-------------|----------|
| <b>toks</b> | function |
| <b>type</b> | function |

## trackers (context)

|                       |            |
|-----------------------|------------|
| <b>data</b>           | data table |
| <b>default</b>        | function   |
| <b>disable</b>        | function   |
| <b>dumphashtofile</b> | function   |
| <b>enable</b>         | function   |
| <b>list</b>           | function   |
| <b>name</b>           | string     |
| <b>register</b>       | function   |
| <b>report</b>         | function   |
| <b>savehash</b>       | function   |
| <b>show</b>           | function   |
| <b>value</b>          | function   |

# typesetters (context)

## **alignments** table

F handler  
F set

## **breakpoints** table

F define  
F handler  
D mapping  
T methods  
T numbers  
F set  
F setreplacement

## **cases** table

T actions  
F handler  
F register  
F set

## **characteralign** table

F handler  
F resetcharacteralign  
F setcharacteralign

## **characters** table

F handler  
F replacensp  
F replacenspaces

## **checkers** table

F handler  
F reset  
F set

## **cleaners** table

F handler  
F set

## **digits** table

T actions  
F handler  
F set

## **directions** table

F getfences  
F getglobal  
F getmethod  
F handler  
T handlers

F installhandler

F processmath

F set

F setcolor

F setmath

F tomode

## **firstlines** table

T actions  
F default  
F line  
F word  
F handler  
F set

## **initials** table

T actions  
F default  
F handler  
F set

## **italics** table

F forcevariant  
F handler  
F reset  
F set

## **kerns** table

D factors  
F handler  
F keepligature  
B keptogether  
D mapping  
F set

## **manipulators** table

F apply  
F applyspecification  
T methods  
F Word  
F Words  
F abbreviatedjournal  
F expandedjournal  
F lowercase  
F stripperperiod  
F uppercase

- T patterns
- U list
- U pair
- F splitspecification

**margins**                      table

- F finalhandler
- F globalhandler
- F ha
- F localhandler
- F save

**processors**                      table

- F apply
- F register
- F reset
- F split
- F startapply
- F stopapply
- F stripped
- F tostring

**spacings**                      table

- F define
- F handler
- D mapping
- T numbers
  - T frenchpunctuation
    - T characters
    - S name
    - N number
- F reset
- F set
- F setup

**xtables**                      table

- F cleanup
- F construct
- F create
- F flush
- F initialize\_construct
- F initialize\_reflow\_height
- F initialize\_reflow\_width
- F next\_row
- F reflow\_height
- F reflow\_width
- F set\_construct
- F set\_reflow\_height
- F set\_reflow\_width

# unicode (extra lua)

## ascii table

F byte  
F char  
F dump  
F find  
F format  
F gfind  
F gmatch  
F gsub  
F len  
F lower  
F match  
F rep  
F reverse  
F sub  
F upper

## grapheme table

F byte  
F char  
F dump  
F find  
F format  
F gfind  
F gmatch  
F gsub  
F len  
F lower  
F match  
F rep  
F reverse  
F sub  
F upper

## latin1 table

F byte  
F char  
F dump  
F find  
F format  
F gfind  
F gmatch  
F gsub

F len  
F lower  
F match  
F rep  
F reverse  
F sub  
F upper

## utf8 table

F byte  
F char  
F characters  
F chrln  
F count  
F dump  
F filetype  
F find  
F format  
F gfind  
F gmatch  
F gsub  
F is\_valid  
F len  
F length  
F lower  
F magic  
F match  
F remapper  
F rep  
F replacer  
F reverse  
F split  
F splitlines  
F sub  
F subtituter  
F tocodes  
F toeight  
F toentities  
F toString  
F totable  
F upper  
F ustring

- F utf16\_to\_utf8
- F utf16\_to\_utf8\_be
- F utf16\_to\_utf8\_le
- F utf32\_to\_utf8
- F utf32\_to\_utf8\_be
- F utf32\_to\_utf8\_le
- F utf8\_to\_utf16
- F utf8\_to\_utf16\_be
- F utf8\_to\_utf16\_le
- F utf8\_to\_utf8
- F values
- F xstring

## url (context)

|                    |          |
|--------------------|----------|
| <b>addscheme</b>   | function |
| <b>barepath</b>    | function |
| <b>construct</b>   | function |
| <b>escape</b>      | function |
| <b>filename</b>    | function |
| <b>hashed</b>      | function |
| <b>hasscheme</b>   | function |
| <b>query</b>       | function |
| <b>split</b>       | function |
| <b>toquery</b>     | function |
| <b>unescapeget</b> | function |

# utilities (context)

## debugger table

- F disable
- F enable
- F savestats
- F showstats
- F showtraceback

## formatters table

- F formatcolumns
- F list
- F stripzeros

## garbagecollector table

- F check
- N criterium
- B enabled

## lua table

- B alwaysstripcode
- F compile
- F loadedluacode
- F loadstripped
- N nofstrippedbytes
- N nofstrippedchunks
- B stripcode
- T strippedchunks
- F strippedloadstring
- T suffixes
  - S lua
  - S luc
  - S lui
  - S luj
  - S luv
  - S tma
  - S tmc
  - S tua
  - S tuc

## packers table

- F hashed
- F new
- F pack
- F simplehashed
- F strip
- F unpack

N version

## parsers table

- F add\_settings\_to\_array
- F arguments\_to\_table
- F array\_to\_string
- F csvsplitter
- F getparameters
- F hash\_to\_string
- F iterator
- F keq\_to\_hash
- F listitem
- F make\_settings\_to\_hash\_pattern
- F mergehashes
- F options\_to\_hash
- T patterns
  - U settings\_to\_array
  - U settings\_to\_hash\_a
  - U settings\_to\_hash\_b
  - U settings\_to\_hash\_c
  - U unittotex
- F process\_stripped\_settings
- F rfc4180splitter
- F runtime
- F settings\_to\_array
- F settings\_to\_array\_with\_repeat
- F settings\_to\_hash
- F settings\_to\_hash\_strict
- F settings\_to\_hash\_tolerant
- F settings\_to\_set
- F simple\_hash\_to\_string
- F splitmethod
- F splitthousands
- F stepper
- F stripped\_settings\_to\_array
- F unittotex
- F unittotxml

## report function

## sequencers table

- F appendaction
- F appendgroup
- F compile



|                      |                        |
|----------------------|------------------------|
| F disableaction      | U prune and no empty   |
| F disablegroup       | U retain               |
| F enableaction       | U retain and collapse  |
| F enablegroup        | U retain and no empty  |
| D functions          | F striplines           |
| F localize           | F striplong            |
| F new                | F tabtospace           |
| F nodeprocessor      | T tracers              |
| F prependaction      | <b>tables</b> table    |
| F prependgroup       | F accesstable          |
| F removeaction       | F definedtable         |
| F replaceaction      | F definetable          |
| F setkind            | F encapsulate          |
| F tostring           | F insertaftervalue     |
| <b>setters</b> table | F insertbeforevalue    |
| F disable            | F migratetable         |
| F enable             | F removevalue          |
| F initialize         | F replacevalue         |
| F list               | <b>templates</b> table |
| F new                | F load                 |
| F register           | F replace              |
| F report             | F replacer             |
| F reset              | F resolve              |
| F show               |                        |
| <b>stacker</b> table |                        |
| F new                |                        |
| <b>storage</b> table |                        |
| F allocate           |                        |
| F checked            |                        |
| F mark               |                        |
| F marked             |                        |
| F setinitializer     |                        |
| F sparse             |                        |
| <b>strings</b> table |                        |
| F collapsecrlf       |                        |
| T formatters         |                        |
| F add                |                        |
| F new                |                        |
| F newrepeater        |                        |
| F nice               |                        |
| T striplinepatterns  |                        |
| U collapse           |                        |
| U prune              |                        |
| U prune and collapse |                        |

## vf (context)

|                |          |
|----------------|----------|
| <b>char</b>    | function |
| <b>down</b>    | function |
| <b>fontid</b>  | function |
| <b>image</b>   | function |
| <b>node</b>    | function |
| <b>nop</b>     | function |
| <b>pop</b>     | function |
| <b>push</b>    | function |
| <b>right</b>   | function |
| <b>rule</b>    | function |
| <b>special</b> | function |

## visualizers (context)

|                              |            |
|------------------------------|------------|
| <b>escapepatterns</b>        | data table |
| <b>getvisualizer</b>         | function   |
| <b>load</b>                  | function   |
| <b>makenested</b>            | function   |
| <b>makepattern</b>           | function   |
| <b>newgrammar</b>            | function   |
| <b>newhandler</b>            | function   |
| <b>parsedxml</b>             | function   |
| <b>pattern</b>               | function   |
| <b>register</b>              | function   |
| <b>registerescapecommand</b> | function   |
| <b>registerescapeline</b>    | function   |
| <b>registerescapepattern</b> | function   |
| <b>signal</b>                | string     |
| <b>signalpattern</b>         | userdata   |
| <b>specifications</b>        | data table |
| <b>visualize</b>             | function   |
| <b>visualizebuffer</b>       | function   |
| <b>visualizefile</b>         | function   |
| <b>visualizestring</b>       | function   |
| <b>write</b>                 | function   |
| <b>writeargument</b>         | function   |
| <b>writedefault</b>          | function   |
| <b>writeemptyline</b>        | function   |
| <b>writenewline</b>          | function   |
| <b>writespace</b>            | function   |

# xml (context)

|                           |          |                        |            |
|---------------------------|----------|------------------------|------------|
| <b>addentitiesdoctype</b> | function | D tex                  |            |
| <b>after</b>              | function | D texline              |            |
| <b>all</b>                | function | D texspace             |            |
| <b>applylpath</b>         | function | D verbose              |            |
| <b>assign</b>             | function | <b>defaultprotocol</b> | string     |
| <b>attribute</b>          | function | <b>delete</b>          | function   |
| <b>before</b>             | function | <b>delete_element</b>  | function   |
| <b>body</b>               | function | <b>each</b>            | function   |
| <b>builtinentities</b>    | table    | <b>each_element</b>    | function   |
| B amp                     |          | <b>elements</b>        | function   |
| B apos                    |          | <b>elementtocdata</b>  | function   |
| B gt                      |          | <b>empty</b>           | function   |
| B lt                      |          | <b>entities</b>        | data table |
| B quot                    |          | <b>erase</b>           | function   |
| <b>cdata</b>              | function | <b>errorhandler</b>    | function   |
| <b>cdatatotext</b>        | function | <b>escaped</b>         | function   |
| <b>checkbom</b>           | function | <b>expressions</b>     | table      |
| <b>checkerror</b>         | function | F boolean              |            |
| <b>checknamespace</b>     | function | F child                |            |
| <b>checkns</b>            | function | F contains             |            |
| <b>cleansed</b>           | function | F count                |            |
| <b>collect</b>            | function | F error                |            |
| <b>collect_elements</b>   | function | F find                 |            |
| <b>collect_tags</b>       | function | F lower                |            |
| <b>collect_texts</b>      | function | F name                 |            |
| <b>collected</b>          | function | F number               |            |
| <b>collecttexts</b>       | function | F oneof                |            |
| <b>content</b>            | function | F print                |            |
| <b>convert</b>            | function | F quit                 |            |
| <b>copy</b>               | function | F tag                  |            |
| <b>count</b>              | function | F text                 |            |
| <b>cprint</b>             | function | F undefined            |            |
| <b>css</b>                | table    | F upper                |            |
| F colorspecification      |          | <b>fillin</b>          | function   |
| F dimension               |          | <b>filter</b>          | function   |
| F fontspecification       |          | <b>finalizers</b>      | table      |
| F padding                 |          | F paragraphs           |            |
| <b>defaulthandlers</b>    | table    | T tex                  |            |
| D file                    |          | F all                  |            |
| D parsedxml               |          | F attribute            |            |
| D string                  |          | F chainattribute       |            |

|                  |                              |          |
|------------------|------------------------------|----------|
| F command        | F table                      |          |
| F concat         | F tag                        |          |
| F concatrange    | F tags                       |          |
| F context        | F text                       |          |
| F count          | F texts                      |          |
| F ctxtext        | F upperall                   |          |
| F default        | <b>first</b>                 | function |
| F first          | <b>found</b>                 | function |
| F function       | <b>functions</b>             | table    |
| F index          | <b>getbuffer</b>             | function |
| F last           | <b>gethandlers</b>           | function |
| F lettered       | <b>gethandlersfunction</b>   | function |
| F lower          | <b>helpers</b>               | table    |
| F lowerall       | F recursetext                |          |
| F match          | <b>include</b>               | function |
| F name           | <b>inclusion</b>             | function |
| F position       | <b>inclusions</b>            | function |
| F reverse        | <b>index</b>                 | function |
| F stripped       | <b>inheritedconvert</b>      | function |
| F tag            | <b>inject</b>                | function |
| F tags           | <b>inject_element</b>        | function |
| F text           | <b>inject_element_after</b>  | function |
| F upper          | <b>inject_element_before</b> | function |
| F upperall       | <b>injectafter</b>           | function |
| T xml            | <b>injectbefore</b>          | function |
| F all            | <b>insert</b>                | function |
| F att            | <b>insert_element</b>        | function |
| F attribute      | <b>insert_element_after</b>  | function |
| F attributes     | <b>insert_element_before</b> | function |
| F cdata          | <b>insertafter</b>           | function |
| F chainattribute | <b>insertbefore</b>          | function |
| F count          | <b>insertcdata</b>           | function |
| F default        | <b>insertcomment</b>         | function |
| F elements       | <b>inspect</b>               | function |
| F empty          | <b>is_valid</b>              | function |
| F first          | <b>kind</b>                  | function |
| F function       | <b>last</b>                  | function |
| F index          | <b>load</b>                  | function |
| F last           | <b>lpath</b>                 | function |
| F lowerall       | <b>lpathcached</b>           | function |
| F match          | <b>lpathcalls</b>            | function |
| F name           | <b>lshow</b>                 | function |
| F position       | <b>makestandalone</b>        | function |
| F reverse        | <b>match</b>                 | function |

|                            |          |                           |          |
|----------------------------|----------|---------------------------|----------|
| <b>name</b>                | function | <b>sprint</b>             | function |
| <b>newhandlers</b>         | function | <b>string</b>             | function |
| <b>nodesettostring</b>     | function | <b>strip</b>              | function |
| <b>originalload</b>        | function | <b>strip_whitespace</b>   | function |
| <b>package</b>             | function | <b>stripelement</b>       | function |
| <b>parent</b>              | function | <b>stripleadingspaces</b> | function |
| <b>parsedentitylpeg</b>    | userdata | <b>table</b>              | function |
| <b>pihandlers</b>          | table    | <b>text</b>               | function |
| <b>placeholders</b>        | table    | <b>textonly</b>           | function |
| F unknown_any_entity       |          | <b>texttodata</b>         | function |
| F unknown_dec_entity       |          | <b>tocdata</b>            | function |
| F unknown_hex_entity       |          | <b>toelement</b>          | function |
| <b>position</b>            | function | <b>tostring</b>           | function |
| <b>privatecodes</b>        | table    | <b>toxml</b>              | function |
| <b>privatetoken</b>        | function | <b>tprint</b>             | function |
| <b>process</b>             | function | <b>traverse</b>           | function |
| <b>process_attributes</b>  | function | <b>unescaped</b>          | function |
| <b>process_elements</b>    | function | <b>unprivatized</b>       | function |
| <b>processattributes</b>   | function | <b>withelement</b>        | function |
| <b>profiled</b>            | table    | <b>withelements</b>       | function |
| <b>raw</b>                 | function | <b>wrap</b>               | function |
| <b>registerentity</b>      | function | <b>xmlns</b>              | table    |
| <b>registers</b>           | function |                           |          |
| <b>remap_name</b>          | function |                           |          |
| <b>remap_namespace</b>     | function |                           |          |
| <b>remap_tag</b>           | function |                           |          |
| <b>remapname</b>           | function |                           |          |
| <b>remapnamespace</b>      | function |                           |          |
| <b>remaptag</b>            | function |                           |          |
| <b>renamespace</b>         | function |                           |          |
| <b>replace</b>             | function |                           |          |
| <b>replace_element</b>     | function |                           |          |
| <b>resolvens</b>           | function |                           |          |
| <b>root</b>                | function |                           |          |
| <b>save</b>                | function |                           |          |
| <b>selection</b>           | function |                           |          |
| <b>separate</b>            | function |                           |          |
| <b>serialize</b>           | function |                           |          |
| <b>setcdata</b>            | function |                           |          |
| <b>setcomment</b>          | function |                           |          |
| <b>sethandlersfunction</b> | function |                           |          |
| <b>setproperty</b>         | function |                           |          |
| <b>settings</b>            | function |                           |          |
| <b>specialhandler</b>      | table    |                           |          |

## zip (extra lua)

|                        |          |
|------------------------|----------|
| <b>archives</b>        | table    |
| <b>close</b>           | function |
| <b>closearchive</b>    | function |
| <b>open</b>            | function |
| <b>openarchive</b>     | function |
| <b>openfile</b>        | function |
| <b>registeredfiles</b> | table    |
| <b>type</b>            | function |

## zlib (extra lua)

|                      |          |
|----------------------|----------|
| <b>adler32</b>       | function |
| <b>compress</b>      | function |
| <b>compressobj</b>   | function |
| <b>crc32</b>         | function |
| <b>decompress</b>    | function |
| <b>decompressobj</b> | function |
| <b>version</b>       | function |