



# ConTeXt

commands

# EN



# ConTeXt

## commands

en / english

August 02, 2019



<code>\AfterPar {...}</code> *    COMMAND
<code>\Alphabeticnumerals {...}</code> *    NUMBER
<code>\AMSTEX</code>
<code>\AmSTeX</code>
<code>\And</code>
<code>\abjadnaivenumerals {...}</code> *    NUMBER
<code>\abjadnodotnumerals {...}</code> *    NUMBER
<code>\abjadnumerals {...}</code> *    NUMBER
<code>\about [...]</code> *    REFERENCE
<code>\activatespacehandler {...}</code> *    on <u>off</u> yes fixed
<code>\acute {...}</code> *    CHARACTER
<code>\adaptcollector [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1    NAME <span style="float:right">OPT</span> 2    inherits: \setupcollector
<code>\adaptfontfeature [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> 1    NAME 2    inherits: \definefontfeature
<code>\adaptlayout [...]<sup>1</sup>,...<sup>OPT</sup> [...,...<sup>2</sup>...,...]</code> 1    NUMBER 2    height = max DIMENSION lines = NUMBER
<code>\adaptpapersize [...]<sup>1</sup>,...<sup>OPT</sup> [...,...<sup>2</sup>...,...]</code> 1    inherits: \setuppapersize <span style="float:right">OPT</span> 2    inherits: \setuppapersize
<code>\addfeature [...]</code> *    NAME
<code>\addfeature {...}</code> *    NAME
<code>\addfontpath [...]*,...</code> *    PATH

<code>\addtocommalist {...} \^2.</code> 1 TEXT 2 CSNAME
<code>\addtoJSreamble {...} {...}</code> 1 NAME 2 CONTENT
<code>\addvalue {...} {...}</code> 1 NAME 2 TEXT
<code>\aftersplitstring ... \at ... \to \^3.</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\aftertestandsplitstring ... \at ... \to \^3.</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\alignbottom</code>
<code>\aligned [...,\^1...] {\^2.}</code> 1 left middle right top bottom line l c r m t b g 2 CONTENT
<code>\alignedbox [...,\^1...] \^2. {\^3.}</code> 1 left middle right top bottom line l c r m t b g 2 CSNAME 3 CONTENT
<code>\alignedline {\^1.} {\^2.} {\^3.}</code> 1 left right middle flushleft flushright center max inner outer innermargin outermargin inneredge outeredge backspace cutspace leftmargin rightmargin leftedge rightedge 2 left right middle flushleft flushright center max inner outer innermargin outermargin inneredge outeredge backspace cutspace leftmargin rightmargin leftedge rightedge 3 CONTENT
<code>\alignhere</code>
<code>\alignmentcharacter</code>
<code>\allinputpaths</code>
<code>\alphabeticnumerals {\^*}</code> * NUMBER
<code>\alwayscitation [...,\^1...,...] [\^2.]</code> 1 reference = REFERENCE <sup>P</sup> <sub>T</sub> alternative = default category entry short page num textnum year index tag keywords author authoryears authornum authoryear before = COMMAND after = COMMAND left = COMMAND right = COMMAND inherits: \setupbtx 2 REFERENCE
<code>\alwayscitation [\^1.] [\^2.]</code> 1 default category entry <sup>P</sup> <sub>T</sub> short page num textnum year index tag keywords author authoryears authornum authoryear 2 REFERENCE

`\alwayscitation [...1...2...]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
               authoryear
  before      = COMMAND
  after       = COMMAND
  left        = COMMAND
  right       = COMMAND
  inherits: \setupbtx
2 KEY = VALUE
```

`\alwayscite [...1...2...]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
               authoryear
  before      = COMMAND
  after       = COMMAND
  left        = COMMAND
  right       = COMMAND
  inherits: \setupbtx
2 REFERENCE
```

`\alwayscite [...1...]OPT [...2...]`

```
1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear
2 REFERENCE
```

`\alwayscite [...1...2...]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
               authoryear
  before      = COMMAND
  after       = COMMAND
  left        = COMMAND
  right       = COMMAND
  inherits: \setupbtx
2 KEY = VALUE
```

`\ampersand`

`\anchor [...1...2...3...]{...4...}`

```
1 NAME
  OPT
2 inherits: \setuplayer
3 inherits: \setuplayerinherits: \setupframed
4 CONTENT
```

`\appendetoks ... \to ...`

```
1 COMMAND
2 CSNAME
```

`\appendgvalue {...1...}{...2...}`

```
1 NAME
2 COMMAND
```

`\appendtocommalist {...1...} ...2...`

```
1 TEXT
2 CSNAME
```

`\appendtoks ... \to ...`

```
1 COMMAND
2 CSNAME
```

`\appendtoksonce ... \to ...`

```
1 COMMAND
2 CSNAME
```

<code>\appendvalue {...} {...}</code> 1 NAME 2 COMMAND
<code>\apply {...} {...}</code> 1 CONTENT 2 CONTENT
<code>\applyalternativestyle {...}</code> * NAME
<code>\applyprocessor {...} {...}</code> 1 NAME 2 CONTENT
<code>\applytocharacters \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 TEXT
<code>\applytofirstcharacter \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringchar \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringcharspaced \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringline \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringlinespaced \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringword \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 TEXT
<code>\applytosplitstringwordspaced \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 TEXT
<code>\applytowords \<sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 TEXT
<code>\arabicdecimals {...}</code> * NUMBER
<code>\arabicexnumerals {...}</code> * NUMBER
<code>\arabicnumerals {...}</code> * NUMBER



<code>\arg {...}</code> *    CONTENT
<code>\asciistr {...}</code> *    CONTENT
<code>\assignalfadimension {...} \^2... {...} {...} {...}</code> 1    small medium big none DIMENSION 2    CSNAME 3    DIMENSION 4    DIMENSION 5    DIMENSION
<code>\assigndimen \^1... {...}</code> 1    CSNAME 2    DIMENSION
<code>\assigndimension {...} \^2... {...} {...} {...}</code> 1    [-+]small [-+]medium [-+]big none DIMENSION 2    CSNAME 3    DIMENSION 4    DIMENSION 5    DIMENSION
<code>\assignifempty \^1... \^2...</code> 1    CSNAME 2    COMMAND
<code>\assigntranslation [...,\^1...,\^2... \to \^2...</code> 1    LANGUAGE = TEXT 2    CSNAME
<code>\assignvalue {...} \^2... {...} {...} {...}</code> 1    small medium big TEXT 2    CSNAME 3    COMMAND 4    COMMAND 5    COMMAND
<code>\assignwidth {...} \^2... {...} {...}</code> 1    fit broad DIMENSION 2    CSNAME 3    TEXT 4    DIMENSION
<code>\assumelongusagecs \^1... {...}</code> 1    CSNAME 2    CONTENT
<code>\astype {...}</code> *    CONTENT
<code>\at {...} {...} [...]</code> 1    TEXT <sup>OPT</sup> OPT 2    TEXT 3    REFERENCE
<code>\atpage [...]</code> *    REFERENCE
<code>\ATTACHMENT [...]\^1... \^2...]</code> 1    NAME    OPT    OPT 2    inherits: \setupattachment instances: attachment

$\backslash attachment$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <u>...</u> ...] 1 NAME OPT OPT 2 inherits: \setupattachment
$\backslash autocap$ {...} * TEXT
$\backslash autodirhbox$ [ <sup>1</sup> ...] {...} <sup>2</sup> 1 TEXT OPT 2 CONTENT
$\backslash autodirvbox$ [ <sup>1</sup> ...] {...} <sup>2</sup> 1 TEXT OPT 2 CONTENT
$\backslash autodirvtop$ [ <sup>1</sup> ...] {...} <sup>2</sup> 1 TEXT OPT 2 CONTENT
$\backslash autoinsertnextspace$
$\backslash autointegral$ {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> 1 TEXT 2 TEXT 3 TEXT
$\backslash automathematics$ {...} * CONTENT
$\backslash autopagestaterealpage$ {...} * NAME
$\backslash autopagestaterealpageorder$ {...} * NAME
$\backslash autosetups$ {...,*...} * NAME
$\backslash autostarttext$ ... $\backslash autostoptext$
$\backslash availablehsize$
$\backslash averagecharwidth$
$\backslash BeforePar$ {...} * COMMAND
$\backslash Big$ ... * CHARACTER
$\backslash Bigg$ ... * CHARACTER
$\backslash Biggl$ ... * CHARACTER
$\backslash Biggm$ ... * CHARACTER

$\backslash\text{Biggr} \dots$ * CHARACTER
$\backslash\text{Bigl} \dots$ * CHARACTER
$\backslash\text{Bigm} \dots$ * CHARACTER
$\backslash\text{Bigr} \dots$ * CHARACTER
$\backslash\text{background} \{...\}$ * CONTENT
$\backslash\text{backgroundimage} \{.^1.\} \{.^2.\} \{.^3.\} \{.^4.\}$ 1 NUMBER 2 DIMENSION 3 DIMENSION 4 COMMAND
$\backslash\text{backgroundimagefill} \{.^1.\} \{.^2.\} \{.^3.\} \{.^4.\}$ 1 NUMBER 2 DIMENSION 3 DIMENSION 4 COMMAND
$\backslash\text{backgroundline} [.^1.] \{.^2.\}$ 1 COLOR 2 CONTENT
$\backslash\text{BACKGROUND} \{...\}$ * CONTENT instances: background
$\backslash\text{bar} \{...\}$ * CHARACTER
$\backslash\text{BAR} \{...\}$ * CONTENT instances: overbar underbar overstrike understrike overbars underbars overstrikes understrikes underrandom underrandoms underdash underdashes underdot underdots nobar hiddenbar
$\backslash\text{hiddenbar} \{...\}$ * CONTENT
$\backslash\text{nobar} \{...\}$ * CONTENT
$\backslash\text{overbar} \{...\}$ * CONTENT
$\backslash\text{overbars} \{...\}$ * CONTENT
$\backslash\text{overstrike} \{...\}$ * CONTENT

<code>\overstrikes {...}</code> *    CONTENT
<code>\underbar {...}</code> *    CONTENT
<code>\underbars {...}</code> *    CONTENT
<code>\underdash {...}</code> *    CONTENT
<code>\underdashes {...}</code> *    CONTENT
<code>\underdot {...}</code> *    CONTENT
<code>\underdots {...}</code> *    CONTENT
<code>\underrandom {...}</code> *    CONTENT
<code>\underrandoms {...}</code> *    CONTENT
<code>\understrike {...}</code> *    CONTENT
<code>\understrikes {...}</code> *    CONTENT
<code>\basegrid [...,...<sup>OP</sup>...,...]</code> *    nx            = NUMBER *    ny            = NUMBER *    dx            = NUMBER *    dy            = NUMBER *    factor        = NUMBER *    scale         = NUMBER *    xstep         = NUMBER *    ystep         = NUMBER *    offset        = DIMENSION *    xoffset       = DIMENSION *    yoffset       = DIMENSION *    align         = middle *    unit          = <u>cm</u> mm in pc pt bp *    style         = STYLE COMMAND *    color         = COLOR *    rulecolor     = COLOR *    rulethickness = DIMENSION
<code>\baselinebottom</code>
<code>\baselineleftbox {...}</code> *    CONTENT
<code>\baselinemiddlebox {...}</code> *    CONTENT

$\backslash\text{baselinerightbox}$ {...} *    CONTENT
$\backslash\text{bordermatrix}$ {...} *    CONTENT
$\backslash\text{bbox}$ {...} *    CONTENT
$\backslash\text{before split string}$ ... <sup>1</sup> \at ... <sup>2</sup> \to ... <sup>3</sup> 1    TEXT 2    TEXT 3    CSNAME
$\backslash\text{before test and split string}$ ... <sup>1</sup> \at ... <sup>2</sup> \to ... <sup>3</sup> 1    TEXT 2    TEXT 3    CSNAME
$\backslash\text{beginBLOCK}$ [... <sup>1</sup> ...] [... <sup>2</sup> ...] ... $\backslash\text{endBLOCK}$ 1    + - NAME            OPT            OPT 2    KEY = VALUE
$\backslash\text{beginhbox}$ ... $\backslash\text{endhbox}$
$\backslash\text{begin of shape box}$ ... $\backslash\text{end of shape box}$
$\backslash\text{begin vbox}$ ... $\backslash\text{end vbox}$
$\backslash\text{begin vtop}$ ... $\backslash\text{end vtop}$
$\backslash\text{beg strut}$ ... $\backslash\text{end strut}$
$\backslash\text{big}$ ... *    CHARACTER
$\backslash\text{bigbodyfont}$
$\backslash\text{bigg}$ ... *    CHARACTER
$\backslash\text{bigger}$
$\backslash\text{biggl}$ ... *    CHARACTER
$\backslash\text{biggm}$ ... *    CHARACTER
$\backslash\text{biggr}$ ... *    CHARACTER
$\backslash\text{bigl}$ ... *    CHARACTER
$\backslash\text{bigm}$ ... *    CHARACTER

<b>\bigr</b> ... * CHARACTER
<b>\bigskip</b>
<b>\bitmapimage</b> [..., <sup>1</sup> ...,...] {... <sup>2</sup> .} 1 color = rgb cmyk gray width = DIMENSION height = DIMENSION x = NUMBER y = NUMBER 2 NUMBER
<b>\blackrule</b> [..., <sup>*</sup> ...,...] * inherits: \setupblackrules
<b>\blackrules</b> [..., <sup>*</sup> ...,...] * inherits: \setupblackrules
<b>\blank</b> [..., <sup>*</sup> ...] * preference <sup>OPT</sup> samepage max force enable disable nowhite packed back overlay always weak strong default before inbetween after fixed flexible none small medium big line halfline quarterline formula white height depth standard NUMBER*small NUMBER*medium NUMBER*big NUMBER*line NUMBER*halfline NUMBER*quarterline NUMBER*formula NUMBER*white NUMBER*height NUMBER*depth category:NUMBER order:NUMBER penalty:NUMBER DIMENSION NAME
<b>\blap</b> {...} * CONTENT
<b>\bleed</b> [..., <sup>1</sup> ...,...] {... <sup>2</sup> .} 1 inherits: \setupbleeding 2 CONTENT
<b>\bleedheight</b>
<b>\bleedwidth</b>
<b>\blockligatures</b> [..., <sup>*</sup> ...] * TEXT
<b>\blocksynctexfile</b> [..., <sup>*</sup> ...] * FILE
<b>\blockuservariable</b> {...} * KEY
<b>\bodyfontenvironmentlist</b>
<b>\bodyfontsize</b>
<b>\bold</b>
<b>\boldface</b>
<b>\bolditalic</b>
<b>\boldslanted</b>

<code>\bookmark [...]{...}</code> 1    SECTION LIST <sup>PT</sup> 2    TEXT
<code>\booleanmodevalue {...}</code> *    NAME
<code>\bordermatrix {...}</code> *    CONTENT
<code>\bottombox {...}</code> *    CONTENT
<code>\bottomleftbox {...}</code> *    CONTENT
<code>\bottomrightbox {...}</code> *    CONTENT
<code>\boxcursor</code>
<code>\boxmarker {...}{...}</code> 1    NAME 2    NUMBER
<code>\boxofsize \... ..<sup>1</sup> ..<sup>2</sup> ..<sup>3</sup>{...}</code> 1    CSNAME 2    DIMENSION 3    CONTENT
<code>\boxreference [...,<sup>1</sup>...] \...<sup>2</sup>{...<sup>3</sup>}</code> 1    REFERENCE 2    CSNAME 3    CONTENT
<code>\bpar ... \epar</code>
<code>\bpos {...}</code> *    NAME
<code>\breakhere</code>
<code>\breve {...}</code> *    CHARACTER
<code>\bTABLE [...,<sup>*</sup>...,...] ... \eTABLE</code> *    inherits: \setupTABLE
<code>\bTABLEbody [...,<sup>*</sup>...,...] ... \eTABLEbody</code> *    inherits: \setupTABLE
<code>\bTABLEfoot [...,<sup>*</sup>...,...] ... \eTABLEfoot</code> *    inherits: \setupTABLE
<code>\bTABLEhead [...,<sup>*</sup>...,...] ... \eTABLEhead</code> *    inherits: \setupTABLE

<code>\bTABLEnext [...,.*=...,...] ... \eTABLEnext</code> <code>* inherits: \setupTABLE</code>
<code>\bTC [...,.*=...,...] ... \eTC</code> <code>* inherits: \bTD</code>
<code>\bTD [...,.*=...,...] ... \eTD</code> <code>* nx = <sup>OPTIONAL</sup>NUMBER</code> <code>ny = NUMBER</code> <code>nc = NUMBER</code> <code>nr = NUMBER</code> <code>n = NUMBER</code> <code>m = NUMBER</code> <code>action = REFERENCE</code> <code>inherits: \setupTABLE</code>
<code>\bTDs [...*] ... \eTDs</code> <code>* NAME</code>
<code>\bTH [...,.*=...,...] ... \eTH</code> <code>* inherits: \bTD</code>
<code>\bTN [...,.*=...,...] ... \eTN</code> <code>* inherits: \bTD</code>
<code>\bTR [...,.*=...,...] ... \eTR</code> <code>* inherits: \bTD</code>
<code>\bTRs [...*] ... \eTRs</code> <code>* NAME</code>
<code>\bTX [...,.*=...,...] ... \eTX</code> <code>* inherits: \bTD</code>
<code>\bTY [...,.*=...,...] ... \eTY</code> <code>* inherits: \setupTABLE</code>
<code>\btxabbreviatedjournal {...*}</code> <code>* NAME</code>
<code>\btxaddjournal [...<sup>1</sup>] [...<sup>2</sup>]</code> <code>1 NAME</code> <code>2 NAME</code>
<code>\btxalwayscitation [...,.*<sup>1</sup>=...,...] [...<sup>2</sup>]</code> <code>1 reference = REFERENCE <sup>OPTIONAL</sup></code> <code>alternative = default category entry short page num textnum year index tag keywords author authoryears authornum</code> <code>authoryear</code> <code>before = COMMAND</code> <code>after = COMMAND</code> <code>left = COMMAND</code> <code>right = COMMAND</code> <code>inherits: \setupbtx</code> <code>2 REFERENCE</code>
<code>\btxalwayscitation [...<sup>1</sup>] [...<sup>2</sup>]</code> <code>1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear</code> <code>2 REFERENCE</code>



```

\btخالwayscitation [...,..1...,...] [...,..2...,...]
1  reference      = REFERENCE
   alternative    = default category entry short page num textnum year index tag keywords author authoryears authornum
                     authoryear
   before        = COMMAND
   after         = COMMAND
   left          = COMMAND
   right         = COMMAND
   inherits: \setupbtx
2  KEY = VALUE

```

```

\btخالauthorfield {...}
*  initials firstnames vons surnames juniors

```

```

\btخالdetail {...}
*  address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language
   month monthfiled nationality note number one two organization pages publisher school series title type volume year
   yearfiled NAME

```

```

\btخالdirect {...}
*  address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language
   month monthfiled nationality note number one two organization pages publisher school series title type volume year
   yearfiled NAME

```

```

\btخالdoif {...} {...}
1  address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language
   month monthfiled nationality note number one two organization pages publisher school series title type volume year
   yearfiled NAME
2  TRUE

```

```

\btخالdoifcombiinlistelse {...} {...} {...} {...}
1  NAME
2  NAME
3  TRUE
4  FALSE

```

```

\btخالdoifelse {...} {...} {...}
1  address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language
   month monthfiled nationality note number one two organization pages publisher school series title type volume year
   yearfiled NAME
2  TRUE
3  FALSE

```

```

\btخالdoifelsecombiinlist {...} {...} {...} {...}
1  NAME
2  NAME
3  TRUE
4  FALSE

```

```

\btخالdoifelsesameasprevious {...} {...} {...}
1  address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language
   month monthfiled nationality note number one two organization pages publisher school series title type volume year
   yearfiled NAME
2  TRUE
3  FALSE

```

```

\btخالdoifelsesameaspreviouschecked {...} {...} {...} {...}
1  always doublesided
2  address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language
   month monthfiled nationality note number one two organization pages publisher school series title type volume year
   yearfiled NAME
3  TRUE
4  FALSE

```

```

\btخالdoifelseuservariable {...} {...} {...}
1  KEY
2  TRUE
3  FALSE

```

`\btxdoifnot {.1.} {.2.}`

1 address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME  
2 TRUE

`\btxdoifsameaspreviouscheckedelse {.1.} {.2.} {.3.} {.4.}`

1 always doublesided  
2 address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME  
3 TRUE  
4 FALSE

`\btxdoifsameaspreviouselse {.1.} {.2.} {.3.}`

1 address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME  
2 TRUE  
3 FALSE

`\btxdoifuservariableelse {.1.} {.2.} {.3.}`

1 KEY  
2 TRUE  
3 FALSE

`\btxexpandedjournal {.*.}`

\* NAME

`\btxfield {.*.}`

\* address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME

`\btxfieldname {.*.}`

\* address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME

`\btxfieldtype {.*.}`

\* address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME

`\btxfirstofrange {.*.}`

\* volume pages

`\btxflush {.*.}`

\* address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language  
month monthfiled nationality note number one two organization pages publisher school series title type volume year  
yearfiled NAME

`\btxflushauthor [.1.] {.2.}`

1 num normal normalsh<sup>OFF</sup>t inverted invertedshort  
2 author editor

`\btxflushauthorinverted {.*.}`

\* author editor

`\btxflushauthorinvertedshort {.*.}`

\* author editor

`\btxflushauthorname {.*.}`

\* author editor

\btxflushauthornormal {...} * author editor
\btxflushauthornormalshort {...} * author editor
\btxflushsuffix
\btxfoundname {...} * address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME
\btxfoundtype {...} * address assignee author booktitle chapter day dayfiled edition editor howpublished institution journal language month monthfiled nationality note number one two organization pages publisher school series title type volume year yearfiled NAME
\btxhiddencitation [...] * REFERENCE
\btxhybridcite [... <sup>1</sup> ... <sup>2</sup> ...] [...] 1 reference = REFERENCE <sup>OPT</sup> alternative = default category entry short page num textnum year index tag keywords author authoryears authornum authoryear before = COMMAND after = COMMAND left = COMMAND right = COMMAND inherits: \setupbtx 2 REFERENCE
\btxhybridcite [... <sup>1</sup> ...] [... <sup>2</sup> ...] 1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear 2 REFERENCE
\btxhybridcite {...} * REFERENCE
\btxhybridcite [... <sup>1</sup> ... <sup>2</sup> ...] [... <sup>2</sup> ... <sup>1</sup> ...] 1 reference = REFERENCE alternative = default category entry short page num textnum year index tag keywords author authoryears authornum authoryear before = COMMAND after = COMMAND left = COMMAND right = COMMAND inherits: \setupbtx 2 KEY = VALUE
\btxlistcitation [... <sup>1</sup> ... <sup>2</sup> ...] [... <sup>2</sup> ...] 1 reference = REFERENCE <sup>OPT</sup> alternative = default category entry short page num textnum year index tag keywords author authoryears authornum authoryear before = COMMAND after = COMMAND left = COMMAND right = COMMAND inherits: \setupbtx 2 REFERENCE
\btxlistcitation [... <sup>1</sup> ...] [... <sup>2</sup> ...] 1 default category entry short page num textnum year index tag keywords author authoryears authornum authoryear 2 REFERENCE

`\btxlistcitation [...,\stackrel{1}{=}\dots][...,\stackrel{2}{=}\dots]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
    authoryear
  before = COMMAND
  after = COMMAND
  left = COMMAND
  right = COMMAND
  inherits: \setupbtx
2 KEY = VALUE
```

`\btxloadjournalist [...]`

`* FILE`

`\btxoneorrange {...} {...} {...}`

```
1 volume pages
2 TRUE
3 FALSE
```

`\btxremapauthor [...]\stackrel{1}{.} [...]\stackrel{2}{.}`

```
1 TEXT
2 TEXT
```

`\btxsavejournalist [...]`

`* FILE`

`\btxsetup {...}`

`* NAME`

`\btxsingularorplural {...}\stackrel{1}{.} {...}\stackrel{2}{.} {...}\stackrel{3}{.}`

```
1 editor producer director
2 TRUE
3 FALSE
```

`\btxsingularplural {...}\stackrel{1}{.} {...}\stackrel{2}{.} {...}\stackrel{3}{.}`

```
1 editor producer director
2 TRUE
3 FALSE
```

`\btxttextcitation [...,\stackrel{1}{=}\dots][...]\stackrel{2}{.}`

```
1 reference = REFERENCEOPT
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
    authoryear
  before = COMMAND
  after = COMMAND
  left = COMMAND
  right = COMMAND
  inherits: \setupbtx
2 REFERENCE
```

`\btxttextcitation [...]\stackrel{1}{.} [...]\stackrel{2}{.}`

```
1 default category entryOPT short page num textnum year index tag keywords author authoryears authornum authoryear
2 REFERENCE
```

`\btxttextcitation [...,\stackrel{1}{=}\dots][...,\stackrel{2}{=}\dots]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
    authoryear
  before = COMMAND
  after = COMMAND
  left = COMMAND
  right = COMMAND
  inherits: \setupbtx
2 KEY = VALUE
```

$\backslash$ buildmathaccent {...} {...} 1 CHARACTER 2 CHARACTER
$\backslash$ buildtextaccent {...} {...} 1 CHARACTER 2 CHARACTER
$\backslash$ buildtextbottomcomma {...} * CHARACTER
$\backslash$ buildtextbottomdot {...} * CHARACTER
$\backslash$ buildtextcedilla {...} * CHARACTER
$\backslash$ buildtextgrave {...} * CHARACTER
$\backslash$ buildtextmacron {...} * CHARACTER
$\backslash$ buildtextognek {...} * CHARACTER
$\backslash$ button [... <sup>1</sup> ... <sup>2</sup> ...] {...} [...] 1 inherits: $\setupbutton$ 2 TEXT 3 REFERENCE
$\backslash$ BUTTON [... <sup>1</sup> ... <sup>2</sup> ...] {...} [...] 1 inherits: $\setupbutton$ 2 TEXT 3 REFERENCE instances: button
$\backslash$ Caps {...} * TEXT
$\backslash$ Character {...} * NUMBER
$\backslash$ Characters {...} * NUMBER
$\backslash$ CONTEXT
$\backslash$ ConTeXt
$\backslash$ Context
$\backslash$ ConvertConstantAfter \... <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> 1 CSNAME 2 TEXT 3 TEXT

$\backslash\text{ConvertToConstant} \mathrel{\backslash}^{1..} \{...\} \{...\}$ 1 CSNAME 2 TEXT 3 TEXT
$\backslash\text{calligraphic}$
$\backslash\text{camel} \{...\}$ * TEXT
$\backslash\text{cap} \{...\}$ * TEXT
$\backslash\text{capital} \{...\}$ * TEXT
$\backslash\text{catcodetablename}$
$\backslash\text{cbox} \mathrel{\backslash}^{1..} \{...\}$ 1 TEXT <small>OPT</small> 2 CONTENT
$\backslash\text{centeraligned} \{...\}$ * CONTENT
$\backslash\text{centerbox} \mathrel{\backslash}^{1..} \{...\}$ 1 TEXT <small>OPT</small> 2 CONTENT
$\backslash\text{centeredbox} \mathrel{\backslash}^{1..} \{...\}$ 1 TEXT <small>OPT</small> 2 CONTENT
$\backslash\text{centeredlastline}$
$\backslash\text{centerednextbox} \mathrel{\backslash}^{1..} \{...\}$ 1 TEXT <small>OPT</small> 2 CONTENT
$\backslash\text{centerline} \{...\}$ * CONTENT
$\backslash\text{cfrac} [\mathrel{\backslash}^{1..}] \{...\} \{...\}$ 1 l c r l <sup>P</sup> l <sup>c</sup> l <sup>r</sup> c <sup>l</sup> c <sup>c</sup> c <sup>r</sup> r <sup>l</sup> r <sup>c</sup> r <sup>r</sup> 2 CONTENT 3 CONTENT
$\backslash\text{character} \{...\}$ * NUMBER
$\backslash\text{CHARACTERKERNING} [\mathrel{\backslash}^{1..}] \{...\}$ 1 NUMBER <small>OPT</small> 2 TEXT
$\backslash\text{characters} \{...\}$ * NUMBER
$\backslash\text{chardescription} \{...\}$ * NUMBER

<code>\charwidthlanguage</code>
<code>\check {...}</code> * CHARACTER
<code>\checkcharacteralign {...}</code> * CONTENT
<code>\checkedblank [...,*,...]</code> * inherits: \blank
<code>\checkedchar {...} {...}</code> 1 NUMBER 2 CHARACTER
<code>\checkedfiller {...}</code> * sym symbol rule width space NAME COMMAND
<code>\checkedstrippedcsname \*...</code> * CSNAME
<code>\checkedstrippedcsname ...</code> * TEXT
<code>\checkinjector [...]</code> * NAME
<code>\checknextindentation [...]</code> * yes no auto
<code>\checknextinjector [...]</code> * NAME
<code>\checkpage [...] [...,...<sup>2</sup>...,...]</code> 1 NAME <small>OPT</small> 2 inherits: \setuppagechecker
<code>\checkparameters [...]</code> * TEXT
<code>\checkpreviousinjector [...]</code> * NAME
<code>\checksoundtrack {...}</code> * NAME
<code>\checktwopassdata {...}</code> * NAME
<code>\checkvariables [...] [...,...<sup>2</sup>...,...]</code> 1 NAME 2 set = COMMAND reset = COMMAND KEY = VALUE
<code>\chem {...} {...} {...}</code> 1 TEXT 2 TEXT 3 TEXT

<pre> \chemical [...] [...] [...] 1  NAME          OPT          OPT 2  TEXT 3  TEXT </pre>
<pre> \chemicalbottext {...} *  TEXT </pre>
<pre> \chemicalmidtext {...} *  TEXT </pre>
<pre> \chemicalsymbol [...] *  NAME </pre>
<pre> \chemicaltext {...} *  TEXT </pre>
<pre> \chemicaltoptext {...} *  TEXT </pre>
<pre> \chineseallnumerals {...} *  NUMBER </pre>
<pre> \chinesecapnumerals {...} *  NUMBER </pre>
<pre> \chinesenumerals {...} *  NUMBER </pre>
<pre> \citation [...] [...] 1  reference      = REFERENCE     alternative    = default category entry short page num textnum year index tag keywords author authoryears authornum                         authoryear     before         = COMMAND     after          = COMMAND     left           = COMMAND     right          = COMMAND     inherits: \setupbtx 2  REFERENCE </pre>
<pre> \citation [...] [...] 1  default category entry short page num textnum year index tag keywords author authoryears authornum authoryear 2  REFERENCE </pre>
<pre> \citation {...} *  REFERENCE </pre>
<pre> \citation [...] [...] [...] 1  reference      = REFERENCE     alternative    = default category entry short page num textnum year index tag keywords author authoryears authornum                         authoryear     before         = COMMAND     after          = COMMAND     left           = COMMAND     right          = COMMAND     inherits: \setupbtx 2  KEY = VALUE </pre>



`\cite [...1...2...] [...]`

```
1 reference OPT= REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
               authoryear
  before      = COMMAND
  after       = COMMAND
  left        = COMMAND
  right       = COMMAND
  inherits: \setupbtx
2 REFERENCE
```

`\cite [1...] [...]`

```
1 defaultOPTcategory entry short page num textnum year index tag keywords author authoryears authornum authoryear
2 REFERENCE
```

`\cite {...}`

\* REFERENCE

`\cite [...1...2...] [...2...2...]`

```
1 reference = REFERENCE
  alternative = default category entry short page num textnum year index tag keywords author authoryears authornum
               authoryear
  before      = COMMAND
  after       = COMMAND
  left        = COMMAND
  right       = COMMAND
  inherits: \setupbtx
2 KEY = VALUE
```

`\clap {...}`

\* CONTENT

`\classfont {...} {...}`

```
1 NAME
2 FONT
```

`\cldcommand {...}`

\* COMMAND

`\cldcontext {...}`

\* COMMAND

`\cldloadfile {...}`

\* FILE

`\cldprocessfile {...}`

\* FILE

`\clip [...1...2...] {...}`

```
1 inherits: \OPTsetupclipping
2 CONTENT
```

`\clippedoverlayimage {...}`

\* FILE

`\clonefield [...1...] [...2...] [...3...] [...4...]`

```
1 NAME
2 NAME
3 NAME
4 NAME
```

`\collect {...}`

\* CONTENT

```
\collectedtext [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] {...} {...}
1 inherits: \setupcollectOPT
2 style = STYLE COMMAND
  color = COLOR
  inherits: \setupframed
3 TEXT
4 CONTENT
```

```
\collectexpanded {...}
* CONTENT
```

```
\color [...]\{...}
1 COLOR
2 CONTENT
```

```
\colorbar [...]*,...]
* COLOR
```

```
\colorcomponents {...}
* COLOR
```

```
\colored [...,\stackrel{1}{=},...] {...}
1 inherits: \definecolor
2 CONTENT
```

```
\colored [...]\{...}
1 COLOR
2 CONTENT
```

```
\coloronly [...]\{...}
1 COLOR
2 CONTENT
```

```
\colorvalue {...}
* COLOR
```

```
\column [...]*,...]
* inherits: \columnbreakOPT
```

```
\columnbreak [...]*,...]
* yes no preferenceOPT local force first last NUMBER NAME
```

```
\columnsetspanwidth {...}
* NUMBER
```

```
\combinepages [...]\{...}\stackrel{1}{=},...]\stackrel{2}{=},...]
1 FILE
2 alternative = a b c horizontal vertical
  n = NUMBER
  nx = NUMBER
  ny = NUMBER
  start = NUMBER
  stop = NUMBER
  distance = DIMENSION
  top = COMMAND
  bottom = COMMAND
  left = COMMAND
  right = COMMAND
  before = COMMAND
  after = COMMAND
  inbetween = COMMAND
  frame = on off
  background = foreground color NAME
  backgroundcolor = COLOR
```

\commalistelement
\commalistsentence [...] [ <sup>1</sup> ,...] [ <sup>2</sup> ,...] 1    TEXT                                 OPT 2    TEXT
\commalistsize
\COMMENT [... <sup>1</sup> ] [..., <sup>2</sup> ...,...] {... <sup>3</sup> } 1    TEXT                 OPT                 OPT 2    inherits: \setupcomment 3    TEXT instances: comment
\comment [... <sup>1</sup> ] [..., <sup>2</sup> ...,...] {... <sup>3</sup> } 1    TEXT                 OPT                 OPT 2    inherits: \setupcomment 3    TEXT
\comparecolorgroup [...] *    NAME
\comparedimension {... <sup>1</sup> } {... <sup>2</sup> } 1    DIMENSION 2    DIMENSION
\comparedimensioneps {... <sup>1</sup> } {... <sup>2</sup> } 1    DIMENSION 2    DIMENSION
\comparepalet [...] *    NAME
\completebt rendering [... <sup>1</sup> ] [..., <sup>2</sup> ...,...] 1    NAME                                 OPT                                 OPT 2    inherits: \setupbt rendering
\completeCOMBINEDLIST [..., <sup>*</sup> ...,...] *    inherits: \setupcombinedlist                 OPT instances: content
\completecontent [..., <sup>*</sup> ...,...] *    inherits: \setupcombinedlist                 OPT
\completelist [... <sup>1</sup> ] [..., <sup>2</sup> ...,...] 1    LIST                                         OPT 2    inherits: \setuplist
\completelistofFLOATS [..., <sup>*</sup> ...,...] *    inherits: \setuplist                                 OPT instances: chemicals figures tables intermezzi graphics
\completelistofchemicals [..., <sup>*</sup> ...,...] *    inherits: \setuplist                                         OPT
\completelistoffigures [..., <sup>*</sup> ...,...] *    inherits: \setuplist                                         OPT

$\backslash\text{completelistofgraphics}$ [...,.. <sup>*</sup> ...,..] * inherits: \setuplist <span style="float:right">OPT</span>
$\backslash\text{completelistofintermezzi}$ [...,.. <sup>*</sup> ...,..] * inherits: \setuplist <span style="float:right">OPT</span>
$\backslash\text{completelistoftables}$ [...,.. <sup>*</sup> ...,..] * inherits: \setuplist <span style="float:right">OPT</span>
$\backslash\text{completelistofpublications}$ [... <sup>1</sup> .] [...,.. <sup>2</sup> ...,..] 1 NAME <span style="float:right">OPT</span> <span style="float:right">OPT</span> 2 inherits: \setupbtxrendering
$\backslash\text{completelistofsorts}$ [... <sup>1</sup> .] [...,.. <sup>2</sup> ...,..] 1 SINGULAR <span style="float:right">OPT</span> 2 inherits: \setupsorting
$\backslash\text{completelistofSORTS}$ [...,.. <sup>*</sup> ...,..] * inherits: \setupsorting <span style="float:right">OPT</span> instances: logos
$\backslash\text{completelistoflogos}$ [...,.. <sup>*</sup> ...,..] * inherits: \setupsorting <span style="float:right">OPT</span>
$\backslash\text{completelistofsynonyms}$ [... <sup>1</sup> .] [...,.. <sup>2</sup> ...,..] 1 SINGULAR <span style="float:right">OPT</span> 2 inherits: \setupsynonyms
$\backslash\text{completelistofSYNONYMS}$ [...,.. <sup>*</sup> ...,..] * inherits: \setupsynonyms <span style="float:right">OPT</span> instances: abbreviations
$\backslash\text{completelistofabbreviations}$ [...,.. <sup>*</sup> ...,..] * inherits: \setupsynonyms <span style="float:right">OPT</span>
$\backslash\text{completepagenumber}$
$\backslash\text{completerefer}$ [... <sup>1</sup> .] [...,.. <sup>2</sup> ...,..] 1 NAME <span style="float:right">OPT</span> 2 inherits: \setupregister
$\backslash\text{completeREGISTER}$ [...,.. <sup>*</sup> ...,..] * inherits: \setupregister <span style="float:right">OPT</span> instances: index
$\backslash\text{completeindex}$ [...,.. <sup>*</sup> ...,..] * inherits: \setupregister <sup>PT</sup>
$\backslash\text{complexorsimple}$ \*.. * CSNAME
$\backslash\text{complexorsimpleempty}$ \*.. * CSNAME
$\backslash\text{complexorsimpleempty}$ \*.. * TEXT CSNAME

<code>\complexorsimple {...}</code> * TEXT CSNAME
<code>\component [...]</code> * FILE
<code>\component ...</code> * FILE
<code>\composedcollector {...}</code> * NAME
<code>\composedlayer {...}</code> * NAME
<code>\compresult</code>
<code>\constantdimen \...</code> * CSNAME
<code>\constantdimenargument \...</code> * CSNAME
<code>\constantemptyargument \...</code> * CSNAME
<code>\constantnumber \...</code> * CSNAME
<code>\constantnumberargument \...</code> * CSNAME
<code>\contentreference [...<sup>1</sup>,...] [...<sup>2</sup>,...<sup>2</sup>,...] {...<sup>3</sup>}</code> 1 REFERENCE 2 inherits: \setupframed 3 CONTENT
<code>\continuednumber {...}</code> * NUMBER
<code>\continueifinputfile {...}</code> * FILE
<code>\convertargument ...<sup>1</sup> \to ...<sup>2</sup></code> 1 TEXT 2 CSNAME
<code>\convertcommand \...<sup>1</sup> \to ...<sup>2</sup></code> 1 CSNAME 2 CSNAME
<code>\convertedcounter [...<sup>1</sup>] [...<sup>2</sup>,...<sup>2</sup>,...] OPT</code> 1 NAME 2 inherits: \setupcounter
<code>\convertedddimen {...<sup>1</sup>} {...<sup>2</sup>}</code> 1 DIMENSION 2 ex em pt in cm mm sp bp pc dd cc nc

$\backslash$ convertedsubcounter [...] <sup>1</sup> [...] <sup>2</sup> [...] <sup>3</sup> ... 1 NAME OPT OPT 2 NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all 3 inherits: \setupcounter
$\backslash$ convertmonth {...} * NUMBER
$\backslash$ convertnumber {...} <sup>1</sup> {...} <sup>2</sup> 1 empty default none month month:mnem character Character characters Characters a A Numbers word words Word Words n N romannumerals Romannumerals i I r R KR RK greek Greek g G abjadnumerals abjadnodotnumerals abjadnaivenumerals thainumerals devanagarinumerals gurmukhinumerals gujaratinnumerals tibetannumerals greeknumerals Greeknumerals arabicnumerals persiannumerals arabicexnumerals arabicdecimals persiandecimals koreannumerals koreanparentnumerals koreancirlenumerals kr kr-p kr-c chinesenumerals chinesecapnumerals chineseallnumerals cn cn-c cn-a sloveniannumerals slovenianNumerals spanishnumerals spanishNumerals mathgreek set_0 set_1 set_2 set_3 continued zero NAME 2 NUMBER
$\backslash$ convertvalue ... <sup>1</sup> \to ... <sup>2</sup> 1 NAME 2 CSNAME
$\backslash$ convertvboxtohbox
$\backslash$ copyboxfromcache {...} <sup>1</sup> {...} <sup>2</sup> ... <sup>3</sup> 1 NAME 2 NUMBER TEXT 3 CSNAME NUMBER
$\backslash$ copyfield [...] <sup>1</sup> [...] <sup>2</sup> 1 NAME 2 NAME
$\backslash$ copyLABELtext [...] <sup>1</sup> [...] <sup>2</sup> ... 1 LANGUAGE OPT 2 KEY = KEY instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
$\backslash$ copybtxlabeltext [...] <sup>1</sup> [...] <sup>2</sup> ... 1 LANGUAGE OPT 2 KEY = KEY
$\backslash$ copyheadtext [...] <sup>1</sup> [...] <sup>2</sup> ... 1 LANGUAGE OPT 2 KEY = KEY
$\backslash$ copylabeltext [...] <sup>1</sup> [...] <sup>2</sup> ... 1 LANGUAGE OPT 2 KEY = KEY
$\backslash$ copymathlabeltext [...] <sup>1</sup> [...] <sup>2</sup> ... 1 LANGUAGE OPT 2 KEY = KEY
$\backslash$ copyoperatortext [...] <sup>1</sup> [...] <sup>2</sup> ... 1 LANGUAGE OPT 2 KEY = KEY
$\backslash$ copyprefixtext [...] <sup>1</sup> [...] <sup>2</sup> ... 1 LANGUAGE OPT 2 KEY = KEY

$\backslash\text{copysuffixtext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>2</sup> ...] 1 LANGUAGE OPT 2 KEY = KEY
$\backslash\text{copytaglabeltext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>2</sup> ...] 1 LANGUAGE OPT 2 KEY = KEY
$\backslash\text{copyunittext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>2</sup> ...] 1 LANGUAGE OPT 2 KEY = KEY
$\backslash\text{coppages}$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>2</sup> ...] <sup>3</sup> [ <sup>3</sup> ... <sup>3</sup> ...] 1 FILE OPT OPT 2 marking = on off offset = DIMENSION n = NUMBER 3 inherits: \setupexternalfigure
$\backslash\text{copyparameters}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] [ <sup>3</sup> ...] 1 TEXT 2 TEXT 3 KEY
$\backslash\text{copyposition}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 NAME
$\backslash\text{copysetups}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME 2 NAME
$\backslash\text{correctwhitespace}$ { <sup>*</sup> ...} * CONTENT
$\backslash\text{countersubs}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME OPT 2 NUMBER
$\backslash\text{counttoken}$ <sup>1</sup> ... \in <sup>2</sup> ... \to <sup>3</sup> ... 1 TEXT 2 TEXT 3 CSNAME
$\backslash\text{counttokens}$ <sup>1</sup> ... \to <sup>2</sup> ... 1 TEXT 2 CSNAME
$\backslash\text{cramped}$ { <sup>*</sup> ...} * CONTENT
$\backslash\text{crampedclap}$ { <sup>*</sup> ...} * CONTENT
$\backslash\text{crampedllap}$ { <sup>*</sup> ...} * CONTENT
$\backslash\text{crampedrlap}$ { <sup>*</sup> ...} * CONTENT
$\backslash\text{crlf}$

<code>\crlfplaceholder</code>
<code>\ctop <sup>1</sup>... {<sup>2</sup>...}</code> 1    TEXT <sup>OPT</sup> 2    CONTENT
<code>\ctxcommand {...}</code> *    COMMAND
<code>\ctxdirectcommand {...}</code> *    COMMAND
<code>\ctxdirectlua {...}</code> *    COMMAND
<code>\ctxfunction {...}</code> *    NAME
<code>\CTXFUNCTIONDEFINITION</code>
<code>\CTXFUNCTION</code>
<code>\ctxlatecommand {...}</code> *    COMMAND
<code>\ctxlatelua {...}</code> *    COMMAND
<code>\ctxloadluafile {...}</code> *    FILE
<code>\ctxlua {...}</code> *    COMMAND
<code>\ctxluabuffer [...]</code> *    BUFFER <sup>OPT</sup>
<code>\ctxluacode {...}</code> *    COMMAND
<code>\ctxreport {...}</code> *    COMMAND
<code>\ctxsprint {...}</code> *    COMMAND
<code>\currentassignmentlistkey</code>
<code>\currentassignmentlistvalue</code>
<code>\currentbtxuservariable {...}</code> *    KEY
<code>\currentcommalistitem</code>
<code>\currentcomponent</code>



\currentdate [...] * year month day week <sup>OPT</sup> day y yy Y m mm M d dd D w W space \_ month:mnem m:mnem d:ord day:ord dd:ord D:ord TEXT referral day:+ day:++ d:+ d:++ dd:+ dd:++ D:+ D:++ month:jalali m:jalali jalali:to jalali:from
\currentenvironment
\currentfeaturetest
\currenttheadnumber
\currentinterface
\currentLABEL [...] {...} 1 REFERENCE OPT OPT 2 TEXT
\currentlanguage
\currentlistentrydestinationattribute
\currentlistentrylimitedtext {...} * TEXT
\currentlistentrynumber
\currentlistentrypagenumber
\currentlistentryreferenceattribute {...} * number text pagenumber all
\currentlistentrytitle
\currentlistentrytitlerendered
\currentlistsymbol
\currentmainlanguage
\currentmessagetext
\currentmoduleparameter {...} * KEY
\currentoutputstream
\currentproduct
\currentproject
\currentregime
\currentregisterpageuserdata {...} * KEY

<code>\currentresponses</code>
<code>\currenttime [...*,...]</code> *    h m TEXT                      OPT
<code>\currentvalue</code>
<code>\currentxtablecolumn</code>
<code>\currentxtablerow</code>
<code>\d {...}</code> *    CHARACTER
<code>\datasetvariable {...} {...} {...}</code> 1    NAME 2    NAME NUMBER 3    KEY realpage
<code>\date [...,*<sup>1</sup>...,...]</code> <code>[...,*<sup>2</sup>...,...]</code> 1    d = NUMBER                      OPT m = NUMBER y = NUMBER 2    inherits: \currentdate
<code>\dayoftheweek {...} {...} {...}</code> 1    NUMBER 2    NUMBER 3    NUMBER
<code>\dayspermonth {...} {...}</code> 1    NUMBER 2    NUMBER
<code>\dddots {...}</code> *    CHARACTER
<code>\ddots {...}</code> *    CHARACTER
<code>\decrement \*</code> *    CSNAME
<code>\decrementcounter [...]</code> <code>[...]</code> 1    NAME                              OPT 2    NUMBER
<code>\decrementedcounter [...]</code> *    NAME
<code>\decrementpagenumber</code>
<code>\decrementsubpagenumber</code>
<code>\decrementvalue {...}</code> *    NAME

<code>\decrement (...,*...)</code> * CSNAME NUMBER
<code>\defaultinterface</code>
<code>\defaultobjectpage</code>
<code>\defaultobjectreference</code>
<code>\defcatcodecommand \<sup>1</sup>... \<sup>2</sup>... {\<sup>3</sup>...}</code> 1 CSNAME 2 CHARACTER NUMBER 3 COMMAND
<code>\defconvertedargument \<sup>1</sup>... {\<sup>2</sup>...}</code> 1 CSNAME 2 TEXT
<code>\defconvertedcommand \<sup>1</sup>... \<sup>2</sup>...</code> 1 CSNAME 2 CSNAME
<code>\defconvertedvalue \<sup>1</sup>... {\<sup>2</sup>...}</code> 1 CSNAME 2 NAME
<code>\define [<sup>1</sup>...] \<sup>2</sup>... {\<sup>3</sup>...}</code> 1 NUMBER <small>OPT</small> 2 CSNAME 3 CONTENT
<code>\defineaccent \<sup>1</sup>... \<sup>2</sup>... \<sup>3</sup>...</code> 1 CHARACTER 2 CHARACTER 3 CHARACTER
<code>\defineactivecharacter \<sup>1</sup>... {\<sup>2</sup>...}</code> 1 CHARACTER 2 COMMAND
<code>\definealternativestyle [...,<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]</code> 1 NAME 2 COMMAND 3 COMMAND
<code>\defineanchor [<sup>1</sup>...] [<sup>2</sup>...] [...,\<sup>3</sup>...,...] [...,\<sup>4</sup>...,...]</code> 1 NAME 2 NAME 3 inherits: \setupplayer <small>OPT</small> 4 inherits: \setupplayerinherits: \setupframed <small>OPT</small>
<code>\defineattachment [<sup>1</sup>...] [<sup>2</sup>...] [...,\<sup>3</sup>...,...]</code> 1 NAME <small>OPT</small> 2 NAME <small>OPT</small> 3 inherits: \setupattachment
<code>\defineattribute [<sup>1</sup>...] [...,\<sup>2</sup>...,...]</code> 1 NAME <small>OPT</small> 2 <u>local</u> <u>global</u> <u>public</u> <u>private</u> <u>pickup</u>

```
\definebackground [...1] [...2] [...,3...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupbackground
```

```
\definebar [...1] [...2] [...,3...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupbar
```

```
\defineblock [...1] [...2] [...,3...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupblock
```

```
\definebodyfont [...,1...] [...,2...] [...,3...] [...,4...]
1 NAME default OPT OPT
2 NAME DIMENSION
3 rm ss tt hw cg
4 tf = FILE
bf = FILE
it = FILE
sl = FILE
bi = FILE
bs = FILE
sc = FILE
mr = FILE
mrlr = FILE
mrrl = FILE
mb = FILE
mblr = FILE
mbrl = FILE
```

```
\definebodyfontenvironment [...1] [...2] [...,3...,...]
1 NAME OPT OPT
2 default DIMENSION
3 big = DIMENSION NUMBER
small = DIMENSION NUMBER
a = DIMENSION NUMBER
b = DIMENSION NUMBER
c = DIMENSION NUMBER
d = DIMENSION NUMBER
text = DIMENSION NUMBER
x = DIMENSION NUMBER
xx = DIMENSION NUMBER
script = DIMENSION NUMBER
scriptscript = DIMENSION NUMBER
interlinespace = DIMENSION
em = slanted italic STYLE COMMAND
* = NUMBER
```

```
\definebodyfontswitch [...1] [...,2...]
1 NAME
2 inherits: \setupbodyfont
```

```
\definebodyfont [...,1...] [...,2...] [...,3...] [...4]
1 NAME default OPT OPT
2 NAME DIMENSION
3 rm ss tt hw cg
4 NAME
```

```
\definebreakpoint [...1] [...2] [...,3...,...]
1 NAME OPT
2 CHARACTER
3 type = 1 2 3 4 5
nleft = NUMBER
nright = NUMBER
left = COMMAND
middle = COMMAND
right = COMMAND
range = yes no
language = LANGUAGE
```

<pre> \definebreakpoints [...] *   NAME </pre>
<pre> \definebtx [...<sup>1</sup>] [...<sup>2</sup>] [...,...<sup>3</sup>...,...] 1   NAME                OPT                OPT 2   NAME 3   inherits: \setupbtx </pre>
<pre> \definebtxdataset [...<sup>1</sup>] [...<sup>2</sup>] [...,...<sup>3</sup>...,...] 1   NAME                OPT                OPT 2   NAME 3   inherits: \setupbtxdataset </pre>
<pre> \definebtxregister [...<sup>1</sup>] [...<sup>2</sup>] [...,...<sup>3</sup>...,...] 1   NAME                OPT                OPT 2   NAME 3   inherits: \setupbtxregister </pre>
<pre> \definebtxrendering [...<sup>1</sup>] [...<sup>2</sup>] [...,...<sup>3</sup>...,...] 1   NAME                OPT                OPT 2   NAME 3   inherits: \setupbtxrendering </pre>
<pre> \definebuffer [...<sup>1</sup>] [...<sup>2</sup>] [...,...<sup>3</sup>...,...] 1   NAME                OPT                OPT 2   BUFFER 3   inherits: \setupbuffer </pre>
<pre> \definebutton [...<sup>1</sup>] [...<sup>2</sup>] [...,...<sup>3</sup>...,...] 1   NAME                OPT                OPT 2   NAME 3   inherits: \setupbutton </pre>
<pre> \definecapitals [...<sup>1</sup>] [...<sup>2</sup>] [...,...<sup>3</sup>...,...] 1   NAME                OPT                OPT 2   NAME 3   inherits: \setupcapitals </pre>
<pre> \definecharacter ...<sup>1</sup> ...<sup>2</sup> 1   CHARACTER 2   NUMBER </pre>
<pre> \definecharacterkerning [...<sup>1</sup>] [...<sup>2</sup>] [...,...<sup>3</sup>...,...] 1   NAME                OPT                OPT 2   NAME 3   inherits: \setupcharacterkerning </pre>
<pre> \definecharacterspacing [...<sup>1</sup>] *   NAME </pre>
<pre> \definechemical [...<sup>1</sup>] {...<sup>2</sup>} 1   NAME 2   CONTENT </pre>
<pre> \definechemicals [...<sup>1</sup>] [...<sup>2</sup>] [...,...<sup>3</sup>...,...] 1   NAME                OPT                OPT 2   NAME 3   inherits: \setupchemical </pre>
<pre> \definechemicalsymbol [...<sup>1</sup>] [...<sup>2</sup>] 1   NAME 2   TEXT </pre>

**\definecollector** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \setupcollector

**\definecolor** [<sup>1</sup>] [<sup>2</sup>...,...]

1 NAME  
2 r = NUMBER  
g = NUMBER  
b = NUMBER  
c = NUMBER  
m = NUMBER  
y = NUMBER  
k = NUMBER  
h = NUMBER  
s = NUMBER  
v = NUMBER  
x = NUMBER  
a = NUMBER none normal multiply screen overlay softlight hardlight colordodge colorburn darken lighten difference  
exclusion hue saturation color luminosity  
t = NUMBER

**\definecolorgroup** [<sup>1</sup>] [<sup>2</sup>...] [x:y:z,...]

1 NAME  
2 gray rgb cmyk spot  
3 TRIPLET

**\definecolor** [<sup>1</sup>] [<sup>2</sup>...]

1 NAME  
2 COLOR

**\definecolumnbreak** [<sup>1</sup>] [<sup>2</sup>...,...]

1 NAME  
2 yes no preference local force first last NUMBER

**\definecolumnset** [<sup>1</sup>] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \setupcolumnset

**\definecolumnsetarea** [<sup>1</sup>] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \setupcolumnsetarea

**\definecolumnsetspan** [<sup>1</sup>] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \setupcolumnsetspan

**\definecombination** [<sup>1</sup>] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \setupcombination

**\definecombinedlist** [<sup>1</sup>] [<sup>2</sup>...,...] [<sup>3</sup>...,...]

1 NAME  
2 LIST  
3 inherits: \setupcombinedlist

**\definecommand** <sup>1</sup>... <sup>2</sup>...

1 CHARACTER  
2 COMMAND

```
\definecomment [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcomment
```

```
\definecomplexorsimple \*...
* CSNAME
```

```
\definecomplexorsimpleempty \*...
* CSNAME
```

```
\definecomplexorsimpleempty {...}
* TEXT CSNAME
```

```
\definecomplexorsimple {...}
* TEXT CSNAME
```

```
\defineconversion [...] [...] [...]
1 LANGUAGE OPT
2 NAME
3 CSNAME
```

```
\defineconversionset [...] [...] [...]
1 NAME SECTIONBLOCK:NAME OPT
2 NAME PROCESSOR->NAME
3 NAME PROCESSOR->NAME
```

```
\defineconversion [...] [...] [...]
1 LANGUAGE OPT
2 NAME
3 TEXT
```

```
\definecounter [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupcounter
```

```
\definedataset [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupdataset
```

```
\definedelimitedtext [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupdelimitedtext
```

```
\definedescription [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupdescription
```

```
\definedfont [...]
* FONT OPT
```

```
\defineeffect [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupeffect
```

```
\defineenumeration [...] [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupenumeration
```

```
\defineexpandable [...] \{}
1 NUMBER
2 CSNAME
3 CONTENT
```

```
\defineexternalfigure [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupexternalfigure
```

```
\definefacingfloat [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupfacingfloat
```

```
\definefallbackfamily [...] [...] [...] [...]
1 NAME
2 rm ss tt mm hw cg roman serif regular sansserif sans support teletype type mono handwritten calligraphic math
mathematics
3 FONT
4 rscale = NUMBER
designsize = default auto
goodies = FILE
range = NUMBER NAME
offset = NUMBER NAME
check = yes no
force = yes no
features = NAME
tf = TEXT
bf = TEXT
it = TEXT
sl = TEXT
bi = TEXT
bs = TEXT
sc = TEXT
```

```
\definefallbackfamily [...] [...] [...] [...]
1 NAME
2 rm ss tt mm hw cg roman serif regular sansserif sans support teletype type mono handwritten calligraphic math
mathematics
3 FONT
4 NAME
```

```
\definefield [...] [...] [...] [...]
1 NAME
2 radio sub text line push check signature
3 NAME
4 NAME
5 NAME
```

```
\definefieldbody [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupfieldbody
```

```
\definefieldbodyset [...] [...]
1 NAME
2 NAME
```

```
\definefieldcategory [...] [...] [...]
1 NAME
2 NAME
3 inherits: \setupfieldcategory
```



```
\definefieldstack [...]1 [...]2 [...]3 [...]
1 NAME
2 NAME
3 inherits: \setupfieldcategory
```

```
\definefiguresymbol [...]1 [...]2 [...]3 [...]
1 NAME
2 FILE NAME
3 inherits: \externalfigure
```

```
\definefileconstant {...}1 {...}2
1 NAME
2 NAME
```

```
\definefilefallback [...]1 [...]2 [...]
1 NAME
2 FILE
```

```
\definefilesynonym [...]1 [...]2
1 NAME
2 FILE
```

```
\definefiller [...]1 [...]2 [...]3 [...]
1 NAME
2 NAME
3 inherits: \setupfiller
```

```
\definefirstline [...]1 [...]2 [...]3 [...]
1 NAME
2 NAME
3 inherits: \setupfirstline
```

```
\definefittingpage [...]1 [...]2 [...]3 [...]
1 NAME
2 NAME
3 inherits: \setupfittingpage
```

```
\definefloat [...]1 [...]2 [...]3 [...]
1 SINGULAR
2 SINGULAR PLURAL
3 inherits: \setupfloat
instances: chemical figure table intermezzo graphic
```

```
\definefloat [...]1 [...]2 [...]3 [...]
1 SINGULAR
2 PLURAL
3 SINGULAR
instances: chemical figure table intermezzo graphic
```

```
\definefont [...]1 [...]2 [...]3 [...]
1 NAME
2 FONT
3 inherits: \setupinterlinespace
```

```
\definefontalternative [...]*
* NAME
```

```

\definefontfallback [...] [...] [...] [...] [...]
1 NAME
2 FONT NAME
3 NAME NUMBER
4 rscale = NUMBER
   force = yes no
   check = yes no
   offset = NUMBER NAME
   target = NUMBER NAME
   features = NAME
   factor = NUMBER
   method = lowercase uppercase

```

```

\definefontfamily [...] [...] [...] [...]
1 NAME
2 rm ss tt mm hw cg roman serif regular sansserif sans support teletype type mono handwritten calligraphic math
   mathematics
3 FONT
4 rscale = NUMBER
   designsize = default auto
   goodies = FILE
   features = NAME
   tf = TEXT
   bf = TEXT
   it = TEXT
   sl = TEXT
   bi = TEXT
   bs = TEXT
   sc = TEXT

```

```

\definefontfamilypreset [...] [...]
1 NAME
2 inherits: \definefontfamily

```

```

\definefontfamilypreset [...] [...]
1 NAME
2 NAME

```

```

\definefontfamily [...] [...] [...] [...]
1 NAME
2 rm ss tt mm hw cg roman serif regular sansserif sans support teletype type mono handwritten calligraphic math
   mathematics
3 FONT
4 NAME

```

```

\definefontfeature [...] [...] [...] [...] [...]
1  NAME
2  NAME
3  language      = NAME
    script       = NAME auto
    mode         = node base auto none
    liga         = yes no
    kern         = yes no
    extrakerns   = yes no
    tlig         = yes no
    trep         = yes no
    missing      = yes no
    dummies      = yes no
    analyze      = yes no
    unicoding    = yes no
    expansion    = NAME
    protrusion   = NAME
    nostackmath  = yes no
    realdimensions = yes no
    itlc         = yes no
    textitalics  = yes no
    mathitalics  = yes no
    slant        = NUMBER
    extend       = NUMBER
    dimensions   = NUMBER
    boundingbox   = yes no background frame empty COLOR
    compose      = yes no
    char-ligatures = yes no
    compat-ligatures = yes no
    goodies      = FILE
    extrafeatures = yes no
    featureset    = NAME
    colorscheme  = NAME
    postprocessor = NAME
    mathdimensions = NAME
    keepligatures = yes no auto
    devanagari    = yes no
    features      = yes no
    tcom          = yes no
    anum         = yes no
    mathsize     = yes no
    decomposehangul = yes no
    mathalternatives = yes no
    mathgaps     = yes no
    checkmarks   = yes no
    NAME         = yes no
    mathnolimitsmode = NUMBER
    blockligatures = yes no

```

```

\definefontfile [...] [...] [...] [...]
1  NAME
2  FILE
3  features      = NAME
    fallbacks    = NAME
    goodies      = NAME
    designsize   = auto default

```

```

\definefontsize [...]
*  NAME

```

```

\definefontsolution [...] [...] [...] [...]
1  NAME
2  NAME
3  inherits: \setupfontsolution

```

```

\definefontstyle [...] [...]
1  NAME
2  NAME

```

```

\definefontsynonym [...] [...] [...]...3...
1 NAME
2 FONT
3 features = NAME
   fallbacks = NAME
   goodies = NAME
   designsize = auto default

```

```

\definefont [...] [...] [...]
1 NAME
2 FONT
3 NAME

```

```

\defineformula [...] [...] [...]...3...
1 NAME
2 NAME
3 inherits: \setupformula

```

```

\defineformulaalternative [...] [...] [...]
1 NAME
2 CSNAME
3 CSNAME

```

```

\defineformulaframed [...] [...] [...]...3...
1 NAME
2 NAME
3 inherits: \setupformulaframed

```

```

\defineframed [...] [...] [...]...3...
1 NAME
2 NAME
3 inherits: \setupframed

```

```

\defineframedcontent [...] [...] [...]...3...
1 NAME
2 NAME
3 inherits: \setupframedcontent

```

```

\defineframedtable [...] [...]
1 NAME
2 NAME

```

```

\defineframedtext [...] [...] [...]...3...
1 NAME
2 NAME
3 inherits: \setupframedtext

```

```

\definefrozenfont [...] [...]
1 NAME
2 FONT

```

```

\defineglobalcolor [...] [...]...2...
1 NAME
2 inherits: \definecolor

```

```

\defineglobalcolor [...] [...]
1 NAME
2 COLOR

```

```

\definegraphicstylesynonym [...] [...]
1 NAME
2 NAME

```

**\definegridsnapping** [<sup>1</sup>...] [<sup>2</sup>...,...]

1 NAME  
2 local global noheight nodepth box max min none line halfline first last minheight maxheight mindepth maxdepth  
top bottom strut NUMBER minheight:NUMBER maxheight:NUMBER mindepth:NUMBER maxdepth:NUMBER box:NUMBER top:NUMBER  
bottom:NUMBER offset:NUMBER

**\definehbox** [<sup>1</sup>...] [<sup>2</sup>...]

1 NAME  
2 DIMENSION

**\definehead** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 SECTION  
3 inherits: \setuphead

**\defineheadalternative** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setupheadalternative

**\definehelp** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setuphelp

**\definehigh** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setuphigh

**\definehighlight** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setuphighlight

**\definehspace** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

1 NAME OPT  
2 NAME  
3 DIMENSION

**\definehyphenationfeatures** [<sup>1</sup>...] [<sup>2</sup>...,...]

1 NAME  
2 characters = TEXT  
hyphens = yes all TEXT  
joiners = yes all TEXT  
rightwords = NUMBER  
hyphenmin = NUMBER  
lefthyphenmin = NUMBER  
righthyphenmin = NUMBER  
lefthyphenchar = NUMBER  
righthyphenchar = NUMBER  
alternative = original tex hyphenate expanded traditional none  
rightedge = tex  
rightchars = word NUMBER

**\defineindentedtext** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setupindentedtext

**\defineindenting** [<sup>1</sup>...] [<sup>2</sup>...,...]

1 NAME  
2 [-+]small [-+]medium [-+]big none no not first next yes always never odd even normal reset toggle DIMENSION

```

\defineinitial [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupinitial

```

```

\defineinsertion [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupinsertion

```

```

\defineinteraction [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupinteraction

```

```

\defineinteractionbar [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupinteractionbar

```

```

\defineinteractionmenu [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupinteractionmenu

```

```

\defineinterfaceconstant {...} {...}
1 NAME
2 NAME

```

```

\defineinterfaceelement {...} {...}
1 NAME
2 NAME

```

```

\defineinterfacevariable {...} {...}
1 NAME
2 NAME

```

```

\defineinterlinespace [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupinterlinespace

```

```

\defineintermediatecolor [...] [...] [...] [...]
1 NAME OPT
2 COLOR NUMBER
3 a = NUMBER
t = NUMBER

```

```

\defineitemgroup [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupitemgroup

```

```

\defineitems [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupitems

```

```

\definelabel [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuplabel

```

**\definelabelclass** [<sup>1</sup>...] [<sup>2</sup>...]

1 NAME OPT  
2 NUMBER

**\definelayer** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setuplayer

**\definelayerpreset** [<sup>1</sup>...] [<sup>2</sup>...,...]

1 NAME  
2 inherits: \setuplayer

**\definelayerpreset** [<sup>1</sup>...] [<sup>2</sup>...]

1 NAME  
2 NAME

**\definelayout** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setuplayout

**\definelinefiller** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setuplinefiller

**\definelinenote** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setuplinenote

**\definelinenumbering** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setuplinenumbering

**\definelines** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setuplines

**\definelist** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 LIST  
3 inherits: \setuplist

**\definelistalternative** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setuplistalternative

**\definelistextra** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setuplistextra

**\definelow** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setuplow

```
\definelowhigh [1...] [2...] [3...,...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuplowhigh
```

```
\definelowmidhigh [1...] [2...] [3...,...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setuplowmidhigh
```

```
\defineMPinstance [1...] [2...] [3...,...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupMPinstance
```

```
\definemakeup [1...] [2...] [3...,...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmakeup
```

```
\definemarginblock [1...] [2...] [3...,...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmarginblock
```

```
\definemargindata [1...] [2...] [3...,...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmargindata
```

```
\definemarker [...]  
* NAME
```

```
\definemarking [1...] [2...] [3...,...,...]
1 NAME OPT OPT
2 MARK
3 inherits: \setupmarking
```

```
\definemathaccent 1... 2...
1 NAME
2 CHARACTER
```

```
\definemathalignment [1...] [2...] [3...,...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathalignment
```

```
\definemathcases [1...] [2...] [3...,...,...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathcases
```

```
\definemathcommand [1...] [2...] [3...] {4...}
1 NAME OPT OPT OPT
2 ord op bin rel open close punct alpha inner nothing limop noloop box
3 one two
4 COMMAND \...#1 \...#1#2
```

```
\definemathdouble [1...] [2...] [3...] [4...]
1 both vfenced NAME
2 NAME
3 NUMBER
4 NUMBER
```



```
\definemathdoubleextensible [...] [...] [...] [...]
1 both vfenced OPT
2 NAME
3 NUMBER
4 NUMBER
```

```
\definematheconomics [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmatheconomics
```

```
\definemathextensible [...] [...] [...]
1 reverse mathematics text chemistry
2 NAME
3 NUMBER
```

```
\definemathfence [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathfence
```

```
\definemathfraction [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathfraction
```

```
\definemathframed [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathframed
```

```
\definemathmatrix [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathmatrix
```

```
\definemathornament [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathornament
```

```
\definemathover [...] [...] [...]
1 top vfenced NAME
2 NAME
3 NUMBER
```

```
\definemathoverextensible [...] [...] [...]
1 top vfenced OPT
2 NAME
3 NUMBER
```

```
\definemathovertextextensible [...] [...] [...]
1 bothtext OPT
2 NAME
3 NUMBER
```

```
\definemathradical [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathradical
```

```
\definemathstackers [...] [...] [...] [...]
1 NAME OPT OPT
2 NAME
3 inherits: \setupmathstackers
```

<pre> \definemathstyle [...] [...] 1 NAME 2 display text script scriptscript cramped uncramped normal packed small big </pre>
<pre> \definemathtriplet [...] [...] [...] 1 NAME          OPT          OPT 2 NAME 3 TEXT </pre>
<pre> \definemathunder [...] [...] [...] 1 bottom vfenced NAME 2 NAME 3 NUMBER </pre>
<pre> \definemathunderextensible [...] [...] [...] 1 bottom vfenced          OPT 2 NAME 3 NUMBER </pre>
<pre> \definemathundertexttextensible [...] [...] [...] 1 bothtext          OPT 2 NAME 3 NUMBER </pre>
<pre> \definemathunstacked [...] [...] [...] 1 wide          OPT 2 NAME 3 NUMBER </pre>
<pre> \definemeasure [...] [...] 1 NAME 2 DIMENSION </pre>
<pre> \definemessageconstant {...} * NAME </pre>
<pre> \definemixedcolumns [...] [...] [...] [...] 1 NAME          OPT          OPT 2 NAME 3 inherits: \setupmixedcolumns </pre>
<pre> \definemode [...] [...] 1 NAME          OPT 2 yes <u>no</u> keep </pre>
<pre> \definemultitonecolor [...] [...] [...] [...] [...] 1 NAME 2 COLOR = NUMBER 3 inherits: \definecolor 4 inherits: \definespotcolor </pre>
<pre> \definenamecolor [...] [...] [...] 1 NAME 2 inherits: \definecolor </pre>
<pre> \definenamecolor [...] [...] 1 NAME 2 COLOR </pre>

`\definenamespace` [<sup>1</sup>...] [<sup>2</sup>...]

```
1 NAME
2 name = TEXT
  parent = TEXT
  style = yes no
  command = yes no list
  setup = yes no list
  set = yes no list
  frame = yes no
```

`\definennarrower` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1 NAME
2 NAME
3 inherits: \setupnarrower
```

`\definernote` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1 NAME
2 NAME
3 inherits: \setupnote
```

`\defineornament` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1 NAME
2 alternative = a b
  inherits: \setupcollector
3 style = STYLE COMMAND
  color = COLOR
  inherits: \setupframed
```

`\defineornament` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1 NAME
2 alternative = a b
  inherits: \setupplayer
3 inherits: \setupplayeredtext
```

`\defineoutputroutine` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1 NAME
2 NAME
3 inherits: \setupoutputroutine
```

`\defineoutputroutinecommand` [...,\*...]

```
* KEY
```

`\defineoverlay` [...,<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1 NAME
2 NAME
3 COMMAND
```

`\definepage` [<sup>1</sup>...] [<sup>2</sup>...]

```
1 NAME
2 REFERENCE
```

`\definepagebreak` [<sup>1</sup>...] [<sup>2</sup>...]

```
1 NAME
2 empty header footer dummy frame NUMBER +NUMBER default reset disable yes no makeup blank preference bigpreference
  left right even odd quadruple last lastpage start stop
```

`\definepagechecker` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1 NAME
2 NAME
3 inherits: \setuppagechecker
```

`\definepagecolumns` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

```
1 NAME
2 NAME
3 inherits: \setuppagecolumns
```

**\definepageinjection** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \setuppageinjection

**\definepageinjectionalternative** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \setuppageinjectionalternative

**\definepageshift** [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...]

1 NAME  
2 horizontal vertical  
3 DIMENSION

**\definepagestate** [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \setuppagestate

**\definepairedbox** [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \setuppairedbox

**\definepalet** [<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME  
2 NAME = COLOR

**\definepalet** [<sup>1</sup>...] [<sup>2</sup>...]

1 NAME  
2 NAME

**\definepapersize** [<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME  
2 width = DIMENSION  
height = DIMENSION  
top = COMMAND  
bottom = COMMAND  
left = COMMAND  
right = COMMAND  
distance = DIMENSION  
page = inherits: \setuppapersize  
paper = inherits: \setuppapersize

**\definepapersize** [<sup>1</sup>...] [...,<sup>2</sup>...,...] [<sup>3</sup>...,...]

1 NAME  
2 inherits: \setuppapersize  
3 inherits: \setuppapersize

**\defineparagraph** [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \setupparagraph

**\defineparagraphs** [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME  
2 NAME  
3 inherits: \setupparagraphs

**\defineparallel** [<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME  
2 NAME

<code>\defineparbuilder [...]</code> <code>*   NAME</code>
<code>\defineperiodkerning [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> <code>1   NAME</code> <code>2   NAME</code> <code>3   inherits: \setupperiodkerning</code>
<code>\defineplacement [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> <code>1   NAME</code> <code>2   NAME</code> <code>3   inherits: \setupplacement</code>
<code>\definepositioning [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> <code>1   NAME</code> <code>2   NAME</code> <code>3   inherits: \setuppositioning</code>
<code>\defineprefixset [...]<sup>1</sup> [...,...<sup>2</sup>...] [...]<sup>3</sup></code> <code>1   NAME SECTIONBLOCK:NAME</code> <code>2   SECTION</code> <code>3   SECTION</code>
<code>\defineprocesscolor [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> <code>1   NAME</code> <code>2   COLOR</code> <code>3   inherits: \definecolor</code>
<code>\defineprocessor [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> <code>1   NAME</code> <code>2   NAME</code> <code>3   inherits: \setupprocessor</code>
<code>\defineprofile [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> <code>1   NAME</code> <code>2   NAME</code> <code>3   inherits: \setupprofile</code>
<code>\defineprogram [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></code> <code>1   NAME</code> <code>2   TEXT</code> <code>3   TEXT</code>
<code>\definepushbutton [...]<sup>1</sup> [...,...<sup>2</sup>...,...]</code> <code>1   NAME</code> <code>2   inherits: \setupfieldcontentframed</code>
<code>\definepushsymbol [...]<sup>1</sup> [...]<sup>2</sup></code> <code>1   NAME</code> <code>2   n r d</code>
<code>\definereference [...]<sup>1</sup> [...,...<sup>2</sup>...]</code> <code>1   NAME</code> <code>2   REFERENCE</code>
<code>\definereferenceformat [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> <code>1   NAME</code> <code>2   NAME</code> <code>3   inherits: \setupreferenceformat</code>
<code>\defineregister [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]</code> <code>1   NAME</code> <code>2   NAME</code> <code>3   inherits: \setupregister</code>

**\definerenderingwindow** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setuprenderingwindow

**\defineresetset** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

1 NAME SECTIONBLOCK:NAME OPT  
2 NUMBER  
3 NUMBER

**\defineruby** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setupruby

**\definescale** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setupscale

**\definescript** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setupscrip

**\definesection** [...]

\* NAME

**\definesectionblock** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...]

1 NAME OPT  
2 NAME  
3 inherits: \setupsectionblock

**\definesectionlevels** [<sup>1</sup>...] [<sup>2</sup>...]

1 NAME  
2 SECTION

**\defineselector** [<sup>1</sup>...] [<sup>2</sup>...<sup>2</sup>...]

1 NAME OPT  
2 inherits: \setupselector

**\defineseparatorset** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

1 NAME SECTIONBLOCK:NAME OPT  
2 COMMAND PROCESSOR->COMMAND  
3 COMMAND PROCESSOR->COMMAND

**\defineshift** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setupshift

**\definesidebar** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sup>3</sup>...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setupsidebar

**\definesort** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] {<sup>4</sup>...}

1 yes no OPT  
2 SINGULAR  
3 NAME  
4 CONTENT

**\definesorting** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

1 SINGULAR OPT  
2 PLURAL  
3 none CSNAME

**\definespotcolor** [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME  
2 COLOR  
3 a = NUMBER none normal multiply screen overlay softlight hardlight colordodge colorburn darken lighten difference  
exclusion hue saturation color luminosity  
t = NUMBER  
e = TEXT  
p = NUMBER

**\definestartstop** [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setupstartstop

**\definestyle** [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setupstyle

**\definestyleinstance** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...]

1 NAME OPT OPT OPT  
2 rm ss tt mm hw cg  
3 tf bf it sl bi bs sc  
4 COMMAND

**\definesubfield** [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...]

1 NAME  
2 NAME  
3 NAME

**\definesubformula** [<sup>1</sup>...] [<sup>2</sup>...] [...,<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setupsubformula

**\definesymbol** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]

1 NAME OPT  
2 NAME  
3 COMMAND

**\definesynonym** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] {<sup>4</sup>...} {<sup>5</sup>...}

1 yes no OPT  
2 SINGULAR  
3 NAME  
4 TEXT  
5 CONTENT

**\definesynonyms** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...]

1 SINGULAR OPT OPT  
2 PLURAL  
3 CSNAME  
4 CSNAME

**\definesystemattribute** [<sup>1</sup>...] [...,<sup>2</sup>...]

1 NAME OPT  
2 local global public private pickup

**\definesystemconstant** {...}

\* NAME

<pre> \definesystemvariable {...} *   NAME </pre>
<pre> \defineTABLEsetup [...] [...<sup>2</sup>...,...] 1   NAME 2   inherits: \setupTABLE </pre>
<pre> \definetabletemplate [...] [...<sup>2</sup>. ] [...<sup>3</sup>] [...<sup>4</sup>] 1   NAME 2   TEMPLATE 3   NAME 4   NAME </pre>
<pre> \definetabulate [...] [...<sup>2</sup>] [...<sup>3</sup>./] 1   NAME 2   NAME 3   TEMPLATE </pre>
<pre> \definetabulation [...] [...<sup>2</sup>] [...<sup>3</sup>...,...] 1   NAME 2   NAME 3   inherits: \setuptabulation </pre>
<pre> \definetext [...] [...<sup>2</sup>] [...<sup>3</sup>] [...<sup>4</sup>] [...<sup>5</sup>] [...<sup>6</sup>] [...<sup>7</sup>] 1   NAME 2   top header text footer bottom 3   text margin edge 4   date pagenumber MARK TEXT COMMAND 5   date pagenumber MARK TEXT COMMAND 6   date pagenumber MARK TEXT COMMAND 7   date pagenumber MARK TEXT COMMAND </pre>
<pre> \definetextbackground [...] [...<sup>2</sup>] [...<sup>3</sup>...,...] 1   NAME 2   NAME 3   inherits: \setuptextbackground </pre>
<pre> \definetextflow [...] [...<sup>2</sup>] [...<sup>3</sup>...,...] 1   NAME 2   NAME 3   inherits: \setuptextflow </pre>
<pre> \definetextnote [...] [...<sup>2</sup>] [...<sup>3</sup>...,...] 1   NAME 2   NAME 3   inherits: \setuptextnote </pre>
<pre> \definetokenlist [...] *   NAME </pre>
<pre> \definetooltip [...] [...<sup>2</sup>] [...<sup>3</sup>...,...] 1   NAME 2   NAME 3   inherits: \setuptooltip </pre>
<pre> \definetransparency [...] [...<sup>2</sup>] 1   NAME 2   NUMBER </pre>
<pre> \definetransparency [...] [...<sup>2</sup>...,...] 1   NAME 2   a = NUMBER none normal multiply screen overlay softlight hardlight colordodge colorburn darken lighten difference         exclusion hue saturation color luminosity         t = NUMBER </pre>



**\definetransparency** [<sup>1</sup>...] [<sup>2</sup>...]

1 NAME  
2 NAME

**\definetwopasslist** {...}

\* NAME

**\definetype** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setuptype

**\definetypeface** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...] [<sup>6</sup>...,...]

1 NAME OPT OPT  
2 rm ss tt mm hw cg  
3 serif sans mono math handwriting calligraphy  
4 NAME  
5 default dtp  
6 rscale = auto NUMBER  
features = NAME  
fallbacks = NAME  
goodies = NAME  
designsize = auto default  
direction = both

**\definetypescriptprefix** [<sup>1</sup>...] [<sup>2</sup>...]

1 NAME  
2 TEXT

**\definetypescriptsynonym** [<sup>1</sup>...] [<sup>2</sup>...]

1 NAME  
2 TEXT

**\definetypesetting** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 TEXT  
3 inherits: \setupexternalfigure

**\definetytyping** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setuptyping

**\defineunit** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setupunit

**\defineuserdata** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setupuserdata

**\defineuserdataalternative** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setupuserdataalternative

**\defineviewerlayer** [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...]

1 NAME OPT OPT  
2 NAME  
3 inherits: \setupviewerlayer

$\backslash\text{definevspace}$ [ <sup>1</sup> ...] [ <sup>2</sup> ] [ <sup>3</sup> ] 1 NAME OPT 2 NAME 3 DIMENSION
$\backslash\text{definevspacing}$ [ <sup>1</sup> ] [ <sup>2</sup> ] 1 NAME 2 inherits: \vspacing
$\backslash\text{definevspacingamount}$ [ <sup>1</sup> ] [ <sup>2</sup> ] [ <sup>3</sup> ] 1 NAME OPT OPT 2 DIMENSION 3 DIMENSION
$\backslash\text{definetable}$ [ <sup>1</sup> ] [ <sup>2</sup> ] [ <sup>3</sup> ... <sup>3</sup> ...] 1 NAME OPT OPT 2 NAME 3 inherits: \setupxtable
$\backslash\text{delimited}$ [ <sup>1</sup> ] [ <sup>2</sup> ] { <sup>3</sup> } 1 NAME OPT 2 LANGUAGE 3 CONTENT
$\backslash\text{delimitedtext}$ [ <sup>1</sup> ] [ <sup>2</sup> ] { <sup>3</sup> } 1 NAME OPT 2 LANGUAGE 3 CONTENT
$\backslash\text{DELIMITEDTEXT}$ [ <sup>1</sup> ] { <sup>2</sup> } 1 LANGUAGE OPT 2 CONTENT instances: quotation quote blockquote speech aside
$\backslash\text{aside}$ [ <sup>1</sup> ] { <sup>2</sup> } 1 LANGUAGE <sup>PT</sup> 2 CONTENT
$\backslash\text{blockquote}$ [ <sup>1</sup> ] { <sup>2</sup> } 1 LANGUAGE OPT 2 CONTENT
$\backslash\text{quotation}$ [ <sup>1</sup> ] { <sup>2</sup> } 1 LANGUAGE OPT 2 CONTENT
$\backslash\text{quote}$ [ <sup>1</sup> ] { <sup>2</sup> } 1 LANGUAGE <sup>PT</sup> 2 CONTENT
$\backslash\text{speech}$ [ <sup>1</sup> ] { <sup>2</sup> } 1 LANGUAGE <sup>OPT</sup> 2 CONTENT
$\backslash\text{depthofstring}$ {*...} * TEXT
$\backslash\text{depthonlybox}$ {*...} * CONTENT

$\backslash\text{depthspanningtext}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ 1 TEXT 2 DIMENSION 3 FONT
$\backslash\text{depthstrut}$
$\backslash\text{DESCRIPTION}$ $[\ldots.^1.\ldots]$ $\{.^2.\}$ $\ldots.^3.\$ $\backslash\text{par}$ 1 REFERENCE OPT OPT 2 TEXT 3 CONTENT
$\backslash\text{determineheadnumber}$ $[\ldots.^*.]$ * SECTION
$\backslash\text{determinelistcharacteristics}$ $[\ldots.^1.\ldots]$ $[\ldots.^2.\ldots]$ 1 LIST OPT 2 inherits: $\backslash\text{setuplist}$
$\backslash\text{determinenoflines}$ $\{.^*.\}$ * CONTENT
$\backslash\text{determineregistercharacteristics}$ $[\ldots.^1.]$ $[\ldots.^2.\ldots]$ 1 NAME OPT 2 language = default DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn LANGUAGE method = default before after first last ch mm zm pm mc zc pc uc numberorder = <u>numbers</u> compress = yes <u>no</u> all criterion = local text current previous <u>all</u> SECTION
$\backslash\text{devanagarinumerals}$ $\{.^*.\}$ * NUMBER
$\backslash\text{digits}$ $\{.^*.\}$ * NUMBER
$\backslash\text{digits}$ $\ldots.^*.$ * NUMBER
$\backslash\text{dimensiontocount}$ $\{.^1.\}$ $\backslash.^2..$ 1 DIMENSION 2 CSNAME
$\backslash\text{directboxfromcache}$ $\{.^1.\}$ $\{.^2.\}$ 1 NAME 2 NUMBER TEXT
$\backslash\text{directcolor}$ $[\ldots.^*.]$ * COLOR
$\backslash\text{directcolored}$ $[\ldots.^*.\ldots]$ * inherits: $\backslash\text{definecolor}$
$\backslash\text{directcolored}$ $[\ldots.^*.]$ * COLOR
$\backslash\text{directconvertedcounter}$ $\{.^1.\}$ $\{.^2.\}$ 1 NAME 2 first previous next last number

<code>\directcopyboxfromcache {...} {...}</code> 1 NAME 2 NUMBER TEXT
<code>\directdummysparameter {...}</code> * KEY
<code>\directgetboxllx ...</code> * CSNAME NUMBER
<code>\directgetboxlly ...</code> * CSNAME NUMBER
<code>\directhighlight {...} {...}</code> 1 NAME 2 TEXT
<code>\directlocalframed [...] {...}</code> 1 NAME 2 CONTENT
<code>\directluacode {...}</code> * COMMAND
<code>\directselect {...} {...} {...} {...} {...} {...}</code> 1 NAME 2 CONTENT 3 CONTENT 4 CONTENT 5 CONTENT 6 CONTENT
<code>\directsetbar {...}</code> * NAME
<code>\directsetup {...}</code> * NAME
<code>\directsymbol {...} {...}</code> 1 NAME 2 NAME
<code>\directvspacing {...,*...}</code> * inherits: \vspacing
<code>\dis {...}</code> * CONTENT
<code>\disabledirectives [...,*...]</code> * NAME
<code>\disableexperiments [...,*...]</code> * NAME
<code>\disablemode [...,*...]</code> * NAME
<code>\disableoutputstream</code>

<code>\disableparpositions</code>
<code>\disableregime</code>
<code>\disabletrackers [...,*,...]</code> <code>*   NAME</code>
<code>\displaymath {...}</code> <code>*   CONTENT</code>
<code>\displaymathematics {...}</code> <code>*   CONTENT</code>
<code>\displaymessage {...}</code> <code>*   TEXT</code>
<code>\distributedhsize {...} {...} {...}</code> <code>1   DIMENSION</code> <code>2   DIMENSION</code> <code>3   NUMBER</code>
<code>\dividedsize {...} {...} {...}</code> <code>1   DIMENSION</code> <code>2   DIMENSION</code> <code>3   NUMBER</code>
<code>\loadaptleftskip {...}</code> <code>*   yes no standard DIMENSION</code>
<code>\loadaptrightskip {...}</code> <code>*   yes no standard DIMENSION</code>
<code>\doaddfeature {...,*,...}</code> <code>*   NAME</code>
<code>\doassign [...] [...<sup>2</sup>...]</code> <code>1   TEXT</code> <code>2   KEY = VALUE</code>
<code>\doassignempty [...] [...<sup>2</sup>...]</code> <code>1   TEXT</code> <code>2   KEY = VALUE</code>
<code>\doboundtext {...} {...} {...}</code> <code>1   TEXT</code> <code>2   DIMENSION</code> <code>3   COMMAND</code>
<code>\docheckassignment {...}</code> <code>*   TEXT</code>
<code>\docheckedpagestate {...} {...} {...} {...} {...} {...} {...}</code> <code>1   REFERENCE</code> <code>2   COMMAND</code> <code>3   COMMAND</code> <code>4   COMMAND</code> <code>5   COMMAND</code> <code>6   COMMAND</code> <code>7   COMMAND</code>

\docheckedpair {...,*...} * TEXT
\documentvariable {...} * KEY
\dodoubleargument \ <sup>1</sup> ... [ <sup>2</sup> ...] [ <sup>3</sup> ...] 1 CSNAME 2 TEXT 3 TEXT
\dodoubleargumentwithset \ <sup>1</sup> ... [..., <sup>2</sup> ...] [ <sup>3</sup> ...] 1 CSNAME 2 TEXT 3 TEXT
\dodoubleempty \ <sup>1</sup> ... [ <sup>2</sup> ...] [ <sup>3</sup> ...] 1 CSNAME 2 TEXT 3 TEXT
\dodoubleemptywithset \ <sup>1</sup> ... [..., <sup>2</sup> ...] [ <sup>3</sup> ...] 1 CSNAME 2 TEXT 3 TEXT
\dodoublegroupempty \ <sup>1</sup> ... { <sup>2</sup> ...} { <sup>3</sup> ...} 1 CSNAME 2 TEXT 3 TEXT
\doeassign [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 TEXT 2 KEY = VALUE
\doexpandedrecurse {...} { <sup>2</sup> ...} 1 NUMBER 2 COMMAND
\dofastloops {...} \ <sup>2</sup> ... 1 NUMBER 2 CSNAME
\dogetattribute {...} * NAME
\dogetattributeid {...} * NAME
\dogetcommacommandelement <sup>1</sup> ... \from <sup>2</sup> ... \to \ <sup>3</sup> ... 1 NUMBER 2 TEXT 3 CSNAME
\dogobbleddoubleempty [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 TEXT 2 TEXT
\dogobblesingleempty [ <sup>1</sup> ...] * TEXT

`\doif {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 TRUE

`\doifallcommon {...,1...} {...,2...} {...3}`

1 TEXT  
2 TEXT  
3 TRUE

`\doifallcommonelse {...,1...} {...,2...} {...3} {...4}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifalldefinedelse {...,1...} {...2} {...3}`

1 NAME  
2 TRUE  
3 FALSE

`\doifallmodes {...,1...} {...2} {...3}`

1 NAME  
2 TRUE  
3 FALSE

`\doifallmodeselse {...,1...} {...2} {...3}`

1 NAME  
2 TRUE  
3 FALSE

`\doifassignmentelse {...1} {...2} {...3}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifassignmentelsecs {...1} \2... \3...`

1 TEXT  
2 CSNAME  
3 CSNAME

`\doifblackelse {...1} {...2} {...3}`

1 COLOR  
2 TRUE  
3 FALSE

`\doifbothsides {...1} {...2} {...3}`

1 COMMAND  
2 COMMAND  
3 COMMAND

`\doifbothsidesoverruled {...1} {...2} {...3}`

1 COMMAND  
2 COMMAND  
3 COMMAND

`\doifboxelse {...1} {...2} {...3} {...4}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifbufferelse {...} {...} {...}`

1 BUFFER  
2 TRUE  
3 FALSE

`\doifcolor {...} {...}`

1 COLOR  
2 TRUE

`\doifcolorelse {...} {...} {...}`

1 COLOR  
2 TRUE  
3 FALSE

`\doifcommandhandler \... {...} {...}`

1 CSNAME  
2 NAME  
3 TRUE

`\doifcommandhandlerelse \... {...} {...} {...}`

1 CSNAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifcommon {...,1...} {...,2...} {...}`

1 TEXT  
2 TEXT  
3 TRUE

`\doifcommonelse {...,1...} {...,2...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifcontent {...} {...} {...} \...4 {...5}`

1 COMMAND  
2 COMMAND  
3 COMMAND  
4 CSNAME  
5 CONTENT

`\doifconversiondefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifconversionnumberelse {...} {...} {...} {...}`

1 NAME  
2 NUMBER  
3 TRUE  
4 FALSE

`\doifcounter {...} {...}`

1 NAME  
2 TRUE

`\doifcounterelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE



`\doifcurrentfonthasfeatureelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifdefined {...} {...}`

1 NAME  
2 TRUE

`\doifdefinedcounter {...} {...}`

1 NAME  
2 TRUE

`\doifdefinedcounterelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifdefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifdimensionelse {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifdimenstringelse {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifdocumentargument {...} {...}`

1 NAME  
2 TRUE

`\doifdocumentargumentelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifdocumentfilename {...} {...}`

1 NUMBER  
2 TRUE

`\doifdocumentfilenameelse {...} {...} {...}`

1 NUMBER  
2 TRUE  
3 FALSE

`\doifdocumentvariable {...} {...}`

1 KEY  
2 TRUE

`\doifdocumentvariableelse {...} {...} {...}`

1 KEY  
2 TRUE  
3 FALSE

`\doifdrawingblackelse {...} {...}`

1 TRUE  
2 FALSE

`\doifelse {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 TRUE  
4 FALSE

`\doifelseallcommon {...,1...} {...,2...} {...} {...4}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifelsealldefined {...,1...} {...2} {...3}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelseallmodes {...,1...} {...2} {...3}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelseassignment {...1} {...2} {...3}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifelseassignmentcs {...1} \... \...3..`

1 TEXT  
2 CSNAME  
3 CSNAME

`\doifelseblack {...1} {...2} {...3}`

1 COLOR  
2 TRUE  
3 FALSE

`\doifelsebox {...1} {...2} {...3} {...4}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifelseboxincache {...1} {...2} {...3} {...4}`

1 NAME  
2 NUMBER TEXT  
3 TRUE  
4 FALSE

`\doifelsebuffer {...1} {...2} {...3}`

1 BUFFER  
2 TRUE  
3 FALSE

`\doifelsecolor {...1} {...2} {...3}`

1 COLOR  
2 TRUE  
3 FALSE

`\doifelsecommandhandler \...1 {...2} {...3} {...4}`

1 CSNAME  
2 NAME  
3 TRUE  
4 FALSE

```
\doifelsecommon {...1,...} {...2,...} {...3} {...4}  
1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE
```

```
\doifelseconversiondefined {...1} {...2} {...3}  
1 NAME  
2 TRUE  
3 FALSE
```

```
\doifelseconversionnumber {...1} {...2} {...3} {...4}  
1 NAME  
2 NUMBER  
3 TRUE  
4 FALSE
```

```
\doifelsecounter {...1} {...2} {...3}  
1 NAME  
2 TRUE  
3 FALSE
```

```
\doifelsecurrentfonthasfeature {...1} {...2} {...3}  
1 NAME  
2 TRUE  
3 FALSE
```

```
\doifelsecurrentsortingtongused {...1} {...2}  
1 TRUE  
2 FALSE
```

```
\doifelsecurrentsynonymshown {...1} {...2}  
1 TRUE  
2 FALSE
```

```
\doifelsecurrentsynonymused {...1} {...2}  
1 TRUE  
2 FALSE
```

```
\doifelsedefined {...1} {...2} {...3}  
1 NAME  
2 TRUE  
3 FALSE
```

```
\doifelsedefinedcounter {...1} {...2} {...3}  
1 NAME  
2 TRUE  
3 FALSE
```

```
\doifelsedimension {...1} {...2} {...3}  
1 TEXT  
2 TRUE  
3 FALSE
```

```
\doifelsedimenstring {...1} {...2} {...3}  
1 TEXT  
2 TRUE  
3 FALSE
```

```
\doifelsedocumentargument {...1} {...2} {...3}  
1 NAME  
2 TRUE  
3 FALSE
```

\doifelsedocumentfilename {...} {...} {...}

1 NUMBER  
2 TRUE  
3 FALSE

\doifelsedocumentvariable {...} {...} {...}

1 KEY  
2 TRUE  
3 FALSE

\doifelsedrawingblack {...} {...}

1 TRUE  
2 FALSE

\doifelseempty {...} {...} {...}

1 CONTENT  
2 TRUE  
3 FALSE

\doifelseemptyvalue {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseemptyvariable {...} {...} {...} {...}

1 NAME  
2 KEY  
3 TRUE  
4 FALSE

\doifelseenv {...} {...} {...}

1 KEY  
2 TRUE  
3 FALSE

\doifelsefastoptionalcheck {...} {...}

1 TRUE  
2 FALSE

\doifelsefastoptionalcheckcs \^1 \^2

1 CSNAME  
2 CSNAME

\doifelsefieldbody {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsefieldcategory {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsefigure {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelsefile {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

`\doifelsefiledefined {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsefileexists {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifelsefirstchar {...} {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifelseflagged {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsefontchar {...} {...} {...} {...}`

1 FONT  
2 NUMBER  
3 TRUE  
4 FALSE

`\doifelsefontfeature {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsefontpresent {...} {...} {...}`

1 FONT  
2 TRUE  
3 FALSE

`\doifelsefontsynonym {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelseframed \... {...} {...}`

1 CSNAME  
2 TRUE  
3 FALSE

`\doifelsehasspace {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifelsehelp {...} {...}`

1 TRUE  
2 FALSE

`\doifelseincsname {...} {...} {...} {...}`

1 TEXT  
2 CSNAME  
3 TRUE  
4 FALSE

`\doifelseinelement {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelseinputfile {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifelseinsertion {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelseinset {...} {...,2...} {...} {...4}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifelseinstring {...} {...} {...} {...4}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifelseinsymbolset {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifelseintoks {...} {...} {...} {...}`

1 COMMAND  
2 COMMAND  
3 TRUE  
4 FALSE

`\doifelseintwopassdata {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifelseitalic {...} {...}`

1 TRUE  
2 FALSE

`\doifelselanguage {...} {...} {...}`

1 LANGUAGE  
2 TRUE  
3 FALSE

`\doifelselayerdata {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelselayoutdefined {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

\doifelselayoutsomeline {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelselayouttextline {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseleapyear {...} {...} {...}

1 NUMBER  
2 TRUE  
3 FALSE

\doifelselist {...} {...} {...}

1 LIST  
2 TRUE  
3 FALSE

\doifelselocation {...} {...}

1 TRUE  
2 FALSE

\doifelselocfile {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelseMPgraphic {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsemainfloatbody {...} {...}

1 TRUE  
2 FALSE

\doifelsemarkedpage {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsemarking {...} {...} {...}

1 MARK  
2 TRUE  
3 FALSE

\doifelsemeaning \... \... {...} {...}

1 CSNAME  
2 CSNAME  
3 TRUE  
4 FALSE

\doifelsemessage {...} {...} {...} {...}

1 NAME  
2 NAME NUMBER  
3 TRUE  
4 FALSE

\doifelsemode {...,<sup>1</sup>...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

`\doifelsenextbgroup {...} {...}`

1 TRUE  
2 FALSE

`\doifelsenextbgroupcs \.^1. \.^2.`

1 CSNAME  
2 CSNAME

`\doifelsenextchar {...} {...} {...}`

1 CHARACTER  
2 TRUE  
3 FALSE

`\doifelsenextoptional {...} {...}`

1 TRUE  
2 FALSE

`\doifelsenextoptionalcs \.^1. \.^2.`

1 CSNAME  
2 CSNAME

`\doifelsenextparenthesis {...} {...}`

1 TRUE  
2 FALSE

`\doifelsenonzeropositive {...} {...} {...}`

1 NUMBER  
2 TRUE  
3 FALSE

`\doifelsenoteonsamepage {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifelsenothing {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifelsenumber {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifelseobjectfound {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifelseobjectreferencefound {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifelseoddpage {...} {...}`

1 COMMAND  
2 COMMAND

`\doifelseoddpagefloat {...} {...}`

1 TRUE  
2 FALSE



\doifelseoldercontext {...} {...} {...}

1 NUMBER  
2 TRUE  
3 FALSE

\doifelseolderversion {...} {...} {...} {...}

1 NUMBER  
2 NUMBER  
3 TRUE  
4 FALSE

\doifelseoverlapping {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

\doifelseoverlay {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseparallel {...} {...,<sup>2</sup>...} {...} {...}

1 NAME  
2 NAME all  
3 TRUE  
4 FALSE

\doifelseparentfile {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifelsepath {...} {...} {...}

1 PATH  
2 TRUE  
3 FALSE

\doifelsepathexists {...} {...} {...}

1 PATH  
2 TRUE  
3 FALSE

\doifelsepatterns {...} {...} {...}

1 LANGUAGE  
2 TRUE  
3 FALSE

\doifelseposition {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsepositionaction {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsepositiononpage {...} {...} {...} {...}

1 NAME  
2 NUMBER  
3 TRUE  
4 FALSE

\doifelsepositionsonsamepage {...<sup>1</sup>,...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifelsepositionsonthispage {...<sup>1</sup>,...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifelsepositionsused {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifelserreferencefound {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifelserightpage {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifelserightpagefloat {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifelserighttopleftinbox ...<sup>1</sup> {...<sup>2</sup>} {...<sup>3</sup>}

1 CSNAME NUMBER  
2 TRUE  
3 FALSE

\doifelsesamelinereference {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifelsesamestring {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelsesetups {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifelsesomebackground {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifelsesomespace {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsesomething {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsesometoks \<sup>1</sup>... {<sup>2</sup>...} {<sup>3</sup>...}

1 CSNAME  
2 TRUE  
3 FALSE

\doifelsestringinstring {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...}

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

\doifelsestructurelisthasnumber {<sup>1</sup>...} {<sup>2</sup>...}

1 TRUE  
2 FALSE

\doifelsestructurelisthaspage {<sup>1</sup>...} {<sup>2</sup>...}

1 TRUE  
2 FALSE

\doifelsesymboldefined {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsesymbolset {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsetext {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 TEXT  
2 TRUE  
3 FALSE

\doifelsetextflow {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsetextflowcollector {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 NAME  
2 TRUE  
3 FALSE

\doifelsetopofpage {<sup>1</sup>...} {<sup>2</sup>...}

1 TRUE  
2 FALSE

\doifelsetypingfile {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 FILE  
2 TRUE  
3 FALSE

\doifelseundefined {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 NAME  
2 TRUE  
3 FALSE

\doifelseurldefined {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 NAME  
2 TRUE  
3 FALSE

```
\doifelsevalue {...} {...} {...} {...}
1 NAME
2 TEXT
3 TRUE
4 FALSE
```

```
\doifelsevaluenothing {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifelsevariable {...} {...} {...} {...}
1 NAME
2 KEY
3 TRUE
4 FALSE
```

```
\doifempty {...} {...}
1 CONTENT
2 TRUE
```

```
\doifemptyelse {...} {...} {...}
1 CONTENT
2 TRUE
3 FALSE
```

```
\doifemptytoks \^1. \^2.
1 CSNAME
2 TRUE
```

```
\doifemptyvalue {...} {...}
1 NAME
2 TRUE
```

```
\doifemptyvalueelse {...} {...} {...}
1 NAME
2 TRUE
3 FALSE
```

```
\doifemptyvariable {...} {...} {...}
1 NAME
2 KEY
3 TRUE
```

```
\doifemptyvariableelse {...} {...} {...} {...}
1 NAME
2 KEY
3 TRUE
4 FALSE
```

```
\doifenv {...} {...}
1 KEY
2 TRUE
```

```
\doifenvelse {...} {...} {...}
1 KEY
2 TRUE
3 FALSE
```

```
\doiffastoptionalcheckcselse \^1. \^2.
1 CSNAME
2 CSNAME
```

`\doiffastoptionalcheckelse {...} {...}`

1 TRUE  
2 FALSE

`\doiffielddbodyelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiffielddcategoryelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiffigureelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doiffile {...} {...}`

1 FILE  
2 TRUE

`\doiffiledefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiffileelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doiffileexistselse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doiffirstcharelse {...} {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifflaggedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiffontcharelse {...} {...} {...} {...}`

1 FONT  
2 NUMBER  
3 TRUE  
4 FALSE

`\doiffontfeatureelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiffontpresentelse {...} {...} {...}`

1 FONT  
2 TRUE  
3 FALSE

`\doiffontsynonymelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifhasspaceelse {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doifhelpelse {...} {...}`

1 TRUE  
2 FALSE

`\doifincsnameelse {...} {...} {...} {...}`

1 TEXT  
2 CSNAME  
3 TRUE  
4 FALSE

`\doifinelementelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifinputfileelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifinsetionelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifinset {...} {...,2...} {...}`

1 TEXT  
2 TEXT  
3 TRUE

`\doifinsetelse {...} {...,2...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifinstring {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE

`\doifinstringelse {...} {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifinsymbolset {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifinsymbolsetelse {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifintokselse {...} {...} {...} {...}`

1 COMMAND  
2 COMMAND  
3 TRUE  
4 FALSE

`\doifintwopassdataelse {...} {...} {...} {...}`

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

`\doifitalicelse {...} {...}`

1 TRUE  
2 FALSE

`\doiflanguageelse {...} {...} {...}`

1 LANGUAGE  
2 TRUE  
3 FALSE

`\doiflayerdataelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiflayoutdefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiflayoutsomelineelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiflayouttextlineelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifleapyearelse {...} {...} {...}`

1 NUMBER  
2 TRUE  
3 FALSE

`\doiflistelse {...} {...} {...}`

1 LIST  
2 TRUE  
3 FALSE

`\doiflocationelse {...} {...}`

1 TRUE  
2 FALSE

`\doiflocfileelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

\doifMPgraphicelse {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifmainfloatbodyelse {...} {...}

1 TRUE  
2 FALSE

\doifmarkingelse {...} {...} {...}

1 MARK  
2 TRUE  
3 FALSE

\doifmeaningelse \... \... {...} {...}

1 CSNAME  
2 CSNAME  
3 TRUE  
4 FALSE

\doifmessageelse {...} {...} {...} {...}

1 NAME  
2 NAME NUMBER  
3 TRUE  
4 FALSE

\doifmode {...,<sup>1</sup>...} {...<sup>2</sup>}

1 NAME  
2 TRUE

\doifmodeelse {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifnextbgroupcselse \... \...<sup>2</sup>

1 CSNAME  
2 CSNAME

\doifnextbgroupelse {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifnextcharelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 CHARACTER  
2 TRUE  
3 FALSE

\doifnextoptionalcselse \... \...<sup>2</sup>

1 CSNAME  
2 CSNAME

\doifnextoptionalelse {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifnextparenthesiselse {...<sup>1</sup>} {...<sup>2</sup>}

1 TRUE  
2 FALSE

\doifnonzeropositiveelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NUMBER  
2 TRUE  
3 FALSE



\doifnot {...} {...} {...}

1 CONTENT  
2 CONTENT  
3 TRUE

\doifnotallcommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...<sup>3</sup>}

1 TEXT  
2 TEXT  
3 TRUE

\doifnotallmodes {...,<sup>1</sup>...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifnotcommandhandler \<sup>1</sup>... {...} {...}

1 CSNAME  
2 NAME  
3 TRUE

\doifnotcommon {...,<sup>1</sup>...} {...,<sup>2</sup>...} {...<sup>3</sup>}

1 TEXT  
2 TEXT  
3 TRUE

\doifnotcounter {...} {...<sup>2</sup>}

1 NAME  
2 TRUE

\doifnotdocumentargument {...<sup>1</sup>} {...<sup>2</sup>}

1 NAME  
2 TRUE

\doifnotdocumentfilename {...<sup>1</sup>} {...<sup>2</sup>}

1 NUMBER  
2 TRUE

\doifnotdocumentvariable {...<sup>1</sup>} {...<sup>2</sup>}

1 KEY  
2 TRUE

\doifnotempty {...} {...<sup>2</sup>}

1 CONTENT  
2 TRUE

\doifnotemptyvalue {...<sup>1</sup>} {...<sup>2</sup>}

1 NAME  
2 TRUE

\doifnotemptyvariable {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 KEY  
3 TRUE

\doifnotenv {...<sup>1</sup>} {...<sup>2</sup>}

1 KEY  
2 TRUE

\doifnoteonsamepageelse {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TRUE  
3 FALSE

\doifnotescollected {...} {...}

1 NAME  
2 TRUE

\doifnotfile {...} {...}

1 FILE  
2 TRUE

\doifnotflagged {...} {...}

1 NAME  
2 TRUE

\doifnothing {...} {...}

1 TEXT  
2 TRUE

\doifnothingelse {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

\doifnotinset {...} {...<sup>2</sup>,...} {...<sup>3</sup>}

1 TEXT  
2 TEXT  
3 TRUE

\doifnotinsidesplitfloat {...}

\* TRUE

\doifnotinstring {...} {...<sup>2</sup>} {...<sup>3</sup>}

1 TEXT  
2 TEXT  
3 TRUE

\doifnotmode {...,<sup>1</sup>...} {...<sup>2</sup>}

1 NAME  
2 TRUE

\doifnotnumber {...} {...<sup>2</sup>}

1 TEXT  
2 TRUE

\doifnotsamestring {...} {...<sup>2</sup>} {...<sup>3</sup>}

1 TEXT  
2 TEXT  
3 TRUE

\doifnotsetups {...} {...<sup>2</sup>}

1 NAME  
2 TRUE

\doifnotvalue {...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 TEXT  
3 TRUE

\doifnotvariable {...} {...<sup>2</sup>} {...<sup>3</sup>}

1 NAME  
2 KEY  
3 TRUE

**\doifnumber** {...} {...}

1 TEXT  
2 TRUE

**\doifnumberelse** {...} {...} {...}

1 TEXT  
2 TRUE  
3 FALSE

**\doifobjectfoundelse** {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

**\doifobjectreferencefoundelse** {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

**\doifoddpagelse** {...} {...}

1 COMMAND  
2 COMMAND

**\doifoddpagefloatelse** {...} {...}

1 TRUE  
2 FALSE

**\doifoldercontextelse** {...} {...} {...}

1 NUMBER  
2 TRUE  
3 FALSE

**\doifolderversionelse** {...} {...} {...} {...}

1 NUMBER  
2 NUMBER  
3 TRUE  
4 FALSE

**\doifoverlappingelse** {...} {...} {...} {...}

1 NAME  
2 NAME  
3 TRUE  
4 FALSE

**\doifoverlayelse** {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

**\doifparallelelse** {...} {...,  
...} {...} {...}

1 NAME  
2 NAME all  
3 TRUE  
4 FALSE

**\doifparentfileelse** {...} {...} {...}

1 FILE  
2 TRUE  
3 FALSE

\doifpathelse {...} {...} {...}

1 PATH  
2 TRUE  
3 FALSE

\doifpathexistself {...} {...} {...}

1 PATH  
2 TRUE  
3 FALSE

\doifpatternself {...} {...} {...}

1 LANGUAGE  
2 TRUE  
3 FALSE

\doifposition {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionaction {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionactionself {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionself {...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositiononpageelse {...} {...} {...} {...}

1 NAME  
2 NUMBER  
3 TRUE  
4 FALSE

\doifpositionsonsamepageelse {...,<sup>1</sup>...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionsonthispageelse {...,<sup>1</sup>...} {...} {...}

1 NAME  
2 TRUE  
3 FALSE

\doifpositionsusedelse {...} {...}

1 TRUE  
2 FALSE

\doifreferencefoundelse {...} {...} {...}

1 REFERENCE  
2 TRUE  
3 FALSE

\doifrightpagefloatelse {...} {...}

1 TRUE  
2 FALSE

```
\doifrighttoleftinboxedelse 1 {...} 3 {...}
```

```
1 CSNAME NUMBER  
2 TRUE  
3 FALSE
```

```
\doifsamelinereferenceelse 1 {...} 2 {...} 3 {...}
```

```
1 REFERENCE  
2 TRUE  
3 FALSE
```

```
\doifsamestring 1 {...} 2 {...} 3 {...}
```

```
1 TEXT  
2 TEXT  
3 TRUE
```

```
\doifsamestringelse 1 {...} 2 {...} 3 {...} 4 {...}
```

```
1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE
```

```
\doifsetups 1 {...} 2 {...}
```

```
1 NAME  
2 TRUE
```

```
\doifsetupself 1 {...} 2 {...} 3 {...}
```

```
1 NAME  
2 TRUE  
3 FALSE
```

```
\doifsomebackground 1 {...} 2 {...} 3 {...}
```

```
1 NAME  
2 TRUE  
3 FALSE
```

```
\doifsomebackgroundelse 1 {...} 2 {...} 3 {...}
```

```
1 NAME  
2 TRUE  
3 FALSE
```

```
\doifsomespaceelse 1 {...} 2 {...} 3 {...}
```

```
1 TEXT  
2 TRUE  
3 FALSE
```

```
\doifsomething 1 {...} 2 {...}
```

```
1 TEXT  
2 TRUE
```

```
\doifsomethingelse 1 {...} 2 {...} 3 {...}
```

```
1 TEXT  
2 TRUE  
3 FALSE
```

```
\doifsometoks \1 {...} 2 {...}
```

```
1 CSNAME  
2 TRUE
```

```
\doifsometokself 1 {...} 2 {...} 3 {...}
```

```
1 CSNAME  
2 TRUE  
3 FALSE
```

`\doifstringinstringelse {...} {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\doifstructurelisthasnumberelse {...} {...}`

1 TRUE  
2 FALSE

`\doifstructurelisthaspageelse {...} {...}`

1 TRUE  
2 FALSE

`\doifsymboldefinedelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doifsymbolsetelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiftext {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doiftextelse {...} {...} {...}`

1 TEXT  
2 TRUE  
3 FALSE

`\doiftextflowcollectorelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiftextflowelse {...} {...} {...}`

1 NAME  
2 TRUE  
3 FALSE

`\doiftopofpageelse {...} {...}`

1 TRUE  
2 FALSE

`\doiftypingfileelse {...} {...} {...}`

1 FILE  
2 TRUE  
3 FALSE

`\doifundefined {...} {...}`

1 NAME  
2 TRUE

`\doifundefinedcounter {...} {...}`

1 NAME  
2 TRUE

<code>\doifundefinedelse {...} {...} {...}</code> 1 NAME 2 TRUE 3 FALSE
<code>\doifunknownfontfeature {...} {...} {...}</code> 1 NAME 2 TRUE 3 FALSE
<code>\doifurldefinedelse {...} {...} {...}</code> 1 NAME 2 TRUE 3 FALSE
<code>\doifvalue {...} {...} {...}</code> 1 NAME 2 TEXT 3 TRUE
<code>\doifvalueelse {...} {...} {...} {...}</code> 1 NAME 2 TEXT 3 TRUE 4 FALSE
<code>\doifvaluenothing {...} {...}</code> 1 NAME 2 TRUE
<code>\doifvaluenothingelse {...} {...} {...}</code> 1 NAME 2 TRUE 3 FALSE
<code>\doifvaluesomething {...} {...}</code> 1 NAME 2 TRUE
<code>\doifvariable {...} {...} {...}</code> 1 NAME 2 KEY 3 TRUE
<code>\doifvariableelse {...} {...} {...} {...}</code> 1 NAME 2 KEY 3 TRUE 4 FALSE
<code>\doindentation</code>
<code>\dollar</code>
<code>\doloop {...}</code> * COMMAND
<code>\doloopoverlist {...,<sup>1</sup>...} {...<sup>2</sup>}</code> 1 TEXT 2 COMMAND
<code>\donothing</code>





<p><code>\dorepeatwithcommand</code> [<sup>1</sup>...] \<sup>2</sup>...</p> <p>1 TEXT NUMBER*TEXT</p> <p>2 CSNAME</p>
<p><code>\doreplacefeature</code> {...,*...}</p> <p>* NAME</p>
<p><code>\doresetandafffeature</code> {...,*...}</p> <p>* NAME</p>
<p><code>\doresetattribute</code> {.*}</p> <p>* NAME</p>
<p><code>\dorotatebox</code> {<sup>1</sup>} \<sup>2</sup>... {<sup>3</sup>...}</p> <p>1 NUMBER</p> <p>2 CSNAME</p> <p>3 CONTENT</p>
<p><code>\dosetattribute</code> {<sup>1</sup>} {<sup>2</sup>...}</p> <p>1 NAME</p> <p>2 NUMBER</p>
<p><code>\dosetleftskipadaption</code> {.*}</p> <p>* yes no standard DIMENSION</p>
<p><code>\dosetrighskipadaption</code> {.*}</p> <p>* yes no standard DIMENSION</p>
<p><code>\dosetupcheckedinterlinespace</code> {...,*=...,...}</p> <p>* inherits: \setupinterlinespace</p>
<p><code>\dosetupcheckedinterlinespace</code> {...,*...}</p> <p>* on off reset auto small medium big NUMBER DIMENSION</p>
<p><code>\dosetupcheckedinterlinespace</code> {.*}</p> <p>* NAME</p>
<p><code>\doseventupleargument</code> \<sup>1</sup>... [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...] [<sup>6</sup>...] [<sup>7</sup>...] [<sup>8</sup>...]</p> <p>1 CSNAME</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 TEXT</p> <p>7 TEXT</p> <p>8 TEXT</p>
<p><code>\doseventupleempty</code> \<sup>1</sup>... [<sup>2</sup>...] [<sup>3</sup>...] [<sup>4</sup>...] [<sup>5</sup>...] [<sup>6</sup>...] [<sup>7</sup>...] [<sup>8</sup>...]</p> <p>1 CSNAME OPT OPT OPT OPT OPT OPT OPT</p> <p>2 TEXT</p> <p>3 TEXT</p> <p>4 TEXT</p> <p>5 TEXT</p> <p>6 TEXT</p> <p>7 TEXT</p> <p>8 TEXT</p>
<p><code>\dosingleargument</code> \<sup>1</sup>... [<sup>2</sup>...]</p> <p>1 CSNAME</p> <p>2 TEXT</p>

$\backslash\text{dosingleempty} \backslash.^1. [.^2.]$ 1 CSNAME OPT 2 TEXT
$\backslash\text{dosinglegroupempty} \backslash.^1. \{.^2.\}$ 1 CSNAME OPT 2 TEXT
$\backslash\text{dosixtupleargument} \backslash.^1. [.^2.] [.^3.] [.^4.] [.^5.] [.^6.] [.^7.]$ 1 CSNAME 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT 7 TEXT
$\backslash\text{dosixtupleempty} \backslash.^1. [.^2.] [.^3.] [.^4.] [.^5.] [.^6.] [.^7.]$ 1 CSNAME OPT OPT OPT OPT OPT OPT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT 7 TEXT
$\backslash\text{dostarttagged} \{.^1.\} \{.^2.\} \dots \backslash\text{dostoptagged}$ 1 NAME 2 NAME
$\backslash\text{dostepwiserecurse} \{.^1.\} \{.^2.\} \{.^3.\} \{.^4.\}$ 1 NUMBER 2 NUMBER 3 [-+]NUMBER 4 COMMAND
$\backslash\text{dosubtractfeature} \{.^1.\} \{.^2.\} \dots \{.^3.\}$ * NAME
$\backslash\text{dot} \{.^1.\}$ * CHARACTER
$\backslash\text{dotfskip} \{.^1.\}$ * DIMENSION
$\backslash\text{dotoks} \backslash.^1.$ * CSNAME
$\backslash\text{dotripleargument} \backslash.^1. [.^2.] [.^3.] [.^4.]$ 1 CSNAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\text{dotripleargumentwithset} \backslash.^1. [.^2.,.^3.] [.^4.] [.^5.]$ 1 CSNAME 2 TEXT 3 TEXT 4 TEXT
$\backslash\text{dotripleempty} \backslash.^1. [.^2.] [.^3.] [.^4.]$ 1 CSNAME OPT OPT OPT 2 TEXT 3 TEXT 4 TEXT

```
\dotripleemptywithset \...1 [...]2,...3 [...]4
1 CSNAME OPT OPT OPT
2 TEXT
3 TEXT
4 TEXT
```

```
\dotriplegroupempty \... {...}1 {...}2 {...}3 {...}4
1 CSNAME OPT OPT OPT
2 TEXT
3 TEXT
4 TEXT
```

```
\doublebond
```

```
\dowith {...}1,... {...}2
1 COMMAND
2 COMMAND
```

```
\dowithnextbox {...}1 \... {...}2 {...}3
1 COMMAND
2 CSNAME
3 CONTENT
```

```
\dowithnextboxcontent {...}1 {...}2 \... {...}3 {...}4
1 COMMAND
2 COMMAND
3 CSNAME
4 CONTENT
```

```
\dowithnextboxcontentcs \...1 \...2 \...3 {...}4
1 CSNAME
2 CSNAME
3 CSNAME
4 CONTENT
```

```
\dowithnextboxcs \...1 \...2 {...}3
1 CSNAME
2 CSNAME
3 CONTENT
```

```
\dowithpargument \*...
* CSNAME
```

```
\dowithrange {...}1,... {...}2
1 NUMBER NUMBER:NUMBER
2 CSNAME
```

```
\dowithwargument \*...
* CSNAME
```

```
\dpofstring {...}
* TEXT
```

```
\dummydigit
```

```
\dummyparameter {...}
* KEY
```

```
\ETEX
```

```
\EveryLine {...}
* COMMAND
```

<code>\EveryPar {...}</code> *    COMMAND
<code>\edefconvertedargument \<sup>1</sup>... {<sup>2</sup>...}</code> 1    CSNAME 2    TEXT
<code>\efcmaxheight {...}</code> *    NAME
<code>\efcmaxwidth {...}</code> *    NAME
<code>\efcminheight {...}</code> *    NAME
<code>\efcminwidth {...}</code> *    NAME
<code>\efcparameter {<sup>1</sup>...} {<sup>2</sup>...}</code> 1    NAME 2    KEY
<code>\effect [<sup>1</sup>...] {<sup>2</sup>...}</code> 1    NAME 2    CONTENT
<code>\elapsedseconds</code>
<code>\elapsedtime</code>
<code>\em</code>
<code>\emphasisboldface</code>
<code>\emphasistypeface</code>
<code>\emptylines [...]</code> *    NUMBER            OPT
<code>\emspace</code>
<code>\enabledirectives [...,*,...]</code> *    NAME
<code>\enableexperiments [...,*,...]</code> *    NAME
<code>\enablemode [...,*,...]</code> *    NAME
<code>\enableoutputstream [...]</code> *    NAME
<code>\enableparpositions</code>

`\enableregime [...]`

\* cp1250 cp1251 cp1252 cp1253 cp1254 cp1255 cp1256 cp1257 cp1258 8859-1 8859-2 8859-3 8859-4 8859-9 8859-10 8859-13 8859-14 8859-15 8859-16 utf windows-1250 windows-1251 windows-1252 windows-1253 windows-1254 windows-1255 windows-1256 windows-1257 windows-1258 il1 il2 il3 il4 il5 il6 il7 il8 il9 il10 iso-8859-1 iso-8859-2 iso-8859-3 iso-8859-4 iso-8859-9 iso-8859-10 iso-8859-13 iso-8859-14 iso-8859-15 iso-8859-16 latin1 latin2 latin3 latin4 latin5 latin6 latin7 latin8 latin9 latin10 utf-8 utf8 windows

`\enabletrackers [...,*,...]`

\* NAME

`\enskip`

`\enspace`

`\ENUMERATION [...,1...] {...,2} ...3 \par`

1 REFERENCE

OPT

OPT

2 TEXT

3 CONTENT

`\env {...}`

\* KEY

`\environment [...]`

\* FILE

`\environment ...`

\* FILE

`\envvar {...} {...}`

1 KEY

2 COMMAND

`\epos {...}`

\* NAME

`\equaldigits {...}`

\* TEXT

`\eTeX`

`\executeifdefined {...} {...}`

1 NAME

2 COMMAND

`\exitloop`

`\exitloopnow`

`\expandcheckedcsname \1... {...,2} {...,3}`

1 CSNAME

2 KEY

3 TEXT

`\expanded {...}`

\* CONTENT

`\expandeddoif {...,1} {...,2} {...,3}`

1 CONTENT

2 CONTENT

3 TRUE

`\expandeddoifelse {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 TRUE  
4 FALSE

`\expandeddoifnot {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 TRUE

`\expandfontsynonym \1 {...}`

1 CSNAME  
2 NAME

`\expdoif {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 TRUE

`\expdoifcommonelse {...,1...} {...,2...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\expdoifelse {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 TRUE  
4 FALSE

`\expdoifelsecommon {...,1...} {...,2...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\expdoifelseinset {...} {...,2...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\expdoifinsetelse {...} {...,2...} {...} {...}`

1 TEXT  
2 TEXT  
3 TRUE  
4 FALSE

`\expdoifnot {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 TRUE

`\externalfigure [...]1 [...]2 [...,3...]3`

1 FILE  
2 NAME  
3 inherits: \setuexternalfigure

`\externalfigurecollectionmaxheight {...}`

\* NAME

`\externalfigurecollectionmaxwidth {...}`

\* NAME

<code>\externalfigurecollectionminheight {...}</code> *    NAME
<code>\externalfigurecollectionminwidth {...}</code> *    NAME
<code>\externalfigurecollectionparameter {...} {...}</code> 1    NAME 2    KEY
<code>\fakebox ...</code> *    CSNAME NUMBER
<code>\fastdecrement \...</code> *    CSNAME
<code>\fastincrement \...</code> *    CSNAME
<code>\fastlocalframed [...] [...] {...}</code> 1    NAME 2    inherits: \setupframed 3    CONTENT
<code>\fastloopfinal</code>
<code>\fastloopindex</code>
<code>\fastscale {...} {...}</code> 1    NUMBER 2    CONTENT
<code>\fastsetup {...}</code> *    NAME
<code>\fastsetupwithargument {...} {...}</code> 1    NAME 2    CONTENT
<code>\fastsetupwithargumentswapped {...} {...}</code> 1    CONTENT 2    NAME
<code>\fastswitchtobodyfont {...}</code> *    x xx small big script scriptscript
<code>\fastxsxy {...} {...} {...}</code> 1    NUMBER 2    NUMBER 3    CONTENT
<code>\feature [...] [...] ...</code> 1    + - = ! > < more less new reset default old local 2    NAME
<code>\feature {...} {..., ...}</code> 1    + - = ! > < more less new reset default old local 2    NAME

<code>\fence</code>	
<code>\fenced [.<sup>1</sup>.] {..<sup>2</sup>}</code>	1 parenthesis bracket brace bar doublebar triplebar angle doubleangle solidus ceiling floor moustache uppercorner lowercorner group openbracket mirroredparenthesis mirroredbracket mirroredbrace mirroredbar mirroreddoublebar mirroredtriplebar mirroredangle mirroreddoubleangle mirroredsolidus mirroredceiling mirroredfloor mirroredmoustache mirroreduppercorner mirroredlowercorner mirroredgroup mirroredopenbracket NAME 2 CONTENT
<code>\FENCE {.*.}</code>	* CONTENT
<code>\fetchallmarkings [.<sup>1</sup>.] [..<sup>2</sup>.]</code>	1 MARK 2 page NAME
<code>\fetchallmarks [.*.]</code>	* MARK
<code>\fetchmark [.<sup>1</sup>.] [..<sup>2</sup>.]<sub>OPT</sub></code>	1 MARK 2 first last current previous next top bottom default both all first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
<code>\fetchmarking [.<sup>1</sup>.] [..<sup>2</sup>.] [..<sup>3</sup>.]</code>	1 MARK 2 page NAME 3 first last current previous next top bottom default both all first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
<code>\fetchonemark [.<sup>1</sup>.] [..<sup>2</sup>.]<sub>OPT</sub></code>	1 MARK 2 first last current previous next top bottom default both all first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
<code>\fetchonemarking [.<sup>1</sup>.] [..<sup>2</sup>.] [..<sup>3</sup>.]</code>	1 MARK 2 page NAME 3 first last current previous next top bottom default both all first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck
<code>\fetchruntimecommand \.<sup>1</sup>. {..<sup>2</sup>.}</code>	1 CSNAME 2 FILE
<code>\fetchtwomarkings [.<sup>1</sup>.] [..<sup>2</sup>.]</code>	1 MARK 2 page NAME
<code>\fetchtwomarks [.*.]</code>	* MARK
<code>\field [.<sup>1</sup>.] [..<sup>2</sup>.]<sub>OPT</sub></code>	1 NAME 2 TEXT
<code>\fieldbody [.<sup>1</sup>.] [..<sup>2</sup>.<sub>OPT</sub>...]</code>	1 NAME 2 inherits: \setupfieldbody



<code>\fieldstack [...]<sup>1</sup> [...]<sup>2</sup>,...] [...]<sup>3</sup>,...]</code> 1 NAME OPT OPT 2 NAME 3 inherits: \setupfieldcategory
<code>\fifthoffivearguments {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup> {...}<sup>5</sup></code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
<code>\fifthofsixarguments {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup> {...}<sup>5</sup> {...}<sup>6</sup></code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
<code>\figurefilename</code>
<code>\figurefilepath</code>
<code>\figurefiletype</code>
<code>\figurefullname</code>
<code>\figureheight</code>
<code>\figurenaturalheight</code>
<code>\figurenaturalwidth</code>
<code>\figuresymbol [...]<sup>1</sup> [...]<sup>2</sup>,...]</code> 1 FILE NAME OPT OPT 2 inherits: \externalfigure
<code>\figurewidth</code>
<code>\filename {...}</code> * FILE
<code>\filledhboxb ...<sup>1</sup> {...}<sup>2</sup></code> 1 TEXT OPT 2 CONTENT
<code>\filledhboxc ...<sup>1</sup> {...}<sup>2</sup></code> 1 TEXT OPT 2 CONTENT
<code>\filledhboxg ...<sup>1</sup> {...}<sup>2</sup></code> 1 TEXT OPT 2 CONTENT
<code>\filledhboxk ...<sup>1</sup> {...}<sup>2</sup></code> 1 TEXT OPT 2 CONTENT

<pre> \filledhboxm <sup>1</sup>... {<sup>2</sup>...} 1  TEXT          OPT 2  CONTENT </pre>
<pre> \filledhboxr <sup>1</sup>... {<sup>2</sup>...} 1  TEXT          OPT 2  CONTENT </pre>
<pre> \filledhboxy <sup>1</sup>... {<sup>2</sup>...} 1  TEXT          OPT 2  CONTENT </pre>
<pre> \filler [...] *  sym symbol rule width space NAME </pre>
<pre> \fillinline [...,<sup>*</sup>...,...] *  inherits: \setupfillinlines </pre>
<pre> \fillinrules [...,<sup>1</sup>...,...] {<sup>2</sup>...} {<sup>3</sup>...} 1  inherits: \setupfillinrules          OPT      OPT 2  TEXT 3  TEXT </pre>
<pre> \fillintext [...,<sup>1</sup>...,...] {<sup>2</sup>...} {<sup>3</sup>...} 1  inherits: \setupfillinrules          OPT      OPT 2  TEXT 3  TEXT </pre>
<pre> \fillupto [<sup>1</sup>...] {<sup>2</sup>...} 1  sym symbol rule width space NAME 2  TEXT </pre>
<pre> \filterfromnext {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} {<sup>4</sup>...} {<sup>5</sup>...} {<sup>6</sup>...} {<sup>7</sup>...} 1  NUMBER          OPT      OPT      OPT      OPT      OPT 2  NUMBER 3  CONTENT 4  CONTENT 5  CONTENT 6  CONTENT 7  CONTENT </pre>
<pre> \filterfromvalue {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} 1  NAME 2  NUMBER 3  NUMBER </pre>
<pre> \filterpages [<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...,...] 1  FILE          OPT 2  even odd NUMBER NUMBER:NUMBER 3  width    =  DIMENSION    n        =  NUMBER    category =  NAME </pre>
<pre> \filterreference {...} *  default text title number page realpage </pre>
<pre> \findtwopassdata {<sup>1</sup>...} {<sup>2</sup>...} 1  NAME 2  NAME </pre>

```
\finishregisterentry [...]1 [...,...2...,...]2 [...,...3...,...]3
1 NAME OPT
2 label = NAME
keys = TEXT PROCESSOR->TEXT
entries = TEXT PROCESSOR->TEXT
alternative = TEXT
3 KEY = VALUE
```

```
\firstcharacter
```

```
\firstcounter [...]1 [...]2
1 NAME OPT
2 NUMBER
```

```
\firstcountervalue [...]*
* NAME
```

```
\firstinlist [...]*,...]
* COMMAND
```

```
\firstoffivearguments {...}1 {...}2 {...}3 {...}4 {...}5
1 TEXT
2 TEXT
3 TEXT
4 TEXT
5 TEXT
```

```
\firstoffourarguments {...}1 {...}2 {...}3 {...}4
1 TEXT
2 TEXT
3 TEXT
4 TEXT
```

```
\firstofoneargument {...}*
* TEXT
```

```
\firstofoneunexpanded {...}*
* TEXT
```

```
\firstofsixarguments {...}1 {...}2 {...}3 {...}4 {...}5 {...}6
1 TEXT
2 TEXT
3 TEXT
4 TEXT
5 TEXT
6 TEXT
```

```
\firstofthreearguments {...}1 {...}2 {...}3
1 TEXT
2 TEXT
3 TEXT
```

```
\firstofthreeunexpanded {...}1 {...}2 {...}3
1 TEXT
2 TEXT
3 TEXT
```

```
\firstoftwoarguments {...}1 {...}2
1 TEXT
2 TEXT
```

```
\firstoftwounexpanded {...}1 {...}2
1 TEXT
2 TEXT
```

<code>\firstrealpage</code>
<code>\firstrealpagenumber</code>
<code>\firstsubcountervalue</code> [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME 2 NUMBER
<code>\firstsubpage</code>
<code>\firstsubpagenumber</code>
<code>\firstuserpage</code>
<code>\firstuserpagenumber</code>
<code>\fitfield</code> [ <sup>1</sup> ...] [..., <sup>2</sup> ...] 1 NAME OPT 2 inherits: \setupfieldbody
<code>\fitfieldframed</code> [..., <sup>1</sup> ...] { <sup>2</sup> ...} 1 inherits: \setupframed OPT 2 CONTENT
<code>\fittopbaselinegrid</code> {.*} * CONTENT
<code>\fixedspace</code>
<code>\fixedspaces</code>
<code>\flag</code> {.*} * NAME
<code>\floatuserdataparameter</code> {.*} * KEY
<code>\flushbox</code> { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 NAME
<code>\flushboxregister</code> ... * CSNAME NUMBER
<code>\flushcollector</code> [...] * NAME
<code>\flushedrightlastline</code>
<code>\flushlayer</code> [...] * NAME
<code>\flushlocalfloats</code>
<code>\flushnextbox</code>

<code>\flushnotes</code>
<code>\flushoutputstream [...]</code> *    NAME
<code>\flushshapebox</code>
<code>\flushtextflow {...}</code> *    NAME
<code>\flushtokens [...]</code> *    NAME
<code>\flushtoks \...</code> *    CSNAME
<code>\fontalternative</code>
<code>\fontbody</code>
<code>\fontchar {...}</code> *    NAME
<code>\fontcharbyindex {...}</code> *    NUMBER
<code>\fontclass</code>
<code>\fontclassname {...} {...}</code> 1    NAME 2    FONT
<code>\fontface</code>
<code>\fontfeaturelist [...] [...]</code> 1    NAME 2    TEXT
<code>\fontsize</code>
<code>\fontstyle</code>
<code>\footnotetext [...,<sup>1</sup>...] {<sup>2</sup>...}</code> 1    REFERENCE            OPT 2    TEXT
<code>\footnotetext [...,<sup>*</sup>...,...]</code> *    title        = TEXT bookmark    = TEXT list        = TEXT reference = REFERENCE
<code>\forcecharacterstripping</code>
<code>\forcelocalfloats</code>
<code>\forgeteverypar</code>

$\backslash$ forgetparameters [...] <sup>1</sup> [...,... <sup>2</sup> ...,...] 1 TEXT 2 KEY = VALUE
$\backslash$ forgetparskip
$\backslash$ forgetragged
$\backslash$ formula [...] <sup>1</sup> ,... <sup>2</sup> {...} 1 packed tight <sup>0</sup> middle frame depth line halflines -line -halflines inherits: \setupbodyfont 2 CONTENT
$\backslash$ formulanumber [...] <sup>*</sup> ,... <sup>OPT</sup> * REFERENCE
$\backslash$ foundbox {...} <sup>1</sup> {...} <sup>2</sup> 1 NAME 2 NAME
$\backslash$ fourthoffivearguments {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...} <sup>4</sup> {...} <sup>5</sup> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT
$\backslash$ fourthoffourarguments {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...} <sup>4</sup> 1 TEXT 2 TEXT 3 TEXT 4 TEXT
$\backslash$ fourthofsixarguments {...} <sup>1</sup> {...} <sup>2</sup> {...} <sup>3</sup> {...} <sup>4</sup> {...} <sup>5</sup> {...} <sup>6</sup> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 TEXT
$\backslash$ FRACTION {...} <sup>1</sup> {...} <sup>2</sup> 1 CONTENT 2 CONTENT instances: xfrac xxfrac frac sfrac dfrac binom dbinom tbinom
$\backslash$ binom {...} <sup>1</sup> {...} <sup>2</sup> 1 CONTENT 2 CONTENT
$\backslash$ dbinom {...} <sup>1</sup> {...} <sup>2</sup> 1 CONTENT 2 CONTENT
$\backslash$ dfrac {...} <sup>1</sup> {...} <sup>2</sup> 1 CONTENT 2 CONTENT
$\backslash$ frac {...} <sup>1</sup> {...} <sup>2</sup> 1 CONTENT 2 CONTENT

$\backslash sfrac \{...\} \{...\}$ 1    CONTENT 2    CONTENT
$\backslash tbinom \{...\} \{...\}$ 1    CONTENT 2    CONTENT
$\backslash xfrac \{...\} \{...\}$ 1    CONTENT 2    CONTENT
$\backslash xxfrac \{...\} \{...\}$ 1    CONTENT 2    CONTENT
$\backslash framed \left[ ..., \dots \stackrel{1}{=} \dots, \dots \right] \{...\}$ 1    inherits: $\backslash setupframed$ 2    CONTENT
$\backslash frameddimension \{...\}$ *    KEY
$\backslash framedparameter \{...\}$ *    KEY
$\backslash FRAMEDTEXT \left[ ..., \dots \stackrel{1}{=} \dots, \dots \right] \{...\}$ 1    inherits: $\backslash setupframedtext$ 2    CONTENT instances: framedtext
$\backslash framedtext \left[ ..., \dots \stackrel{1}{=} \dots, \dots \right] \{...\}$ 1    inherits: $\backslash setupframedtext$ 2    CONTENT
$\backslash FRAMED \left[ ..., \dots \stackrel{1}{=} \dots, \dots \right] \{...\}$ 1    inherits: $\backslash setupframed$ 2    CONTENT instances: unframed fitfieldframed
$\backslash fitfieldframed \left[ ..., \dots \stackrel{1}{=} \dots, \dots \right] \{...\}$ 1    inherits: $\backslash setupframed$ <small>OPT</small> 2    CONTENT
$\backslash unframed \left[ ..., \dots \stackrel{1}{=} \dots, \dots \right] \{...\}$ 1    inherits: $\backslash setupframed$ 2    CONTENT
$\backslash freezedimenmacro \stackrel{1}{\backslash} \dots \stackrel{2}{\backslash} \dots$ 1    CSNAME 2    CSNAME
$\backslash freezemeasure \left[ \stackrel{1}{.} \dots \right] \left[ \stackrel{2}{.} \dots \right]$ 1    NAME 2    DIMENSION
$\backslash frenchspacing$
$\backslash from \left[ \stackrel{*}{.} \dots \right]$ *    REFERENCE

<code>\fromlinenote [...]{...}</code> 1    REFERENCE 2    TEXT
<code>\frozenhbox {...}</code> *    CONTENT
<code>\frule .. .* .. \relax</code> *    width <sub>␣</sub> DIMENSION height <sub>␣</sub> DIMENSION depth <sub>␣</sub> DIMENSION radius <sub>␣</sub> DIMENSION line <sub>␣</sub> DIMENSION type <sub>␣</sub> TEXT data <sub>␣</sub> TEXT name <sub>␣</sub> TEXT
<code>\GetPar</code>
<code>\GotoPar</code>
<code>\Greeknumerals {...}</code> *    NUMBER
<code>\gdefconvertedargument \<sup>1</sup>... {\<sup>2</sup>...}</code> 1    CSNAME 2    TEXT
<code>\gdefconvertedcommand \<sup>1</sup>... \<sup>2</sup>...</code> 1    CSNAME 2    CSNAME
<code>\getboxfromcache {\<sup>1</sup>...} {\<sup>2</sup>...} \<sup>3</sup>...</code> 1    NAME 2    NUMBER TEXT 3    CSNAME NUMBER
<code>\getboxllx \<sup>*</sup>...</code> *    CSNAME NUMBER
<code>\getboxlly \<sup>*</sup>...</code> *    CSNAME NUMBER
<code>\getbuffer [...,\<sup>*</sup>...]</code> *    BUFFER <span style="margin-left: 100px;">OPT</span>
<code>\getbufferdata [...]</code> *    BUFFER <span style="margin-left: 100px;">OPT</span>
<code>\getBUFFER</code>
<code>\getcommacommandsize [...,\<sup>*</sup>...]</code> *    COMMAND
<code>\getcommalistsize [...,\<sup>*</sup>...]</code> *    COMMAND
<code>\getdayoftheweek {\<sup>1</sup>...} {\<sup>2</sup>...} {\<sup>3</sup>...}</code> 1    NUMBER 2    NUMBER 3    NUMBER
<code>\getdayspermonth {\<sup>1</sup>...} {\<sup>2</sup>...}</code> 1    NUMBER 2    NUMBER



\getdefinedbuffer [...] *    BUFFER
\getdocumentargument {...} *    NAME
\getdocumentargumentdefault {...} {...} 1    NAME 2    TEXT
\getdocumentfilename {...} *    NUMBER
\getdummyparameters [...,... <sup>*</sup> ...,...] *    KEY   =   VALUE
\getemptyparameters [... <sup>1</sup> ] [...,... <sup>2</sup> ...,...] 1    TEXT 2    KEY   =   VALUE
\getparameters [... <sup>1</sup> ] [...,... <sup>2</sup> ...,...] 1    TEXT 2    KEY   =   VALUE
\getexpandedparameters [... <sup>1</sup> ] [...,... <sup>2</sup> ...,...] 1    TEXT 2    KEY   =   VALUE
\getfiguredimensions [... <sup>1</sup> ] [...,... <sup>2</sup> ...,...] 1    FILE 2    inherits: \setupexternalfigure <div style="text-align: right; margin-right: 100px;"><small>OPT</small></div>
\getfirstcharacter {...} *    TEXT
\getfirsttwopassdata {...} *    NAME
\getfromcommacommand [..., <sup>1</sup> ...] [... <sup>2</sup> ] 1    COMMAND 2    NUMBER
\getfromcommalist [..., <sup>1</sup> ...] [... <sup>2</sup> ] 1    COMMAND 2    NUMBER
\getfromtwopassdata {... <sup>1</sup> } {... <sup>2</sup> } 1    NAME 2    NAME
\getglyphdirect {... <sup>1</sup> } {... <sup>2</sup> } 1    FONT 2    NUMBER CHARACTER
\getglyphstyled {... <sup>1</sup> } {... <sup>2</sup> } 1    FONT 2    NUMBER CHARACTER

<pre> \getgparameters [...] [...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getinlineuserdata </pre>
<pre> \getlasttwopassdata {...} * NAME </pre>
<pre> \getlocalfloat {...} * NUMBER </pre>
<pre> \getlocalfloats </pre>
<pre> \getMPdrawing </pre>
<pre> \getMPlayer [...] [...] [...] {...} 1 NAME 2 inherits: \setupframed 3 CONTENT </pre>
<pre> \getmarking [...] [...] [...] 1 MARK 2 page NAME 3 first last current previous next top bottom default both all first:nocheck last:nocheck previous:nocheck next:nocheck top:nocheck bottom:nocheck </pre>
<pre> \getmessage {...} {...} 1 NAME 2 NAME NUMBER </pre>
<pre> \getnamedglyphdirect {...} {...} 1 FONT 2 NAME </pre>
<pre> \getnamedglyphstyled {...} {...} 1 FONT 2 NAME </pre>
<pre> \getnamedtwopassdatalist \... {...} 1 CSNAME 2 NAME </pre>
<pre> \getnaturaldimensions ... * CSNAME NUMBER </pre>
<pre> \getnoflines {...} * DIMENSION </pre>
<pre> \getobject {...} {...} 1 NAME 2 NAME </pre>
<pre> \getobjectdimensions {...} {...} 1 NAME 2 NAME </pre>
<pre> \getpaletsize [...] * NAME </pre>

<pre> \getparameters [.<sup>1</sup>.] [...,<sup>2</sup>...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getprivatechar {...} * NAME </pre>
<pre> \getprivateslot {...} * NAME </pre>
<pre> \getrandomcount \.<sup>1</sup>. {.<sup>2</sup>.} {.<sup>3</sup>.} 1 CSNAME 2 NUMBER 3 NUMBER </pre>
<pre> \getrandomdimen \.<sup>1</sup>. {.<sup>2</sup>.} {.<sup>3</sup>.} 1 CSNAME 2 DIMENSION 3 DIMENSION </pre>
<pre> \getrandomfloat \.<sup>1</sup>. {.<sup>2</sup>.} {.<sup>3</sup>.} 1 CSNAME 2 NUMBER 3 NUMBER </pre>
<pre> \getrandomnumber \.<sup>1</sup>. {.<sup>2</sup>.} {.<sup>3</sup>.} 1 CSNAME 2 NUMBER 3 NUMBER </pre>
<pre> \getrandomseed \.* * CSNAME </pre>
<pre> \getrawparameters [.<sup>1</sup>.] [...,<sup>2</sup>...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getrawgparameters [.<sup>1</sup>.] [...,<sup>2</sup>...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getrawnoflines {...} * DIMENSION </pre>
<pre> \getrawparameters [.<sup>1</sup>.] [...,<sup>2</sup>...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getrawxparameters [.<sup>1</sup>.] [...,<sup>2</sup>...,...] 1 TEXT 2 KEY = VALUE </pre>
<pre> \getreference [.<sup>1</sup>.] [.<sup>2</sup>.] 1 default text title number page realpage 2 REFERENCE </pre>
<pre> \getreferenceentry {...} * default text title number page realpage </pre>
<pre> \getroundednoflines {...} * DIMENSION </pre>

\getsubstring {...} {...} {...} 1    NUMBER 2    NUMBER 3    TEXT
\gettokenlist [...] *    NAME
\gettwopassdata {...} *    NAME
\gettwopassdatalist {...} *    NAME
\getuserdata
\getuvalue {...} *    NAME
\getvalue {...} *    NAME
\getvariable {...} {...} 1    NAME 2    KEY
\getvariabledefault {...} {...} {...} 1    NAME 2    KEY 3    COMMAND
\getxparameters [...] [...,... <sup>2</sup> ...,...] 1    TEXT 2    KEY = VALUE
\globaldisablemode [...,*...] *    NAME
\globalenablemode [...,*...] *    NAME
\globalletempty \... *    CSNAME
\globalpopbox ... *    CSNAME NUMBER
\globalpopmacro \... *    CSNAME
\globalpreventmode [...,*...] *    NAME
\globalprocesscommalist [...] \... 1    COMMAND 2    CSNAME
\globalpushbox ... *    CSNAME NUMBER

`\globalpushmacro \*...`  
`* CSNAME`

`\globalpushreferenceprefix {...} ... \globalpopreferenceprefix`  
`* + - TEXT`

`\globalswapcounts \1... \2...`  
`1 CSNAME`  
`2 CSNAME`

`\globalswapdimens \1... \2...`  
`1 CSNAME`  
`2 CSNAME`

`\globalswapmacros \1... \2...`  
`1 CSNAME`  
`2 CSNAME`

`\globalundefine {...}`  
`* NAME`

`\glyphfontfile {...}`  
`* FONT`

`\gobbledoubleempty [1...] [2...]`  
`1 TEXT`  
`2 TEXT`  

OPT

OPT

`\gobbleeightarguments {...} {...} {...} {...} {...} {...} {...} {...}`  
`1 CONTENT`  
`2 CONTENT`  
`3 CONTENT`  
`4 CONTENT`  
`5 CONTENT`  
`6 CONTENT`  
`7 CONTENT`  
`8 CONTENT`

`\gobblefivearguments {...} {...} {...} {...} {...}`  
`1 CONTENT`  
`2 CONTENT`  
`3 CONTENT`  
`4 CONTENT`  
`5 CONTENT`

`\gobblefiveoptionals [1] [2] [3] [4] [5]`  
`1 TEXT`  
`2 TEXT`  
`3 TEXT`  
`4 TEXT`  
`5 TEXT`

`\gobblefourarguments {...} {...} {...} {...}`  
`1 CONTENT`  
`2 CONTENT`  
`3 CONTENT`  
`4 CONTENT`

`\gobblefouroptionals [...] [...] [...] [...]`  
`1 TEXT`  
`2 TEXT`  
`3 TEXT`  
`4 TEXT`

`\gobbleninearguments {...} {...} {...} {...} {...} {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT  
8 CONTENT  
9 CONTENT

`\gobbleoneargument {...}`

\* CONTENT

`\gobbleoneoptional [...]`

\* TEXT

`\gobblesevenarguments {...} {...} {...} {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT

`\gobblesingleempty [...]`

\* TEXT

OPT

`\gobblesixarguments {...} {...} {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT

`\gobblespacetokens`

`\gobbletenarguments {...} {...} {...} {...} {...} {...} {...} {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT  
4 CONTENT  
5 CONTENT  
6 CONTENT  
7 CONTENT  
8 CONTENT  
9 CONTENT  
10 CONTENT

`\gobblethreearguments {...} {...} {...}`

1 CONTENT  
2 CONTENT  
3 CONTENT

`\gobblethreeoptionals [...] [...] [...]`

1 TEXT  
2 TEXT  
3 TEXT

`\gobbletwoarguments {...} {...}`

1 CONTENT  
2 CONTENT

<code>\gobbletwooptionals [...] [...]</code> 1 TEXT 2 TEXT
<code>\gobbleuntil \...</code> * CSNAME
<code>\gobbleuntilrelax ... \relax</code> * CONTENT
<code>\godown [...]</code> * DIMENSION
<code>\goto {...} [...]</code> 1 CONTENT 2 REFERENCE
<code>\gotobox {...} [...]</code> 1 CONTENT 2 REFERENCE
<code>\gotopage {...} [...]</code> 1 TEXT 2 REFERENCE
<code>\grabbufferdata [...] [...] [...] [...]</code> 1 CATEGORY                    OPT 2 NAME 3 NAME 4 NAME
<code>\grabbufferdatadirect {...} {...} {...}</code> 1 NAME 2 NAME 3 NAME
<code>\grabuntil {...} \...</code> 1 NAME 2 CSNAME
<code>\grave {...}</code> * CHARACTER
<code>\graycolor [...] {...}</code> 1 COLOR 2 CONTENT
<code>\grayvalue {...}</code> * COLOR
<code>\greedystring \at ... \to ... \and \...</code> 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\greeknumerals {...}</code> * NUMBER
<code>\grid [..., ..., ..., ...]</code> * inherits: <code>\basegrid</code>

<code>\groupedcommand {...} {...}</code> 1    COMMAND 2    COMMAND
<code>\gsetboxllx <sup>1</sup>... {...}</code> 1    CSNAME NUMBER 2    DIMENSION
<code>\gsetboxlly <sup>1</sup>... {...}</code> 1    CSNAME NUMBER 2    DIMENSION
<code>\gujaratinumerals {...}</code> *    NUMBER
<code>\gurmukhinumerals {...}</code> *    NUMBER
<code>\hairline</code>
<code>\hairspace</code>
<code>\halflinestrut</code>
<code>\halfstrut</code>
<code>\halfwaybox {...}</code> *    CONTENT
<code>\handletokens <sup>1</sup>... \with \<sup>2</sup>...</code> 1    TEXT 2    CSNAME
<code>\handwritten</code>
<code>\hash</code>
<code>\hat {...}</code> *    CHARACTER
<code>\hboxofvbox ...</code> *    CSNAME NUMBER
<code>\hboxreference [...<sup>1</sup>,...] {...<sup>2</sup>}</code> 1    REFERENCE 2    CONTENT
<code>\hboxBOX {...}</code> *    CONTENT
<code>\hdofstring {...}</code> *    TEXT
<code>\headhbox <sup>1</sup>... {...<sup>2</sup>}</code> 1    TEXT        OPT 2    CONTENT



```
\headnumber [.^1.] [.^2.]
1 SECTION OPT
2 previous current next first last
```

<code>\headnumbercontent</code>
---------------------------------

```
\headnumberdistance
```

<code>\headnumberwidth</code>
-------------------------------

```
\headreferenceattributes
```

`\headsetupspace`

\headtextcontent

`\headtextdistance`

```
\headtextwidth
```

```
\headvbox ... {...}
1 TEXT OPT
2 CONTENT
```

`\headwidth`

```
\heightanddepthofstring {...}
*   TEXT
```

```
\heightofstring {...}
* TEXT
```

```
\heightspanningtext {.^.^.^}
1 TEXT
2 DIMENSION
3 FONT
```

```
\helptext [...] {...} {...}
1 REFERENCE OPT
2 TEXT
3 TEXT
```

```
\HELP [..1] {..2} {..3}
1  REFERENCE
2  TEXT
3  TEXT
instances: helptext
```

```
\helptext [.1.] {.2.} {.3.}
1 REFERENCE OPT
2 TEXT
3 TEXT
```

```
\hglue ...
*   DIMENSION
```

```
\hiddencitation [...]  
* REFERENCE
```

## \* REFERENCE

1	NAME	OPT
2	NAME	

\* CONTENT

1	NAME
2	TEXT

\* TEXT

\* TEXT

```
instances: unitshigh
```

\* CONTENT

```

1  left rightGPT
2  CONTENT
3  CONTENT

```

1	CONTENT
2	CONTENT
3	CONTENT

\* NUMBER<sup>OPT</sup>

```
* inherits: \setuppositionbar
```

```
* inherits: \setuppositionbar
```

\* CONTENT

1	NAME
2	CONTENT

1 DIMENSION  
2 NUMBER

\* CONTENT

\hsmashbox {...} * CSNAME NUMBER
\hsmashed {...} * CONTENT
\hspace [...] [...] <div> 1 NAME OPT OPT  2 small medium big normal <u>default</u> none .5 1 2 3 speech quote interquotation quotation sentence intersentence final NAME </div>
\htdpofstring {...} * TEXT
\htofstring {...} * TEXT
\hyphen
\hyphenatedcoloredword {...} * TEXT
\hyphenatedfile {...} * FILE
\hyphenatedfilename {...} * TEXT
\hyphenatedhbox {...} * CONTENT
\hyphenatedpar {...} * TEXT
\hyphenatedurl {...} * TEXT
\hyphenatedword {...} * TEXT
\INRSTEX
\ibox {...} * CONTENT
\ifassignment ... <sup>1</sup> \else ... <sup>2</sup> \fi <div> 1 TRUE  2 FALSE </div>
\iff
\ifinobject ... <sup>1</sup> \else ... <sup>2</sup> \fi <div> 1 TRUE  2 FALSE </div>
\ifinoutputstream ... <sup>1</sup> \else ... <sup>2</sup> \fi <div> 1 TRUE  2 FALSE </div>

<code>\ifparameters <sup>1</sup>... \else <sup>2</sup>... \fi</code> 1 TRUE 2 FALSE
<code>\iftrialeasetting <sup>1</sup>... \else <sup>2</sup>... \fi</code> 1 TRUE 2 FALSE
<code>\ignoreimplicitspaces</code>
<code>\ignoretagsinexport [...*,...]</code> * NAME
<code>\ignorevalue {...}</code> * NAME
<code>\immediatesavetwopassdata {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}</code> 1 NAME 2 NUMBER 3 CONTENT
<code>\impliedby</code>
<code>\implies</code>
<code>\in {<sup>1</sup>...} {<sup>2</sup>...} [<sup>3</sup>...]</code> 1 TEXT <sup>PPT</sup> OPT 2 TEXT 3 REFERENCE
<code>\includemenu [...]</code> * NAME
<code>\includeversioninfo {...}</code> * NAME
<code>\increment \...</code> * CSNAME
<code>\incrementcounter [...] [<sup>2</sup>...]</code> 1 NAME OPT 2 NUMBER
<code>\incrementedcounter [...]</code> * NAME
<code>\incrementpagenumber</code>
<code>\incrementsubpagenumber</code>
<code>\incrementvalue {...}</code> * NAME
<code>\increment (...*,...)</code> * CSNAME NUMBER
<code>\indentation</code>

<code>\infofont</code>
<code>\infofontbold</code>
<code>\inframed [...<sup>1</sup>...<sup>2</sup>] {...}</code> 1 inherits: <code>\setupfframed</code> 2 CONTENT
<code>\infull {...}</code> * NAME
<code>\inheritparameter [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>]</code> 1 TEXT 2 TEXT 3 KEY
<code>\inhibitblank</code>
<code>\initializeboxstack {...}</code> * NAME
<code>\inline {...<sup>1</sup>} [...<sup>2</sup>]</code> 1 TEXT OPT 2 REFERENCE
<code>\inlinebuffer [...<sup>*</sup>...]</code> * BUFFER OPT
<code>\inlinedbox {...}</code> * CONTENT
<code>\inlinemath {...}</code> * CONTENT
<code>\inlinemathematics {...}</code> * CONTENT
<code>\inlinemessage {...}</code> * TEXT
<code>\inlineordisplaymath {...<sup>1</sup>} {...<sup>2</sup>}</code> 1 CONTENT 2 CONTENT
<code>\inlineprettyprintbuffer {...<sup>1</sup>} {...<sup>2</sup>}</code> 1 BUFFER 2 mp lua xml parsed-xml nested tex context none NAME
<code>\inlinerange [...]</code> * REFERENCE
<code>\innerflushshapebox</code>
<code>\input {...}</code> * FILE
<code>\inputfilebarename</code>

<code>\inputfilename</code>
<code>\inputfilerealsuffix</code>
<code>\inputfilesuffix</code>
<code>\inputgivenfile {...}</code> *    FILE
<code>\input ...</code> *    FILE
<code>\insertpages [...]<sup>1</sup> [...,<sup>2</sup>...] [...,<sup>3</sup>...<sup>=</sup>...]</code> 1    FILE 2    NUMBER 3    width    = DIMENSION n        = NUMBER category = NAME
<code>\installactionhandler {...}</code> *    NAME
<code>\installactivecharacter ...</code> *    CHARACTER
<code>\installanddefineactivecharacter ...<sup>1</sup> {...<sup>2</sup>}</code> 1    CHARACTER 2    COMMAND
<code>\installattributestack \...<sup>*</sup></code> *    CSNAME
<code>\installautocommandhandler \...<sup>1</sup> {...<sup>2</sup>} \...<sup>3</sup></code> 1    CSNAME 2    NAME 3    CSNAME
<code>\installautosetuphandler \...<sup>1</sup> {...<sup>2</sup>}</code> 1    CSNAME 2    NAME
<code>\installbasicautosetuphandler \...<sup>1</sup> {...<sup>2</sup>} \...<sup>3</sup></code> 1    CSNAME 2    NAME 3    CSNAME
<code>\installbasicparameterhandler \...<sup>1</sup> {...<sup>2</sup>}</code> 1    CSNAME 2    NAME
<code>\installbottomframerenderer {...<sup>1</sup>} {...<sup>2</sup>}</code> 1    NAME 2    COMMAND
<code>\installcommandhandler \...<sup>1</sup> {...<sup>2</sup>} \...<sup>3</sup></code> 1    CSNAME 2    NAME 3    CSNAME
<code>\installcorenamespace {...<sup>*</sup>}</code> *    NAME

\installdefinehandler \<sup>1</sup>... {<sup>2</sup>...} \<sup>3</sup>...

1 CSNAME  
2 NAME  
3 CSNAME

\installdefinitionset \<sup>1</sup>... {<sup>2</sup>...}

1 CSNAME  
2 NAME

\installdefinitionsetmember \<sup>1</sup>... {<sup>2</sup>...} \<sup>3</sup>... {<sup>4</sup>...}

1 CSNAME  
2 NAME  
3 CSNAME  
4 NAME

\installdirectcommandhandler \<sup>1</sup>... {<sup>2</sup>...}

1 CSNAME  
2 NAME

\installdirectparameterhandler \<sup>1</sup>... {<sup>2</sup>...}

1 CSNAME  
2 NAME

\installdirectparametersethandler \<sup>1</sup>... {<sup>2</sup>...}

1 CSNAME  
2 NAME

\installdirectsetuphandler \<sup>1</sup>... {<sup>2</sup>...}

1 CSNAME  
2 NAME

\installdirectstyleandcolorhandler \<sup>1</sup>... {<sup>2</sup>...}

1 CSNAME  
2 NAME

\installframedautocommandhandler \<sup>1</sup>... {<sup>2</sup>...} \<sup>3</sup>...

1 CSNAME  
2 NAME  
3 CSNAME

\installframedcommandhandler \<sup>1</sup>... {<sup>2</sup>...} \<sup>3</sup>...

1 CSNAME  
2 NAME  
3 CSNAME

\installglobalmacrostack \\*...

\* CSNAME

\installlanguage [<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME  
2 inherits: \setuplanguage

\installlanguage [<sup>1</sup>...] [...<sup>2</sup>...]

1 NAME  
2 LANGUAGE

\installleftframerenderer {<sup>1</sup>...} {<sup>2</sup>...}

1 NAME  
2 COMMAND

\installmacrostack \\*...

\* CSNAME

<pre> \installnamespace {...} *   NAME </pre>
<pre> \installoutputroutine \.^.^ {...} 1   CSNAME 2   COMMAND </pre>
<pre> \installpagearrangement .^.^ {...} 1   NAME 2   COMMAND </pre>
<pre> \installparameterhandler \.^.^ {...} 1   CSNAME 2   NAME </pre>
<pre> \installparameterhashhandler \.^.^ {...} 1   CSNAME 2   NAME </pre>
<pre> \installparametersethandler \.^.^ {...} 1   CSNAME 2   NAME </pre>
<pre> \installparentinjector \.^.^ {...} 1   CSNAME 2   NAME </pre>
<pre> \installrightframerenderer {.^.^} {.^.^} 1   NAME 2   COMMAND </pre>
<pre> \installrootparameterhandler \.^.^ {...} 1   CSNAME 2   NAME </pre>
<pre> \installsetuphandler \.^.^ {...} 1   CSNAME 2   NAME </pre>
<pre> \installsetupononlycommandhandler \.^.^ {...} 1   CSNAME 2   NAME </pre>
<pre> \installshipoutmethod {.^.^} {.^.^} 1   NAME 2   COMMAND </pre>
<pre> \installsimplecommandhandler \.^.^ {...} \.^.^ 1   CSNAME 2   NAME 3   CSNAME </pre>
<pre> \installsimpleframedcommandhandler \.^.^ {...} \.^.^ 1   CSNAME 2   NAME 3   CSNAME </pre>
<pre> \installstyleandcolorhandler \.^.^ {...} 1   CSNAME 2   NAME </pre>



$\backslash$ installswitchcommandhandler $\backslash^{.1.} \{...\} \backslash^{.3.}$ 1 CSNAME 2 NAME 3 CSNAME
$\backslash$ installswitchsetuphandler $\backslash^{.1.} \{...\}$ 1 CSNAME 2 NAME
$\backslash$ installtexdirective $\{^{.1.}...\} \{^{.2.}...\} \{^{.3.}...\}$ 1 NAME 2 COMMAND 3 COMMAND
$\backslash$ installtextracker $\{^{.1.}...\} \{^{.2.}...\} \{^{.3.}...\}$ 1 NAME 2 COMMAND 3 COMMAND
$\backslash$ installtopframerenderer $\{^{.1.}...\} \{^{.2.}...\}$ 1 NAME 2 COMMAND
$\backslash$ installunitsseparator $\{^{.1.}...\} \{^{.2.}...\}$ 1 NAME 2 COMMAND
$\backslash$ installunitsspace $\{^{.1.}...\} \{^{.2.}...\}$ 1 NAME 2 COMMAND
$\backslash$ installversioninfo $\{^{.1.}...\} \{^{.2.}...\}$ 1 NAME 2 COMMAND
$\backslash$ integerrounding $\{^{.*}...\}$ * NUMBER
$\backslash$ interactionbar $[^{.1.}...] [^{.2.}..., ..., ^{.2.}..., ...]$ 1 NAME 2 inherits: \setupinteractionbar
$\backslash$ interactionbuttons $[^{.1.}..., ..., ^{.1.}..., ...] [^{.2.}..., ...]$ 1 inherits: \setupinteractionbar <sup>OPT</sup> 2 page subpage REFERENCE
$\backslash$ interactionmenu $[^{.1.}...] [^{.2.}..., ..., ^{.2.}..., ...]$ 1 NAME 2 inherits: \setupinteractionmenu
$\backslash$ intertext $\{^{.*}...\}$ * TEXT
$\backslash$ invokepagehandler $\{^{.1.}...\} \{^{.2.}...\}$ 1 normal none NAME 2 CONTENT
$\backslash$ italic
$\backslash$ italicbold

<code>\italiccorrection</code>
<code>\italicface</code>
<code>\item [...,*,...]</code> <code>*   REFERENCE<sup>OPT</sup></code>
<code>\items [...,..<sup>1</sup>...,..<sup>2</sup>...] {...}</code> <code>1   inherits: \setupitems<sup>OPT</sup></code> <code>2   TEXT</code>
<code>\itemtag [...,*,...]</code> <code>*   REFERENCE   <sup>OPT</sup></code>
<code>\jobfilename</code>
<code>\jobfilesuffix</code>
<code>\kap {...}</code> <code>*   TEXT</code>
<code>\keepblocks [...,<sup>1</sup>...] [...,<sup>2</sup>...]</code> <code>1   NAME                   <sup>OPT</sup></code> <code>2   NAME</code>
<code>\keeplinestogether {...}</code> <code>*   NUMBER</code>
<code>\keepunwantedspaces</code>
<code>\kerncharacters [...,<sup>1</sup>...] [...,<sup>2</sup>...]</code> <code>1   NUMBER                   <sup>OPT</sup></code> <code>2   TEXT</code>
<code>\koreancirclenumerals {...}</code> <code>*   NUMBER</code>
<code>\koreannumerals {...}</code> <code>*   NUMBER</code>
<code>\koreannumeralsc {...}</code> <code>*   NUMBER</code>
<code>\koreannumeralsp {...}</code> <code>*   NUMBER</code>
<code>\koreanparentnumerals {...}</code> <code>*   NUMBER</code>
<code>\LAMSTEX</code>
<code>\LATEX</code>
<code>\LamSTeX</code>
<code>\LaTeX</code>

<code>\LUAJITTEX</code>
<code>\LUAMETATEX</code>
<code>\LUATEX</code>
<code>\Lua</code>
<code>\LuajitTeX</code>
<code>\LuaMetaTeX</code>
<code>\LuaTeX</code>
<code>\LABELlanguage</code> instances: head label mathlabel taglabel unit operator prefix suffix btxlabel
<code>\btxlabellanguage</code>
<code>\headlanguage</code>
<code>\labellanguage</code>
<code>\mathlabellanguage</code>
<code>\operatorlanguage</code>
<code>\prefixlanguage</code>
<code>\suffixlanguage</code>
<code>\taglabellanguage</code>
<code>\unitlanguage</code>
<code>\LABELtexts {...} {...}</code> 1 KEY 2 TEXT instances: head label mathlabel
<code>\headtexts {...} {...}</code> 1 KEY 2 TEXT
<code>\labeltexts {...} {...}</code> 1 KEY 2 TEXT
<code>\mathlabeltexts {...} {...}</code> 1 KEY 2 TEXT
<code>\LABELtext {...}</code> * KEY instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

$\backslash\text{btxlabeltext}$ {...} * KEY
$\backslash\text{headtext}$ {...} * KEY
$\backslash\text{labeltext}$ {...} * KEY
$\backslash\text{mathlabeltext}$ {...} * KEY
$\backslash\text{operatortext}$ {...} * KEY
$\backslash\text{prefixtext}$ {...} * KEY
$\backslash\text{suffixtext}$ {...} * KEY
$\backslash\text{taglabeltext}$ {...} * KEY
$\backslash\text{unittext}$ {...} * KEY
$\backslash\text{LABEL}$ [..., <sup>1</sup> ...] {... <sup>2</sup> } 1 REFERENCE <sub>OPT</sub> <sub>OPT</sub> 2 TEXT
$\backslash\text{language}$ [...] * LANGUAGE
$\backslash\text{languageCharacters}$ {...} * NUMBER
$\backslash\text{languagecharacters}$ {...} * NUMBER
$\backslash\text{languagecharwidth}$ {...} * LANGUAGE
$\backslash\text{LANGUAGE}$
$\backslash\text{lastcounter}$ [...] <sup>1</sup> [...] <sup>2</sup> <sub>OPT</sub> 1 NAME 2 NUMBER
$\backslash\text{lastcountervalue}$ [...] * NAME
$\backslash\text{lastdigit}$ {...} * NUMBER
$\backslash\text{lastlinewidth}$

<code>\lastnaturalboxdp</code>
<code>\lastnaturalboxht</code>
<code>\lastnaturalboxwd</code>
<code>\lastpredefinedsymbol</code>
<code>\lastrealpage</code>
<code>\lastrealpagenumber</code>
<code>\lastsubcountervalue [.<sup>1</sup>.] [.<sup>2</sup>.]</code> 1 NAME 2 NUMBER
<code>\lastsubpage</code>
<code>\lastsubpagenumber</code>
<code>\lasttwodigits {.*}</code> * NUMBER
<code>\lastuserpage</code>
<code>\lastuserpagenumber</code>
<code>\lateluacode {.*}</code> * COMMAND
<code>\layeredtext [...<sup>1</sup>...<sup>2</sup>...] [...<sup>3</sup>...<sup>4</sup>...] {...} {...}</code> 1 inherits: \setuplayer <sup>OPT</sup> 2 inherits: \setuplayeredtext 3 TEXT 4 CONTENT
<code>\layerheight</code>
<code>\layerwidth</code>
<code>\lazysavetaggedtwopassdata {.<sup>1</sup>.} {.<sup>2</sup>.} {.<sup>3</sup>.} {.<sup>4</sup>.}</code> 1 NAME 2 NUMBER 3 NAME 4 CONTENT
<code>\lazysavetwopassdata {.<sup>1</sup>.} {.<sup>2</sup>.} {.<sup>3</sup>.}</code> 1 NAME 2 NUMBER 3 CONTENT
<code>\lbox .<sup>1</sup>. {.<sup>2</sup>.}</code> 1 TEXT <sup>OPT</sup> 2 CONTENT

$\left$ ... * \bgroup \egroup \letteropenbrace [ ] ( ) < > /      \lbrace \lbracket \lbrack \lparenthesis \lparent \lparen \langle \llangle \lVert \lvert \solidus \lfloor \lceil \lceil \ulcorner \llcorner \loustache \llbracket \lgroup \linterval \lointerval \llointerval \lrointerval \{ \[ \[ \[ \[ \[ CHARACTER
$\leftaligned$ {...} * CONTENT
$\leftbottombox$ {...} * CONTENT
$\leftbox$ {...} * CONTENT
$\lefthbox$ {...} * CONTENT
$\leftLABELtext$ {...} * KEY instances: head label mathlabel
$\leftheadtext$ {...} * KEY
$\leftlabeltext$ {...} * KEY
$\leftmathlabeltext$ {...} * KEY
$\leftline$ {...} * CONTENT
$\lefttorrighthbox$ ... <sup>1</sup> {...} <sup>2</sup> 1 TEXT OPT 2 CONTENT
$\lefttorrightvbox$ ... <sup>1</sup> {...} <sup>2</sup> 1 TEXT OPT 2 CONTENT
$\lefttorrightvtop$ ... <sup>1</sup> {...} <sup>2</sup> 1 TEXT OPT 2 CONTENT
$\leftskipadaption$
$\leftsubguillemot$
$\lefttopbox$ {...} * CONTENT
$\lefttoright$
$\lefttorrighthbox$ ... <sup>1</sup> {...} <sup>2</sup> 1 TEXT OPT 2 CONTENT

<code>\lefttorightvbox</code> <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
<code>\lefttorightvtop</code> <sup>1</sup> ... { <sup>2</sup> ...} 1 TEXT OPT 2 CONTENT
<code>\letbeundefined</code> { <sup>*</sup> ...} <sup>*</sup> NAME
<code>\letcatcodecommand</code> \ <sup>1</sup> ... <sup>2</sup> ... \ <sup>3</sup> ... 1 CSNAME 2 CHARACTER NUMBER 3 CSNAME
<code>\letcscsname</code> \ <sup>1</sup> ... \csname <sup>2</sup> ... \endcsname 1 CSNAME 2 NAME
<code>\letcsnamecs</code> \csname <sup>1</sup> ... \endcsname \ <sup>2</sup> ... 1 NAME 2 CSNAME
<code>\letcsnamecsname</code> \csname <sup>1</sup> ... \endcsname \csname <sup>2</sup> ... \endcsname 1 NAME 2 NAME
<code>\letdummyparameter</code> { <sup>1</sup> ...} \ <sup>2</sup> ... 1 KEY 2 CSNAME
<code>\letempty</code> \ <sup>*</sup> ... <sup>*</sup> CSNAME
<code>\letgvalue</code> { <sup>1</sup> ...} \ <sup>2</sup> ... 1 NAME 2 CSNAME
<code>\letgvalueempty</code> { <sup>*</sup> ...} <sup>*</sup> NAME
<code>\letgvalurelax</code> { <sup>*</sup> ...} <sup>*</sup> NAME
<code>\letterampersand</code>
<code>\letterat</code>
<code>\letterbackslash</code>
<code>\letterbar</code>
<code>\letterbgroup</code>
<code>\letterclosebrace</code>
<code>\lettercolon</code>

<code>\letterdollar</code>
<code>\letterdoublequote</code>
<code>\lettereingroup</code>
<code>\letterescape</code>
<code>\letterexclamationmark</code>
<code>\letterhash</code>
<code>\letterhat</code>
<code>\letterleftbrace</code>
<code>\letterleftbracket</code>
<code>\letterleftparenthesis</code>
<code>\letterless</code>
<code>\lettermore</code>
<code>\letteropenbrace</code>
<code>\letterpercent</code>
<code>\letterquestionmark</code>
<code>\letterrightbrace</code>
<code>\letterrightbracket</code>
<code>\letterrightparenthesis</code>
<code>\lettersinglequote</code>
<code>\letterslash</code>
<code>\letterspacing</code> [ <sup>1</sup> ...] { <sup>2</sup> ...} 1    NUMBER                    OPT 2    TEXT
<code>\lettertilde</code>
<code>\letterunderscore</code>
<code>\letvalue</code> { <sup>1</sup> ...} \ <sup>2</sup> .. 1    NAME 2    CSNAME
<code>\letvalueempty</code> { <sup>1</sup> ...} *    NAME



<code>\letvaluerelax {...}</code> * NAME
<code>\lfence {...}</code> * \bgroup \egroup \letteropenbrace [ ] ( ) < > /             \lbrace \lbracket \lbrack \lparenthesis \lparent \lparen \langle \llangle \lVert \lvert \solidus \lfloor \lceil \lceil \ulcorner \llcorner \lmoustache \llbracket \lgroup \linterval \lointerval \llointerval \lrointerval \{ \[ \[ \[ \[ \[ CHARACTER
<code>\lhbox {...}</code> * CONTENT
<code>\limitatefirstline {...} {...} {...}</code> 1 TEXT 2 DIMENSION 3 COMMAND
<code>\limitatelines {...} {...} {...}</code> 1 NUMBER 2 COMMAND 3 TEXT
<code>\limitatetext {...} {...} {...}</code> 1 TEXT 2 [-+]DIMENSION 3 COMMAND
<code>\limitatetext {...} {...} {...}</code> 1 TEXT 2 [-+]DIMENSION 3 COMMAND
<code>\limitatetext {...} {...} {...}</code> 1 TEXT 2 [-+]DIMENSION 3 COMMAND
<code>\line {...}</code> * CONTENT
<code>\linebox {...}</code> * CONTENT
<code>\LINENOTE {...}</code> * TEXT instances: linenote
<code>\linenote {...}</code> * TEXT
<code>\linespanningtext {...} {...} {...}</code> 1 TEXT 2 DIMENSION 3 FONT
<code>\linewidth</code>
<code>\listcitation [...<sup>1</sup>...] [...<sup>2</sup>]</code> 1 reference = REFERENCE alternative = default category entry short page num textnum year index tag keywords author authoryears authornum authoryear before = COMMAND after = COMMAND left = COMMAND right = COMMAND inherits: \setupbtx 2 REFERENCE

`\listcitation [...]1 [...]2`

1 default category<sup>OPT</sup> entry short page num textnum year index tag keywords author authoryears authornum authoryear  
2 REFERENCE

`\listcitation [...]1 [...]2`

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx  
2 KEY = VALUE

`\listcite [...]1 [...]2`

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx  
2 REFERENCE

`\listcite [...]1 [...]2`

1 default category<sup>OPT</sup> entry short page num textnum year index tag keywords author authoryears authornum authoryear  
2 REFERENCE

`\listcite [...]1 [...]2`

1 reference = REFERENCE  
alternative = default category entry short page num textnum year index tag keywords author authoryears authornum  
authoryear  
before = COMMAND  
after = COMMAND  
left = COMMAND  
right = COMMAND  
inherits: \setupbtx  
2 KEY = VALUE

`\listlength`

`\listnamespaces`

`\llap {...}`

\* CONTENT

`\loadanyfile [...]`

\* FILE

`\loadanyfileonce [...]`

\* FILE

`\loadbtxdefinitionfile [...]`

\* FILE

`\loadbtxreplacementfile [...]`

\* FILE

`\loadcldfile [...]`

\* FILE

\loadcldfileonce [...] * FILE
\loadfontgoodies [...] * FILE
\loadluafile [...] * FILE
\loadluafileonce [...] * FILE
\loadspellchecklist [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 NAME 2 FILE
\loadtexfile [...] * FILE
\loadtexfileonce [...] * FILE
\loadtypescriptfile [...] * FILE
\localframed [ <sup>1</sup> ] [..., <sup>2</sup> ... <sub>OPT</sub> ,...] { <sup>3</sup> ...} 1 NAME 2 inherits: \setupframed 3 CONTENT
\localframedwithsettings [ <sup>1</sup> ] [..., <sup>2</sup> ... <sub>OPT</sub> ,...] { <sup>3</sup> ...} 1 NAME 2 inherits: \setupframed 3 CONTENT
\localhsize
\localpopbox ... * CSNAME NUMBER
\localpopmacro \... * CSNAME
\localpushbox ... * CSNAME NUMBER
\localpushmacro \... * CSNAME
\localundefine {...} * NAME
\locatedfilepath
\locatefilepath {...} * FILE

$\backslash\text{locfilename} \{...\}$ * FILE
$\backslash\text{lohi} [^{.1}] \{...\} \{...\}$ 1 left <del>right</del> 2 CONTENT 3 CONTENT
$\backslash\text{lomihi} \{...\} \{...\} \{...\}$ 1 CONTENT 2 CONTENT 3 CONTENT
$\backslash\text{low} \{...\}$ * CONTENT
$\backslash\text{lowerbox} \{...\} \backslash^{.2} \{...\}$ 1 DIMENSION 2 CSNAME 3 CONTENT
$\backslash\text{lowercased} \{...\}$ * TEXT
$\backslash\text{lowercasestring} \dots \backslash\text{to} \backslash^{.2}$ 1 TEXT 2 CSNAME
$\backslash\text{lowerlefthdoubleninequote}$
$\backslash\text{lowerleftsingleninequote}$
$\backslash\text{lowerrightdoubleninequote}$
$\backslash\text{lowerrightsingleninequote}$
$\backslash\text{LOWHIGH} [^{.1}] \{...\} \{...\}$ 1 left <del>right</del> <sup>OPT</sup> 2 CONTENT 3 CONTENT
$\backslash\text{LOWMIDHIGH} \{...\} \{...\} \{...\}$ 1 CONTENT 2 CONTENT 3 CONTENT
$\backslash\text{LOW} \{...\}$ * CONTENT <b>instances:</b> unitslow
$\backslash\text{unitslow} \{...\}$ * CONTENT
$\backslash\text{lrtbbox} \{...\} \{...\} \{...\} \{...\} \{...\}$ 1 DIMENSION 2 DIMENSION 3 DIMENSION 4 DIMENSION 5 CONTENT

$\backslash\text{top}$ $\overset{1}{...}$ $\{\overset{2}{...}\}$ 1 TEXT <small>OPT</small> 2 CONTENT
$\backslash\text{trhbox}$ $\overset{1}{...}$ $\{\overset{2}{...}\}$ 1 TEXT <small>OPT</small> 2 CONTENT
$\backslash\text{trvbox}$ $\overset{1}{...}$ $\{\overset{2}{...}\}$ 1 TEXT <small>OPT</small> 2 CONTENT
$\backslash\text{trvtop}$ $\overset{1}{...}$ $\{\overset{2}{...}\}$ 1 TEXT <small>OPT</small> 2 CONTENT
$\backslash\text{luaocode}$ $\{...\}$ * COMMAND
$\backslash\text{luaconditional}$ $\backslash^*...$ * CSNAME
$\backslash\text{luaenvironment}$ $...$ * FILE
$\backslash\text{luaexpanded}$ $\{...\}$ * COMMAND
$\backslash\text{luaexpr}$ $\{...\}$ * CONTENT
$\backslash\text{luafunction}$ $\{...\}$ * COMMAND
$\backslash\text{luajitTeX}$
$\backslash\text{luamajorversion}$
$\backslash\text{luametaTeX}$
$\backslash\text{luaminorversion}$
$\backslash\text{luaparameterset}$ $\{\overset{1}{...}\}$ $\{\overset{2}{...}\}$ 1 NAME 2 CONTENT
$\backslash\text{luasetup}$ $\{...\}$ * NAME
$\backslash\text{luaTeX}$
$\backslash\text{luaversion}$
$\backslash\text{METAFONT}$
$\backslash\text{METAFUN}$

<code>\METAPOST</code>
<code>\MetaFont</code>
<code>\MetaFun</code>
<code>\MetaPost</code>
<code>\MKII</code>
<code>\MKIV</code>
<code>\MKIX</code>
<code>\MKVI</code>
<code>\MKXI</code>
<code>\MONTH {.*.}</code> *    NUMBER
<code>\MONTHLONG {.*.}</code> *    NUMBER
<code>\MONTHSHORT {.*.}</code> *    NUMBER
<code>\MPanchor {.*.}</code> *    NAME
<code>\MPbetex {.*.}</code> *    NAME
<code>\MPc {.*.}</code> *    NAME
<code>\MPcode {<sup>1</sup>.*.} {<sup>2</sup>.*.}</code> 1    NAME        OPT 2    CONTENT
<code>\MPcolor {.*.}</code> *    COLOR
<code>\MPcoloronly {.*.}</code> *    COLOR
<code>\MPcolumn {.*.}</code> *    NAME
<code>\MPd {.*.}</code> *    NAME
<code>\MPdrawing {.*.}</code> *    CONTENT

\MPfontsizehskip {...} *    FONT
\MPgetmultipars {...} {...} 1    NAME 2    NAME
\MPgetmultishape {...} {...} 1    NAME 2    NAME
\MPgetposboxes {..., <sup>1</sup> ...} {... <sup>2</sup> } 1    NAME 2    NAME
\MPH {...} *    NAME
\MPII
\MPIV
\MPinclusions [... <sup>1</sup> ] {... <sup>2</sup> } {... <sup>3</sup> } 1    +                    OPT        OPT 2    NAME 3    CONTENT
\MPleftskip {...} *    NAME
\MPll {...} *    NAME
\MPlr {...} *    NAME
\MPls {...} *    NAME
\MPmenubuttons {...} *    NAME
\MPn {...} *    NAME
\MPoptions {...} *    COLOR
\MPoverlayanchor {...} *    NAME
\MPp {...} *    NAME
\MPpage {...} *    NAME

\MPpardata {...}

\* NAME

$$\backslash \text{MPplus} \{ \dots \}^1 \{ \dots \}^2 \{ \dots \}^3$$

1 NAME

2 NUMBER

3 CONTENT

$$\backslash \text{MP}_{\text{pos}} \{..*\}$$

\* NAME

$$\backslash MPpositiongraphic \{...\} \{...,.. \overset{2}{=} ..,..\}$$

1 NAME

```

1      NAME
2      KEY  =  VALUE

```

$$\backslash \text{MPposset} \{...\}$$

\* NAME

$$\backslash\mathrm{MP}r \{.\overset{*}{.}\}$$

\* NAME

$$\backslash \text{MPrawvar} \{...\} \{...\}$$

1 NAME

2 KEY

$$\backslash \text{MPregion} \{...\}$$

\* NAME

`\MPrest {..1.} {..2.}`

1 NAME

2 CONTENT

\MPrightskip {...}

\* NAME

$$\backslash\mathrm{MPrs}\{...\}$$

\* NAME

`\MPstring {...}`

\* NAME

$$\backslash\mathrm{MPtext}\{\dots\}$$

\* NAME

`\MPtransparency {...}`

\* COLOR

$$\backslash\mathrm{MPu1} \{.\ast.\}$$

\* NAME

$$\backslash \text{MPur} \{...\}$$

\* NAME

\MPVI

$$\backslash \text{MPv} \quad \{ \dots \}^1 \quad \{ \dots \}^2 \quad \{ \dots \}^3$$

1 NAME

1	NAME
2	NUMBER

3 CONTENT



<code>\MPvar {...}</code> * KEY
<code>\MPvariable {...}</code> * KEY
<code>\MPvv {...} {...}</code> 1 NAME 2 CONTENT
<code>\MPw {...}</code> * NAME
<code>\MPwhd {...}</code> * NAME
<code>\MPx {...}</code> * NAME
<code>\MPxy {...}</code> * NAME
<code>\MPxywhd {...}</code> * NAME
<code>\MPy {...}</code> * NAME
<code>\m [...] {...}</code> 1 NAME 2 CONTENT
<code>\mainlanguage [...]</code> * LANGUAGE
<code>\makecharacteractive ...</code> * CHARACTER
<code>\makerawcommalist [...<sup>1</sup>,...] \<sup>2</sup>...</code> 1 COMMAND 2 CSNAME
<code>\makestrutofbox ...</code> * CSNAME NUMBER
<code>\mapfontsize [...] [...<sup>2</sup>]</code> 1 DIMENSION 2 DIMENSION
<code>\margindata [...] [...,<sup>2</sup>...<sub>OPT</sub>,...] [...,<sup>3</sup>...<sub>OPT</sub>,...] {...<sup>4</sup>}</code> 1 NAME 2 reference = REFERENCE inherits: \setupmargindata 3 inherits: \setupmarginframed 4 CONTENT

`\MARGINDATA [...,\1...,...] [...,\2...,...] {\3...}`

1 reference = REFERENCE<sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

instances: inleftmargin inrightmargin inoutermargin ininnermargin inleftedge inrightedge  
 inouteredge ininneredge atleftmargin atrightmargin inleft inright inouter ininner inmargin  
 inother margintext

`\atleftmargin [...,\1...,...] [...,\2...,...] {\3...}`

1 reference = REFERENCE<sup>T</sup><sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\atrightmargin [...,\1...,...] [...,\2...,...] {\3...}`

1 reference = REFERENCE<sup>OPT</sup><sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\ininner [...,\1...,...] [...,\2...,...] {\3...}`

1 reference = REFERENCE<sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\ininneredge [...,\1...,...] [...,\2...,...] {\3...}`

1 reference = REFERENCE<sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\ininnermargin [...,\1...,...] [...,\2...,...] {\3...}`

1 reference = REFERENCE<sup>OPT</sup><sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\inleft [...,\1...,...] [...,\2...,...] {\3...}`

1 reference = REFERENCE<sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\inleftedge [...,\1...,...] [...,\2...,...] {\3...}`

1 reference = REFERENCE<sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\inleftmargin [...,\1...,...] [...,\2...,...] {\3...}`

1 reference = REFERENCE<sup>T</sup><sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

`\inmargin [...,\1...,...] [...,\2...,...] {\3...}`

1 reference = REFERENCE<sup>OPT</sup>  
 inherits: \setupmargindata  
 2 inherits: \setupmarginframed  
 3 CONTENT

```

\inother [...1...1...] [...2...2...] {...3}
1 reference = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inouter [...1...1...] [...2...2...] {...3}
1 reference = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inouteredge [...1...1...] [...2...2...] {...3}
1 reference = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inoutermargin [...1...1...] [...2...2...] {...3}
1 reference = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inright [...1...1...] [...2...2...] {...3}
1 reference = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inrightedge [...1...1...] [...2...2...] {...3}
1 reference = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\inrightmargin [...1...1...] [...2...2...] {...3}
1 reference = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\marginext [...1...1...] [...2...2...] {...3}
1 reference = REFERENCEOPT
  inherits: \setupmargindata
2 inherits: \setupmarginframed
3 CONTENT

```

```

\markcontent [...1] {...2}
1 reset all NAMEOPT
2 CONTENT

```

```

\markedpages [...]
* NAME

```

```

\marking (...1,...) (...2,...) [...3]
1 POSITION
2 POSITION
3 REFERENCE

```

```

\markinjector [...]
* NAME

```

$\backslash\text{markpage}$ [ <sup>1</sup> ..] [ <sup>2</sup> ...,...] 1 NAME OPT 2 [-+]NUMBER
$\backslash\text{mat}$ {...} * CONTENT
$\backslash\text{math}$ [ <sup>1</sup> ..] {... <sup>2</sup> ...} 1 NAME OPT 2 CONTENT
$\backslash\text{mathbf}$
$\backslash\text{mathbi}$
$\backslash\text{mathblackboard}$
$\backslash\text{mathbs}$
$\backslash\text{MATHCOMMAND}$ {... <sup>1</sup> ...} {... <sup>2</sup> ...} 1 TEXT OPT OPT 2 TEXT
$\backslash\text{mathdefault}$
$\backslash\text{mathdouble}$ [ <sup>1</sup> ..] {... <sup>2</sup> ...} {... <sup>3</sup> ...} {... <sup>4</sup> ...} 1 both vfenced OPT 2 NUMBER 3 TEXT 4 TEXT
$\backslash\text{MATHDOUBLEEXTENSIBLE}$ {... <sup>1</sup> ...} {... <sup>2</sup> ...} 1 TEXT 2 TEXT instances: doublebar doublebrace doubleparent doublebracket overbarunderbar overbraceunderbrace overparentunderparent overbracketunderbracket
$\backslash\text{doublebar}$ {... <sup>1</sup> ...} {... <sup>2</sup> ...} 1 TEXT 2 TEXT
$\backslash\text{doublebrace}$ {... <sup>1</sup> ...} {... <sup>2</sup> ...} 1 TEXT 2 TEXT
$\backslash\text{doublebracket}$ {... <sup>1</sup> ...} {... <sup>2</sup> ...} 1 TEXT 2 TEXT
$\backslash\text{doubleparent}$ {... <sup>1</sup> ...} {... <sup>2</sup> ...} 1 TEXT 2 TEXT
$\backslash\text{overbarunderbar}$ {... <sup>1</sup> ...} {... <sup>2</sup> ...} 1 TEXT 2 TEXT
$\backslash\text{overbraceunderbrace}$ {... <sup>1</sup> ...} {... <sup>2</sup> ...} 1 TEXT 2 TEXT

$\overbrace{\underbrace{\dots}^{\scriptscriptstyle 1}}^{\scriptscriptstyle 2}$
1 TEXT 2 TEXT
$\overparent{\underparent{\dots}^{\scriptscriptstyle 1}}^{\scriptscriptstyle 2}$
1 TEXT 2 TEXT
$\mathbf{mathematics} [\dots]^{\scriptscriptstyle 1} \{\dots\}^{\scriptscriptstyle 2}$
1 NAME 2 CONTENT
$\mathbf{mathematics} [\dots]^{\scriptscriptstyle 1} \{\dots\}^{\scriptscriptstyle 2}$
1 inherits: $\mathbf{setupmathematics}$ 2 CONTENT
$\mathbf{MATHEXTENSIBLE} \{\dots\}^{\scriptscriptstyle 1} \{\dots\}^{\scriptscriptstyle 2}$
1 TEXT 2 TEXT
instances: xrel xequal xleftarrow xrightarrow xleftrightharpoon xLeftarrow xRightarrow xleftrightharpoon xtwoheadleftarrow xtwoheadrightarrow xmapsto xhookleftarrow xhookrightarrow xleftharpoondown xleftharpoonup xrightharpoondown xrighttharpoonup xrightoverleftarrow xleftrightharpoons xrightleftharpoons xtriplerel mrel mequal mleftarrow mrightarrow mleftrightharpoon mLeftarrow mRightarrow mLeftrightharpoon mtwoheadleftarrow mtwoheadrightarrow mmapsto mhookleftarrow mhookrightarrow mleftharpoondown mleftharpoonup mrightharpoondown mrightharpoonup mrightoverleftarrow mleftrightharpoons mrightleftharpoons mtriplerel eleftrightarrowfill erightarrowfill eleftrightharpoonfill etwoheadrightarrowfill eleftharpoondownfill eleftharpoonupfill erightharpoondownfill erightharpoonupfill eoverbarfill eunderbarfill eoverbracefill eunderbracefill eoverparentfill eunderparentfill eoverbracketfill eunderbracketfill trel tequal tmapsto tleftarrow trightarrow tleftrightharpoon tLeftarrow tRightarrow tLeftrightharpoon ttwoheadleftarrow ttwoheadrightarrow thookleftarrow thookrightarrow tleftharpoondown tleftharpoonup trightharpoondown trightharpoonup trightoverleftarrow tleftrightharpoons trightleftharpoons ttriplerel cleftarrow crightarrow crightoverleftarrow
$\cleftarrow \{\dots\}^{\scriptscriptstyle 1} \{\dots\}^{\scriptscriptstyle 2}$
1 TEXT 2 TEXT
$\crightarrow \{\dots\}^{\scriptscriptstyle 1} \{\dots\}^{\scriptscriptstyle 2}$
1 TEXT 2 TEXT
$\crightoverleftarrow \{\dots\}^{\scriptscriptstyle 1} \{\dots\}^{\scriptscriptstyle 2}$
1 TEXT 2 TEXT
$\eleftrightarrowfill \{\dots\}^{\scriptscriptstyle 1} \{\dots\}^{\scriptscriptstyle 2}$
1 TEXT 2 TEXT
$\eleftharpoondownfill \{\dots\}^{\scriptscriptstyle 1} \{\dots\}^{\scriptscriptstyle 2}$
1 TEXT 2 TEXT
$\eleftharpoonupfill \{\dots\}^{\scriptscriptstyle 1} \{\dots\}^{\scriptscriptstyle 2}$
1 TEXT 2 TEXT
$\eleftrightarrowfill \{\dots\}^{\scriptscriptstyle 1} \{\dots\}^{\scriptscriptstyle 2}$
1 TEXT 2 TEXT

`\eoverbarfill {...} {...}`

1    TEXT                    OPT            OPT  
2    TEXT

`\eoverbracefill {...} {...}`

1    TEXT                    OPT            OPT  
2    TEXT

`\eoverbracketfill {...} {...}`

1    TEXT                    OPT            OPT  
2    TEXT

`\eoverparentfill {...} {...}`

1    TEXT                    OPT            OPT  
2    TEXT

`\erightarrowfill {...} {...}`

1    TEXT                    OPT            OPT  
2    TEXT

`\erightharpoondownfill {...} {...}`

1    TEXT                    OPT            OPT  
2    TEXT

`\erightharpoonupfill {...} {...}`

1    TEXT                    OPT            OPT  
2    TEXT

`\etwoheadrightarrowfill {...} {...}`

1    TEXT                    OPT            OPT  
2    TEXT

`\eunderbarfill {...} {...}`

1    TEXT                    OPT            OPT  
2    TEXT

`\eunderbracefill {...} {...}`

1    TEXT                    OPT            OPT  
2    TEXT

`\eunderbracketfill {...} {...}`

1    TEXT                    OPT            OPT  
2    TEXT

`\eunderparentfill {...} {...}`

1    TEXT                    OPT            OPT  
2    TEXT

`\mequal {...} {...}`

1    TEXT            OPT            OPT  
2    TEXT

`\mhookleftarrow {...} {...}`

1    TEXT                    OPT            OPT  
2    TEXT

`\mhookrightarrow {...} {...}`

1    TEXT                    OPT            OPT  
2    TEXT

`\mLeftarrow {...} {...}`

1    TEXT                    OPT            OPT

2    TEXT

`\mLeftrightarrow {...} {...}`

1    TEXT                    OPT            OPT

2    TEXT

`\mleftarrow {...} {...}`

1    TEXT                    OPT            OPT

2    TEXT

`\mleftharpoondown {...} {...}`

1    TEXT                    OPT            OPT

2    TEXT

`\mleftharpoonup {...} {...}`

1    TEXT                    OPT            OPT

2    TEXT

`\mleftrightharpoonrightarrow {...} {...}`

1    TEXT                    OPT            OPT

2    TEXT

`\mleftrightharpoons {...} {...}`

1    TEXT                    OPT            OPT

2    TEXT

`\mmapsto {...} {...}`

1    TEXT                    OPT            OPT

2    TEXT

`\mRrightarrow {...} {...}`

1    TEXT                    OPT            OPT

2    TEXT

`\mrel {...} {...}`

1    TEXT    OPT            OPT

2    TEXT

`\mrightarrow {...} {...}`

1    TEXT                    OPT            OPT

2    TEXT

`\mrightharpoondown {...} {...}`

1    TEXT                    OPT            OPT

2    TEXT

`\mrightharpoonup {...} {...}`

1    TEXT                    OPT            OPT

2    TEXT

`\mrightrightleftharpoons {...} {...}`

1    TEXT                    OPT            OPT

2    TEXT

`\mrightrightoverleftarrow {...} {...}`

1    TEXT                    OPT            OPT

2    TEXT

`\mtriplelrel {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\mtwoheadleftarrow {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\mtwoheadrightarrow {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\tequal {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\thookleftarrow {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\thookrightarrow {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\tLeftarrow {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\tLeftrightarrow {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\tleftarrow {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\tleftharpoondown {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\tleftharpoonup {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\tleftrightarrow {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\tleftrightharpoons {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\tmapsto {...} {...}`

1 TEXT OPT OPT  
2 TEXT

`\tRrightarrow {...} {...}`

1 TEXT OPT OPT  
2 TEXT



`\trel {...} {...}`

1    TEXT    OPT    OPT  
2    TEXT

`\trightarrow {...} {...}`

1    TEXT    OPT    OPT  
2    TEXT

`\trightharpoondown {...} {...}`

1    TEXT    OPT    OPT  
2    TEXT

`\trightharpoonup {...} {...}`

1    TEXT    OPT    OPT  
2    TEXT

`\trightleftharpoons {...} {...}`

1    TEXT    OPT    OPT  
2    TEXT

`\trightoverleftarrow {...} {...}`

1    TEXT    OPT    OPT  
2    TEXT

`\ttriplelrel {...} {...}`

1    TEXT    OPT    OPT  
2    TEXT

`\twoheadleftarrow {...} {...}`

1    TEXT    OPT    OPT  
2    TEXT

`\twoheadrightarrow {...} {...}`

1    TEXT    OPT    OPT  
2    TEXT

`\xequal {...} {...}`

1    TEXT    OPT    OPT  
2    TEXT

`\xhookleftarrow {...} {...}`

1    TEXT    OPT    OPT  
2    TEXT

`\xhookrightarrow {...} {...}`

1    TEXT    OPT    OPT  
2    TEXT

`\xLeftarrow {...} {...}`

1    TEXT    OPT    OPT  
2    TEXT

`\xLeftrightarrow {...} {...}`

1    TEXT    OPT    OPT  
2    TEXT

`\xleftarrow {...} {...}`

1    TEXT    OPT    OPT  
2    TEXT

$$\xleftarrow{\text{tharpoondown}} \{...\} \{...\}$$

1	TEXT	OPT	OPT
2	TEXT		

$$\xleftarrow{\text{tharpoonup}} \{...\} \{...\}$$

1	TEXT	OPT	OPT
2	TEXT		

$$\xleftrightarrow{\dots} \{\dots\}$$

1	TEXT	OPT	OPT
2	TEXT		

$$\xleftrightarrow{\hspace{1cm}} \{.\!\!.^1.\!\!.\} \{.\!\!.^2.\!\!.\}$$

1	TEXT	OPT	OPT
2	TEXT		

$$\backslash xmapsto \{.^1..\} \{.^2..\}$$

1	TEXT	OPT	OPT
2	TEXT		

 $\xrightarrow{\{...\} \{...\}}$ 

1	TEXT	OPT	OPT
2	TEXT		

$$\backslash xrel \{.^1..\} \{.^2..\}$$

1	TEXT	OPT	OPT
2	TEXT		

 $\xrightarrow{\{...\} \{...\}}$ 

1	TEXT	OPT	OPT
2	TEXT		

$$\xrightarrow{\text{tharpoondown}} \{...\} \{...\}$$

1	TEXT	OPT	OPT
2	TEXT		

$$\xrightarrow{\text{...}} \text{...}$$

1	TEXT	OPT	OPT
2	TEXT		

 $\xrightarrow{\text{left}} \{...\} \{...\}$ 

1	TEXT	OPT	OPT
2	TEXT		

$$\xrightarrow{\scriptscriptstyle 1} \xleftarrow{\scriptscriptstyle 2}$$

1	TEXT	OPT	OPT
2	TEXT		

$$\backslash xtriplerel \{...\} \{...\}$$

1	TEXT	OPT	OPT
2	TEXT		

 $\twoheadrightarrow \{...\} \{...\}$ 

1	TEXT	OPT	OPT
2	TEXT		

 $\xrightarrow{\text{twohead}} \{...\} \{...\}$ 

```

1  TEXT                                OPT      OPT
2  TEXT

```

 $\mathfrak{f}$

$\backslash\text{MATHFRAMED}$ [ $\dots$ <sup>1</sup> $\stackrel{=}{\dots}$ $\dots$ ] { $\dots$ <sup>2</sup> } 1 inherits: $\backslash\text{setupmathframed}$ 2 CONTENT instances: mframed inmframed mcframed
$\backslash\text{inmframed}$ [ $\dots$ <sup>1</sup> $\stackrel{=}{\dots}$ $\dots$ ] { $\dots$ <sup>2</sup> } 1 inherits: $\backslash\text{setupmathframed}$ 2 CONTENT
$\backslash\text{mcframed}$ [ $\dots$ <sup>1</sup> $\stackrel{=}{\dots}$ $\dots$ ] { $\dots$ <sup>2</sup> } 1 inherits: $\backslash\text{setupmathframed}$ 2 CONTENT
$\backslash\text{mframed}$ [ $\dots$ <sup>1</sup> $\stackrel{=}{\dots}$ $\dots$ ] { $\dots$ <sup>2</sup> } 1 inherits: $\backslash\text{setupmathframed}$ 2 CONTENT
$\backslash\text{mathfunction}$ { $\dots$ } * CONTENT
$\backslash\text{mathit}$
$\backslash\text{mathitalic}$
$\backslash\text{MATHMATRIX}$ { $\dots$ } * CONTENT
$\backslash\text{mathop}$ { $\dots$ } * CONTENT
$\backslash\text{MATHORNAMENT}$ { $\dots$ } * CONTENT
$\backslash\text{mathover}$ [ $\dots$ <sup>1</sup> ] { $\dots$ <sup>2</sup> } { $\dots$ <sup>3</sup> } 1 top vfenced <sup>OPT</sup> 2 NUMBER 3 TEXT
$\backslash\text{MATHOVEREXTENSIBLE}$ { $\dots$ } * TEXT
$\backslash\text{MATHOVERTEXTEXTENSIBLE}$ { $\dots$ <sup>1</sup> } { $\dots$ <sup>2</sup> } 1 TEXT 2 TEXT instances:
$\backslash\text{MATHRADICAL}$ [ $\dots$ <sup>1</sup> ] { $\dots$ <sup>2</sup> } 1 TEXT <sup>OPT</sup> 2 CONTENT
$\backslash\text{mathrm}$
$\backslash\text{mathscript}$
$\backslash\text{mathsl}$
$\backslash\text{mathss}$

$\backslash\mathtext$ $\dots \{.^2.\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathtextbf$ $\dots \{.^2.\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathtextbi$ $\dots \{.^2.\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathtextbs$ $\dots \{.^2.\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathtextit$ $\dots \{.^2.\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathtextsl$ $\dots \{.^2.\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathtexttf$ $\dots \{.^2.\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathtf$
$\backslash\mathtripler$ $[.^1.] \{.^2.\} \{.^3.\} \{.^4.\}$ 1    NAME            OPT            OPT            OPT            OPT 2    TEXT 3    TEXT 4    TEXT
$\backslash\mathtripler$ $[.^1.] \{.^2.\} \{.^3.\} \{.^4.\}$ 1    NAME            OPT            OPT            OPT            OPT 2    TEXT 3    TEXT 4    TEXT
$\backslash\mathtt$
$\backslash\mathunder$ $[.^1.] \{.^2.\} \{.^3.\}$ 1    bottom vfence $\mathcal{I}$ 2    NUMBER 3    TEXT
$\backslash\mathunderextensible$ $\{.^*.\}$ *    TEXT
$\backslash\mathunderextextensible$ $\{.^1.\} \{.^2.\}$ 1    TEXT 2    TEXT instances:
$\backslash\mathunstacked$
$\backslash\mathupright$

$\backslash\mathsf{word} \dots \{.^2.\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathsf{wordbf} \dots \{.^2.\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathsf{wordbi} \dots \{.^2.\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathsf{wordbs} \dots \{.^2.\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathsf{wordit} \dots \{.^2.\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathsf{wordsl} \dots \{.^2.\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathsf{wordtf} \dots \{.^2.\}$ 1    TEXT            OPT 2    TEXT
$\backslash\mathsf{math} [\dots\overset{1}{=}\dots] \{.^2.\}$ 1    inherits: $\backslash\mathsf{setupmathematics}$ OPT 2    CONTENT
$\backslash\mathsf{maxaligned} \{.^*\}$ *    CONTENT
$\backslash\mathsf{mbox} \{.^*\}$ *    CONTENT
$\backslash\mathsf{measure} \{.^*\}$ *    NAME
$\backslash\mathsf{measured} \{.^*\}$ *    NAME
$\backslash\mathsf{medskip}$
$\backslash\mathsf{medspace}$
$\backslash\mathsf{menubutton} [\dots\overset{1}{=}\dots] \{.^2.\} \{.^3.\}$ 1    inherits: $\backslash\mathsf{setupbutton}$ 2    TEXT 3    REFERENCE
$\backslash\mathsf{menubutton} [.^1] [\dots\overset{2}{=}\dots] \{.^3.\} \{.^4.\}$ 1    NAME 2    inherits: $\backslash\mathsf{setupinteractionmenu}$ OPT 3    TEXT 4    REFERENCE

<code>\message {...}</code> * TEXT
<code>\mfence {...}</code> * CHARACTER
<code>\mfunction {...}</code> * CONTENT
<code>\mfunctionlabeltext {...}</code> * NAME
<code>\mhbox {...}</code> * CONTENT
<code>\midaligned {...}</code> * CONTENT
<code>\middle ...</code> * CHARACTER
<code>\middlealigned {...}</code> * CONTENT
<code>\middlebox {...}</code> * CONTENT
<code>\midhbox {...}</code> * CONTENT
<code>\midsubsentence</code>
<code>\minimalhbox ...<sup>1</sup> {...<sup>2</sup>}</code> 1 TEXT           OPT 2 CONTENT
<code>\mirror {...}</code> * CONTENT
<code>\mixedcaps {...}</code> * TEXT
<code>\mkvibuffer [...<sup>*</sup>]</code> * BUFFER           OPT
<code>\moduleparameter {...<sup>1</sup>} {...<sup>2</sup>}</code> 1 FILE 2 KEY
<code>\molecule {...}</code> * CONTENT
<code>\mono</code>
<code>\monobold</code>
<code>\mononormal</code>

$\backslash\text{month}\{...\}$ *    NUMBER
$\backslash\text{monthlong}\{...\}$ *    NUMBER
$\backslash\text{monthshort}\{...\}$ *    NUMBER
$\backslash\text{mprandomnumber}$
$\backslash\text{mtext}\{...\}$ *    CONTENT
$\backslash\text{m}[\dots,\dots,\dots,\dots,\dots]\{...\}$ 1 $\text{inherit}_{\text{PT}}\backslash\text{setupmathematics}$ 2    CONTENT
$\backslash\text{NormalizeFontHeight}\backslash^{.1}\{...\}\{...\}\{...\}$ 1    CSNAME 2    TEXT 3    DIMENSION 4    FONT
$\backslash\text{NormalizeFontWidth}\backslash^{.1}\{...\}\{...\}\{...\}$ 1    CSNAME 2    TEXT 3    DIMENSION 4    FONT
$\backslash\text{NormalizeTextHeight}\{.^1\}\{.^2\}\{.^3\}$ 1    FONT 2    DIMENSION 3    TEXT
$\backslash\text{NormalizeTextWidth}\{.^1\}\{.^2\}\{.^3\}$ 1    FONT 2    DIMENSION 3    TEXT
$\backslash\text{Numbers}\{...\}$ *    NUMBER
$\backslash\text{namedheadnumber}\{...\}$ *    SECTION
$\backslash\text{namedstructureheadlocation}\{...\}$ *    SECTION
$\backslash\text{namedstructureuservariable}\{.^1\}\{.^2\}$ 1    SECTION 2    KEY
$\backslash\text{namedstructurevariable}\{.^1\}\{.^2\}$ 1    SECTION 2    KEY

$\backslash\text{namedtaggedlabeltexts}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ $\{.^4.\}$ $\{.^5.\}$ 1 NAME 2 NAME 3 NAME 4 NAME 5 CONTENT
$\backslash\text{naturalhbox}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalhpack}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturaltpack}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalvbox}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalvcenter}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalvpack}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalvtop}$ $\{.^1.\}$ $\{.^2.\}$ 1 TEXT OPT 2 CONTENT
$\backslash\text{naturalwd}$ $\{.^*\}$ * CSNAME NUMBER
$\backslash\text{negatecolorbox}$ $\{.^*\}$ * CSNAME NUMBER
$\backslash\text{negated}$ $\{.^*\}$ * TEXT
$\backslash\text{negemspace}$
$\backslash\text{negenspace}$
$\backslash\text{negthinspace}$
$\backslash\text{newattribute}$ $\{.^*\}$ * CSNAME
$\backslash\text{newcatcodetable}$ $\{.^*\}$ * CSNAME
$\backslash\text{newcounter}$ $\{.^*\}$ * CSNAME



<code>\newevery \<sup>1</sup>... \<sup>2</sup>...</code> 1 CSNAME 2 CSNAME
<code>\newfrenchspacing</code>
<code>\newmode {...}</code> * NAME
<code>\newsignal \*</code> * CSNAME
<code>\newsystemmode {...}</code> * NAME
<code>\nextbox</code>
<code>\nextboxdp</code>
<code>\nextboxht</code>
<code>\nextboxhtdp</code>
<code>\nextboxwd</code>
<code>\nextcounter [...] [...]</code> 1 NAME <small>OPT</small> 2 NUMBER
<code>\nextcountervalue [...]</code> * NAME
<code>\nextdepth</code>
<code>\nextparagraphs</code>
<code>\nextPARAGRAPHS</code>
<code>\nextrealpage</code>
<code>\nextrealpagenumber</code>
<code>\nextsubcountervalue [...] [...]</code> 1 NAME 2 NUMBER
<code>\nextsubpage</code>
<code>\nextsubpagenumber</code>
<code>\nextuserpage</code>
<code>\nextuserpagenumber</code>
<code>\nocharacteralign</code>

<code>\nocitation [...]</code> *   REFERENCE
<code>\nocitation {...}</code> *   REFERENCE
<code>\nocite [...]</code> *   REFERENCE
<code>\nocite {...}</code> *   REFERENCE
<code>\nodetostring \<sup>1</sup>... {\<sup>2</sup>...}</code> 1   CSNAME 2   CONTENT
<code>\nofigurepages</code>
<code>\noflines</code>
<code>\noflocalfloats</code>
<code>\noheaderandfooterlines</code>
<code>\noheightstrut</code>
<code>\noindentation</code>
<code>\noitem</code>
<code>\nonfrenchspacing</code>
<code>\nonmathematics {...}</code> *   CONTENT
<code>\normal</code>
<code>\normalboldface</code>
<code>\normalframedwithsettings [...,\<sup>1</sup>...,...,\<sup>2</sup>...]{...}</code> 1   inherits: \setupframed 2   CONTENT
<code>\normalitalicface</code>
<code>\normalizebodyfontsize \<sup>1</sup>... {\<sup>2</sup>...}</code> 1   CSNAME 2   DIMENSION
<code>\normalizedfontsize</code>
<code>\normalizefontdepth \<sup>1</sup>... {\<sup>2</sup>...} {\<sup>3</sup>...} {\<sup>4</sup>...}</code> 1   CSNAME 2   TEXT 3   DIMENSION 4   FONT

`\normalizefontheight \1... {2...} {3...} {4...}`

1 CSNAME  
2 TEXT  
3 DIMENSION  
4 FONT

`\normalizefontline \1... {2...} {3...} {4...}`

1 CSNAME  
2 TEXT  
3 DIMENSION  
4 FONT

`\normalizefontwidth \1... {2...} {3...} {4...}`

1 CSNAME  
2 TEXT  
3 DIMENSION  
4 FONT

`\normalizetextdepth {1...} {2...} {3...}`

1 FONT  
2 DIMENSION  
3 TEXT

`\normalizetextheight {1...} {2...} {3...}`

1 FONT  
2 DIMENSION  
3 TEXT

`\normalizetextline {1...} {2...} {3...}`

1 FONT  
2 DIMENSION  
3 TEXT

`\normalizetextwidth {1...} {2...} {3...}`

1 FONT  
2 DIMENSION  
3 TEXT

`\normalslantedface`

`\normaltypeface`

`\nospace`

`\note [1...] [2...]`

1 NAME <sup>OPT</sup>  
2 REFERENCE

`\notesymbol [1...] [2...]`

1 NAME <sup>OPT</sup>  
2 REFERENCE

`\NOTE [...1,...] {2...}`

1 REFERENCE<sup>OPT</sup>  
2 TEXT

instances: footnote endnote

`\NOTE [...,*...,...]`

\* title = TEXT  
bookmark = TEXT  
list = TEXT  
reference = REFERENCE

instances: footnote endnote

<pre> \endnote [...,..<sup>1</sup>,...] * title      = TEXT   bookmark   = TEXT   list       = TEXT   reference  = REFERENCE </pre>
<pre> \footnote [...,..<sup>1</sup>,...] * title      = TEXT   bookmark   = TEXT   list       = TEXT   reference  = REFERENCE </pre>
<pre> \endnote [...,..<sup>1</sup>,...] {..<sup>2</sup>.} 1 REFERENCE <sup>OPT</sup> 2 TEXT </pre>
<pre> \footnote [...,..<sup>1</sup>,...] {..<sup>2</sup>.} 1 REFERENCE <sup>OPT</sup> 2 TEXT </pre>
<pre> \notopandbottomlines </pre>
<pre> \notragged </pre>
<pre> \notsmallcapped {..<sup>*</sup>.} * TEXT </pre>
<pre> \ntimes {..<sup>1</sup>.} {..<sup>2</sup>.} 1 TEXT 2 NUMBER </pre>
<pre> \numberofpoints {..<sup>*</sup>.} * DIMENSION </pre>
<pre> \numbers {..<sup>*</sup>.} * NUMBER </pre>
<pre> \obeydepth </pre>
<pre> \objectdepth </pre>
<pre> \objectheight </pre>
<pre> \objectmargin </pre>
<pre> \objectwidth </pre>
<pre> \obox {..<sup>*</sup>.} * CONTENT </pre>
<pre> \offset [...,..<sup>1</sup>,...] {..<sup>2</sup>.} 1 inherits: \setupoffset<sup>OPT</sup> 2 CONTENT </pre>
<pre> \offsetbox [...,..<sup>1</sup>,...] \^..<sup>2</sup>. {..<sup>3</sup>.} 1 inherits: \setupoffsetbox<sup>OPT</sup> 2 CSNAME 3 CONTENT </pre>

\onedigitrounding {...} * NUMBER
\ordinaldaynumber {...} * NUMBER
\ordinalstr {...} * TEXT
\ornamenttext [... <sup>1</sup> ... <sup>2</sup> ...] [... <sup>2</sup> ... <sup>3</sup> ...] {...} {...} <div>1 alternative = a b OPT inherits: \setupcollector</div> <div>2 style = STYLE COMMAND color = COLOR inherits: \setupframed</div> <div>3 TEXT</div> <div>4 CONTENT</div>
\ornamenttext [... <sup>1</sup> ] {... <sup>2</sup> } {... <sup>3</sup> }
\ornamenttext [... <sup>1</sup> ... <sup>2</sup> ...] [... <sup>2</sup> ... <sup>3</sup> ...] {...} {...} <div>1 alternative = a b OPT inherits: \setupplayer</div> <div>2 inherits: \setuplayeredtext</div> <div>3 TEXT</div> <div>4 CONTENT</div>
\ORNAMENT {...} {...} 1 TEXT 2 CONTENT
\outputfilename
\outputstreambox [...] * NAME
\outputstreamcopy [...] * NAME
\outputstreamunvbox [...] * NAME
\outputstreamunvcopy [...] * NAME
\over [...] * REFERENCE
\overlaybutton [...] * REFERENCE
\overlaybutton {...} * REFERENCE
\overlaycolor
\overlaydepth

<code>\overlayfigure {...}</code> *    FILE
<code>\overlayheight</code>
<code>\overlayimage {...}</code> *    FILE
<code>\overlaylinecolor</code>
<code>\overlaylinewidth</code>
<code>\overlayoffset</code>
<code>\overlayrollbutton [...]<sup>1</sup> [...]<sup>2</sup></code> 1    REFERENCE 2    REFERENCE
<code>\overlaywidth</code>
<code>\overloaderror</code>
<code>\overset {...}<sup>1</sup> {...}<sup>2</sup></code> 1    TEXT 2    TEXT
<code>\PDFcolor {...}</code> *    NAME
<code>\PDFETEX</code>
<code>\PDFTEX</code>
<code>\PICTEX</code>
<code>\PiCTeX</code>
<code>\PointsToBigPoints {...}<sup>1</sup> \^2...</code> 1    DIMENSION 2    CSNAME
<code>\PointsToReal {...}<sup>1</sup> \^2...</code> 1    DIMENSION 2    CSNAME
<code>\PointsToWholeBigPoints {...}<sup>1</sup> \^2...</code> 1    DIMENSION 2    CSNAME
<code>\PPCHTEX</code>
<code>\PPCHTeX</code>
<code>\PRAGMA</code>

<p><b>\PtToCm {...}</b></p> <p>* DIMENSION</p>
<p><b>\page [...,*,...]</b></p> <p>* inherits:<sup>OPT</sup>\pagebreak</p>
<p><b>\pagearea [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></b></p> <p>1 top header text footer bottom<sup>OPT</sup></p> <p>2 text margin edge</p> <p>3 left right lefttext <u>middletext</u> righttext</p>
<p><b>\pagebreak [...,*,...]</b></p> <p>* empty header footer dummy frame NUMBER +NUMBER default reset disable yes no makeup blank preference bigpreference left right even odd quadruple last lastpage start stop NAME</p>
<p><b>\pagefigure [...]<sup>1</sup> [...,...]<sup>2</sup> [...,...]</b></p> <p>1 FILE<sup>OPT</sup></p> <p>2 offset = default overlay none DIMENSION</p>
<p><b>\pageinjection [...]<sup>1</sup> [...,...]<sup>2</sup> [...,...]</b></p> <p>1 NAME<sup>OPT</sup> <sup>OPT</sup></p> <p>2 KEY = VALUE</p>
<p><b>\pageinjection [...,...]<sup>1</sup> [...,...]<sup>2</sup> [...,...]</b></p> <p>1 inherits: \setuppageinjection<sup>OPT</sup></p> <p>2 KEY = VALUE</p>
<p><b>\pagenumber</b></p>
<p><b>\pagereference [...,*,...]</b></p> <p>* REFERENCE</p>
<p><b>\pagestaterealpage {...}<sup>1</sup> {...}<sup>2</sup></b></p> <p>1 NAME</p> <p>2 NAME NUMBER</p>
<p><b>\pagestaterealpageorder {...}<sup>1</sup> {...}<sup>2</sup></b></p> <p>1 NAME</p> <p>2 NAME NUMBER</p>
<p><b>\paletsize</b></p>
<p><b>\PARAGRAPHS</b></p>
<p><b>\pdfactualtext {...}<sup>1</sup> {...}<sup>2</sup></b></p> <p>1 CONTENT</p> <p>2 TEXT</p>
<p><b>\pdfbackendactualtext {...}<sup>1</sup> {...}<sup>2</sup></b></p> <p>1 CONTENT</p> <p>2 TEXT</p>
<p><b>\pdfbackendcurrentresources</b></p>
<p><b>\pdfbackendsetcatalog {...}<sup>1</sup> {...}<sup>2</sup></b></p> <p>1 NAME</p> <p>2 TEXT</p>

<code>\pdfbackendsetcolorspace {<sup>1</sup>.<sup>2</sup>.}</code> 1 NAME 2 TEXT
<code>\pdfbackendsettextgstate {<sup>1</sup>.<sup>2</sup>.}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetinfo {<sup>1</sup>.<sup>2</sup>.}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetname {<sup>1</sup>.<sup>2</sup>.}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpageattribute {<sup>1</sup>.<sup>2</sup>.}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpageresource {<sup>1</sup>.<sup>2</sup>.}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpagesattribute {<sup>1</sup>.<sup>2</sup>.}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetpattern {<sup>1</sup>.<sup>2</sup>.}</code> 1 NAME 2 TEXT
<code>\pdfbackendsetshade {<sup>1</sup>.<sup>2</sup>.}</code> 1 NAME 2 TEXT
<code>\pdfcolor {<sup>*</sup>.}</code> <sup>*</sup> NAME
<code>\pdfeTeX</code>
<code>\pdfTeX</code>
<code>\percent</code>
<code>\percentdimen {<sup>1</sup>.<sup>2</sup>.}</code> 1 DIMENSION CSNAME 2 DIMENSION NUMBER
<code>\periods [<sup>*</sup>.]</code> <sup>*</sup> NUMBER <sup>OPT</sup>
<code>\periods [...,<sup>*</sup>...]</code> <sup>*</sup> inherits: \setup <sup>OPT</sup> periods
<code>\permitcaretescape</code>
<code>\permitcircumflexescape</code>



<code>\permitspacesbetweengroups</code>
<code>\persiandecimals {...}</code> *    NUMBER
<code>\persiannumerals {...}</code> *    NUMBER
<code>\phantom {...}</code> *    CONTENT
<code>\phantombox [...,*...,...]</code> *    width    = DIMENSION *    height   = DIMENSION *    depth    = DIMENSION
<code>\pickupgroupedcommand {...} {...} {...}</code> 1    COMMAND 2    COMMAND 3    COMMAND
<code>\placeattachments</code>
<code>\placebookmarks [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>*,...]</code> 1    SECTION LIST                    OPT                    OPT                    OPT 2    SECTION LIST 3    inherits: \setupbookmark
<code>\placebtxrendering [...]<sup>1</sup> [...,<sup>2</sup>*,...]<sup>2</sup></code> 1    NAME                            OPT                    OPT 2    inherits: \setupbtxrendering
<code>\placecitation [...]</code> *    REFERENCE
<code>\placecombinedlist [...]<sup>1</sup> [...,<sup>2</sup>*,...]<sup>2</sup></code> 1    LIST                            OPT 2    inherits: \setupcombinedlist
<code>\placeCOMBINEDLIST [...,*...,...]</code> *    inherits: \setupcombinedlist <sup>OPT</sup> <b>instances: content</b>
<code>\placecontent [...,*...,...]</code> *    inherits: \setupcombinedlist <sup>OPT</sup>
<code>\placecomments</code>
<code>\placecurrentformulanumber</code>
<code>\placedbox {...}</code> *    CONTENT

`\placefloat [...1] [...2,...] [...3,...] {...4} {...5}`

1 SINGULAR  
2 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge  
rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [--]line halfline grid high  
low fit 90 180 270 nonumber none local here force margin [--]hang hanging tall both middle offset top bottom auto  
page leftpage rightpage somewhere effective header footer tblr lrtb tblr lrtb fxtb btlr lrbt btlr lrtb fxtb fixd  
3 REFERENCE  
4 TEXT  
5 CONTENT

`\placefloatwithsetups [...1] [...2,...] [...3,...] {...4} {...5}`

1 NAME  
2 split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge  
rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [--]line halfline grid high  
low fit 90 180 270 nonumber none local here force margin [--]hang hanging tall both middle offset top bottom auto  
page leftpage rightpage somewhere effective header footer tblr lrtb tblr lrtb fxtb btlr lrbt btlr lrtb fxtb fixd  
3 REFERENCE  
4 TEXT  
5 CONTENT

`\placeFLOAT [...1,...] [...2,...] {...3} {...4}`

1 split always left<sup>OPT</sup>right inner<sup>OPT</sup>outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge  
rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [--]line halfline grid high  
low fit 90 180 270 nonumber none local here force margin [--]hang hanging tall both middle offset top bottom auto  
page leftpage rightpage somewhere effective header footer tblr lrtb tblr lrtb fxtb btlr lrbt btlr lrtb fxtb fixd  
2 REFERENCE  
3 TEXT  
4 CONTENT

instances: chemical figure table intermezzo graphic

`\placechemical [...1,...] [...2,...] {...3} {...4}`

1 split always left<sup>OPT</sup>right inner<sup>OPT</sup>outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge  
rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [--]line halfline grid high  
low fit 90 180 270 nonumber none local here force margin [--]hang hanging tall both middle offset top bottom auto  
page leftpage rightpage somewhere effective header footer tblr lrtb tblr lrtb fxtb btlr lrbt btlr lrtb fxtb fixd  
2 REFERENCE  
3 TEXT  
4 CONTENT

`\placefigure [...1,...] [...2,...] {...3} {...4}`

1 split always left<sup>OPT</sup>right inner<sup>OPT</sup>outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge  
rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [--]line halfline grid high  
low fit 90 180 270 nonumber none local here force margin [--]hang hanging tall both middle offset top bottom auto  
page leftpage rightpage somewhere effective header footer tblr lrtb tblr lrtb fxtb btlr lrbt btlr lrtb fxtb fixd  
2 REFERENCE  
3 TEXT  
4 CONTENT

`\placegraphic [...1,...] [...2,...] {...3} {...4}`

1 split always left<sup>OPT</sup>right inner<sup>OPT</sup>outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge  
rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [--]line halfline grid high  
low fit 90 180 270 nonumber none local here force margin [--]hang hanging tall both middle offset top bottom auto  
page leftpage rightpage somewhere effective header footer tblr lrtb tblr lrtb fxtb btlr lrbt btlr lrtb fxtb fixd  
2 REFERENCE  
3 TEXT  
4 CONTENT

`\placeintermezzo [...1,...] [...2,...] {...3} {...4}`

1 split always left<sup>OPT</sup>right inner<sup>OPT</sup>outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge  
rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [--]line halfline grid high  
low fit 90 180 270 nonumber none local here force margin [--]hang hanging tall both middle offset top bottom auto  
page leftpage rightpage somewhere effective header footer tblr lrtb tblr lrtb fxtb btlr lrbt btlr lrtb fxtb fixd  
2 REFERENCE  
3 TEXT  
4 CONTENT

`\placetable [...1,...] [...2,...] {...3} {...4}`

1 split always left<sup>OPT</sup>right inner<sup>OPT</sup>outer backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge  
rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high  
low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto  
page leftpage rightpage somewhere effective header footer tblr lrtb tblr rltb fxtb btlr lrbt btrl rltb fxbt fixd  
2 REFERENCE  
3 TEXT  
4 CONTENT

`\placefootnotes [...*,...]`

\* inherits: \setupnote <sup>OPT</sup>

`\placeformula [...1,...] {...2}`

1 + - REFERENCE <sup>OPT</sup> <sup>OPT</sup>  
2 TEXT

`\placeframed [...1] [...2,...2,...] {...3}`

1 NAME <sup>OPT</sup>  
2 inherits: \setupframed  
3 CONTENT

`\placeheadnumber [...]`

\* SECTION

`\placeheadtext [...]`

\* SECTION

`\placehelp`

`\placeinitial [...]`

\* NAME <sup>OPT</sup>

`\placelayer [...]`

\* NAME

`\placelayeredtext [...1] [...2,...2,...] [...3,...3,...] {...4} {...5}`

1 NAME <sup>OPT</sup> <sup>OPT</sup>  
2 inherits: \setuplayer  
3 inherits: \setuplayeredtext  
4 TEXT  
5 CONTENT

`\placelist [...1,...] [...2,...2,...]`

1 LIST <sup>OPT</sup>  
2 inherits: \setuplist

`\placelistofFLOATS [...*,...]`

\* inherits: \setuplist <sup>OPT</sup>  
instances: chemicals figures tables intermezzi graphics

`\placelistofchemicals [...*,...]`

\* inherits: \setuplist <sup>OPT</sup>

`\placelistoffigures [...*,...]`

\* inherits: \setuplist <sup>OPT</sup>

`\placelistofgraphics [...*,...]`

\* inherits: \setuplist <sup>OPT</sup>

`\placelistofintermezzi [...*,...]`

\* inherits: \setuplist <sup>OPT</sup>

$\backslash\text{placelistoftables}$ [... <sup>*</sup> ...] * inherits: \setuplist <small>OPT</small>
$\backslash\text{placelistofpublications}$ [... <sup>1</sup> ] [... <sup>2</sup> ...] 1 NAME <small>OPT</small> <small>OPT</small> 2 inherits: \setupbtxrendering
$\backslash\text{placelistofsorts}$ [... <sup>1</sup> ] [... <sup>2</sup> ...] 1 SINGULAR <small>OPT</small> 2 inherits: \setupsorting
$\backslash\text{placelistofSORTS}$ [... <sup>*</sup> ...] * inherits: \setupsorting <small>OPT</small> instances: logos
$\backslash\text{placelistoflogos}$ [... <sup>*</sup> ...] * inherits: \setupsorting <small>OPT</small>
$\backslash\text{placelistofsynonyms}$ [... <sup>1</sup> ] [... <sup>2</sup> ...] 1 SINGULAR <small>OPT</small> 2 inherits: \setupsynonyms
$\backslash\text{placelistofSYNONYMS}$ [... <sup>*</sup> ...] * inherits: \setupsynonyms <small>OPT</small> instances: abbreviations
$\backslash\text{placelistofabbreviations}$ [... <sup>*</sup> ...] * inherits: \setupsynonyms <small>OPT</small>
$\backslash\text{placelocalfootnotes}$ [... <sup>*</sup> ...] * inherits: \setupnote <small>OPT</small>
$\backslash\text{placelocalnotes}$ [... <sup>1</sup> ] [... <sup>2</sup> ...] 1 NAME <small>OPT</small> 2 inherits: \setupnote
$\backslash\text{placement}$ [... <sup>1</sup> ] [... <sup>2</sup> ...] {... <sup>3</sup> } 1 NAME <small>OPT</small> 2 inherits: \setupplacement 3 CONTENT
$\backslash\text{PLACEMENT}$ [... <sup>1</sup> ...] {... <sup>2</sup> } 1 inherits: \setupplacEment <small>OPT</small> 2 CONTENT
$\backslash\text{placenamefloat}$ [... <sup>1</sup> ] [... <sup>2</sup> ] 1 NAME 2 REFERENCE
$\backslash\text{placenameformula}$ [... <sup>1</sup> ...] {... <sup>2</sup> } {... <sup>3</sup> } 1 + - REFERENCE <small>OPT</small> <small>OPT</small> 2 TEXT 3 TEXT
$\backslash\text{placenotes}$ [... <sup>1</sup> ...] [... <sup>2</sup> ...] 1 NAME <small>OPT</small> 2 inherits: \setupnote

$\backslash\text{placeongrid}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 normal standard <sup>OPT</sup> yes strict tolerant top bottom both broad fit first last high one low none line strut box min max middle math math:line math:halfline math:-line math:-halfline NAME 2 CONTENT
$\backslash\text{placeongrid}$ [..., <sup>1</sup> ...] { <sup>2</sup> ...} 1 inherits: $\backslash\text{definegrid}$ <sup>OPT</sup> snapping 2 CONTENT
$\backslash\text{placeontopofeachother}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1 CONTENT 2 CONTENT
$\backslash\text{placepagenumber}$
$\backslash\text{placepairedbox}$ [ <sup>1</sup> ...] [..., <sup>2</sup> ...] <sup>OPT</sup> { <sup>3</sup> ...} { <sup>4</sup> ...} 1 NAME 2 inherits: $\backslash\text{setuppairedbox}$ 3 CONTENT 4 TEXT
$\backslash\text{placePAIREDBOX}$ [..., <sup>1</sup> ...] <sup>OPT</sup> { <sup>2</sup> ...} { <sup>3</sup> ...} 1 inherits: $\backslash\text{setuppairedbox}$ <sup>OPT</sup> 2 CONTENT 3 TEXT instances: legend
$\backslash\text{placelegend}$ [..., <sup>1</sup> ...] <sup>OPT</sup> { <sup>2</sup> ...} { <sup>3</sup> ...} 1 inherits: $\backslash\text{setuppairedbox}$ <sup>OPT</sup> 2 CONTENT 3 TEXT
$\backslash\text{placeparallel}$ [ <sup>1</sup> ...] [..., <sup>2</sup> ...] [..., <sup>3</sup> ...] <sup>OPT</sup> 1 NAME 2 NAME 3 inherits: $\backslash\text{setupparallel}$
$\backslash\text{placerawheaddata}$ [...*] * SECTION
$\backslash\text{placerawheadnumber}$ [...*] * SECTION
$\backslash\text{placerawheadtext}$ [...*] * SECTION
$\backslash\text{placerawlist}$ [ <sup>1</sup> ...] [..., <sup>2</sup> ...] <sup>OPT</sup> 1 LIST 2 inherits: $\backslash\text{setuplist}$
$\backslash\text{placeregister}$ [ <sup>1</sup> ...] [..., <sup>2</sup> ...] <sup>OPT</sup> 1 NAME 2 inherits: $\backslash\text{setupregister}$
$\backslash\text{placeREGISTER}$ [...,*...] <sup>OPT</sup> * inherits: $\backslash\text{setupregister}$ <sup>OPT</sup> instances: index
$\backslash\text{placeindex}$ [...,*...] <sup>OPT</sup> * inherits: $\backslash\text{setupregister}$ <sup>OPT</sup>

<code>\placereadingwindow [...] [...]</code> 1    NAME 2    NAME
<code>\placesidebyside {...} {...}</code> 1    CONTENT 2    CONTENT
<code>\placesubformula [...,<sup>1</sup>...] {...<sup>2</sup>}</code> 1    + - REFERENCE                    OPT                    OPT 2    TEXT
<code>\popattribute \...</code> *    CSNAME
<code>\popmacro \...</code> *    CSNAME
<code>\popmode [...]</code> *    NAME
<code>\popsystemmode {...}</code> *    NAME
<code>\position [...,<sup>1</sup>...] (...,<sup>2</sup>...) {...<sup>3</sup>}</code> 1    inherits: \setup <sup>OPT</sup> positioning 2    POSITION 3    CONTENT
<code>\positionoverlay {...}</code> *    NAME
<code>\positionregionoverlay {...<sup>1</sup>} {...<sup>2</sup>}</code> 1    NAME 2    NAME
<code>\postponenotes</code>
<code>\predefinedfont [...]</code> *    FONT
<code>\predefinefont [...<sup>1</sup>] [...<sup>2</sup>]</code> 1    NAME 2    FONT
<code>\predefinesymbol [...]</code> *    NAME
<code>\prefixedpagenumber</code>
<code>\prependetoks ... \to \...</code> 1    COMMAND 2    CSNAME
<code>\prependgvalue {...<sup>1</sup>} {...<sup>2</sup>}</code> 1    NAME 2    COMMAND

<pre> \prependtocommalist {...} \^{.2}... 1 TEXT 2 CSNAME </pre>
<pre> \prependtoks ... \to \^{.2}... 1 COMMAND 2 CSNAME </pre>
<pre> \prependtoksonce ... \to \^{.2}... 1 COMMAND 2 CSNAME </pre>
<pre> \prependvalue {...} {...} 1 NAME 2 COMMAND </pre>
<pre> \prerollblank [...,*...] * inherits: \blank </pre>
<pre> \presetdocument [...,..^{.2}...] * inherits: \setupdocument </pre>
<pre> \presetfieldsymbols [...,*...] * NAME </pre>
<pre> \presetLABELtext [...^{.1}...] [...,..^{.2}...] 1 LANGUAGE OPT 2 KEY = VALUE instances: head label mathlabel taglabel unit operator prefix suffix btxlabel </pre>
<pre> \presetbtxlabeltext [...^{.1}...] [...,..^{.2}...] 1 LANGUAGE OPT 2 KEY = VALUE </pre>
<pre> \presetheadtext [...^{.1}...] [...,..^{.2}...] 1 LANGUAGE OPT 2 KEY = VALUE </pre>
<pre> \presetlabeltext [...^{.1}...] [...,..^{.2}...] 1 LANGUAGE OPT 2 KEY = VALUE </pre>
<pre> \presetmathlabeltext [...^{.1}...] [...,..^{.2}...] 1 LANGUAGE OPT 2 KEY = VALUE </pre>
<pre> \presetoperatortext [...^{.1}...] [...,..^{.2}...] 1 LANGUAGE OPT 2 KEY = VALUE </pre>
<pre> \presetprefixtext [...^{.1}...] [...,..^{.2}...] 1 LANGUAGE OPT 2 KEY = VALUE </pre>
<pre> \presetsuffixtext [...^{.1}...] [...,..^{.2}...] 1 LANGUAGE OPT 2 KEY = VALUE </pre>
<pre> \presettaglabeltext [...^{.1}...] [...,..^{.2}...] 1 LANGUAGE OPT 2 KEY = VALUE </pre>

<pre> \presetunittext [...] [<sup>1</sup>...<sup>2</sup>...,...] 1  LANGUAGE          OPT 2  KEY  =  VALUE </pre>
<pre> \pretocommalist {...} \<sup>2</sup>... 1  TEXT 2  CSNAME </pre>
<pre> \prettyprintbuffer {...} {<sup>2</sup>...} 1  BUFFER 2  mp lua xml parsed-xml nested tex context none NAME </pre>
<pre> \prevcounter [...] [<sup>2</sup>...] 1  NAME              OPT 2  NUMBER </pre>
<pre> \prevcountervalue [...] *  NAME </pre>
<pre> \preventmode [...,*...] *  NAME </pre>
<pre> \prevrealpage </pre>
<pre> \prevrealpagenumber </pre>
<pre> \prevsubcountervalue [<sup>1</sup>...] [<sup>2</sup>...] 1  NAME 2  NUMBER </pre>
<pre> \prevsubpage </pre>
<pre> \prevsubpagenumber </pre>
<pre> \prevuserpage </pre>
<pre> \prevuserpagenumber </pre>
<pre> \procent </pre>
<pre> \processaction [<sup>1</sup>...] [<sup>2</sup>...=&gt;...,...] 1  COMMAND 2  APPLY </pre>
<pre> \processallactionsinset [<sup>1</sup>...] [<sup>2</sup>...=&gt;...,...] 1  COMMAND 2  APPLY </pre>
<pre> \processassignlist [...,<sup>1</sup>...] \<sup>2</sup>... 1  TEXT 2  CSNAME </pre>
<pre> \processassignmentcommand [...,<sup>1</sup>...,...] \<sup>2</sup>... 1  KEY  =  VALUE 2  CSNAME </pre>
<pre> \processassignmentlist [...,<sup>1</sup>...,...] \<sup>2</sup>... 1  KEY  =  VALUE 2  CSNAME </pre>



<pre> \processbetween {...} \<sup>2</sup>... 1 NAME 2 CSNAME </pre>
<pre> \processblocks [...,<sup>1</sup>...] [...,<sup>2</sup>...] [...,<sup>3</sup>...<sub>OPT</sub>,...] 1 NAME 2 NAME 3 criterium = <u>text</u> SECTION </pre>
<pre> \processbodyfontenvironmentlist \*... * CSNAME </pre>
<pre> \processcolorcomponents {...} * COLOR </pre>
<pre> \processcommaccommand [...,<sup>1</sup>...] \<sup>2</sup>... 1 COMMAND 2 CSNAME </pre>
<pre> \processcommalist [...,<sup>1</sup>...] \<sup>2</sup>... 1 COMMAND 2 CSNAME </pre>
<pre> \processcommalistwithparameters [...,<sup>1</sup>...] \<sup>2</sup>... 1 COMMAND 2 CSNAME </pre>
<pre> \processcontent {...} \<sup>2</sup>... 1 NAME 2 CSNAME </pre>
<pre> \processfile {...} * FILE </pre>
<pre> \processfilemany {...} * FILE </pre>
<pre> \processfilenone {...} * FILE </pre>
<pre> \processfileonce {...} * FILE </pre>
<pre> \processfirstactioninset [...<sup>1</sup>...] [...,<sup>2</sup>...=&gt;...<sup>3</sup>...] 1 COMMAND 2 APPLY </pre>
<pre> \processisolatedchars {...} \<sup>2</sup>... 1 TEXT 2 CSNAME </pre>
<pre> \processisolatedwords {...} \<sup>2</sup>... 1 TEXT 2 CSNAME </pre>
<pre> \processlinetablebuffer [...<sup>1</sup>...] * BUFFER OPT </pre>
<pre> \processlinetablefile {...} * FILE </pre>

\processlist {...} {...} {...} \...

- 1 CHARACTER
- 2 CHARACTER
- 3 TEXT
- 4 CSNAME

\processMPbuffer [...<sup>\*</sup>...]

- \* NAME

OPT

\processMPfigurefile {...}

- \* FILE

\processmonth {...} {...} {...}

- 1 NUMBER
- 2 NUMBER
- 3 COMMAND

\processranges [...<sup>1</sup>...]<sup>2</sup>

- 1 NUMBER NUMBER:NUMBER
- 2 CSNAME

\processseparatedlist [...<sup>1</sup>] [...<sup>2</sup>] {...<sup>3</sup>}

- 1 TEXT
- 2 TEXT
- 3 CSNAME COMMAND

\processTEXbuffer [...]

- \* BUFFER

OPT

\processtokens {...} {...} {...} {...} {...}

- 1 COMMAND
- 2 COMMAND
- 3 COMMAND
- 4 COMMAND
- 5 TEXT

\processuntil \...

- \* CSNAME

\processxtablebuffer [...]

- \* NAME

OPT

\processyear {...} {...} {...} {...}

- 1 NUMBER
- 2 COMMAND
- 3 COMMAND
- 4 COMMAND

\product [...]

- \* FILE

\product ...

- \* FILE

\profiledbox [...<sup>1</sup>] [...<sup>2</sup>...<sup>2</sup>...]<sup>3</sup> {...}

- 1 none fixed strict half<sup>OPT</sup>fixed quarter<sup>OPT</sup>fixed eight<sup>OPT</sup>fixed NAME
- 2 inherits: \setupprofile
- 3 CONTENT

\profilegivenbox {...<sup>1</sup>} ...<sup>2</sup>

- 1 none fixed strict half<sup>OPT</sup>fixed quarter<sup>OPT</sup>fixed eight<sup>OPT</sup>fixed NAME
- 2 CSNAME NUMBER

<code>\program [...]</code> *   NAME
<code>\project [...]</code> *   FILE
<code>\project ...</code> *   FILE
<code>\pseudoMixedCapped {...}</code> *   TEXT
<code>\pseudoSmallCapped {...}</code> *   TEXT
<code>\pseudoSmallcapped {...}</code> *   TEXT
<code>\pseudosmallcapped {...}</code> *   TEXT
<code>\purenumber {...}</code> *   NUMBER
<code>\pusharrangedpages ... \poparrangedpages</code>
<code>\pushattribute \...</code> *   CSNAME
<code>\pushbackground [...] ... \popbackground</code> *   NAME
<code>\pushbar [...] ... \popbar</code> *   NAME
<code>\pushbutton [...<sup>1</sup>] [...<sup>2</sup>]</code> 1   NAME 2   REFERENCE
<code>\pushcatcodetable ... \popcatcodetable</code>
<code>\pushcolor [...] ... \popcolor</code> *   COLOR
<code>\pushendofline ... \popendofline</code>
<code>\pushindentation ... \popindentation</code>
<code>\pushMPdrawing ... \popMPdrawing</code>
<code>\pushmacro \...</code> *   CSNAME
<code>\pushmathstyle ... \popmathstyle</code>

<p><code>\pushmode [...]</code></p> <p>* NAME</p>
<p><code>\pushoutputstream [...]</code></p> <p>* NAME <small>OPT</small></p>
<p><code>\pushpath [...]</code> ... <code>\poppath</code></p> <p>* PATH</p>
<p><code>\pushpunctuation ... \poppunctuation</code></p>
<p><code>\pushrandomseed ... \poprandomseed</code></p>
<p><code>\pushreferenceprefix {...}</code> ... <code>\popreferenceprefix</code></p> <p>* + - TEXT</p>
<p><code>\pushsystemmode {...}</code></p> <p>* NAME</p>
<p><code>\putboxincache {...} {...} ...</code></p> <p>1 NAME</p> <p>2 NUMBER TEXT</p> <p>3 CSNAME NUMBER</p>
<p><code>\putnextboxincache {...} {...} \^3 {...} {...}</code></p> <p>1 NAME</p> <p>2 NUMBER TEXT</p> <p>3 CSNAME</p> <p>4 CONTENT</p>
<p><code>\qqquad</code></p>
<p><code>\quad</code></p>
<p><code>\quads [...]</code></p> <p>* NUMBER <small>OPT</small></p>
<p><code>\quarterstrut</code></p>
<p><code>\quitcommalist</code></p>
<p><code>\quitprevcommalist</code></p>
<p><code>\quittypescriptscanning</code></p>
<p><code>\ReadFile {...}</code></p> <p>* FILE</p>
<p><code>\Romannumerals {...}</code></p> <p>* NUMBER</p>
<p><code>\raggedbottom</code></p>
<p><code>\raggedcenter</code></p>
<p><code>\raggedleft</code></p>

<code>\raggedright</code>
<code>\raggedwidecenter</code>
<code>\raisebox {<sup>1</sup>.} \<sup>2</sup>... {<sup>3</sup>.}</code> 1    DIMENSION 2    CSNAME 3    CONTENT
<code>\randomizetext {<sup>*</sup>.}</code> *    TEXT
<code>\randomnumber {<sup>1</sup>.} {<sup>2</sup>.}</code> 1    NUMBER 2    NUMBER
<code>\rawcounter [<sup>1</sup>.] [<sup>2</sup>.<sub>OPT</sub>]</code> 1    NAME 2    NUMBER
<code>\rawcountervalue [<sup>*</sup>.]</code> *    NAME
<code>\rawdate [...,<sup>*</sup>...]</code> *    inherits: \currentdate
<code>\rawdoifelseinset {<sup>1</sup>.} {...,<sup>2</sup>...} {<sup>3</sup>.} {<sup>4</sup>.}</code> 1    TEXT 2    TEXT 3    TRUE 4    FALSE
<code>\rawdoifinset {<sup>1</sup>.} {...,<sup>2</sup>...} {<sup>3</sup>.}</code> 1    TEXT 2    TEXT 3    TRUE
<code>\rawdoifinsetelse {<sup>1</sup>.} {...,<sup>2</sup>...} {<sup>3</sup>.} {<sup>4</sup>.}</code> 1    TEXT 2    TEXT 3    TRUE 4    FALSE
<code>\rawgetparameters [<sup>1</sup>.] [...,<sup>2</sup>==...]</code> 1    TEXT 2    KEY = VALUE
<code>\rawprocessaction [<sup>1</sup>.] [...,<sup>2</sup>=&gt;...]</code> 1    COMMAND 2    APPLY
<code>\rawprocesscommacommand [...,<sup>1</sup>...] \<sup>2</sup>...</code> 1    COMMAND 2    CSNAME
<code>\rawprocesscommalist [...,<sup>1</sup>...] \<sup>2</sup>...</code> 1    COMMAND 2    CSNAME
<code>\rawstructurelistuservariable {<sup>*</sup>.}</code> *    KEY

<pre> \rawsubcountervalue [...] [...] 1  NAME 2  NUMBER </pre>
<pre> \rbox ... {...} 1  TEXT <sup>OPT</sup> 2  CONTENT </pre>
<pre> \readfile {...} {...} {...} 1  FILE 2  TRUE 3  FALSE </pre>
<pre> \readfixfile {...} {...} {...} {...} 1  PATH 2  FILE 3  TRUE 4  FALSE </pre>
<pre> \readjobfile {...} {...} {...} 1  FILE 2  TRUE 3  FALSE </pre>
<pre> \readlocfile {...} {...} {...} 1  FILE 2  TRUE 3  FALSE </pre>
<pre> \readsetfile {...} {...} {...} {...} 1  PATH 2  FILE 3  TRUE 4  FALSE </pre>
<pre> \readsysfile {...} {...} {...} 1  FILE 2  TRUE 3  FALSE </pre>
<pre> \readtexfile {...} {...} {...} 1  FILE 2  TRUE 3  FALSE </pre>
<pre> \readxmlfile {...} {...} {...} 1  FILE 2  TRUE 3  FALSE </pre>
<pre> \realpagenumber </pre>
<pre> \realSmallCapped {...} *  TEXT </pre>
<pre> \realSmallcapped {...} *  TEXT </pre>
<pre> \realSmallcapped {...} *  TEXT </pre>
<pre> \recursedepth </pre>

<code>\recurselevel</code>
<code>\recursestring</code>
<code>\redoconvertfont</code>
<code>\ref [...]<sup>1</sup> [...]<sup>2</sup></code> 1 default text title number page realpage 2 REFERENCE
<code>\reference [...]<sup>1</sup>, [...] {...}<sup>2</sup></code> 1 REFERENCE 2 TEXT
<code>\REFERENCEFORMAT {...}<sup>1</sup> {...}<sup>2</sup> [...]<sup>3</sup></code> 1 TEXT OPT OPT 2 TEXT 3 REFERENCE
<code>\referenceprefix</code>
<code>\referring (...)<sup>1</sup>, (...) (...)<sup>2</sup>, [...] [...]<sup>3</sup></code> 1 POSITION 2 POSITION 3 REFERENCE
<code>\registerattachment [...]<sup>1</sup> [...]<sup>2</sup>, [...]</code> 1 NAME 2 inherits: \setupattachment
<code>\registerctxluafile {...}<sup>1</sup> {...}<sup>2</sup></code> 1 FILE 2 NUMBER
<code>\registerexternalfigure [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup>, [...]</code> 1 FILE OPT OPT 2 NAME 3 inherits: \setupeexternalfigure
<code>\registerfontclass {...}</code> * NAME
<code>\registerhyphenationexception [...]<sup>1</sup> [...]<sup>2</sup></code> 1 LANGUAGE OPT 2 TEXT
<code>\registerhyphenationpattern [...]<sup>1</sup> [...]<sup>2</sup></code> 1 LANGUAGE OPT 2 TEXT
<code>\registermenubuttons [...]<sup>1</sup> [...]<sup>2</sup></code> 1 NAME 2 TEXT
<code>\registersort [...]<sup>1</sup> [...]<sup>2</sup></code> 1 SINGULAR 2 NAME
<code>\registersynonym [...]<sup>1</sup> [...]<sup>2</sup></code> 1 SINGULAR 2 NAME

```
\registerunit [...]1 [...,...2...,...]
1 prefix unit operatorOPT suffixe symbol packaged
2 KEY = VALUE
```

```
\REGISTER [...]1 {...+...2+...}
1 TEXT PROCESSOR->TEXT
2 INDEX
instances: index
```

```
\index [...]1 {...+...2+...}
1 TEXT PROCESSOR->TEXT
2 INDEX
```

```
\REGISTER [...]1 {...}2 {...+...3+...}
1 TEXT PROCESSOR->TEXT
2 TEXT
3 INDEX
instances: index
```

```
\index [...]1 {...}2 {...+...3+...}
1 TEXT PROCESSOR->TEXT
2 TEXT
3 INDEX
```

```
\regular
```

```
\relatemarking [...]1 [...]2
1 MARK
2 MARK
```

```
\relateparameterhandlers {...}1 {...}2 {...}3 {...}4
1 NAME
2 NAME
3 NAME
4 NAME
```

```
\relaxvalueifundefined {...}
* NAME
```

```
\remainingcharacters
```

```
\remark (...1,...) (...2,...) [...,...3...,...]4 {...}
1 POSITION
2 POSITION
3 POSITION
4 TEXT
inherits: \setupframed
```

```
\removebottomthings
```

```
\removedepth
```

```
\removefromcommalist {...}1 \...2
1 TEXT
2 CSNAME
```

```
\removelastskip
```

```
\removelastspace
```

```
\removemarkedcontent [...]1
* NAME
```



<code>\removepunctuation</code>
<code>\removesubstring <sup>1</sup>... \from <sup>2</sup>... \to <sup>3</sup>...</code> 1 TEXT 2 TEXT 3 CSNAME
<code>\removetoks <sup>1</sup>... \from <sup>2</sup>...</code> 1 COMMAND 2 CSNAME
<code>\removeunwantedspaces</code>
<code>\repeathead [...]</code> * SECTION
<code>\replacefeature [...]</code> * NAME
<code>\replacefeature {...}</code> * NAME
<code>\replaceincommalist <sup>1</sup>... {<sup>2</sup>...}</code> 1 CSNAME 2 NUMBER
<code>\replaceword [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]</code> 1 NAME 2 TEXT 3 TEXT
<code>\rescan {...}</code> * CONTENT
<code>\rescanwithsetup {<sup>1</sup>...} {<sup>2</sup>...}</code> 1 NAME 2 CONTENT
<code>\resetallattributes</code>
<code>\resetandaddfeature [...]</code> * NAME
<code>\resetandaddfeature {...}</code> * NAME
<code>\resetbar</code>
<code>\resetboxesincache {...}</code> * NAME
<code>\resetbreakpoints</code>
<code>\resetbuffer [...]</code> * BUFFER
<code>\resetcharacteralign</code>

<code>\resetcharacterkerning</code>
<code>\resetcharacterspacing</code>
<code>\resetcharacterstripping</code>
<code>\resetcollector [...]</code> * NAME
<code>\resetcounter [...]<sup>1</sup> [...]<sup>2</sup></code> 1 NAME OPT 2 NUMBER
<code>\resetdigitsmanipulation</code>
<code>\resetdirection</code>
<code>\resetfeature</code>
<code>\resetflag {...}</code> * NAME
<code>\resetfontcolorscheme</code>
<code>\resetfontfallback [...]<sup>1</sup> [...]<sup>2</sup></code> 1 NAME OPT 2 FONT
<code>\resetfontsolution</code>
<code>\resethyphenationfeatures</code>
<code>\resetinjector [...]</code> * NAME
<code>\resetinteractionmenu [...]</code> * NAME
<code>\resetitaliccorrection</code>
<code>\resetlayer [...]</code> * NAME
<code>\resetlocalfloats</code>
<code>\resetMPdrawing</code>
<code>\resetMPenvironment</code>
<code>\resetMPinstance [...]</code> * NAME
<code>\resetmarker [...]</code> * NAME

\resetmarking [...] * MARK
\resetmode {...} * NAME
\resetpagenumber
\resetparallel [...] <sup>1</sup> [..., <sup>2</sup> ...] 1 NAME OPT 2 NAME <u>all</u>
\resetpath
\resetpenalties \.*.. * CSNAME
\resetperiodkerning
\resetprofile
\resetrecurselevel
\resetreference [...] * NAME
\resetreplacement
\resetscript
\resetsetups [...] * NAME
\resetshownsynonyms [...] * SINGULAR
\resetsubpagenumber
\resetsymbolset
\resetssystemmode {...} * NAME
\resettimer
\resettokenlist [...] * NAME
\resettrackers
\resettrialtypesetting
\resetusedsortings [...] * SINGULAR

\resetusedsynonyms [...] * SINGULAR
\resetuserpagenumber
\resetvalue {...} * NAME
\resetvisualizers
\reshapebox {...} * COMMAND
\resolvedglyphdirect {...} {...} 1 FONT 2 e:NAME x:NUMBER d:NUMBER s:NUMBER i:NUMBER n:NAME c:NAME u:NAME a:NAME
\resolvedglyphstyled {...} {...} 1 FONT 2 e:NAME x:NUMBER d:NUMBER s:NUMBER i:NUMBER n:NAME c:NAME u:NAME a:NAME
\restartcounter [...] [... <sup>2</sup> ] [... <sup>3</sup> ] 1 NAME 2 NUMBER 3 NUMBER
\restorebox {...} {... <sup>2</sup> } 1 NAME 2 NAME
\restorecatcodes
\restorecounter [...] * NAME
\restorecurrentattributes {...} * NAME
\restoreendofline
\restoreglobalbodyfont
\reusableMPgraphic {...} {..., <sup>2</sup> ...} 1 NAME 2 KEY = VALUE
\reuseMPgraphic {...} {..., <sup>2</sup> ...} 1 NAME 2 KEY = VALUE
\reuserandomseed
\reversehbox ... {... <sup>2</sup> } 1 TEXT 2 CONTENT

```
\reversehpack ... {...}
```

$$\backslash\mathrm{reversetpack} \quad \dots \quad \{ \dots \}$$
$$\backslash\mathrm{reversebox} \dots \{ \dots \}$$
$$\backslash reversevpack \dots \{ \dots \}$$

```
\reversevtop ... {...}
```

```
\revivefeature
```

```

\rfence {...}

* \egroup \bgroup \letterclosebrace ] [ ( > < / | \| \rbrace \rbracket \rbracket \rparenthesis
\rparent \rparen \rangle \rrangle \rVert \vert \solidus \rfloor \rceil \rceil \urcorner \lrcorner
\rmoustache \rrbracket \rgroup \rinterval \rointerval \rlointerval \rointerval \} \} \} \> \ CHARACTER

```

$$\text{\texttt{\textbackslash rhbox \{.*\}}}$$

```

\right ...
* \egroup \bgroup \letterclosebrace ] [ ( > < / |      || \rbrace \rbracket \rbracket \rparenthesis
\rparent \rparen \rangle \rrangle \rVert \vert \solidus \rfloor \rceil \rceil \urcorner \lrcorner
\rmoustache \rrbracket \rgroup \rinterval \rointerval \rlointerval \rrointerval \} \} \} \> \ CHARACTER

```

$$\text{\texttt{\textbackslashrightaligned \{...\}}}$$

`\rightbottombox {...}`

```
\rightbox {...}
```

```
\righthbox {...}
```

```
\rightLABELtext {...}
* KEY
instances: head label mathlabel
```

$$\backslash rightheadtext \{...\}$$
$$\backslash rightlabeltext \{...\}$$
$$\backslash rightmathlabeltext \{...\}$$

<code>\rightline {...}</code> *    CONTENT
<code>\rightorleftpageaction {...} {...}</code> 1    COMMAND 2    COMMAND
<code>\rightpageorder</code>
<code>\rightskipadaption</code>
<code>\rightsubguillemot</code>
<code>\righttopleft</code>
<code>\righttolefthbox ...<sup>1</sup> {...}</code> 1    TEXT                    OPT 2    CONTENT
<code>\righttopleftvbox ...<sup>1</sup> {...}</code> 1    TEXT                    OPT 2    CONTENT
<code>\righttopleftvtop ...<sup>1</sup> {...}</code> 1    TEXT                    OPT 2    CONTENT
<code>\righttopbox {...}</code> *    CONTENT
<code>\ring {...}</code> *    CHARACTER
<code>\rlap {...}</code> *    CONTENT
<code>\robustaddtocommalist {...} \<sup>2</sup>...</code> 1    TEXT 2    CSNAME
<code>\robustdoifelseinset {...} {...,<sup>2</sup>...} {...<sup>3</sup>} {...<sup>4</sup>}</code> 1    TEXT 2    TEXT 3    TRUE 4    FALSE
<code>\robustdoifinsetelse {...} {...,<sup>2</sup>...} {...<sup>3</sup>} {...<sup>4</sup>}</code> 1    TEXT 2    TEXT 3    TRUE 4    FALSE
<code>\robustpretocommalist {...} \<sup>2</sup>...</code> 1    TEXT 2    CSNAME
<code>\rollbutton [...,<sup>1</sup>...,...] ...<sup>2</sup> [...<sup>3</sup>]</code> 1    inherits: \setupbutton 2    TEXT 3    REFERENCE

**\rollbutton** [<sup>1</sup>...] [<sup>2</sup>...<sub>=</sub>...<sub>=</sub>...] <sup>3</sup>... [<sup>4</sup>...]  
1 NAME OPT OPT  
2 inherits: \setupinteractionmenu  
3 TEXT  
4 REFERENCE

**\roman**

**\romannumerals** {...}  
\* NUMBER

**\rotate** [<sup>1</sup>...<sub>=</sub>...<sub>=</sub>...] {<sup>2</sup>...}  
1 inherits: \setuprotate OPT  
2 CONTENT

**\rtlhbox** <sup>1</sup>... {<sup>2</sup>...}  
1 TEXT OPT  
2 CONTENT

**\rtlvbox** <sup>1</sup>... {<sup>2</sup>...}  
1 TEXT OPT  
2 CONTENT

**\rtlvtop** <sup>1</sup>... {<sup>2</sup>...}  
1 TEXT OPT  
2 CONTENT

**\rtop** <sup>1</sup>... {<sup>2</sup>...}  
1 TEXT OPT  
2 CONTENT

**\ruby** [<sup>1</sup>...] {<sup>2</sup>...} {<sup>3</sup>...}  
1 NAME OPT  
2 TEXT  
3 TEXT

**\ruledhbox** <sup>1</sup>... {<sup>2</sup>...}  
1 TEXT OPT  
2 CONTENT

**\ruledhpack** <sup>1</sup>... {<sup>2</sup>...}  
1 TEXT OPT  
2 CONTENT

**\ruledmbox** {...}  
\* CONTENT

**\ruledtopv** <sup>1</sup>... {<sup>2</sup>...}  
1 TEXT OPT  
2 CONTENT

**\ruledtpack** <sup>1</sup>... {<sup>2</sup>...}  
1 TEXT OPT  
2 CONTENT

**\ruledvbox** <sup>1</sup>... {<sup>2</sup>...}  
1 TEXT OPT  
2 CONTENT

<pre> \ruledvpack <sup>1</sup>... {<sup>2</sup>...} 1  TEXT      OPT 2  CONTENT </pre>
<pre> \ruledvtop <sup>1</sup>... {<sup>2</sup>...} 1  TEXT      OPT 2  CONTENT </pre>
<pre> \runMPbuffer [...,<sup>*</sup>...] *  NAME      OPT </pre>
<pre> \runninghbox {<sup>*</sup>...} *  CONTENT </pre>
<pre> \ScaledPointsToBigPoints {<sup>1</sup>...} \<sup>2</sup>... 1  DIMENSION 2  CSNAME </pre>
<pre> \ScaledPointsToWholeBigPoints {<sup>1</sup>...} \<sup>2</sup>... 1  DIMENSION 2  CSNAME </pre>
<pre> \SmallCapped {<sup>*</sup>...} *  TEXT </pre>
<pre> \Smallcapped {<sup>*</sup>...} *  TEXT </pre>
<pre> \safechar {<sup>*</sup>...} *  NUMBER </pre>
<pre> \samplefile {<sup>*</sup>...} *  FILE </pre>
<pre> \sans </pre>
<pre> \sansbold </pre>
<pre> \sansnormal </pre>
<pre> \sansserif </pre>
<pre> \savebox {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...} 1  NAME 2  NAME 3  CONTENT </pre>
<pre> \savebtxdataset [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...<sup>=</sup>...,...] 1  NAME      OPT      OPT      OPT 2  FILE 3  dataset   =  NAME    type      =  bib lua xml    file      =  FILE    criterium =  all text intro reference current here previous local component SECTIONBLOCK:all SECTIONBLOCK:reference                 SECTIONBLOCK:current SECTIONBLOCK:previous </pre>
<pre> \savebuffer [...,<sup>*</sup>...,...] *  list      =  NAME    file      =  FILE    prefix    =  <u>yes</u> no </pre>



<code>\savebuffer [...<sup>1</sup>,...] [...<sup>2</sup>]</code> 1    BUFFER 2    FILE
<code>\savecolor ... \restorecolor</code>
<code>\savecounter [...]</code> *    NAME
<code>\savecurrentattributes {...}</code> *    NAME
<code>\savenormalmeaning \...</code> *    CSNAME
<code>\savetaggedtwopassdata {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>}</code> 1    NAME 2    NUMBER 3    NAME 4    CONTENT
<code>\savetwopassdata {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}</code> 1    NAME 2    NUMBER 3    CONTENT
<code>\sbox {...}</code> *    CONTENT
<code>\scale [...<sup>1</sup>] [...<sup>2</sup><sub>OPT</sub>,...<sup>2</sup><sub>OPT</sub>] {...<sup>3</sup>}</code> 1    NAME    OPT 2    inherits: \setupscale 3    CONTENT
<code>\screen [...<sup>*</sup>,...]</code> *    inherits: \page <sub>SET</sub>
<code>\SCRIPT</code> instances: hangul hanzi nihongo ethiopic thai latin test
<code>\ethiopic</code>
<code>\hangul</code>
<code>\hanzi</code>
<code>\latin</code>
<code>\nihongo</code>
<code>\test</code>
<code>\thai</code>

`\secondoffivearguments {...} {...} {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT

`\secondoffourarguments {...} {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT

`\secondofsixarguments {...} {...} {...} {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TEXT  
4 TEXT  
5 TEXT  
6 TEXT

`\secondofthreearguments {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TEXT

`\secondofthreeunexpanded {...} {...} {...}`

1 TEXT  
2 TEXT  
3 TEXT

`\secondoftwoarguments {...} {...}`

1 TEXT  
2 TEXT

`\secondoftwounexpanded {...} {...}`

1 TEXT  
2 TEXT

`\SECTION [...,1...] {...2}`

1 REFERENCE OPT  
2 TEXT

instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection  
title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

`\SECTION [...,*...] [...]`

\* title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection  
title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

`\chapter [...,*...] [...]`

\* title = TEXT  
bookmark = TEXT  
marking = TEXT  
list = TEXT  
reference = REFERENCE  
ownnumber = TEXT

`\part [...,.*=...,...]`

```
* title      = TEXT
bookmark    = TEXT
marking     = TEXT
list        = TEXT
reference   = REFERENCE
ownnumber   = TEXT
```

`\section [...,.*=...,...]`

```
* title      = TEXT
bookmark    = TEXT
marking     = TEXT
list        = TEXT
reference   = REFERENCE
ownnumber   = TEXT
```

`\subject [...,.*=...,...]`

```
* title      = TEXT
bookmark    = TEXT
marking     = TEXT
list        = TEXT
reference   = REFERENCE
ownnumber   = TEXT
```

`\subsection [...,.*=...,...]`

```
* title      = TEXT
bookmark    = TEXT
marking     = TEXT
list        = TEXT
reference   = REFERENCE
ownnumber   = TEXT
```

`\subsubject [...,.*=...,...]`

```
* title      = TEXT
bookmark    = TEXT
marking     = TEXT
list        = TEXT
reference   = REFERENCE
ownnumber   = TEXT
```

`\subsubsection [...,.*=...,...]`

```
* title      = TEXT
bookmark    = TEXT
marking     = TEXT
list        = TEXT
reference   = REFERENCE
ownnumber   = TEXT
```

`\subsubsubject [...,.*=...,...]`

```
* title      = TEXT
bookmark    = TEXT
marking     = TEXT
list        = TEXT
reference   = REFERENCE
ownnumber   = TEXT
```

`\subsubsubsection [...,.*=...,...]`

```
* title      = TEXT
bookmark    = TEXT
marking     = TEXT
list        = TEXT
reference   = REFERENCE
ownnumber   = TEXT
```

`\subsubsubsubject [...,.*=...,...]`

```
* title      = TEXT
bookmark    = TEXT
marking     = TEXT
list        = TEXT
reference    = REFERENCE
ownnumber   = TEXT
```

`\subsubsubsubsection [...,.*=...,...]`

```
* title      = TEXT
bookmark    = TEXT
marking     = TEXT
list        = TEXT
reference    = REFERENCE
ownnumber   = TEXT
```

`\subsubsubsubsubject [...,.*=...,...]`

```
* title      = TEXT
bookmark    = TEXT
marking     = TEXT
list        = TEXT
reference    = REFERENCE
ownnumber   = TEXT
```

`\title [...,.*=...,...]`

```
* title      = TEXT
bookmark    = TEXT
marking     = TEXT
list        = TEXT
reference    = REFERENCE
ownnumber   = TEXT
```

`\chapter [...,1...] {..2}`

```
1 REFERENCE OPT
2 TEXT
```

`\SECTION [...,1...] {..2} {..3}`

```
1 REFERENCE OPT
2 NUMBER
3 TEXT
```

instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection  
title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject

`\chapter [...,1...] {..2} {..3}`

```
1 REFERENCE OPT
2 NUMBER
3 TEXT
```

`\part [...,1...] {..2} {..3}`

```
1 REFERENCEOPT
2 NUMBER
3 TEXT
```

`\section [...,1...] {..2} {..3}`

```
1 REFERENCE OPT
2 NUMBER
3 TEXT
```

`\subject [...,1...] {..2} {..3}`

```
1 REFERENCE OPT
2 NUMBER
3 TEXT
```

`\subsection [...,1...] {..2} {..3}`

```
1 REFERENCE OPT
2 NUMBER
3 TEXT
```

$\backslash\text{subsubject } [..., \overset{1}{...}] \{...\} \{...\}$ 1    REFERENCE                    OPT 2    NUMBER 3    TEXT
$\backslash\text{subsubsection } [..., \overset{1}{...}] \{...\} \{...\}$ 1    REFERENCE                    OPT 2    NUMBER 3    TEXT
$\backslash\text{subsubsubject } [..., \overset{1}{...}] \{...\} \{...\}$ 1    REFERENCE                    OPT 2    NUMBER 3    TEXT
$\backslash\text{subsubsubsection } [..., \overset{1}{...}] \{...\} \{...\}$ 1    REFERENCE                    OPT 2    NUMBER 3    TEXT
$\backslash\text{subsubsubsubject } [..., \overset{1}{...}] \{...\} \{...\}$ 1    REFERENCE                    OPT 2    NUMBER 3    TEXT
$\backslash\text{subsubsubsubsection } [..., \overset{1}{...}] \{...\} \{...\}$ 1    REFERENCE                    OPT 2    NUMBER 3    TEXT
$\backslash\text{subsubsubsubsubject } [..., \overset{1}{...}] \{...\} \{...\}$ 1    REFERENCE                    OPT 2    NUMBER 3    TEXT
$\backslash\text{title } [..., \overset{1}{...}] \{...\} \{...\}$ 1    REFERENCE                    OPT 2    NUMBER 3    TEXT
$\backslash\text{part } [..., \overset{1}{...}] \{...\}$ 1    REFERENCE <sup>PT</sup> 2    TEXT
$\backslash\text{section } [..., \overset{1}{...}] \{...\}$ 1    REFERENCE                    OPT 2    TEXT
$\backslash\text{subject } [..., \overset{1}{...}] \{...\}$ 1    REFERENCE                    OPT 2    TEXT
$\backslash\text{subsection } [..., \overset{1}{...}] \{...\}$ 1    REFERENCE                    OPT 2    TEXT
$\backslash\text{subsubject } [..., \overset{1}{...}] \{...\}$ 1    REFERENCE                    OPT 2    TEXT
$\backslash\text{subsubsection } [..., \overset{1}{...}] \{...\}$ 1    REFERENCE                    OPT 2    TEXT

<pre> \subsubsubject [...<sup>1</sup>,...] {..<sup>2</sup>.} 1  REFERENCE          OPT 2  TEXT </pre>
<pre> \subsubsubsection [...<sup>1</sup>,...] {..<sup>2</sup>.} 1  REFERENCE          OPT 2  TEXT </pre>
<pre> \subsubsubsubject [...<sup>1</sup>,...] {..<sup>2</sup>.} 1  REFERENCE          OPT 2  TEXT </pre>
<pre> \subsubsubsubsection [...<sup>1</sup>,...] {..<sup>2</sup>.} 1  REFERENCE          OPT 2  TEXT </pre>
<pre> \subsubsubsubsubject [...<sup>1</sup>,...] {..<sup>2</sup>.} 1  REFERENCE          OPT 2  TEXT </pre>
<pre> \title [...<sup>1</sup>,...] {..<sup>2</sup>.} 1  REFERENCE OPT 2  TEXT </pre>
<pre> \seeREGISTER [...<sup>1</sup>] {...+..<sup>2</sup>+...} {...<sup>3</sup>.} 1  TEXT PROCESSOR-&gt;TEXT OPT 2  INDEX 3  TEXT PROCESSOR-&gt;TEXT instances: index </pre>
<pre> \seeindex [...<sup>1</sup>] {...+..<sup>2</sup>+...} {...<sup>3</sup>.} 1  TEXT PROCESSOR-&gt;TEXT 2  INDEX 3  TEXT PROCESSOR-&gt;TEXT </pre>
<pre> \select {...} {...<sup>2</sup>} {...<sup>3</sup>} {...<sup>4</sup>} {...<sup>5</sup>} {...<sup>6</sup>} 1  NAME          OPT      OPT      OPT      OPT      OPT 2  CONTENT 3  CONTENT 4  CONTENT 5  CONTENT 6  CONTENT </pre>
<pre> \selectblocks [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...<sup>3</sup>,...] 1  NAME          OPT      OPT 2  NAME 3  criterium = text SECTION </pre>
<pre> \serializecommalist [...*,...] *  COMMAND </pre>
<pre> \serializedcommalist </pre>
<pre> \serif </pre>
<pre> \serifbold </pre>
<pre> \serifnormal </pre>
<pre> \setautopagestaterealpageno {...} *  NAME </pre>

\setbar [...] *   NAME
\setbigbodyfont
\setboxllx <sup>1</sup> . . { <sup>2</sup> . .} 1   CSNAME NUMBER 2   DIMENSION
\setboxlly <sup>1</sup> . . { <sup>2</sup> . .} 1   CSNAME NUMBER 2   DIMENSION
\setbreakpoints [...] *   reset NAME
\setbuffer [...] ... \endbuffer *   NAME
\setcapstrut
\setcatcodetable \*.. *   CSNAME
\setcharacteralign { <sup>1</sup> . .} { <sup>2</sup> . .} 1   NUMBER 2   TEXT number->TEXT text->TEXT
\setcharacteraligndetail { <sup>1</sup> . .} { <sup>2</sup> . .} { <sup>3</sup> . .} { <sup>4</sup> . .} 1   NUMBER 2   TEXT number->TEXT text->TEXT 3   DIMENSION 4   DIMENSION
\setcharactercasing [...] *   reset WORD word Word Words capital Capital none random mixed camel cap Cap
\setcharactercleaning [...] *   reset 1
\setcharacterkerning [...] *   reset NAME
\setcharacterspacing [...] *   reset NAME
\setcharacterstripping [...] *   reset 1
\setcharstrut { <sup>1</sup> . .} *   TEXT
\setcollector [ <sup>1</sup> . .] [... <sup>2</sup> ... <sup>3</sup> ...] { <sup>3</sup> . .} 1   NAME 2   inherits: \setupcollector 3   CONTENT
\setcolormodel1 [...] *   black bw gray rgb cmyk <u>all</u> none

<pre> \setcounter [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup> 1  NAME                OPT 2  NUMBER 3  NUMBER </pre>
<pre> \setcounterown [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup> 1  NAME                OPT 2  NUMBER 3  TEXT </pre>
<pre> \setcurrentfontclass {...} *  NAME </pre>
<pre> \setdataset [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...] 1  NAME                OPT 2  NAME 3  KEY = VALUE </pre>
<pre> \setdefaultpenalties </pre>
<pre> \setdigitsmanipulation [...] *  reset NUMBER </pre>
<pre> \setdirection [...] *  NUMBER </pre>
<pre> \setdocumentargument {...}<sup>1</sup> {...}<sup>2</sup> 1  NAME 2  TEXT </pre>
<pre> \setdocumentargumentdefault {...}<sup>1</sup> {...}<sup>2</sup> 1  NAME 2  TEXT </pre>
<pre> \setdocumentfilename {...}<sup>1</sup> {...}<sup>2</sup> 1  NUMBER 2  TEXT </pre>
<pre> \setdummyparameter {...}<sup>1</sup> {...}<sup>2</sup> 1  KEY 2  COMMAND </pre>
<pre> \setelementexporttag [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup> 1  NAME                OPT 2  <u>export</u> nature pdf 3  inline display mixed </pre>
<pre> \setemeasure {...}<sup>1</sup> {...}<sup>2</sup> 1  NAME 2  DIMENSION </pre>
<pre> \setevalue {...}<sup>1</sup> {...}<sup>2</sup> 1  NAME 2  CONTENT </pre>
<pre> \setevariable {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> 1  NAME 2  KEY 3  VALUE </pre>



`\setevariables [.1.] [.,.,.2.,.,.]`

1 NAME  
2 set = COMMAND  
reset = COMMAND  
KEY = VALUE

`\setfirstline [.*.]`

\* NAME OPT

`\setfirstpasscharacteralign`

`\setflag {.*.}`

\* NAME

`\setfont *.*`

\* FONT

`\setfontcolorscheme [.*.]`

\* NAME

`\setfontfeature {.*.}`

\* NAME

`\setfontsolution [.*.]`

\* NAME

`\setfontstrut`

`\setglobalscript [.*.]`

\* hangul hanzi nihongo ethiopic thai test NAME

`\setgmeasure {.1.} {.2.}`

1 NAME  
2 DIMENSION

`\setgvalue {.1.} {.2.}`

1 NAME  
2 CONTENT

`\setgvariable {.1.} {.2.} {.3.}`

1 NAME  
2 KEY  
3 VALUE

`\setgvariables [.1.] [.,.,.2.,.,.]`

1 NAME  
2 set = COMMAND  
reset = COMMAND  
KEY = VALUE

`\sethboxregister .1. {.2.}`

1 CSNAME NUMBER  
2 CONTENT

`\sethyphenatedurlafter {.*.}`

\* TEXT

`\sethyphenatedurlbefore {.*.}`

\* TEXT

<pre> \sethyphenatedurlnormal {...} *   TEXT </pre>
<pre> \sethyphenationfeatures [...,*...] *   NAME reset                                 OPT </pre>
<pre> \setinitial [...<sup>1</sup>] [...,<sup>2</sup>...,...] 1   NAME          OPT          OPT 2   inherits: \setupinitial </pre>
<pre> \setinjector [...<sup>1</sup>] [...,<sup>2</sup>...,...] [...<sup>3</sup>] 1   NAME 2   NUMBER 3   COMMAND </pre>
<pre> \setinteraction [...<sup>*</sup>] *   hidden NAME </pre>
<pre> \setinterfacecommand {...<sup>1</sup>} {...<sup>2</sup>} 1   NAME 2   NAME </pre>
<pre> \setinterfaceconstant {...<sup>1</sup>} {...<sup>2</sup>} 1   NAME 2   NAME </pre>
<pre> \setinterfaceelement {...<sup>1</sup>} {...<sup>2</sup>} 1   NAME 2   NAME </pre>
<pre> \setinterfacemessage {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>} 1   NAME 2   title NAME NUMBER 3   TEXT </pre>
<pre> \setinterfacevariable {...<sup>1</sup>} {...<sup>2</sup>} 1   NAME 2   NAME </pre>
<pre> \setinternalrendering [...<sup>1</sup>] [...<sup>2</sup>] {...<sup>3</sup>} 1   NAME 2   auto embed 3   CONTENT </pre>
<pre> \setitaliccorrection [...<sup>*</sup>] *   reset 1 2 </pre>
<pre> \setJSreamble {...<sup>1</sup>} {...<sup>2</sup>} 1   NAME 2   CONTENT </pre>
<pre> \setlayer [...<sup>1</sup>] [...<sup>2</sup>] [...,<sup>3</sup>...,...] {...<sup>4</sup>} 1   NAME          OPT          OPT 2   left right even odd 3   inherits: \setuplayer 4   CONTENT </pre>
<pre> \setlayerframed [...<sup>1</sup>] [...,<sup>2</sup>...,...] [...,<sup>3</sup>...,...] {...<sup>4</sup>} 1   NAME          OPT          OPT 2   inherits: \setuplayer 3   inherits: \setupframed 4   CONTENT </pre>

```
\setlayerframed [...] [...2...] {3...}
1 NAME OPT
2 inherits: \setuplayerinherits: \setupframed
3 CONTENT
```

```
\setlayertext [1...] [...2...] [...3...] {4...}
1 NAME OPT OPT
2 inherits: \setuplayer
3 align = inherits: \setupalign
width = DIMENSION
style = STYLE COMMAND
color = COLOR
4 TEXT
```

```
\setlinefiller [...]
* filler NAME
```

```
\setlocalhsize [...]
* [-+]DIMENSION OPT
```

```
\setlocalscript [...]
* hangul hanzi nihongo ethiopic thai test NAME
```

```
\setMPlayer [1...] [2...] [...3...] {4...}
1 NAME OPT
2 NAME
3 inherits: \setuplayer
4 CONTENT
```

```
\setMPpositiongraphic {1...} {2...} {3...}
1 NAME OPT
2 NAME
3 KEY = VALUE
```

```
\setMPpositiongraphicrange {1...} {2...} {3...} {4...}
1 NAME OPT
2 NAME
3 NAME
4 KEY = VALUE
```

```
\setMPtext {1...} {2...}
1 NAME
2 TEXT
```

```
\setMPvariable [1...] [2...]
1 NAME
2 KEY = VALUE
```

```
\setMPvariables [1...] [...2...]
1 NAME OPT
2 KEY = VALUE
```

```
\setmainbodyfont
```

```
\setmainparbuilder [...]
* default oneline basic NAME
```

```
\setmarker [1...] [2...]
1 NAME
2 NUMBER
```

$\backslash\text{setmarking}$ [ <sup>1</sup> ...] { <sup>2</sup> ...} 1 MARK 2 TEXT
$\backslash\text{setmathstyle}$ {...,*...} * display text script scriptscript cramped uncramped normal packed small big NAME
$\backslash\text{setmeasure}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 DIMENSION
$\backslash\text{setmessagetext}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 NAME NUMBER
$\backslash\text{setmode}$ {.*...} * NAME
$\backslash\text{setnostrut}$
$\backslash\text{setnote}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] <sup>OPT</sup> { <sup>3</sup> ...} 1 NAME 2 REFERENCE 3 TEXT
$\backslash\text{setnotetext}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...,...] <sup>OPT</sup> { <sup>3</sup> ...} 1 NAME 2 REFERENCE 3 TEXT
$\backslash\text{setnotetext}$ [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] 1 NAME 2 title = TEXT bookmark = TEXT list = TEXT reference = REFERENCE
$\backslash\text{setnote}$ [ <sup>1</sup> ...] [..., <sup>2</sup> ...,...] 1 NAME 2 title = TEXT bookmark = TEXT list = TEXT reference = REFERENCE
$\backslash\text{setobject}$ { <sup>1</sup> ...} { <sup>2</sup> ...} \ <sup>3</sup> ... { <sup>4</sup> ...} 1 NAME 2 NAME 3 CSNAME 4 CONTENT
$\backslash\text{setoldstyle}$
$\backslash\text{setpagereference}$ { <sup>1</sup> ...} { <sup>2</sup> ...,...} 1 NAME 2 REFERENCE
$\backslash\text{setpagestate}$ [ <sup>1</sup> ...] [ <sup>2</sup> ...] <sup>OPT</sup> 1 NAME 2 NAME NUMBER
$\backslash\text{setpagestaterealpageno}$ { <sup>1</sup> ...} { <sup>2</sup> ...} 1 NAME 2 NAME NUMBER

`\setpenalties \1 \2 \3`

1 CSNAME  
2 NUMBER  
3 NUMBER

`\setpercentdimen \1 \2`

1 DIMENSION CSNAME  
2 DIMENSION NUMBER

`\setperiodkerning [...]`

\* reset NAME

`\setposition {...}`

\* NAME

`\setpositionbox \1 \2 \3`

1 NAME  
2 CSNAME  
3 CONTENT

`\setpositiondata \1 \2 \3 \4`

1 NAME  
2 DIMENSION  
3 DIMENSION  
4 DIMENSION

`\setpositiondataplus \1 \2 \3 \4 \5,...`

1 NAME  
2 DIMENSION  
3 DIMENSION  
4 DIMENSION  
5 TEXT

`\setpositiononly {...}`

\* NAME

`\setpositionplus \1 \2,... \3 \4`

1 NAME  
2 TEXT  
3 CSNAME  
4 CONTENT

`\setpositionstrut {...}`

\* NAME

`\setprofile [...]`

\* none fixed strict halffixed quarterfixed eightsfixed NAME

`\setrandomseed {...}`

\* NUMBER

`\setreference [...1,...] [...2,...]`

1 REFERENCE  
2 KEY = VALUE

`\setreferencedobject \1 \2 \3 \4`

1 NAME  
2 NAME  
3 CSNAME  
4 CONTENT

```

\setregisterentry [...]1 [...,...2...,...]2 [...,...3...,...]3
1 NAME
2 label = NAME
keys = TEXT PROCESSOR->TEXT
entries = TEXT PROCESSOR->TEXT
keys:1 = TEXT
keys:2 = TEXT
keys:3 = TEXT
entries:1 = TEXT
entries:2 = TEXT
entries:3 = TEXT
alternative = TEXT
3 KEY = VALUE

```

```

\setreplacement [...]
* reset NAME

```

```

\setrigidcolumnbalance ...
* CSNAME NUMBER

```

```

\setrigidcolumnhsize {...}1 {...}2 {...}3
1 DIMENSION
2 DIMENSION
3 NUMBER

```

```

\setscript [...]
* hangul hanzi nihongo ethiopic thai test NAME

```

```

\setsecondpasscharacteralign

```

```

\setsectionblock [...]1 [...,...2...,...]2
1 NAME
2 bookmark = TEXT

```

```

\setsimplecolumnshsize [...,...*...,...]*
* n = NUMBER
width = DIMENSION
distance = DIMENSION
lines = NUMBER

```

```

\setsmallbodyfont

```

```

\setsmallcaps

```

```

\setstackbox {...}1 {...}2 {...}3
1 NAME
2 NAME
3 CONTENT

```

```

\setstructurepageregister [...]1 [...,...2...,...]2 [...,...3...,...]3
1 NAME
2 label = NAME
keys = TEXT PROCESSOR->TEXT
entries = TEXT PROCESSOR->TEXT
keys:1 = TEXT
keys:2 = TEXT
keys:3 = TEXT
entries:1 = TEXT
entries:2 = TEXT
entries:3 = TEXT
alternative = TEXT
3 KEY = VALUE

```

```

\setstrut

```

<code>\setsuperiors</code>
<code>\setsystemmode {...}</code> *    NAME
<code>\settabular</code>
<code>\settaggedmetadata [..., ...*..., ...]</code> *    KEY   =   VALUE
<code>\settestcrlf</code>
<code>\settextcontent [...] [...] [...] [...] [...] OPT OPT</code> 1    top header text footer bottom 2    text margin edge 3    left <u>middle</u> right 4    date pagenumber MARK TEXT COMMAND 5    date pagenumber MARK TEXT COMMAND
<code>\settightobject {...} {...} \^3... {...}</code> 1    NAME 2    NAME 3    CSNAME 4    CONTENT
<code>\settightreferencedobject {...} {...} \^3... {...}</code> 1    NAME 2    NAME 3    CSNAME 4    CONTENT
<code>\settightstrut</code>
<code>\settightunreferencedobject {...} {...} \^3... {...}</code> 1    NAME 2    NAME 3    CSNAME 4    CONTENT
<code>\settokenlist [...] {...}</code> 1    NAME 2    TEXT
<code>\settrialtypesetting</code>
<code>\setuevalue {...} {...}</code> 1    NAME 2    CONTENT
<code>\setugvalue {...} {...}</code> 1    NAME 2    CONTENT
<code>\setunreferencedobject {...} {...} \^3... {...}</code> 1    NAME 2    NAME 3    CSNAME 4    CONTENT
<code>\setup [...] [...]</code> *    NAME

```
\setupalign [...,*...]
*   broad wide bottom height line high low lohi flushright flushleft middle yes no width normal reset inner outer
    flushinner flushouter left right center disable last end paragraph lefttoright righttoleft l2r r2l table lesshyphenation
    morehyphenation hanging nothanging hz fullhz nohz hyphenated nothyphenated tolerant verytolerant stretch extremestretch
    final 1*final 2*final 3*final 4*final more 1*more 2*more
```

```
\setupalternativestyles [...,*=...,...]
*   method = normal auto
```

```
\setuparranging [...,*...]
*   disable mirrored doublesided negative 90 180 270 reset background normal 2*16 2*8 2*4 2*2 2**2 2SIDE 2TOP 2UP
    2DOWN 2*4*2 2*2*4 2TOPSIDE 2*8*Z 2*6*Z 1*8 1*4 3SIDE TRYPTICHON ZFLYER-8 ZFLYER-10 ZFLYER-12 MAPFLYER-12 DOUBLEWINDOW
    1*2-Conference 1*4-Conference 2*2*2 2*2*3 XY NAME
```

```
\setupattachment [...,1...] [...,2=...,...]
1   NAME                               OPT
2   title                             = TEXT
    subtitle                          = TEXT
    author                            = TEXT
    file                              = FILE
    name                              = NAME
    buffer                            = BUFFER
    type                              = NAME
    state                             = start stop
    method                            = normal hidden
    symbol                            = Graph Paperclip Pushpin Default
    width                             = fit DIMENSION
    height                           = fit DIMENSION
    depth                             = fit DIMENSION
    color                             = COLOR
    textlayer                         = NAME
    location                          = leftedge rightedge inmargin leftmargin rightmargin text high none
    distance                          = DIMENSION
```

```
\setupattachments [...,1...] [...,2=...,...]
1   NAME                               OPT
2   inherits: \setupattachment
```

```
\setupbackend [...,*=...,...]
*   export                            = yes FILE
    xhtml                             = FILE
    file                              = FILE
    intent                             = Coated_FOGRA39_(ISO_12647-2:2004) GRACoL2006_Coated1v2.icc ISO_Coated_v2_300 ISO_Coated_v2_(ECI)
    ISOnewspaper26v4 ISOnewspaper26v4_gr ISO_Uncoated ISO_Uncoated_Yellowish ISO_Web_Coated Japan_Color_2001_Coated
    Japan_Color_2002_Newspaper Japan_Web_Coated_(Ad) SNAP_2007 SWOP2006_Coated3v2.icc SWOP2006_Coated5v2.icc
    Uncoated_FOGRA29_(ISO_12647-2:2004) Web_Coated_FOGRA28_(ISO_12647-2:2004) PSR_LWC_PLUS_V2_PT PSR_LWC_STD_V2_PT
    PSR_SC_PLUS_V2_PT PSR_SC_STD_V2_PT PSRgravureMF
    space                             = yes no
    xmpfile                           = FILE
    format                            = version default PDF/X-1a:2001 PDF/X-1a:2003 PDF/X-3:2002 PDF/X-3:2003 PDF/X-4 PDF/X-4p PDF/X-5g PDF/X-
    5pg PDF/X-5n PDF/A-1a:2005 PDF/A-1b:2005 PDF/A-2a PDF/A-3a PDF/UA-1
    level                             = NUMBER
    option                            = always never
    profile                           = FILE
```

```
\setupbackground [...,1...] [...,2=...,...]
1   NAME                               OPT
2   state                             = start stop
    leftoffset                        = DIMENSION
    rightoffset                       = DIMENSION
    topoffset                         = DIMENSION
    bottomoffset                      = DIMENSION
    before                           = COMMAND
    after                             = COMMAND
    inherits: \setupframed
```

```
\setupbackgrounds [...,1...] [...,2...,...] [...,3=...,...]
1   top header text footer bottom    OPT
2   leftedge leftmargin text rightmargin rightedge
3   inherits: \setupframed
```



```
\setupbackgrounds [...,1...] [...,2...,...]
1  paper page leftpage rightOPTpage text hidden
2  state = start stop
    inherits: \setupframed
```

```
\setupbar [...,1...] [...,2...,...]
1  NAME OPT
2  color          = COLOR
    continue      = yes no all
    empty         = yes no
    unit          = ex em pt in cm mm sp bp pc dd cc nc
    order         = foreground background
    rulethickness = DIMENSION
    method        = NUMBER
    offset        = NUMBER
    dy            = NUMBER
    max           = NUMBER
    foregroundstyle = STYLE COMMAND
    foregroundcolor = COLOR
    mp            = NAME
    left          = TEXT
    right         = TEXT
```

```
\setupbars [...,1...] [...,2...,...]
1  NAME OPT
2  inherits: \setupbar
```

```
\setupblackrules [...,*...,...]
*  width          = max DIMENSION
    height        = max DIMENSION
    depth         = max DIMENSION
    distance      = DIMENSION
    n             = NUMBER
    alternative    = a b
    style         = STYLE COMMAND
    color         = COLOR
    type          = mp yes no
    mp            = NAME
```

```
\setupblank [...,*...]
*  inherits: \blankOPT
```

```
\setupbleeding [...,*...,...]
*  width          = DIMENSION
    height        = DIMENSION
    offset        = DIMENSION
    hoffset       = DIMENSION
    voffset       = DIMENSION
    location      = t b l r bl lb br rb tl lt tr rt
    stretch      = yes no
    page          = yes no
```

```
\setupblock [...,1...] [...,2...,...]
1  NAME OPT
2  before         = COMMAND
    after         = COMMAND
    left          = COMMAND
    right         = COMMAND
    alternative    = paragraph text
    inner         = COMMAND
    setups        = NAME
    align         = left right middle flushleft flushright inner outer
    style         = STYLE COMMAND
    color         = COLOR
```

```
\setupbodyfont [...,*...]
*  DIMENSION NAME globalPTreset x xx small big script scriptscript rm ss tt hw cg roman serif regular sans sansserif
    support type teletype mono handwritten calligraphic
```

**\setupbookmark** [<sup>1</sup>...<sup>\*</sup>...]

```
* force           = yes no
  number          = yes no
  numberseparatorset = NAME
  numberconversionset = NAME
  numberstarter    = COMMAND
  numberstopper    = COMMAND
  numbersegments   = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
                    current
  sectionblock     = yes no
```

**\setupbottom** [<sup>1</sup>...<sup>2</sup>...]

```
1 text margin edgeOPT
2 state      = start stop empty high none normal nomarking NAME
  style      = STYLE COMMAND
  color      = COLOR
  strut      = yes no
  n          = NUMBER
  before     = COMMAND
  after      = COMMAND
  leftstyle  = STYLE COMMAND
  rightstyle = STYLE COMMAND
  leftcolor  = COLOR
  rightcolor = COLOR
  width      = DIMENSION
  leftwidth  = DIMENSION
  rightwidth = DIMENSION
```

**\setupbottomtexts** [<sup>1</sup>...]<sup>OPT</sup> [<sup>2</sup>...]<sup>OPT</sup> [<sup>3</sup>...]<sup>OPT</sup> [<sup>4</sup>...]<sup>OPT</sup> [<sup>5</sup>...]<sup>OPT</sup>

```
1 text margin edge
2 date pagenumber MARK TEXT COMMAND
3 date pagenumber MARK TEXT COMMAND
4 date pagenumber MARK TEXT COMMAND
5 date pagenumber MARK TEXT COMMAND
```

**\setupbtx** [<sup>1</sup>...]<sup>OPT</sup> [<sup>2</sup>...<sup>2</sup>...]

```
1 NAMEOPT
2 specification = default apa aps NAME
  dataset       = default NAME
  command       = \...##1
  left          = COMMAND
  right         = COMMAND
  authorconversion = normal normalshort normalinverted invertedshort short
  etallimit     = NUMBER
  etaldisplay   = NUMBER
  etaloption    = last
  stopper       = initials
  interaction    = start stop number text page all
  alternative    = default category entry short page num textnum year index tag keywords author authoryears
                  authornum authoryear
  sorttype      = normal reverse
  compress      = yes no
  default       = default NAME
  style         = STYLE COMMAND
  color         = COLOR
```

**\setupbtxdataset** [<sup>1</sup>...<sup>1</sup>...]<sup>OPT</sup> [<sup>2</sup>...<sup>2</sup>...]

```
1 NAMEOPT
2 language = LANGUAGE
```

**\setupbtxlist** [<sup>1</sup>...]<sup>OPT</sup> [<sup>2</sup>...<sup>2</sup>...]

```
1 NAMEOPT
2 inherits: \setuplist
```

**\setupbtxregister** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 state = start stop  
dataset = NAME  
field = keyword range pagenumber author  
register = NAME  
method = once  
alternative = normalshort invertedshort  
style = STYLE COMMAND  
color = COLOR

**\setupbtxrendering** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 textstate = start stop  
pagestate = start stop  
separator = COMMAND  
criterium = previous cite here all none  
filter = TEXT  
specification = NAME  
title = TEXT  
before = COMMAND  
after = COMMAND  
dataset = NAME  
method = dataset force local global none  
sorttype = short dataset list reference used default cite index  
repeat = yes no  
group = NAME  
numbering = yes no num index tag short page

**\setupbtx** [...]

\* NAME

**\setupbuffer** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 BUFFER OPT  
2 before = COMMAND  
after = COMMAND  
strip = yes no

**\setupbutton** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 state = start stop  
samepage = yes no empty none normal default  
style = STYLE COMMAND  
color = COLOR  
contrastcolor = COLOR  
alternative = hidden  
inherits: \setupframed

**\setupcapitals** [...,<sup>1</sup>...] [...,<sup>2</sup>...,...]

1 NAME OPT  
2 title = yes no  
sc = yes no  
style = STYLE COMMAND

**\setupcaption** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME                OPT
2  suffix               = COMMAND
   suffixseparator      = COMMAND
   suffixstopper        = COMMAND
   location             = left right middle low high grid lines overlay inner outer innermargin outermargin leftmargin
                        rightmargin lefthanging righthanging hang top bottom stretch tolerant verytolerant none
                        default
   command              = \...##1
   numbercommand        = \...##1
   textcommand          = \...##1
   spacebefore          = inherits: \blank
   spaceinbetween       = inherits: \blank
   spaceafter           = inherits: \blank
   distance             = DIMENSION
   headstyle            = STYLE COMMAND
   headcolor            = COLOR
   headseparator        = TEXT
   inbetween            = COMMAND
   style                = STYLE COMMAND
   color                = COLOR
   topoffset            = DIMENSION
   bottomoffset         = DIMENSION
   number               = yes no none
   group                = TEXT
   leftmargin           = DIMENSION
   rightmargin          = DIMENSION
   innermargin          = DIMENSION
   outermargin          = DIMENSION
   align                = inherits: \setupalign
   width                = fit max DIMENSION
   minwidth             = fit DIMENSION
   maxwidth             = DIMENSION
   inherits: \setupcounterinherits: \setupframed

```

**\setupcaptions** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME                OPT
2  inherits: \setupcaption

```

**\setupcharacteralign** [...<sup>\*</sup>,...]

```

* leftwidth    = DIMENSION
  rightwidth   = DIMENSION
  leftsample   = TEXT
  rightsample  = TEXT
  character    = TEXT number->TEXT text->TEXT

```

**\setupcharacterkerning** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME                OPT
2  factor              = max NUMBER
   width               = DIMENSION
   features            = NAME
   style               = STYLE COMMAND
   color               = COLOR

```

**\setupcharacterspacing** [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>,...]

```

1  NAME                OPT
2  NUMBER
3  left                = NUMBER
   right               = NUMBER
   alternative         = 0 1

```

```

\setupchemical [...1,...] [...2...,...]
1  NAME                OPT
2  strut                = yes no auto cap fit line default CHARACTER
   width                = fit none NUMBER
   height               = fit none NUMBER
   left                 = fit none NUMBER
   right                = fit none NUMBER
   top                  = fit none NUMBER
   bottom               = fit none NUMBER
   scale                = small medium big normal NUMBER
   rotation             = NUMBER
   symalign             = auto
   axis                 = on off
   framecolor           = COLOR
   rulethickness        = DIMENSION
   offset               = DIMENSION
   unit                 = DIMENSION
   factor               = NUMBER
   frame                = on off
   rulecolor            = COLOR
   bodyfont             = inherits: \setupbodyfont
   size                 = small medium big
   style                = STYLE COMMAND
   color                = COLOR

```

```

\setupchemicalframed [...1,...] [...2...,...]
1  NAME                OPT
2  inherits: \setupframed

```

```

\setupclipping [...*...,...]
*  state                = start stop
   width                = DIMENSION
   height               = DIMENSION
   hoffset              = DIMENSION
   voffset              = DIMENSION
   x                    = NUMBER
   y                    = NUMBER
   nx                   = NUMBER
   ny                   = NUMBER
   sx                   = NUMBER
   sy                   = NUMBER
   leftoffset           = DIMENSION
   rightoffset          = DIMENSION
   topoffset            = DIMENSION
   bottomoffset         = DIMENSION
   mp                   = NAME
   n                    = NUMBER
   offset               = DIMENSION

```

```

\setupcollector [...1,...] [...2...,...]
1  NAME                OPT
2  rotation             = left right inner outer NUMBER
   corner               = left middle right top bottom
   x                    = DIMENSION
   y                    = DIMENSION
   hoffset              = DIMENSION
   voffset              = DIMENSION
   location             = left middle right top bottom line l c r m t b g
   state                = start stop

```

```

\setupcolor [...*]
*  FILE

```

```

\setupcolors [...*...,...]
*  state                = start stop
   spot                 = yes no
   expansion            = yes no
   factor               = yes no
   rgb                  = yes no
   cmyk                 = yes no
   conversion           = yes no always
   pagecolormodel       = auto none NAME
   textcolor            = COLOR
   intent               = overprint knockout none

```

```
\setupcolumns [...,..*...,...]
* inherits: \setupmixedcolumns
```

```
\setupcolumnset [...,1...] [...,..2...,...]
1 NAME NAME:NUMBER OPT
2 n = NUMBER
  nleft = NUMBER
  nright = NUMBER
  width = DIMENSION auto
  distance = DIMENSION
  lines = NUMBER
  maxwidth = DIMENSION
  maxheight = DIMENSION
  direction = normal reverse
  page = inherits: \page
  inherits: \setupframed
```

```
\setupcolumnsetarea [...,1...] [...,..2...,...]
1 NAME OPT
2 state = start stop repeat
  x = NUMBER
  y = NUMBER
  nx = NUMBER
  ny = NUMBER
  style = STYLE COMMAND
  color = COLOR
  clipoffset = DIMENSION
  rightoffset = DIMENSION
  inherits: \setupframed
```

```
\setupcolumnsetareatext [...1] [...2]
1 NAME
2 TEXT
```

```
\setupcolumnsetlines [...1] [...2] [...3] [...4]
1 NAME
2 NUMBER
3 NUMBER
4 NUMBER
```

```
\setupcolumnsetspan [...,1...] [...,..2...,...]
1 NAME OPT
2 n = NUMBER
  style = STYLE COMMAND
  color = COLOR
  before = COMMAND
  after = COMMAND
  inherits: \setupframed
```

```
\setupcolumnsetstart [...1] [...2] [...3] [...4]
1 NAME
2 NUMBER
3 NUMBER
4 NUMBER
```

```
\setupcombination [...,1...] [...,..2...,...]
1 NAME OPT
2 nx = NUMBER
  ny = NUMBER
  width = fit DIMENSION
  height = fit DIMENSION
  location = left middle right top bottom
  distance = DIMENSION
  alternative = label text
  align = inherits: \setupalign
  continue = yes no
  before = COMMAND
  after = COMMAND
  inbetween = COMMAND
  style = STYLE COMMAND
  color = COLOR
```

```
\setupcombinedlist [...]1 [...]2...]
```

```
1 LIST
```

```
2 criterium = local intro reference SECTIONBLOCK:reference all SECTIONBLOCK:all text SECTIONBLOCK:text current
              SECTIONBLOCK:current here previous SECTIONBLOCK:previous component SECTION SECTIONBLOCK:SECTION
  reference = NUMBER
  extras    = NAME
  order     = command all title
  alternative = a b c d e f g left right top bottom command none interactive paragraph horizontal vertical NAME
```

```
\setupCOMBINEDLIST [...]*...]
```

```
* inherits: \setupcombinedlist
```

```
instances: content
```

```
\setupcontent [...]*...]
```

```
* inherits: \setupcombinedlist
```

```
\setupcomment [...]1... [...]2...]
```

```
1 NAME OPT
```

```
2 state = start stop none
  method = normal hidden
  symbol = Comment Help Insert Key Newparagraph Note Paragraph Default
  width = fit DIMENSION
  height = fit DIMENSION
  depth = fit DIMENSION
  title = TEXT
  subtitle = TEXT
  author = TEXT
  nx = NUMBER
  ny = NUMBER
  color = COLOR
  option = xml max
  textlayer = NAME
  location = leftedge rightedge inmargin leftmargin rightmargin text high none
  distance = DIMENSION
  space = yes
  buffer = BUFFER
```

```
\setupcounter [...]1... [...]2...]
```

```
1 NAME OPT
```

```
2 start = NUMBER
  counter = NAME
  method = page
  state = start stop
  way = bypage byblock bytext byhead bySECTION
  prefix = yes no
  prefixseparatorset = NAME
  prefixconversion = NAME
  prefixconversionset = NAME
  prefixstarter = COMMAND PROCESSOR->COMMAND
  prefixstopper = COMMAND PROCESSOR->COMMAND
  prefixset = NAME
  prefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
                  current
  numberorder = reverse
  numberseparatorset = NAME
  numberconversion = NAME
  numberconversionset = NAME
  numberstarter = COMMAND PROCESSOR->COMMAND
  numberstopper = COMMAND PROCESSOR->COMMAND
  numbersegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all
  type = first previous next last number
  criterium = strict positive all
  prefixconnector = COMMAND PROCESSOR->COMMAND
```

```
\setupdataset [...]1... [...]2...]
```

```
1 NAME OPT
```

```
2 delay = yes no
```

`\setupdelimitedtext [...1,...] [...2...,...]`

```

1  NAME NAME:NUMBER          OPT
2  before      = COMMAND
   after       = COMMAND
   language    = local global LANGUAGE
   method      = font
   repeat      = yes no
   location    = text paragraph margin
   left        = COMMAND
   middle      = COMMAND
   right       = COMMAND
   nextleft    = COMMAND
   nextright   = COMMAND
   spacebefore = inherits: \blank
   spaceafter  = inherits: \blank
   leftmargin  = yes no standard DIMENSION
   rightmargin = yes no standard DIMENSION
   indenting   = inherits: \setupindenting
   indentnext  = yes no auto
   style       = STYLE COMMAND
   color       = COLOR
   symstyle    = STYLE COMMAND
   symcolor    = COLOR

```

`\setupdescription [...1,...] [...2...,...]`

```

1  NAME          OPT
2  title         = yes no
   level         = NUMBER
   text          = TEXT
   headcommand   = \...##1
   before        = COMMAND
   after         = COMMAND
   inbetween     = COMMAND
   alternative    = left right inmargin inleft inright margin leftmargin rightmargin innermargin outermargin
                   serried hanging top empty command NAME
   align         = inherits: \setupalign
   headalign     = inherits: \setupalign
   indenting     = inherits: \setupindenting
   display       = yes no
   indentnext    = yes no auto
   width         = fit broad line DIMENSION
   distance      = none DIMENSION
   stretch      = NUMBER
   shrink        = NUMBER
   hang          = fit broad none margin NUMBER
   closesymbol   = COMMAND
   closecommand  = \...##1
   expansion     = yes no xml
   referenceprefix = + - TEXT
   sample        = TEXT
   margin        = yes no standard DIMENSION
   style         = STYLE COMMAND
   color         = COLOR
   headstyle     = STYLE COMMAND
   headcolor     = COLOR
   aligntitle    = yes no

```

`\setupdirections [...*...,...]`

```

*  bidi    = on off local global
   method  = one two default
   fences  = yes no
   break   = both before

```

`\setupdocument [...*...,...]`

```

*  before      = COMMAND
   after       = COMMAND
   metadata:author = TEXT
   metadata:title  = TEXT
   metadata:subject = TEXT
   metadata:keywords = TEXT
   KEY          = VALUE

```



**\setupeffect** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1  NAME          OPT
2  method        = none command
   stretch      = NUMBER
   rulethickness = DIMENSION
   alternative    = normal inner outer both hidden stretch
```

**\setupenumeration** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1  NAME          OPT
2  title         = yes no
   number        = yes no
   numbercommand = \...##1
   titledistance = DIMENSION
   titlestyle    = STYLE COMMAND
   titlecolor    = COLOR
   titlecommand  = \...##1
   titleleft     = COMMAND
   titleright    = COMMAND
   left          = COMMAND
   right         = COMMAND
   symbol        = COMMAND
   starter       = COMMAND
   stopper       = COMMAND
   coupling      = NAME
   counter       = NAME
   level         = NUMBER
   text          = TEXT
   headcommand   = \...##1
   before        = COMMAND
   after         = COMMAND
   inbetween     = COMMAND
   alternative    = left right inmargin inleft inright margin leftmargin rightmargin innermargin outermargin
                  serried hanging top empty command NAME
   align         = inherits: \setupalign
   headalign     = inherits: \setupalign
   indenting     = inherits: \setupindenting
   display       = yes no
   indentnext    = yes no auto
   width         = fit broad line DIMENSION
   distance      = none DIMENSION
   stretch      = NUMBER
   shrink        = NUMBER
   hang          = fit broad none margin NUMBER
   closesymbol   = COMMAND
   closecommand  = \...##1
   expansion     = yes no xml
   referenceprefix = + - TEXT
   sample        = TEXT
   margin        = yes no standard DIMENSION
   style         = STYLE COMMAND
   color         = COLOR
   headstyle     = STYLE COMMAND
   headcolor     = COLOR
   aligntitle    = yes no
   inherits: \setupcounter
```

**\setupenumerations** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```
1  NAME          OPT
2  inherits: \setupenumeration
```

**\setupenv** [...<sup>\*</sup>,...]

```
*  set    = COMMAND
   reset  = COMMAND
   KEY    = VALUE
```

`\setupexport [...,*...]`

```
* align      = flushleft middle flushright normal
bodyfont    = DIMENSION
width       = DIMENSION
title       = TEXT
subtitle    = TEXT
author      = TEXT
alternative = html div
properties  = yes no
hyphen      = yes no
cssfile     = FILE
firstpage   = FILE
lastpage    = FILE
```

`\setupexternalfigure [...,1...] [...,*2...]`

```
1 NAME          OPT
2 width         = DIMENSION
height         = DIMENSION
label          = NAME
page           = NUMBER
object         = yes no
prefix         = TEXT
method         = pdf mps jpg png jp2 jbig svg eps gif tif mov buffer tex cld auto
controls       = yes no
preview        = yes no
mask           = none
resolution     = NUMBER
color          = COLOR
arguments      = TEXT
repeat         = yes no
factor         = fit broad max auto default
hfactor        = fit broad max auto default
wfactor        = fit broad max auto default
maxwidth       = DIMENSION
maxheight      = DIMENSION
equalwidth     = DIMENSION
equalheight    = DIMENSION
scale          = NUMBER
xscale         = NUMBER
yscale         = NUMBER
s              = NUMBER
sx             = NUMBER
sy            = NUMBER
lines          = NUMBER
location       = local global default
directory      = PATH
option         = test frame empty
foregroundcolor = COLOR
reset          = yes no
background     = color foreground NAME
frame          = on off
backgroundcolor = COLOR
xmax           = NUMBER
ymax           = NUMBER
frames         = on off
interaction    = yes all none reference layer bookmark
bodyfont       = DIMENSION
comment        = COMMAND TEXT
size           = none media crop trim art
cache          = PATH
resources      = PATH
display        = FILE
conversion     = TEXT
order          = LIST
crossreference  = yes no NUMBER
transform       = auto NUMBER
userpassword   = TEXT
ownerpassword  = TEXT
```

`\setupexternalsoundtracks [...,*...]`

```
* option = repeat
```

`\setupfacingfloat [...1,...] [...2,...]`

1 NAME OPT  
2 inbetween = COMMAND  
page = inherits: \page  
spaceinbetween = inherits: \blank  
style = STYLE COMMAND  
color = COLOR  
inherits: \setupframed

`\setupfield [...1,...] [...2,...] [...3,...] [...4,...] [...5,...]`

1 NAME OPT OPT OPT OPT  
2 reset label frame horizontal vertical  
3 inherits: \setupfieldtotalframed  
4 inherits: \setupfieldlabelframed  
5 inherits: \setupfieldcontentframed

`\setupfieldbody [...1,...] [...2,...]`

1 NAME OPT  
2 category = NAME  
inherits: \setupfieldcategory

`\setupfieldcategory [...1,...] [...2,...]`

1 NAME OPT  
2 start = NUMBER  
style = STYLE COMMAND  
color = COLOR  
type = radio sub text line push check signature  
values = TEXT  
default = TEXT  
fieldframecolor = COLOR  
fieldbackgroundcolor = COLOR  
width = DIMENSION  
height = DIMENSION  
depth = DIMENSION  
align = left middle right flushleft center flushright  
n = NUMBER  
symbol = NAME  
fieldlayer = NAME  
option = readonly required protected sorted unavailable nocheck fixed file hidden printable auto  
clickin = REFERENCE  
clickout = REFERENCE  
regionin = REFERENCE  
regionout = REFERENCE  
afterkey = REFERENCE  
format = REFERENCE  
validate = REFERENCE  
calculate = REFERENCE  
focusin = REFERENCE  
focusout = REFERENCE  
openpage = REFERENCE  
closepage = REFERENCE

`\setupfieldcontentframed [...1,...] [...2,...]`

1 NAME OPT  
2 inherits: \setupframed inherits: \setupfieldcategory

`\setupfieldlabelframed [...1,...] [...2,...]`

1 NAME OPT  
2 inherits: \setupframed

`\setupfields [...1,...] [...2,...] [...3,...] [...4,...]`

1 reset label frame OPT horizontal vert OPT cal  
2 inherits: \setupfieldtotalframed  
3 inherits: \setupfieldlabelframed  
4 inherits: \setupfieldcontentframed

```

\setupfieldtotalframed [...1,...] [...2,...]
1  NAME                      OPT
2  before                    = COMMAND
   after                     = COMMAND
   inbetween                  = COMMAND
   distance                   = DIMENSION
   alternative                = reset label frame horizontal vertical
   inherits: \setupframed

```

```

\setupfiller [...1,...] [...2,...]
1  NAME                      OPT
2  leftmargin                = DIMENSION
   rightmargin               = DIMENSION
   left                      = COMMAND
   right                     = COMMAND
   alternative                = symbol stretch rule space
   method                    = local global middle broad
   width                     = DIMENSION
   height                    = DIMENSION
   depth                     = DIMENSION
   offset                    = DIMENSION
   distance                  = DIMENSION
   align                     = left right middle flushleft flushright inner outer
   symbol                    = COMMAND
   style                     = STYLE COMMAND
   color                     = COLOR

```

```

\setupfillinlines [...*,...]
*  before                    = COMMAND
   after                     = COMMAND
   margin                    = DIMENSION
   width                     = DIMENSION
   distance                  = DIMENSION
   rulethickness             = DIMENSION
   color                     = COLOR

```

```

\setupfillinrules [...*,...]
*  before                    = COMMAND
   after                     = COMMAND
   n                         = NUMBER
   interlinespace            = small medium big NUMBER
   distance                  = DIMENSION
   width                     = fit broad DIMENSION
   separator                 = COMMAND
   style                     = STYLE COMMAND
   color                     = COLOR

```

```

\setupfirstline [...1,...] [...2,...]
1  NAME                      OPT
2  n                         = NUMBER
   alternative                = default line word
   style                     = STYLE COMMAND
   color                     = COLOR

```

```

\setupfittingpage [...1,...] [...2,...]
1  NAME                      OPT
2  pagestate                 = start stop
   command                   = \...##1
   margin                    = page
   scale                     = NUMBER
   paper                     = auto default NAME
   inherits: \setupframed

```

```

\setupfloat [...1,...] [...2,...]
1 SINGULAR OPT
2 indentnext = yes no auto
   default = inherits: \placefloat
   fallback = inherits: \placefloat
   inner = COMMAND
   criterium = DIMENSION
   method = NUMBER
   sidemethod = NUMBER
   textmethod = NUMBER
   sidealign = height depth line halfline grid normal
   grid = inherits: \suptogrid
   local = yes no
   command = \...##1
   availablewidth = DIMENSION
   availableheight = DIMENSION
   minwidth = DIMENSION
   maxwidth = DIMENSION
   location = left right middle flushleft flushright center max inner outer innermargin outermargin
             inneredge outeredge backspace cutspace leftmargin rightmargin leftedge rightedge
   leftmargindistance = DIMENSION
   rightmargindistance = DIMENSION
   leftmargin = DIMENSION
   rightmargin = DIMENSION
   innermargin = DIMENSION
   outermargin = DIMENSION
   bottombefore = COMMAND
   bottomafter = COMMAND
   expansion = yes no xml
   referenceprefix = + - TEXT
   xmlsetup = NAME
   catcodes = NAME
   freeregion = yes no
   spacebefore = none inherits: \blank
   spaceafter = none inherits: \blank
   width = DIMENSION
   height = DIMENSION
   offset = DIMENSION none overlay
   sidespacebefore = none inherits: \blank
   sidespaceafter = none inherits: \blank
   spacebeforeinside = none inherits: \blank
   spaceafterside = none inherits: \blank
   sidethreshold = old dimension
   margin = DIMENSION
   ntop = NUMBER
   nbottom = NUMBER
   step = small medium big line depth
   nlines = NUMBER
   cache = yes no
   compress = yes no
   compressdistance = DIMENSION
   inherits: \setupframed

```

```

\setupfloatframed [...1,...] [...2,...]
1 NAME OPT
2 inherits: \setupframed

```

```

\setupfloats [...1,...] [...2,...]
1 SINGULAR OPT
2 inherits: \setupfloat

```

```

\setupfloatsplitting [...*,...]
* before = COMMAND
  after = COMMAND
  inbetween = COMMAND
  lines = auto NUMBER
  conversion = NAME

```

```

\setupfontexpansion [...1] [...2,...]
1 NAME
2 vector = NAME
  factor = NUMBER
  stretch = NUMBER
  shrink = NUMBER
  step = NUMBER

```

```
\setupfontprotrusion [...]1 [...,...2...,...]
```

- 1 NAME
- 2 vector = NAME
  - factor = NUMBER
  - left = NUMBER
  - right = NUMBER

```
\setupfonts [...,...*...,...]
```

\* language = no auto

```
\setupfontsolution [...]1,... [...,...2...,...]
```

- 1 NAME OPT
- 2 goodies = FILE
  - solution = NAME
  - less = NAME
  - more = NAME
  - method = preroll split normal reverse random
  - criterium = NUMBER

```
\setupfooter [...]1 [...,...2...,...]
```

- 1 text margin edge<sup>OPT</sup>
- 2 state = start stop empty high none normal nomarking NAME
  - style = STYLE COMMAND
  - color = COLOR
  - strut = yes no
  - n = NUMBER
  - before = COMMAND
  - after = COMMAND
  - leftstyle = STYLE COMMAND
  - rightstyle = STYLE COMMAND
  - leftcolor = COLOR
  - rightcolor = COLOR
  - width = DIMENSION
  - leftwidth = DIMENSION
  - rightwidth = DIMENSION

```
\setupfootertexts [...]1 [...]2 [...]3 [...]4 [...]5
```

- 1 text margin edge OPT OPT OPT OPT OPT
- 2 date pagenumber MARK TEXT COMMAND
- 3 date pagenumber MARK TEXT COMMAND
- 4 date pagenumber MARK TEXT COMMAND
- 5 date pagenumber MARK TEXT COMMAND

```
\setupfootnotes [...,...*...,...]
```

\* inherits: \setupnote

```
\setupforms [...,...*...,...]
```

\* method = XML HTML PDF

export = yes no

`\setupformula [...1,...] [...2...,...]`

```

1  NAME                      OPT
2  location                  = left right
    align                    = left middle right flushleft center flushright normal
    split                    = yes no page
    strut                    = yes no
    distance                 = DIMENSION
    left                     = COMMAND
    right                     = COMMAND
    spacebefore              = inherits: \blank
    spaceafter               = inherits: \blank
    numbercommand            = \...##1
    color                    = COLOR
    numberstyle              = STYLE COMMAND
    numbercolor              = COLOR
    option                   = packed tight middle frame depth line halfline -line -halfline inherits: \setupbodyfont
    margin                   = yes no standard DIMENSION
    leftmargin               = DIMENSION
    rightmargin              = DIMENSION
    alternative              = NAME
    indentnext               = yes no auto
    grid                     = inherits: \suptogrid
    frame                    = number
    hang                     = none auto
    expansion                 = yes no xml
    referenceprefix          = + - TEXT
    xmlsetup                 = NAME
    catcodes                 = NAME
    inherits: \setupcounter

```

`\setupformulaframed [...1,...] [...2...,...]`

```

1  NAME                      OPT
2  inherits: \setupframed

```

`\setupformulas [...1,...] [...2...,...]`

```

1  NAME                      OPT
2  inherits: \setupformula

```

`\setupframed [...1,...] [...2.,...]`

```

1  NAME                      OPT
2  corner                    = rectangular round NUMBER
   framecorner              = rectangular round NUMBER
   backgroundcorner        = rectangular round NUMBER
   radius                   = DIMENSION
   frameradius              = DIMENSION
   backgroundradius        = DIMENSION
   depth                    = DIMENSION
   frameddepth              = DIMENSION
   backgrounddepth         = DIMENSION
   framecolor               = COLOR
   topframe                 = on off small NAME
   bottomframe              = on off small NAME
   leftframe                = on off small NAME
   rightframe               = on off small NAME
   region                   = yes no
   rulethickness            = DIMENSION
   frameoffset              = DIMENSION
   frame                    = on off overlay small closed none
   background               = foreground color NAME
   backgroundoffset         = frame DIMENSION
   component                = NAME
   extras                   = COMMAND
   foregroundstyle          = STYLE COMMAND
   foregroundcolor           = COLOR
   setups                   = NAME
   offset                   = default overlay none DIMENSION
   width                    = local fit max broad fixed DIMENSION
   height                   = fit max broad DIMENSION
   minheight                = DIMENSION
   align                    = inherits: \setupalign
   strut                    = yes no none local global
   autostrut                = yes no
   location                 = height depth high low top middle bottom line lohi hanging keep formula mathematics normal
   autowidth                = yes no force
   lines                    = NUMBER
   top                      = COMMAND
   bottom                   = COMMAND
   blank                    = yes no
   profile                  = NAME
   empty                    = yes no
   loffset                  = DIMENSION
   roffset                  = DIMENSION
   toffset                  = DIMENSION
   boffset                  = DIMENSION
   orientation              = NUMBER

```

`\setupframedcontent [...1,...] [...2.,...]`

```

1  NAME                      OPT
2  left                      = COMMAND
   right                     = COMMAND
   leftoffset                = DIMENSION
   rightoffset               = DIMENSION
   topoffset                 = DIMENSION
   bottomoffset              = DIMENSION
   linecorrection            = yes no
   inherits: \setupframed

```

`\setupframedtable [...1] [...2.,...]`

```

1  NAME                      OPT
2  before                    = COMMAND
   after                     = COMMAND
   inbetween                 = COMMAND
   distance                  = DIMENSION
   inherits: \setupframed

```

`\setupframedtablecolumn [...1] [...2.] [...3.,...]`

```

1  NAME                      OPT
2  NUMBER each
3  inherits: \setupframed

```

`\setupframedtablerow [...1] [...2.] [...3.,...]`

```

1  NAME                      OPT
2  NUMBER each
3  inherits: \setupframed

```



```

\setupframedtext [...1,...] [...2...2...]
1  NAME                      OPT
2  left                      = COMMAND
   right                    = COMMAND
   inner                    = COMMAND
   location                  = left right middle none
   depthcorrection          = on off
   bodyfont                  = inherits: \setupbodyfont
   indenting                 = inherits: \setupindenting
   style                     = STYLE COMMAND
   color                     = COLOR
   inherits: \setupframedinherits: \setupplacement

```

```

\setupframedtexts [...1,...] [...2...2...]
1  NAME                      OPT
2  inherits: \setupframedtext

```

```

\setupglobalreferenceprefix [...*]
*  + - TEXT

```

`\setuphead [...1,...] [...2,...]`

```

1 SECTION OPT
2 frontpartlabel = NAME
  bodypartlabel = NAME
  appendixlabel = NAME
  backpartlabel = NAME
  expansion = yes no xml
  catcodes = NAME
  sectionresetset = NAME
  sectionseparatorset = NAME
  sectionconversionset = NAME
  conversion = NAME
  sectionstarter = COMMAND PROCESSOR->COMMAND
  sectionstopper = COMMAND PROCESSOR->COMMAND
  sectionset = NAME
  sectionsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
                    current
  referenceprefix = + - TEXT
  style = STYLE COMMAND
  color = COLOR
  textstyle = STYLE COMMAND
  textcolor = COLOR
  numberstyle = STYLE COMMAND
  numbercolor = COLOR
  coupling = SECTION
  ownnumber = yes no
  beforesection = COMMAND
  aftersection = COMMAND
  insidesection = COMMAND
  incrementnumber = yes no list empty
  placehead = yes no hidden empty section
  number = yes no
  page = inherits: \page
  marking = page reset
  header = start stop high none normal empty nomarking NAME
  text = start stop high none normal empty nomarking NAME
  footer = start stop high none normal empty nomarking NAME
  before = COMMAND
  after = COMMAND
  inbetween = COMMAND
  continue = yes no
  aligntitle = yes no float
  interlinespace = NAME
  interaction = list reference
  internalgrid = NAME
  grid = normal standard yes strict tolerant top bottom both broad fit first last high one low
        none line strut box min max middle math math:line math:halfline math:-line math:-halfline
        NAME
  align = inherits: \setupalign
  tolerance = inherits: \setuptolerance
  strut = yes no
  hang = line broad fit none NUMBER
  margin = DIMENSION
  indentnext = yes no auto
  alternative = text paragraph normal margin inmargin top middle bottom reverse margintext NAME
  width = DIMENSION
  numberwidth = DIMENSION
  textwidth = DIMENSION
  distance = DIMENSION
  textdistance = DIMENSION
  commandbefore = COMMAND
  commandafter = COMMAND
  command = \...##1##2
  textcommand = \...##1
  deeptextcommand = \...##1
  numbercommand = \...##1
  deepnumbercommand = \...##1
  location = NAME
  criterium = strict positive all
  hidenummer = yes no

```

`\setupheadalternative [...1,...] [...2,...]`

```

1 NAME OPT
2 alternative = horizontal vertical somewhere
  renderingsetup = NAME

```

```

\setupheader [...] [...]
1 text margin edgeOPT
2 state = start stop empty high none normal nomarking NAME
  style = STYLE COMMAND
  color = COLOR
  strut = yes no
  n = NUMBER
  before = COMMAND
  after = COMMAND
  leftstyle = STYLE COMMAND
  rightstyle = STYLE COMMAND
  leftcolor = COLOR
  rightcolor = COLOR
  width = DIMENSION
  leftwidth = DIMENSION
  rightwidth = DIMENSION

```

```

\setupheadertexts [...] [...] [...] [...] [...]
1 text margin edgeOPT OPT OPT OPT OPT
2 date pagenumber MARK TEXT COMMAND
3 date pagenumber MARK TEXT COMMAND
4 date pagenumber MARK TEXT COMMAND
5 date pagenumber MARK TEXT COMMAND

```

```

\setupheadnumber [...] [...]
1 SECTION
2 [-+]NUMBER

```

```

\setupheads [...] [...]
1 SECTIONOPT
2 inherits: \setuphead

```

```

\setuphelp [...] [...]
1 NAMEOPT
2 inherits: \setupframed

```

```

\setuphigh [...] [...]
1 NAMEOPT
2 distance = DIMENSION
  up = DIMENSION
  style = STYLE COMMAND
  color = COLOR

```

```

\setuphighlight [...] [...]
1 NAMEOPT
2 command = yes no
  style = STYLE COMMAND
  color = COLOR

```

```

\setuphyphenation [...]
* method = original tex default hyphenate expanded traditional none

```

```

\setuphyphenmark [...]
* sign = normal wide

```

```

\setupindentedtext [...] [...]
1 NAMEOPT
2 before = COMMAND
  after = COMMAND
  distance = DIMENSION
  sample = TEXT
  text = TEXT
  width = fit broad DIMENSION
  separator = COMMAND
  style = STYLE COMMAND
  color = COLOR
  headstyle = STYLE COMMAND
  headcolor = COLOR

```

`\setupindenting [...1,...]`

\* [-+]small [-+]medium [<sup>PT</sup>+]big none no not first next yes always never odd even normal reset toggle DIMENSION NAME

`\setupinitial [...1,...2,...]`

1 NAME OPT  
2 n = NUMBER  
m = NUMBER  
before = COMMAND  
distance = DIMENSION  
hoffset = DIMENSION  
voffset = line DIMENSION  
style = STYLE COMMAND  
color = COLOR  
font = FONT  
text = TEXT  
location = margin text  
method = first last auto none

`\setupinsertion [...1,...2,...]`

1 NAME OPT  
2 location = page text columns firstcolumn lastcolumn

`\setupinteraction [...1,...2,...]`

1 NAME OPT  
2 state = start stop  
style = STYLE COMMAND  
color = COLOR  
contrastcolor = COLOR  
title = TEXT  
subtitle = COLOR  
author = TEXT  
date = TEXT  
keyword = TEXT  
focus = standard frame width minwidth height minheight fit tight  
menu = on off  
fieldlayer = auto NAME  
calculate = REFERENCE  
click = yes no  
display = normal new  
page = yes no page name auto  
openaction = REFERENCE  
closeaction = REFERENCE  
openpageaction = REFERENCE  
closepageaction = REFERENCE  
symbolset = NAME  
height = DIMENSION  
depth = DIMENSION  
focusoffset = DIMENSION

`\setupinteractionbar [...1,...2,...]`

1 NAME OPT  
2 alternative = a b c d e f g  
state = start stop  
command = CSNAME  
width = DIMENSION  
height = DIMENSION max broad  
depth = DIMENSION max  
distance = DIMENSION  
step = small medium big  
backgroundcolor = COLOR  
style = STYLE COMMAND  
color = COLOR  
contrastcolor = COLOR  
symbol = yes no  
inherits: \setupframed

`\setupinteractionmenu [...1,...] [...2,...]`

1 NAME OPT  
2 alternative = vertical horizontal hidden  
category = NAME  
leftoffset = overlay frame none default DIMENSION  
rightoffset = overlay frame none default DIMENSION  
topoffset = overlay frame none default DIMENSION  
bottomoffset = overlay frame none default DIMENSION  
maxwidth = DIMENSION  
maxheight = DIMENSION  
itemalign = left middle right flushleft flushright low high lohi  
state = start empty local  
left = COMMAND  
right = COMMAND  
distance = overlay DIMENSION  
before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
position = yes no  
middle = COMMAND  
style = STYLE COMMAND  
color = COLOR  
samepage = yes no empty none normal default  
contrastcolor = COLOR  
inherits: \setupframed

`\setupinteractionscreen [...*,...]`

\* width = fit max tight DIMENSION  
height = fit max tight DIMENSION  
backspace = DIMENSION  
horoffset = DIMENSION  
veroffset = DIMENSION  
topspace = DIMENSION  
option = fit max singlesided doublesided bookmark auto none default fixed landscape portrait page paper  
attachment layer title lefttoright righttoleft nomenubar  
copies = NUMBER  
print = LIST  
delay = none NUMBER

`\setupinteraction [...]`

\* NAME OPT

`\setupinterlinespace [...1,...] [...2,...]`

1 NAME OPT  
2 line = DIMENSION  
height = NUMBER  
depth = NUMBER  
minheight = NUMBER  
mindepth = NUMBER  
distance = DIMENSION  
top = NUMBER height  
bottom = NUMBER  
stretch = NUMBER  
shrink = NUMBER

`\setupinterlinespace [...*,...]`

\* on off reset auto small medium <sup>opt</sup>big NUMBER DIMENSION

`\setupinterlinespace [...]`

\* NAME

`\setupitaliccorrection [...*,...]`

\* text always global none

```

\setupitemgroup [...]1 [...]2 [...]3 [...]4
1 NAME OPT OPT OPT
2 each NUMBER
3 intro random continue packed autointro broad text before after nowwhite margin inmargin atmargin intext loose fit
  nofit paragraph joinedup serried stopper nostopper unpacked repeat norepeat reverse columns one two three four
  five six seven eight nine standard NUMBER*broad NUMBER*serried horizontal NAME
4 before = COMMAND
  after = COMMAND
  inbetween = COMMAND
  beforehead = COMMAND
  afterhead = COMMAND
  lefttext = COMMAND
  righttext = COMMAND
  left = COMMAND
  right = COMMAND
  factor = NUMBER
  step = DIMENSION
  width = DIMENSION
  distance = DIMENSION
  margin = yes no standard DIMENSION
  leftmargin = yes no standard DIMENSION
  rightmargin = yes no standard DIMENSION
  leftmargindistance = yes no standard DIMENSION
  rightmargindistance = yes no standard DIMENSION
  align = inherits: \setupalign
  indenting = inherits: \setupindenting
  start = NUMBER
  symalign = left middle right flushleft center flushright
  symbol = NAME
  n = NUMBER
  indentnext = yes no auto
  inner = COMMAND
  command = CSNAME
  items = NUMBER
  maxwidth = DIMENSION
  itemalign = left right middle flushleft flushright inner outer
  alignsymbol = yes no
  textdistance = small medium big none space DIMENSION
  placestopper = yes no
  style = STYLE COMMAND
  color = COLOR
  headstyle = STYLE COMMAND
  headcolor = COLOR
  marstyle = STYLE COMMAND
  marcolor = COLOR
  symstyle = STYLE COMMAND
  symcolor = COLOR
  grid = inherits: \definegridsnapping
inherits: \setupcounter

```

```

\setupitemgroups [...1,...] [...2,...]
1 NAME NAME:NUMBER OPT
2 before = COMMAND
  after = COMMAND
  inbetween = COMMAND
  beforehead = COMMAND
  afterhead = COMMAND
  lefttext = COMMAND
  righttext = COMMAND
  left = COMMAND
  right = COMMAND
  factor = NUMBER
  step = DIMENSION
  width = DIMENSION
  distance = DIMENSION
  option = intro random continue packed autointro broad text before after nowwhite margin inmargin
           atmargin intext loose fit nofit paragraph joinedup serried stopper unpacked repeat norepeat
           reverse columns one two three four five six seven eight nine standard NUMBER*broad NUMBER*serried
           horizontal NAME
margin = yes no standard DIMENSION
leftmargin = yes no standard DIMENSION
rightmargin = yes no standard DIMENSION
leftmargindistance = yes no standard DIMENSION
rightmargindistance = yes no standard DIMENSION
align = inherits: \setupalign
indenting = inherits: \setupindenting
start = NUMBER
symalign = left middle right flushleft center flushright
symbol = NAME
n = NUMBER
indentnext = yes no auto
inner = COMMAND
command = CSNAME
items = NUMBER
maxwidth = DIMENSION
itemalign = left right middle flushleft flushright inner outer
alignsymbol = yes no
textdistance = small medium big none space DIMENSION
placestopper = yes no
style = STYLE COMMAND
color = COLOR
headstyle = STYLE COMMAND
headcolor = COLOR
marstyle = STYLE COMMAND
marcolor = COLOR
symstyle = STYLE COMMAND
symcolor = COLOR
grid = inherits: \definegridsnapping
inherits: \setupcounter

```

```

\setupitemgroup [...1,...] [...2,...]
1  NAME NAME:NUMBER      OPT
2  before                 =  COMMAND
   after                  =  COMMAND
   inbetween              =  COMMAND
   beforehead             =  COMMAND
   afterhead              =  COMMAND
   lefttext               =  COMMAND
   righttext              =  COMMAND
   left                   =  COMMAND
   right                  =  COMMAND
   factor                 =  NUMBER
   step                   =  DIMENSION
   width                  =  DIMENSION
   distance               =  DIMENSION
   option                 =  intro random continue packed autointro broad text before after nowwhite margin inmargin
                           atmargin intext loose fit nofit paragraph joinedup serried stopper unpacked repeat norepeat
                           reverse columns one two three four five six seven eight nine standard NUMBER*broad NUMBER*serried
                           horizontal NAME
   margin                 =  yes no standard DIMENSION
   leftmargin             =  yes no standard DIMENSION
   rightmargin            =  yes no standard DIMENSION
   leftmargindistance     =  yes no standard DIMENSION
   rightmargindistance    =  yes no standard DIMENSION
   align                  =  inherits: \setupalign
   indenting              =  inherits: \setupindenting
   start                  =  NUMBER
   symalign               =  left middle right flushleft center flushright
   symbol                 =  NAME
   n                      =  NUMBER
   indentnext            =  yes no auto
   inner                  =  COMMAND
   command                =  CSNAME
   items                 =  NUMBER
   maxwidth               =  DIMENSION
   itemalign              =  left right middle flushleft flushright inner outer
   alignsymbol            =  yes no
   textdistance           =  small medium big none space DIMENSION
   placestopper           =  yes no
   style                  =  STYLE COMMAND
   color                 =  COLOR
   headstyle              =  STYLE COMMAND
   headcolor              =  COLOR
   marstyle               =  STYLE COMMAND
   marcolor               =  COLOR
   symstyle               =  STYLE COMMAND
   symcolor               =  COLOR
   grid                   =  inherits: \definegridsnapping
   inherits: \setupcounter

```



```

\setupITEMGROUP [...,1...] [...,2...] [...,3...,...]
1  each NUMBER          OPT          OPT          OPT
2  intro random continue packed autointro broad text before after nowwhite margin inmargin atmargin intext loose fit
   nofit paragraph joinedup serried stopper nostopper unpacked repeat norepeat reverse columns one two three four
   five six seven eight nine standard NUMBER*broad NUMBER*serried horizontal NAME
3  before                = COMMAND
   after                 = COMMAND
   inbetween             = COMMAND
   beforehead            = COMMAND
   afterhead             = COMMAND
   lefttext              = COMMAND
   righttext             = COMMAND
   left                  = COMMAND
   right                 = COMMAND
   factor                = NUMBER
   step                  = DIMENSION
   width                 = DIMENSION
   distance              = DIMENSION
   margin                = yes no standard DIMENSION
   leftmargin            = yes no standard DIMENSION
   rightmargin           = yes no standard DIMENSION
   leftmargindistance    = yes no standard DIMENSION
   rightmargindistance   = yes no standard DIMENSION
   align                 = inherits: \setupalign
   indenting             = inherits: \setupindenting
   start                 = NUMBER
   symalign              = left middle right flushleft center flushright
   symbol                = NAME
   n                     = NUMBER
   indentnext            = yes no auto
   inner                 = COMMAND
   command               = CSNAME
   items                 = NUMBER
   maxwidth              = DIMENSION
   itemalign             = left right middle flushleft flushright inner outer
   alignsymbol           = yes no
   textdistance          = small medium big none space DIMENSION
   placestopper          = yes no
   style                 = STYLE COMMAND
   color                 = COLOR
   headstyle             = STYLE COMMAND
   headcolor             = COLOR
   marstyle              = STYLE COMMAND
   marcolor              = COLOR
   symstyle              = STYLE COMMAND
   symcolor              = COLOR
   grid                  = inherits: \definegridsnapping
   inherits: \setupcounter
instances: itemize

```

```

\setupitemize [...1,...] [...2,...] [...3,...]
1  each NUMBER      OPT      OPT      OPT
2  intro random continue packed autointro broad text before after nowwhite margin inmargin atmargin intext loose fit
   nofit paragraph joinedup serried stopper nostopper unpacked repeat norepeat reverse columns one two three four
   five six seven eight nine standard NUMBER*broad NUMBER*serried horizontal NAME
3  before           = COMMAND
   after            = COMMAND
   inbetween        = COMMAND
   beforehead       = COMMAND
   afterhead        = COMMAND
   lefttext         = COMMAND
   righttext        = COMMAND
   left             = COMMAND
   right            = COMMAND
   factor           = NUMBER
   step             = DIMENSION
   width            = DIMENSION
   distance         = DIMENSION
   margin           = yes no standard DIMENSION
   leftmargin       = yes no standard DIMENSION
   rightmargin      = yes no standard DIMENSION
   leftmargindistance = yes no standard DIMENSION
   rightmargindistance = yes no standard DIMENSION
   align            = inherits: \setupalign
   indenting        = inherits: \setupindenting
   start            = NUMBER
   symalign         = left middle right flushleft center flushright
   symbol           = NAME
   n                = NUMBER
   indentnext       = yes no auto
   inner            = COMMAND
   command          = CSNAME
   items            = NUMBER
   maxwidth         = DIMENSION
   itemalign        = left right middle flushleft flushright inner outer
   alignsymbol      = yes no
   textdistance     = small medium big none space DIMENSION
   placestopper     = yes no
   style            = STYLE COMMAND
   color            = COLOR
   headstyle        = STYLE COMMAND
   headcolor        = COLOR
   marstyle         = STYLE COMMAND
   marcolor         = COLOR
   symstyle         = STYLE COMMAND
   symcolor         = COLOR
   grid             = inherits: \definegridsnapping
   inherits: \setupcounter

```

```

\setupitems [...1,...] [...2,...]
1  NAME      OPT
2  alternative = left right top bottom inmargin
   textwidth  = DIMENSION
   width      = DIMENSION
   distance   = DIMENSION
   symbol     = none NAME
   align      = left middle right flushleft flushright inner outer margin
   textalign  = left middle right flushleft flushright inner outer
   n          = NUMBER
   before     = COMMAND
   after      = COMMAND
   inbetween  = COMMAND

```

```

\setuplabel [...1...2...] [...2...1...]
1 NAME OPT
2 title = yes no
  number = yes no
  numbercommand = \...##1
  titledistance = DIMENSION
  titlestyle = STYLE COMMAND
  titlecolor = COLOR
  titlecommand = \...##1
  titleleft = COMMAND
  titleright = COMMAND
  left = COMMAND
  right = COMMAND
  symbol = COMMAND
  starter = COMMAND
  stopper = COMMAND
  coupling = NAME
  counter = NAME
  level = NUMBER
  text = TEXT
  headcommand = \...##1
  before = COMMAND
  after = COMMAND
  inbetween = COMMAND
  alternative = left right inmargin inleft inright margin leftmargin rightmargin innermargin outermargin
                serried hanging top empty command intext NAME

  align = inherits: \setupalign
  headalign = inherits: \setupalign
  indenting = inherits: \setupindenting
  display = yes no
  indentnext = yes no auto
  width = fit broad line DIMENSION
  distance = none DIMENSION
  stretch = NUMBER
  shrink = NUMBER
  hang = fit broad none margin NUMBER
  closesymbol = COMMAND
  closecommand = \...##1
  expansion = yes no xml
  referenceprefix = + - TEXT
  sample = TEXT
  margin = yes no standard DIMENSION
  style = STYLE COMMAND
  color = COLOR
  headstyle = STYLE COMMAND
  headcolor = COLOR
  aligntitle = yes no
  inherits: \setupcounter

```

```

\setupLABELtext [...1...2...]
1 LANGUAGE OPT
2 KEY = VALUE
instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

```

```

\setupbtxlabeltext [...1...2...]
1 LANGUAGE OPT
2 KEY = VALUE

```

```

\setupheadtext [...1...2...]
1 LANGUAGE OPT
2 KEY = VALUE

```

```

\setuplabeltext [...1...2...]
1 LANGUAGE OPT
2 KEY = VALUE

```

```

\setupmathlabeltext [...1...2...]
1 LANGUAGE OPT
2 KEY = VALUE

```

```

\setupoperatortext [...1...2...]
1 LANGUAGE OPT
2 KEY = VALUE

```

`\setupprefixtext [...]1 [...,...2...]`

1 LANGUAGE OPT

2 KEY = VALUE

`\setupsuffixtext [...]1 [...,...2...]`

1 LANGUAGE OPT

2 KEY = VALUE

`\setuptaglabeltext [...]1 [...,...2...]`

1 LANGUAGE OPT

2 KEY = VALUE

`\setupunittext [...]1 [...,...2...]`

1 LANGUAGE OPT

2 KEY = VALUE

`\setuplanguage [...]1 [...,...2...]`

1 LANGUAGE default OPT

2 default = LANGUAGE  
state = start stop  
date = inherits: \currentdate  
time = inherits: \currenttime  
patterns = FILE  
lefthyphenmin = NUMBER  
righthyphenmin = NUMBER  
lefthyphenchar = NUMBER  
righthyphenchar = NUMBER  
setups = NAME  
spacing = broad packed  
font = auto NAME  
bidi = left right l2r r2l  
text = TEXT  
limittext = TEXT  
hyphen = TEXT  
compoundhyphen = TEXT  
leftcompoundhyphen = TEXT  
rightcompoundhyphen = TEXT  
leftquote = COMMAND  
rightquote = COMMAND  
leftquotation = COMMAND  
rightquotation = COMMAND  
leftspeech = COMMAND  
rightspeech = COMMAND  
leftsentence = COMMAND  
middlespeech = COMMAND  
rightsentence = COMMAND  
midsentence = COMMAND  
leftsubsentence = COMMAND  
rightsubsentence = COMMAND  
factor = yes no

`\setupplayer [...,1...] [...,2...]`

```

1  NAME          OPT
2  state          = start stop continue next repeat
   option         = test
   page           = NUMBER
   width          = DIMENSION
   height         = DIMENSION
   region         = NAME
   rotation       = left right inner outer NUMBER
   position       = yes no overlay
   hoffset        = max DIMENSION
   voffset        = max DIMENSION
   offset         = DIMENSION
   dx             = DIMENSION
   dy             = DIMENSION
   sx             = NUMBER
   sy             = NUMBER
   x              = DIMENSION
   y              = DIMENSION
   corner         = left middle right top bottom
   location       = grid left middle right top bottom line l c r m t b g
   line           = NUMBER
   column         = NUMBER
   direction      = normal reverse
   doublesided    = yes no
   method         = fit overlay
   repeat         = yes
   preset         = lefttop righttop leftbottom rightbottom middle middletop middlebottom middleleft middleright
                  leftopleft lefttopright NAME

```

`\setuplayeredtext [...,1...] [...,2...]`

```

1  NAME          OPT
2  style         = STYLE COMMAND
   color         = COLOR
   inherits:     \setupframed

```

\setuplayout [...]<sup>1</sup> [...,...<sup>2</sup>...,...]

```

1  NAME          OPT
2  state          = start stop normal repeat
   margin         = DIMENSION
   edge           = DIMENSION
   margindistance = DIMENSION
   edgedistance   = DIMENSION
   leftedgedistance = DIMENSION
   rightedgedistance = DIMENSION
   leftmargindistance = DIMENSION
   rightmargindistance = DIMENSION
   topdistance    = DIMENSION
   headerdistance  = DIMENSION
   footerdistance  = DIMENSION
   bottomdistance = DIMENSION
   preset         = NAME
   leftmargin     = DIMENSION
   rightmargin    = DIMENSION
   leftedge       = DIMENSION
   rightedge      = DIMENSION
   header         = DIMENSION
   footer         = DIMENSION
   top            = DIMENSION
   bottom         = DIMENSION
   backspace      = DIMENSION
   topspace       = DIMENSION
   setups         = NAME
   cutspace       = DIMENSION
   width          = DIMENSION middle fit
   bottomspace    = DIMENSION
   lines          = NUMBER
   height         = DIMENSION middle fit
   horoffset      = DIMENSION
   veroffset      = DIMENSION
   columns        = NUMBER
   columndistance = DIMENSION
   method         = default normal NAME
   location       = left middle right top bottom singlesided doublesided
   textwidth      = DIMENSION
   textheight     = DIMENSION
   nx            = NUMBER
   ny            = NUMBER
   dx            = DIMENSION
   dy            = DIMENSION
   scale         = NUMBER
   sx            = NUMBER
   sy            = NUMBER
   marking        = on off page empty color one two four
   grid          = yes no off
   textdistance   = DIMENSION
   alternative    = default normal makeup NAME
   clipoffset     = DIMENSION
   cropoffset     = DIMENSION auto
   trimoffset     = DIMENSION
   bleedoffset    = DIMENSION
   artoffset      = DIMENSION

```

\setuplayouttext [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]

```

1  top header text footer bottomOPT
2  text margin edge
3  state          = start stop empty high none normal nomarking NAME
   style         = STYLE COMMAND
   color         = COLOR
   strut         = yes no
   n             = NUMBER
   before        = COMMAND
   after         = COMMAND
   leftstyle     = STYLE COMMAND
   rightstyle    = STYLE COMMAND
   leftcolor     = COLOR
   rightcolor    = COLOR
   width         = DIMENSION
   leftwidth     = DIMENSION
   rightwidth    = DIMENSION

```

\setuplayout [...]

\* reset NAME

`\setuplinefiller [...,1...] [...,2...]`

```
1 NAME OPT
2 location = left right both
scope = left right local
mp = NAME
height = DIMENSION
depth = DIMENSION
distance = DIMENSION
threshold = DIMENSION
rulethickness = DIMENSION
before = COMMAND
after = COMMAND
color = COLOR
textstyle = STYLE COMMAND
textcolor = COLOR
align = inherits: \setupalign
```

`\setuplinefillers [...,1...] [...,2...]`

```
1 NAME OPT
2 inherits: \setuplinefiller
```

`\setuplinenote [...,1...] [...,2...]`

```
1 NAME OPT
2 compress = yes no
compressmethod = separator stopper space
compressseparator = COMMAND
compressdistance = DIMENSION
inherits: \setupnote
```

`\setuplinenumbering [...,1...] [...,2...]`

```
1 NAME OPT
2 start = NUMBER
step = NUMBER
method = page first next
conversion = NAME
continue = yes no
location = text begin end default left right inner outer inleft inright margin inmargin
distance = DIMENSION
align = inner outer flushleft flushright left right middle auto
command = \...##1
left = COMMAND
right = COMMAND
margin = DIMENSION
width = margin DIMENSION
style = STYLE COMMAND
color = COLOR
```

`\setuplines [...,1...] [...,2...]`

```
1 NAME OPT
2 option = packed
before = COMMAND
after = COMMAND
inbetween = COMMAND
indenting = inherits: \setupindenting
align = inherits: \setupalign
space = yes on off fixed default
command = COMMAND
style = STYLE COMMAND
color = COLOR
left = COMMAND
right = COMMAND
```

`\setuplinetable` [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...,...=...,...]

```

1  r c          OPT      OPT
2  odd even header NUMBER
3  lines        = fit NUMBER
   before       = COMMAND
   after        = COMMAND
   inbetween    = COMMAND
   stretch     = yes no DIMENSION
   maxwidth     = fit DIMENSION
   nleft       = NUMBER
   n            = NUMBER
   repeat      = yes no
   nx          = NUMBER
   width       = DIMENSION
   height      = fit line DIMENSION
   distance    = DIMENSION
   leftoffset  = DIMENSION
   rightoffset = DIMENSION
   align       = inherits: \setupalign
   background  = color
   backgroundcolor = COLOR
   xheight     = max DIMENSION
   xdepth     = max DIMENSION
   style       = STYLE COMMAND
   color       = COLOR

```

`\setuplinewidth` [.\*]

\* small medium big DIMENSION



```

\setuplist [...1,...] [...2,...]
1  LIST
2  state = start stop
location = none here
type = simple command userdata
criterion = local intro reference SECTIONBLOCK:reference all SECTIONBLOCK:all text SECTIONBLOCK:text
current SECTIONBLOCK:current here previous SECTIONBLOCK:previous component SECTION
SECTIONBLOCK:SECTION
list = NAME
width = fit broad DIMENSION
height = fit broad DIMENSION
depth = fit broad DIMENSION
symbol = one two three none default
label = yes no none NAME
starter = COMMAND
stopper = COMMAND
command = \...##1##2##3
numbercommand = \...##1
textcommand = \...##1
pagecommand = \...##1
pagenumber = yes no always
headnumber = yes no always
before = COMMAND
after = COMMAND
inbetween = COMMAND
margin = none DIMENSION
distance = none DIMENSION
aligntitle = yes no
numeralalign = left right middle flushleft flushright inner outer
align = inherits: \setupalign
hang = yes no
left = COMMAND
right = COMMAND
interaction = yes no all number text title page sectionnumber pagenumber
limittext = yes no TEXT
style = STYLE COMMAND
color = COLOR
numberstyle = STYLE COMMAND
numbercolor = COLOR
textstyle = STYLE COMMAND
textcolor = COLOR
pagestyle = STYLE COMMAND
pagecolor = COLOR
reference = NUMBER
extras = NAME
order = command all title
alternative = a b c d e f g left right top bottom command none interactive paragraph horizontal
vertical NAME
maxwidth = DIMENSION
pageprefix = yes no
pageprefixseparatorset = NAME
pageprefixconversionset = NAME
pageprefixset = NAME
pageprefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
current
pageprefixconnector = COMMAND PROCESSOR->COMMAND
pageconversionset = NAME
pagestarter = COMMAND PROCESSOR->COMMAND
pagestopper = COMMAND PROCESSOR->COMMAND
inherits: \setupcounterinherits: \setupframed

```

```

\setuplistalternative [...1,...] [...2,...]
1  NAME
2  before = COMMAND
after = COMMAND
command = \...##1##2##3
renderingsetup = NAME
width = DIMENSION
distance = DIMENSION
stretch = DIMENSION
filler = COMMAND

```

```

\setuplistextra [...1,...] [...2,...]
1  NAME
2  before = COMMAND
after = COMMAND

```

`\setuplocalfloats [...,..*...,...]`

\* before = COMMAND  
after = COMMAND  
inbetween = COMMAND

`\setuplocalinterlinespace [...,..1...] [...,..2...,...]`

1 NAME OPT  
2 inherits: \setupinterlinespace

`\setuplocalinterlinespace [...,..*...]`

\* on off reset auto small medium big NUMBER DIMENSION

`\setuplocalinterlinespace [...,..*...]`

\* NAME

`\setuplow [...,..1...] [...,..2...,...]`

1 NAME OPT  
2 distance = DIMENSION  
down = DIMENSION  
style = STYLE COMMAND  
color = COLOR

`\setuplowhigh [...,..1...] [...,..2...,...]`

1 NAME OPT  
2 distance = DIMENSION  
up = DIMENSION  
down = DIMENSION  
style = STYLE COMMAND  
color = COLOR

`\setuplowmidhigh [...,..1...] [...,..2...,...]`

1 NAME OPT  
2 up = DIMENSION  
down = DIMENSION  
style = STYLE COMMAND  
color = COLOR

`\setupMPgraphics [...,..*...,...]`

\* color = local global  
mpy = FILE

`\setupMPinstance [...,..1...] [...,..2...,...]`

1 NAME OPT  
2 format = metafun mpost  
initializations = yes no  
setups = NAME  
textstyle = STYLE COMMAND  
textcolor = COLOR  
extensions = yes no  
method = binary decimal double scaled default

`\setupMPpage [...,..*...,...]`

\* pagestate = start stop  
command = \...##1  
margin = page  
scale = NUMBER  
paper = auto default NAME  
inherits: \setupframed

`\setupMPvariables [...,..1...] [...,..2...,...]`

1 NAME OPT  
2 KEY = VALUE

`\setupmakeup [...1,...] [...2...,...]`

```
1 NAME OPT
2 page = inherits: \page
  command = COMMAND
  width = DIMENSION
  height = DIMENSION
  align = inherits: \setupalign
  setups = NAME
  top = COMMAND
  bottom = COMMAND
  before = COMMAND
  after = COMMAND
  location = top
  reference = REFERENCE
  pagestate = start stop
  headerstate = start stop high empty none normal
  footerstate = start stop high empty none normal
  topstate = start stop high empty none normal
  bottomstate = start stop high empty none normal
  textstate = start stop high empty none normal
  doublesided = yes no empty
  style = STYLE COMMAND
  color = COLOR
```

`\setupmarginblock [...1,...] [...2...,...]`

```
1 NAME OPT
2 state = start stop
  width = DIMENSION
  before = COMMAND
  after = COMMAND
  inbetween = COMMAND
  align = inherits: \setupalign
  style = STYLE COMMAND
  color = COLOR
  top = COMMAND
  bottom = COMMAND
  location = left right middle inmargin
  left = COMMAND
  right = COMMAND
```

`\setupmargindata [...1,...] [...2...,...]`

```
1 NAME OPT
2 strut = yes no auto cap fit line default CHARACTER
  command = \...##1
  width = DIMENSION
  align = inherits: \setupalign
  anchor = region text
  location = left right inner outer
  method = top line first depth height
  category = default edge
  scope = local global
  option = text paragraph
  margin = local normal margin edge
  distance = DIMENSION
  hoffset = DIMENSION
  voffset = DIMENSION
  dy = DIMENSION
  bottomspace = DIMENSION
  threshold = DIMENSION
  line = NUMBER
  stack = yes continue
  style = STYLE COMMAND
  color = COLOR
```

`\setupmarginframed [...1,...] [...2...,...]`

```
1 NAME OPT
2 inherits: \setupframed
```

`\setupmarginrule [1...] [...2...,...]`

```
1 NUMBER OPT
2 inherits: \setupsidebar
```

`\setupmarginrules [...1] [...2...]`

1    NUMBER                    OPT  
2    inherits: \setupmarginrule

`\setupmarking [...1...] [...2...]`

1    MARK                    OPT  
2    state            = start stop  
     expansion        = yes no  
     separator        = COMMAND  
     filtercommand    = \...##1

`\setupmathalignment [...1...] [...2...]`

1    NAME                    OPT  
2    n                = NUMBER  
     m                = NUMBER  
     distance        = DIMENSION  
     number          = auto  
     separator        = TEXT  
     align            = left middle right normal  
     location        = top center bottom normal  
     grid             = math no

`\setupmathcases [...1...] [...2...]`

1    NAME                    OPT  
2    left                = COMMAND  
     right               = COMMAND  
     strut               = yes no  
     style                = STYLE COMMAND  
     distance            = DIMENSION  
     numberdistance    = DIMENSION

`\setupmathematics [...1...] [...2...]`

1    NAME                    OPT  
2    openup                = yes no  
     symbolset            = NAME  
     functionstyle        = STYLE COMMAND  
     compact               = yes no  
     align                = l2r r2l righttoleft  
     bidi                 = yes no  
     sygreek              = normal italic none  
     lcgreek              = normal italic none  
     ucgreek              = normal italic none  
     italics              = 1 2 3 4 none reset  
     autopunctuation    = yes no all comma yes,semicolon comma,semicolon all,semicolon  
     setups                = NAME  
     domain               = NAME reset  
     textstyle            = STYLE COMMAND  
     textcolor            = COLOR  
     functioncolor        = COLOR  
     integral             = limits nolimits autolimits displaylimits none  
     stylealternative    = NAME  
     default              = normal italic  
     fraction             = ams ctx  
     ampersand            = normal  
     collapsing          = 1 2 3 none reset  
     kernpairs            = yes no

`\setupmathfence [...1...] [...2...]`

1    NAME                    OPT  
2    command            = yes no  
     left                = NUMBER  
     middle              = NUMBER  
     right               = NUMBER  
     mathstyle          = display text script scriptscript cramped uncramped normal packed small big  
     color                = COLOR  
     state                = auto  
     method              = auto  
     size                = NUMBER  
     factor              = none auto NUMBER  
     mathclass          = NUMBER

```

\setupmathfraction [...1,...] [...2...,...]
1 NAME OPT
2 topdistance = DIMENSION
bottomdistance = DIMENSION
margin = DIMENSION
color = COLOR
strut = yes no math tight
alternative = inner outer both
rule = yes no auto
left = NUMBER
right = NUMBER
rulethickness = DIMENSION
mathstyle = STYLE COMMAND
distance = no none overlay
inlinethreshold = auto NUMBER
displaythreshold = auto NUMBER
fences = NAME

```

```

\setupmathfractions [...1,...] [...2...,...]
1 NAME OPT
2 inherits: \setupmathfraction

```

```

\setupmathframed [...1,...] [...2...,...]
1 NAME OPT
2 inherits: \setupframed

```

```

\setupmathmatrix [...1,...] [...2...,...]
1 NAME OPT
2 left = COMMAND
right = COMMAND
strut = yes no NUMBER
align = left middle right normal
style = STYLE COMMAND
distance = DIMENSION
simplecommand = TEXT
location = top bottom high low lohi normal

```

```

\setupmathornament [...1,...] [...2...,...]
1 NAME OPT
2 alternative = mp
color = COLOR
mpoffset = DIMENSION
mp = NAME

```

```

\setupmathradical [...1,...] [...2...,...]
1 NAME OPT
2 alternative = default normal mp
color = COLOR
mpoffset = DIMENSION
mp = NAME

```

`\setupmathstackers [...1,...] [...2,...]`

```

1  NAME                      OPT
2  left                      = COMMAND
   right                     = COMMAND
   topcommand                = \...##1
   bottomcommand             = \...##1
   middlecommand             = \...##1
   mp                        = NAME
   mpheight                  = DIMENSION
   mpdepth                   = DIMENSION
   mpoffset                  = DIMENSION
   color                     = COLOR
   hoffset                   = DIMENSION
   voffset                   = DIMENSION
   minheight                 = DIMENSION
   mindepth                  = DIMENSION
   mathclass                 = rel ord
   offset                    = min max normal
   location                  = top bottom high low middle NUMBER
   strut                     = yes no
   alternative               = normal default mp
   minwidth                  = DIMENSION
   distance                  = DIMENSION
   moffset                   = DIMENSION
   order                     = normal reverse
   mathlimits                = yes no

```

`\setupmathstyle [...*,...]`

\* display text script scriptscript cramped uncramped normal packed small big NAME

`\setupmixedcolumns [...1,...] [...2,...]`

```

1  NAME                      OPT
2  grid                      = inherits: \definegridsnapping
   rulethickness             = DIMENSION
   method                   = otr box
   before                   = COMMAND
   after                    = COMMAND
   distance                  = DIMENSION
   n                         = NUMBER
   maxheight                 = DIMENSION
   maxwidth                  = DIMENSION
   step                     = DIMENSION
   profile                   = NAME
   align                     = inherits: \setupalign
   setups                   = NAME
   balance                   = yes no
   splitmethod               = none fixed
   alternative               = local global
   internalgrid              = line halfline
   separator                 = rule
   strut                     = yes no
   color                     = COLOR
   rulecolor                 = COLOR
   direction                 = normal reverse
   inherits: \setupframed

```

`\setupmodule [...1] [...2,...]`

```

1  FILE                      OPT
2  test                      = yes no
   KEY                       = VALUE

```

`\setupnarrower [...1,...] [...2,...]`

```

1  NAME                      OPT
2  left                      = DIMENSION
   middle                    = DIMENSION
   right                     = DIMENSION
   default                   = [-+]left [-+]middle [-+]right NUMBER*left NUMBER*middle NUMBER*right reset
   before                    = COMMAND
   after                     = COMMAND

```

```

\setupnotation [...1,...] [...2,...]
1  NAME                OPT
2  title                = yes no
   number               = yes no
   type                 = note
   numbercommand        = \...##1
   titledistance        = DIMENSION
   titlestyle           = STYLE COMMAND
   titlecolor           = COLOR
   titlecommand         = \...##1
   titleleft            = COMMAND
   titleright           = COMMAND
   left                 = COMMAND
   right                = COMMAND
   symbol               = COMMAND
   starter              = COMMAND
   stopper              = COMMAND
   coupling             = NAME
   counter              = NAME
   level                = NUMBER
   text                 = TEXT
   headcommand          = \...##1
   before               = COMMAND
   after                = COMMAND
   inbetween            = COMMAND
   alternative           = left right inmargin inleft inright margin leftmargin rightmargin innermargin outermargin
                        serried hanging top command note NAME
   align                = inherits: \setupalign
   headalign            = inherits: \setupalign
   indenting            = inherits: \setupindenting
   display              = yes no
   indentnext           = yes no auto
   width                = fit broad line DIMENSION
   distance             = none DIMENSION
   stretch             = NUMBER
   shrink               = NUMBER
   hang                 = fit broad none margin NUMBER
   closesymbol          = COMMAND
   closecommand         = \...##1
   expansion            = yes no xml
   referenceprefix      = + - TEXT
   sample               = TEXT
   margin               = yes no standard DIMENSION
   style                = STYLE COMMAND
   color                = COLOR
   headstyle            = STYLE COMMAND
   headcolor            = COLOR
   aligntitle           = yes no
   inherits: \setupcounter

```

```

\setupnotations [...1,...] [...2,...]
1  NAME                OPT
2  inherits: \setupnotation

```

```

\setupnote [...1,...] [...2,...]
1 NAME OPT
2 interaction = yes no number text all
symbolcommand = \...##1
textcommand = \...##1
indicator = yes no
textseparator = COMMAND
width = DIMENSION
height = DIMENSION
distance = DIMENSION
rulecommand = COMMAND
rule = on off normal left right command paragraph
split = tolerant strict verystrict NUMBER
factor = NUMBER
location = text page high bottom none columns firstcolumn lastcolumn
next = COMMAND
n = NUMBER
rulecolor = COLOR
rulethickness = DIMENSION
setups = NAME
interlinespace = NAME
paragraph = yes no
before = COMMAND
after = COMMAND
inbetween = COMMAND
scope = page
columndistance = DIMENSION
continue = yes no
alternative = grid fixed columns note none
criterium = page
bodyfont = inherits: \setupbodyfont
align = inherits: \setupalign
textstyle = STYLE COMMAND
textcolor = COLOR
anchor = next
spacebefore = inherits: \blank
spaceinbetween = inherits: \blank
inherits: \setupframed

```

```

\setupnotes [...1,...] [...2,...]
1 NAME OPT
2 inherits: \setupnote

```

```

\setupoffset [...*,...]
* inherits: \setupoffsetbox

```

```

\setupoffsetbox [...*,...]
* x = DIMENSION
y = DIMENSION
leftoffset = DIMENSION
rightoffset = DIMENSION
topoffset = DIMENSION
bottomoffset = DIMENSION
method = fixed
width = DIMENSION
height = DIMENSION
depth = DIMENSION
location = left middle right top bottom line l c r m t b g

```

```

\setupoppositeplacing [...*,...]
* state = start stop
before = COMMAND
after = COMMAND
inbetween = COMMAND

```

```

\setupoutputroutine [...1] [...2,...]
1 NAME OPT
2 KEY = CSNAME

```

```

\setupoutputroutine [...*]
* NAME

```



`\setuppagechecker [...,1...] [...,2...,...]`

1 NAME OPT  
2 lines = NUMBER  
offset = DIMENSION  
method = 0 1 2 3  
before = COMMAND  
after = COMMAND  
inbetween = COMMAND

`\setuppagecolumns [...,1...] [...,2...,...]`

1 NAME OPT  
2 separator = NAME  
direction = normal reverse  
distance = DIMENSION  
n = NUMBER  
maxwidth = DIMENSION  
align = inherits: \setupalign  
blank = inherits: \blank  
color = COLOR  
setups = NAME  
page = inherits: \page  
inherits: \setupframed

`\setuppagecomment [...,*...,...]`

\* location = left right top bottom none  
state = start stop none  
offset = DIMENSION  
distance = DIMENSION  
width = DIMENSION  
height = DIMENSION

`\setuppageinjection [...,1...] [...,2...,...]`

1 NAME OPT  
2 state = previous next NUMBER  
delay = yes no  
alternative = figure buffer setups none NAME  
page = inherits: \page  
pagestate = start stop  
n = NUMBER  
inherits: \setupframed

`\setuppageinjectionalternative [...,1...] [...,2...,...]`

1 NAME OPT  
2 renderingsetup = NAME

`\setuppagenumber [...,*...,...]`

\* viewerprefix = TEXT  
state = start stop none keep empty  
inherits: \setupcounter

`\setuppagenumbering [...,*...,...]`

\* alternative = singlesided doublesided  
page = inherits: \page  
strut = yes no  
command = \...##1  
left = COMMAND  
right = COMMAND  
state = start stop  
width = DIMENSION  
location = header footer left middle right inleft inright margin inmargin atmargin marginedge  
style = STYLE COMMAND  
color = COLOR

`\setuppageshift [...1] [...2] [...3]`

1 page paper OPT OPT  
2 NAME  
3 NAME

**\setuppagestate** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

- 1 NAME OPT
- 2 delay = yes no

**\setuppagetransitions** [...]

\* reset auto start random NUMBER

**\setuppairedbox** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

- 1 NAME OPT
- 2 before = COMMAND
- after = COMMAND
- inbetween = COMMAND
- location = left middle right top bottom high low
- n = NUMBER
- distance = DIMENSION
- bodyfont = inherits: \setupbodyfont
- width = DIMENSION
- height = DIMENSION
- maxwidth = DIMENSION
- maxheight = DIMENSION
- align = inherits: \setupalign
- style = STYLE COMMAND
- color = COLOR

**\setupPAIREDBOX** [...<sup>\*</sup>,...]

\* inherits: \setuppairedbox

instances: legend

**\setuplegend** [...<sup>\*</sup>,...]

\* inherits: \setuppairedbox

**\setuppalet** [...]

\* NAME

**\setuppaper** [...<sup>\*</sup>,...]

\* inherits: \setuppapersize

**\setuppapersize** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

- 1 NAME OPT
- 2 top = COMMAND
- bottom = COMMAND
- left = COMMAND
- right = COMMAND
- method = normal none NAME
- scale = NUMBER
- nx = NUMBER
- ny = NUMBER
- dx = DIMENSION
- dy = DIMENSION
- width = DIMENSION
- height = DIMENSION
- topspace = DIMENSION
- backspace = DIMENSION
- offset = DIMENSION
- page = reset landscape mirrored negative rotated 90 180 270 NAME
- paper = reset landscape mirrored negative rotated 90 180 270 NAME
- option = fit max
- distance = DIMENSION

**\setuppapersize** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

- 1 reset landscape mirrored OPT negative rotated 90 180 270 NAME
- 2 reset landscape mirrored OPT negative rotated 90 180 270 NAME

**\setupparagraph** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

- 1 NAME OPT
- 2 style = STYLE COMMAND
- color = COLOR
- align = inherits: \setupalign
- setups = NAME

`\setupparagraphintro [...1,...] [...2]`

1 reset each first next  
2 COMMAND

`\setupparagraphnumbering [...,*...,...]`

\* state = start stop line reset  
distance = DIMENSION  
style = STYLE COMMAND  
color = COLOR

`\setupparagraphs [...1] [...,2,...] [...,3...,...]`

1 NAME OPT OPT  
2 each NUMBER  
3 n = NUMBER  
before = COMMAND  
after = COMMAND  
width = DIMENSION  
distance = DIMENSION  
height = DIMENSION fit  
top = COMMAND  
bottom = COMMAND  
align = inherits: \setupalign  
inner = COMMAND  
command = COMMAND  
rule = on off  
rulethickness = DIMENSION  
rulecolor = COLOR  
style = STYLE COMMAND  
color = COLOR

`\setupparagraphs [...1] [...,2...,...]`

1 NAME NAME:NUMBER OPT  
2 n = NUMBER  
before = COMMAND  
after = COMMAND  
width = DIMENSION  
distance = DIMENSION  
height = DIMENSION fit  
top = COMMAND  
bottom = COMMAND  
align = inherits: \setupalign  
inner = COMMAND  
command = COMMAND  
rule = on off  
rulethickness = DIMENSION  
rulecolor = COLOR  
style = STYLE COMMAND  
color = COLOR

`\setupparallel [...1] [...,2,...] [...,3...,...]`

1 NAME  
2 NAME  
3 setups = NAME  
start = NUMBER  
n = NUMBER  
criterium = all

`\setupperiodkerning [...1,...] [...,2...,...]`

1 NAME OPT  
2 factor = NUMBER

`\setupperiods [...,*...,...]`

\* n = NUMBER  
width = DIMENSION fit  
distance = DIMENSION  
symbol = COMMAND

```
\setupplacement [...1,...] [...2,...]
1 NAME OPT
2 before = COMMAND
  after = COMMAND
  left = COMMAND
  right = COMMAND
  grid = inherits: \snaptogrid
  linecorrection = on off
  depthcorrection = on off
  margin = yes no standard
```

```
\setuppositionbar [...*,...]
* style = STYLE COMMAND
  color = COLOR
  n = NUMBER
  min = NUMBER
  max = NUMBER
  text = TEXT
  width = DIMENSION
  height = DIMENSION
  depth = DIMENSION
```

```
\setuppositioning [...1,...] [...2,...]
1 NAME OPT
2 offset = yes no
  unit = ex em pt in cm mm sp bp pc dd cc nc
  state = start overlay
  xoffset = DIMENSION
  yoffset = DIMENSION
  xstep = absolute relative
  ystep = absolute relative
  xscale = NUMBER
  yscale = NUMBER
  xfactor = NUMBER
  yfactor = NUMBER
  factor = NUMBER
  scale = NUMBER
```

```
\setupprocessor [...1,...] [...2,...]
1 NAME OPT
2 state = start stop
  left = COMMAND
  right = COMMAND
  command = \...##1
  style = STYLE COMMAND
  color = COLOR
```

```
\setupprofile [...1,...] [...2,...]
1 NAME OPT
2 height = DIMENSION
  depth = DIMENSION
  distance = DIMENSION
  factor = NUMBER
  lines = NUMBER
  method = strict fixed none
```

```
\setupprograms [...*,...]
* style = STYLE COMMAND
  color = COLOR
```

```
\setupquotation [...*,...]
* inherits: \setupdelimitedtext
```

```
\setupquote [...*,...]
* inherits: \setupdelimitedtext
```

```
\setuprealpagenumber [...*,...]
* inherits: \setupcounter
```

```
\setupreferenceformat [...,1...] [...,2...,...]
```

```
1 NAME OPT
2 label = * NAME
left = COMMAND
right = COMMAND
type = default text title number page realpage
setups = NAME
autocase = yes no
text = TEXT
style = STYLE COMMAND
color = COLOR
```

```
\setupreferenceprefix [...]
```

```
* + - TEXT
```

```
\setupreferencestructureprefix [...,1] [...,2] [...,3...,...]
```

```
1 NAME SECTION OPT OPT
2 default
3 prefix = yes no
prefixseparatorset = NAME
prefixconversion = NAME
prefixconversionset = NAME
prefixstarter = COMMAND PROCESSOR->COMMAND
prefixstopper = COMMAND PROCESSOR->COMMAND
prefixset = NAME
prefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
current
numberconversion = NAME
numberconversionset = NAME
numberstarter = COMMAND PROCESSOR->COMMAND
numberstopper = COMMAND PROCESSOR->COMMAND
numbersegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all
numberseparatorset = NAME
prefixconnector = COMMAND PROCESSOR->COMMAND
```

```
\setupreferencing [...,*...,...]
```

```
* state = start stop
expansion = yes no xml
autofile = yes no
export = yes no
left = COMMAND
right = COMMAND
width = DIMENSION
doublesided = yes no
interaction = label text symbol all
separator = COMMAND
prefix = + - TEXT
```

\setupregister [...]<sup>1</sup> [...,...]<sup>2</sup> [...,...]

```

1 NAME NAME:NUMBER OPT
2 referencemethod = forward
  expansion = yes no xml
  ownnumber = yes no
  xmlsetup = NAME
  alternative = a b A B
  method = default before after first last ch mm zm pm mc zc pc uc
  compress = yes no all packed text
  check = yes no
  criterium = local text current previous all SECTION
  pageprefixseparatorset = COMMAND
  pageprefixconversionset = NAME
  pageprefixstarter = COMMAND PROCESSOR->COMMAND
  pageprefixstopper = COMMAND PROCESSOR->COMMAND
  pageprefixset = NAME
  pageprefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
                        current
  pageprefixconnector = COMMAND
  pageprefix = yes no
  pageseparatorset = NAME
  pageconversionset = NAME
  pagestarter = COMMAND PROCESSOR->COMMAND
  pagestopper = COMMAND PROCESSOR->COMMAND
  pagesegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all
  maxwidth = DIMENSION
  indicator = yes no
  before = COMMAND
  after = COMMAND
  command = \...##1
  textcommand = \...##1
  deeptextcommand = \...##1
  pagecommand = \...##1
  distance = DIMENSION
  interaction = text pagenumber
  pagenumber = yes no
  symbol = a n none 1 2 COMMAND
  language = default DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn LANGUAGE
  style = STYLE COMMAND
  color = COLOR
  textstyle = STYLE COMMAND
  textcolor = COLOR
  pagestyle = STYLE COMMAND
  pagecolor = COLOR
  pageleft = COMMAND
  pageright = COMMAND
  n = NUMBER
  balance = yes no
  align = inherits: \setupalign
  numberorder = numbers

```

\setupregisters [...]<sup>1</sup> [...,...]<sup>2</sup>

```

1 NAME NAME:NUMBER OPT
2 referencemethod = forward
  expansion = yes no xml
  ownnumber = yes no
  xmlsetup = NAME
  alternative = a b A B
  method = default before after first last ch mm zm pm mc zc pc uc
  compress = yes no all packed text
  check = yes no
  criterium = local text current previous all SECTION
  pageprefixseparatorset = COMMAND
  pageprefixconversionset = NAME
  pageprefixstarter = COMMAND PROCESSOR->COMMAND
  pageprefixstopper = COMMAND PROCESSOR->COMMAND
  pageprefixset = NAME
  pageprefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
                        current
  pageprefixconnector = COMMAND
  pageprefix = yes no
  pageseparatorset = NAME
  pageconversionset = NAME
  pagestarter = COMMAND PROCESSOR->COMMAND
  pagestopper = COMMAND PROCESSOR->COMMAND
  pagesegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all
  maxwidth = DIMENSION
  indicator = yes no
  before = COMMAND
  after = COMMAND
  command = \...##1
  textcommand = \...##1
  deeptextcommand = \...##1
  pagecommand = \...##1
  distance = DIMENSION
  interaction = text pagenumber
  pagenumber = yes no
  symbol = a n none 1 2 COMMAND
  language = default DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn LANGUAGE
  style = STYLE COMMAND
  color = COLOR
  textstyle = STYLE COMMAND
  textcolor = COLOR
  pagestyle = STYLE COMMAND
  pagecolor = COLOR
  pageleft = COMMAND
  pageright = COMMAND
  n = NUMBER
  balance = yes no
  align = inherits: \setupalign
  numberorder = numbers

```

```

\setupregisters [...1,...] [...2,...] [...3,...3,...]
1  NAME                OPT                OPT
2  NUMBER
3  referencemethod      = forward
   expansion            = yes no xml
   ownnumber            = yes no
   xmlsetup             = NAME
   alternative          = a b A B
   method               = default before after first last ch mm zm pm mc zc pc uc
   compress             = yes no all packed text
   check                = yes no
   criterium            = local text current previous all SECTION
   pageprefixseparatorset = COMMAND
   pageprefixconversionset = NAME
   pageprefixstarter    = COMMAND PROCESSOR->COMMAND
   pageprefixstopper    = COMMAND PROCESSOR->COMMAND
   pageprefixset        = NAME
   pageprefixsegments   = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
                           current
   pageprefixconnector  = COMMAND
   pageprefix           = yes no
   pageseparatorset     = NAME
   pageconversionset    = NAME
   pagestarter          = COMMAND PROCESSOR->COMMAND
   pagestopper          = COMMAND PROCESSOR->COMMAND
   pagesegments         = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all
   maxwidth             = DIMENSION
   indicator            = yes no
   before               = COMMAND
   after                = COMMAND
   command              = \...##1
   textcommand          = \...##1
   deeptextcommand      = \...##1
   pagecommand          = \...##1
   distance             = DIMENSION
   interaction          = text pagenumber
   pagenumber           = yes no
   symbol               = a n none 1 2 COMMAND
   language             = default DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn LANGUAGE
   style                = STYLE COMMAND
   color                = COLOR
   textstyle            = STYLE COMMAND
   textcolor            = COLOR
   pagestyle            = STYLE COMMAND
   pagecolor            = COLOR
   pageleft             = COMMAND
   pageright            = COMMAND
   n                    = NUMBER
   balance              = yes no
   align                = inherits: \setupalign
   numberorder          = numbers

```



```

\setupregister [...] [...] [...]
1 NAME OPT OPT
2 NUMBER
3 referencemethod = forward
expansion = yes no xml
ownnumber = yes no
xmlsetup = NAME
alternative = a b A B
method = default before after first last ch mm zm pm mc zc pc uc
compress = yes no all packed text
check = yes no
criterium = local text current previous all SECTION
pageprefixseparatorset = COMMAND
pageprefixconversionset = NAME
pageprefixstarter = COMMAND PROCESSOR->COMMAND
pageprefixstopper = COMMAND PROCESSOR->COMMAND
pageprefixset = NAME
pageprefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
current
pageprefixconnector = COMMAND
pageprefix = yes no
pageseparatorset = NAME
pageconversionset = NAME
pagestarter = COMMAND PROCESSOR->COMMAND
pagestopper = COMMAND PROCESSOR->COMMAND
pagesegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all
maxwidth = DIMENSION
indicator = yes no
before = COMMAND
after = COMMAND
command = \...##1
textcommand = \...##1
deeptextcommand = \...##1
pagecommand = \...##1
distance = DIMENSION
interaction = text pagenumber
pagenumber = yes no
symbol = a n none 1 2 COMMAND
language = default DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn LANGUAGE
style = STYLE COMMAND
color = COLOR
textstyle = STYLE COMMAND
textcolor = COLOR
pagestyle = STYLE COMMAND
pagecolor = COLOR
pageleft = COMMAND
pageright = COMMAND
n = NUMBER
balance = yes no
align = inherits: \setupalign
numberorder = numbers

```

```

\setupREGISTER [...1,...] [...2,...]
1  NUMBER          OPT
2  referencemethod = forward
   expansion       = yes no xml
   ownnumber       = yes no
   xmlsetup        = NAME
   alternative     = a b A B
   method         = default before after first last ch mm zm pm mc zc pc uc
   compress        = yes no all packed text
   check           = yes no
   criterium       = local text current previous all SECTION
   pageprefixseparatorset = COMMAND
   pageprefixconversionset = NAME
   pageprefixstarter = COMMAND PROCESSOR->COMMAND
   pageprefixstopper = COMMAND PROCESSOR->COMMAND
   pageprefixset   = NAME
   pageprefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
                        current
   pageprefixconnector = COMMAND
   pageprefix      = yes no
   pageseparatorset = NAME
   pageconversionset = NAME
   pagestarter     = COMMAND PROCESSOR->COMMAND
   pagestopper     = COMMAND PROCESSOR->COMMAND
   pagesegments    = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all
   maxwidth        = DIMENSION
   indicator       = yes no
   before          = COMMAND
   after           = COMMAND
   command         = \...##1
   textcommand     = \...##1
   deeptextcommand = \...##1
   pagecommand     = \...##1
   distance        = DIMENSION
   interaction     = text pagenumber
   pagenumber      = yes no
   symbol          = a n none 1 2 COMMAND
   language        = default DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn LANGUAGE
   style           = STYLE COMMAND
   color           = COLOR
   textstyle       = STYLE COMMAND
   textcolor       = COLOR
   pagestyle       = STYLE COMMAND
   pagecolor       = COLOR
   pageleft        = COMMAND
   pageright       = COMMAND
   n               = NUMBER
   balance         = yes no
   align           = inherits: \setupalign
   numberorder     = numbers
instances: index

```

`\setupindex [...1,...] [...2,...]`

```
1  NUMBER          OPT
2  referencemethod  = forward
   expansion        = yes no xml
   ownnumber        = yes no
   xmlsetup         = NAME
   alternative      = a b A B
   method           = default before after first last ch mm zm pm mc zc pc uc
   compress         = yes no all packed text
   check            = yes no
   criterium        = local text current previous all SECTION
   pageprefixseparatorset = COMMAND
   pageprefixconversionset = NAME
   pageprefixstarter = COMMAND PROCESSOR->COMMAND
   pageprefixstopper = COMMAND PROCESSOR->COMMAND
   pageprefixset     = NAME
   pageprefixsegments = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all SECTION SECTION:SECTION SECTION:* SECTION:all
                        current
   pageprefixconnector = COMMAND
   pageprefix        = yes no
   pageseparatorset  = NAME
   pageconversionset  = NAME
   pagestarter       = COMMAND PROCESSOR->COMMAND
   pagestopper       = COMMAND PROCESSOR->COMMAND
   pagesegments      = NUMBER NUMBER:NUMBER NUMBER:* NUMBER:all
   maxwidth          = DIMENSION
   indicator         = yes no
   before            = COMMAND
   after            = COMMAND
   command           = \...##1
   textcommand       = \...##1
   deeptextcommand   = \...##1
   pagecommand       = \...##1
   distance          = DIMENSION
   interaction        = text pagenumber
   pagenumber        = yes no
   symbol            = a n none 1 2 COMMAND
   language          = default DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn LANGUAGE
   style             = STYLE COMMAND
   color             = COLOR
   textstyle         = STYLE COMMAND
   textcolor         = COLOR
   pagestyle         = STYLE COMMAND
   pagecolor         = COLOR
   pageleft          = COMMAND
   pageright         = COMMAND
   n                 = NUMBER
   balance           = yes no
   align             = inherits: \setupalign
   numberorder       = numbers
```

`\setuprenderingwindow [...1,...] [...2,...]`

```
1  NAME          OPT
2  openpageaction = REFERENCE
   closepageaction = REFERENCE
   inherits: \setupframed
```

`\setuprotate [...*,...]`

```
*  location = fit broad depth high middle default normal
   rotation = left right inner outer NUMBER
   inherits: \setupframed
```

`\setuprubby [...1,...] [...2,...]`

```
1  NAME          OPT
2  location      = top left right none
   align         = auto flushleft middle flushright
   stretch      = yes no
   hoffset       = DIMENSION
   voffset       = DIMENSION
   distance      = none DIMENSION
   left          = COMMAND
   right         = COMMAND
   style         = STYLE COMMAND
   color         = COLOR
```

**\setups** [...<sup>1</sup>,...]

\* NAME

**\setupscale** [...<sup>1</sup>,...]<sup>2</sup> [...<sup>2</sup>,...]

1 NAME OPT  
2 scale = NUMBER  
xscale = NUMBER  
yscale = NUMBER  
width = DIMENSION  
height = DIMENSION  
depth = yes no  
lines = NUMBER  
factor = fit broad max min auto default  
hfactor = fit broad max min auto default  
wfactor = fit broad max min auto default  
maxwidth = DIMENSION  
maxheight = DIMENSION  
s = NUMBER  
sx = NUMBER  
sy = NUMBER  
equalwidth = DIMENSION  
equalheight = DIMENSION  
grid = yes fit height depth halfline

**\setupscript** [...<sup>1</sup>,...]<sup>2</sup> [...<sup>2</sup>,...]

1 NAME OPT  
2 method = hangul hanzi nihongo ethiopic thai test  
preset = NAME  
features = auto

**\setupscripts** [...<sup>1</sup>,...]<sup>2</sup> [...<sup>2</sup>,...]

1 NAME OPT  
2 inherits: \setupscript

**\setupsectionblock** [...<sup>1</sup>,...]<sup>2</sup> [...<sup>2</sup>,...]

1 NAME OPT  
2 page = inherits: \page  
before = COMMAND  
after = COMMAND  
number = yes no

**\setupselector** [...<sup>1</sup>,...]<sup>2</sup> [...<sup>2</sup>,...]

1 NAME  
2 n = NUMBER  
m = NUMBER

**\setupshift** [...<sup>1</sup>,...]<sup>2</sup> [...<sup>2</sup>,...]

1 NAME OPT  
2 continue = yes no  
unit = ex em pt in cm mm sp bp pc dd cc nc  
method = NUMBER  
dy = NUMBER  
align = inherits: \setupalign  
style = STYLE COMMAND  
color = COLOR

**\setupsidebar** [...<sup>1</sup>,...]<sup>2</sup> [...<sup>2</sup>,...]

1 NAME OPT  
2 rulethickness = DIMENSION  
rulecolor = COLOR  
alternative = NUMBER  
topoffset = DIMENSION  
bottomoffset = DIMENSION  
distance = DIMENSION  
leftmargindistance = DIMENSION  
level = NUMBER

**\setupsorting** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 SINGULAR OPT  
2 expansion = yes no xml  
alternative = first last normal NAME  
next = COMMAND  
command = \...##1##2##3  
textcommand = \...##1  
synonymcommand = \...##1  
language = default DIN\_5007-1 DIN\_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn LANGUAGE  
method = default before after first last ch mm zm pm mc zc pc uc  
criterium = current previous local text all SECTION  
style = STYLE COMMAND  
color = COLOR  
textstyle = STYLE COMMAND  
textcolor = COLOR  
synonymstyle = STYLE COMMAND  
synonymcolor = COLOR

**\setupspacing** [...]

\* fixed packed broad<sup>OPT</sup>

**\setupspellchecking** [...<sup>\*</sup>,...]

\* state = start stop  
method = 1 2 3  
list = NAME

**\setupstartstop** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
setups = NAME  
left = COMMAND  
right = COMMAND  
style = STYLE COMMAND  
color = COLOR

**\setupstretched** [...<sup>\*</sup>,...]

\* inherits: \setupcharacterkerning

**\setupstruts** [...]

\* yes no auto cap<sup>OPT</sup>Fit line default CHARACTER

**\setupstyle** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 method = command  
style = STYLE COMMAND  
color = COLOR

**\setupsubformula** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 indentnext = yes no auto

**\setupsubformulas** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

1 NAME OPT  
2 inherits: \setupsubformula

**\setupsubpagenumber** [...<sup>\*</sup>,...]

\* inherits: \setupcounter

**\setupsymbols** [...<sup>\*</sup>,...]

\* stylealternative = text math

**\setupsymbolset** [...]

\* NAME

```
\setupsynctex [...,*...,...]
```

```
* state = start stop  
method = min max
```

```
\setupsynonyms [...,1...] [...,2...,...]
```

```
1 SINGULAR OPT  
2 expansion = yes no xml  
alternative = first last normal NAME  
next = COMMAND  
command = \...##1##2##3  
textcommand = \...##1  
synonymcommand = \...##1  
language = default DIN_5007-1 DIN_5007-2 Duden de-DE de-CH de-AT ru-iso9 ocs-scn LANGUAGE  
method = default before after first last ch mm zm pm mc zc pc uc  
criterium = current previous local text all SECTION  
style = STYLE COMMAND  
color = COLOR  
textstyle = STYLE COMMAND  
textcolor = COLOR  
synonymstyle = STYLE COMMAND  
synonymcolor = COLOR
```

```
\setups {...,*...}
```

```
* NAME
```

```
\setupTABLE [...,1...] [...,2...] [...,3...,...]
```

```
1 r c x y row columnHT first last0 start header each odd even one NUMBER -NUMBER  
2 first least each two odd even NUMBER -NUMBER  
3 extras = COMMAND  
left = COMMAND  
right = COMMAND  
headcolor = COLOR  
headstyle = STYLE COMMAND  
leftmargindistance = DIMENSION  
rightmargindistance = DIMENSION  
columnndistance = DIMENSION  
maxwidth = DIMENSION  
setups = NAME  
textwidth = DIMENSION local  
split = yes no repeat auto  
header = repeat  
option = stretch tight  
before = COMMAND  
after = COMMAND  
samepage = before after both  
spaceinbetween = inherits: \blank  
splitoffset = DIMENSION  
aligncharacter = yes no  
alignmentcharacter = TEXT number->TEXT text->TEXT  
distance = DIMENSION  
color = COLOR  
style = math STYLE COMMAND  
inherits: \setupframed
```

```
\setupTEXpage [...,*...,...]
```

```
* pagestate = start stop  
command = \...##1  
margin = page  
scale = NUMBER  
paper = auto default NAME  
inherits: \setupframed
```

**\setuptables** [...<sup>1</sup>...<sup>2</sup>...]

```
* text      = DIMENSION max
  split     = yes no repeat auto
  frame     = on off
  NL        = inherits: \blank
  VL        = small medium big none NUMBER
  HL        = small medium big none NUMBER
  distance  = small medium big none
  align     = left middle right
  commands  = COMMAND
  bodyfont  = inherits: \setupbodyfont
  rulethickness = DIMENSION
  height    = strut NUMBER
  depth     = strut NUMBER
  openup    = DIMENSION
```

**\setuptabulate** [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>...]

```
1 NAME      OPT      OPT
2 NAME
3 inherits: \setuptabulation
```

**\setuptabulation** [...<sup>1</sup>...]<sup>2</sup> [...<sup>3</sup>...]

```
1 NAME      OPT
2 format    = TEMPLATE none
  before    = COMMAND
  after     = COMMAND
  distance  = small medium big none blank depth grid DIMENSION
  blank     = preference samepage max force enable disable nowhite packed back overlay always weak strong
              default before inbetween after fixed flexible none small medium big line halfline quarterline
              formula white height depth standard NUMBER*small NUMBER*medium NUMBER*big NUMBER*line NUMBER*halfline
              NUMBER*quarterline NUMBER*formula NUMBER*white NUMBER*height NUMBER*depth category:NUMBER
              order:NUMBER penalty:NUMBER DIMENSION NAME
  headstyle = STYLE COMMAND
  headcolor = COLOR
  background = NAME
  backgroundcolor = COLOR
  foregroundstyle = STYLE COMMAND
  foregroundcolor = COLOR
  align      = left middle right dimension
  rule       = line normal
  rulecolor  = COLOR
  rulethickness = DIMENSION
  bodyfont   = inherits: \setupbodyfont
  indenting  = yes no
  split      = yes no repeat auto
  unit       = DIMENSION
  margin     = DIMENSION
  inner      = COMMAND
  EQ         = COMMAND
  header     = yes repeat text
  frame      = on off
  title      = TEXT
  kepttogether = yes no
```

**\setuptagging** [...<sup>1</sup>...<sup>2</sup>...]

```
* state = start stop
  method = auto
```

**\setuptext** [...<sup>1</sup>]<sup>2</sup> [...<sup>3</sup>...]

```
1 text margin edge
2 state      = start stop empty high none normal nomarking NAME
  style      = STYLE COMMAND
  color      = COLOR
  strut      = yes no
  n          = NUMBER
  before     = COMMAND
  after      = COMMAND
  leftstyle  = STYLE COMMAND
  rightstyle = STYLE COMMAND
  leftcolor  = COLOR
  rightcolor = COLOR
  width      = DIMENSION
  leftwidth  = DIMENSION
  rightwidth = DIMENSION
```

`\setuptextbackground [...1,...] [...2,...]`

```

1 NAME OPT
2 state = start stop
  location = text paragraph always none
  criterium = NUMBER
  alternative = NUMBER
  mp = NAME
  method = NAME
  background = color
  backgroundcolor = COLOR
  corner = rectangular round
  level = NUMBER
  backgroundoffset = DIMENSION
  before = COMMAND
  after = COMMAND
  align = inherits: \setupalign
  dash = NUMBER
  radius = DIMENSION
  frame = on off
  framecolor = COLOR
  rulethickness = DIMENSION
  voffset = DIMENSION
  frameoffset = DIMENSION
  leftoffset = yes no standard DIMENSION
  rightoffset = yes no standard DIMENSION
  topoffset = small medium big line DIMENSION
  bottomoffset = small medium big line DIMENSION
  style = STYLE COMMAND
  color = COLOR

```

`\setuptextflow [...1,...] [...2,...]`

```

1 NAME OPT
2 width = DIMENSION
  style = STYLE COMMAND
  color = COLOR

```

`\setuptextnote [...1,...] [...2,...]`

```

1 NAME OPT
2 rule = NAME
  note = NAME
  n = * NUMBER
  empty = yes no none number

```

`\setuptextrules [...*,...]`

```

* before = COMMAND
  after = COMMAND
  inbetween = COMMAND
  rulethickness = DIMENSION
  location = left inmargin
  style = STYLE COMMAND
  color = COLOR
  rulecolor = COLOR
  width = DIMENSION
  height = DIMENSION
  distance = DIMENSION
  depthcorrection = on off
  bodyfont = inherits: \setupbodyfont

```

`\setuptexttexts [...1] [...2] [...3] [...4] [...5]`

```

1 text margin edge OPT OPT OPT OPT OPT
2 date pagenummer MARK TEXT COMMAND
3 date pagenummer MARK TEXT COMMAND
4 date pagenummer MARK TEXT COMMAND
5 date pagenummer MARK TEXT COMMAND

```



`\setupthinrules [...,*=...,...]`

\* height = max DIMENSION  
depth = max DIMENSION  
background = color  
frame = on off  
rulethickness = DIMENSION  
alternative = a b c none  
backgroundcolor = COLOR  
color = COLOR  
interlinespace = small medium big NUMBER  
before = COMMAND  
after = COMMAND  
inbetween = COMMAND  
n = NUMBER

`\setuptolerance [...,*,...]`

\* horizontal vertical verystrict strict tolerant verytolerant space stretch

`\setuptooltip [...,1,...] [...,2,...,...]`

1 NAME <sup>OPT</sup>  
2 location = left middle right  
inherits: \setupframed

`\setuptop [...,1,...] [...,2,...,...]`

1 text margin <sup>OPT</sup>edge  
2 state = start stop empty high none normal nomarking NAME  
style = STYLE COMMAND  
color = COLOR  
strut = yes no  
n = NUMBER  
before = COMMAND  
after = COMMAND  
leftstyle = STYLE COMMAND  
rightstyle = STYLE COMMAND  
leftcolor = COLOR  
rightcolor = COLOR  
width = DIMENSION  
leftwidth = DIMENSION  
rightwidth = DIMENSION

`\setuptoptexts [...,1,...] [...,2,...] [...,3,...] [...,4,...] [...,5,...]`

1 text margin edge <sup>OPT</sup> <sup>OPT</sup> <sup>OPT</sup> <sup>OPT</sup> <sup>OPT</sup>  
2 date pagenumbers MARK TEXT COMMAND  
3 date pagenumbers MARK TEXT COMMAND  
4 date pagenumbers MARK TEXT COMMAND  
5 date pagenumbers MARK TEXT COMMAND

`\setuptype [...,1,...] [...,2,...,...]`

1 NAME <sup>OPT</sup>  
2 option = mp lua xml parsed-xml nested tex context none NAME  
command = CSNAME  
left = COMMAND  
right = COMMAND  
tab = yes no NUMBER  
compact = absolute last all  
escape = yes no TEXT PROCESSOR->TEXT  
style = STYLE COMMAND  
color = COLOR  
lines = yes no normal hyphenated  
space = on off normal fixed stretch

**\setuptyping** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME          OPT
2  oddmargin     = DIMENSION
   evenmargin    = DIMENSION
   margin        = yes no standard DIMENSION
   option        = mp lua xml parsed-xml nested tex context none NAME
   style         = STYLE COMMAND
   color         = COLOR
   align         = inherits: \setupalign
   lines         = yes no normal hyphenated
   space         = on off normal fixed stretch
   keeptogether  = yes no
   before        = COMMAND
   after         = COMMAND
   strip         = yes no NUMBER
   range         = NUMBER NAME
   tab          = yes no NUMBER
   escape        = yes no TEXT PROCESSOR->TEXT
   indentnext    = yes no auto
   continue      = yes no
   start         = NUMBER
   stop          = NUMBER
   step          = NUMBER
   numbering     = file line no
   blank        = inherits: \blank

```

**\setupunit** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME          OPT
2  method        = 1 2 3 4 5 6
   language       = LANGUAGE
   alternative    = text mathematics
   order         = reverse normal
   separator      = small medium big normal none NAME
   space         = small medium big normal none NAME
   style         = STYLE COMMAND
   color         = COLOR

```

**\setupurl** [...<sup>\*</sup>,...]

```

*  style = STYLE COMMAND
   color = COLOR

```

**\setupuserdata** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME          OPT
2  before        = COMMAND
   after         = COMMAND
   align         = inherits: \setupalign
   setups        = NAME
   style         = STYLE COMMAND
   color         = COLOR
   alternative    = default NAME
   KEY           = VALUE

```

**\setupuserdataalternative** [...<sup>1</sup>,...] [...<sup>2</sup>,...]

```

1  NAME          OPT
2  renderingsetup = NAME
   KEY           = VALUE

```

**\setupuserpagenumber** [...<sup>\*</sup>,...]

```

*  viewerprefix = TEXT
   state        = start stop none keep empty
   inherits: \setupcounter

```

**\setupversion** [...<sup>\*</sup>,...]

```

*  concept file temporary final NAME

```

**\setupviewerlayer** [...<sup>\*</sup>,...]

```

*  title        = TEXT
   state        = start stop
   export       = yes no
   printable    = yes no
   scope        = local global
   method       = none command

```

`\setupvspacing [...,*...]`

\* inherits: \vspacing <sup>OPT</sup>

`\setupwhitespace [...,*...]`

\* fix fixed flexible line<sup>OPT</sup> halfline quarterline none small medium big default DIMENSION

`\setupwithargument {...} {...}^2`

1 NAME

2 CONTENT

`\setupwithargumentswapped {...} {...}^2`

1 CONTENT

2 NAME

`\setupxml [...,*...]`

\* default = hidden none text

compress = yes no

`\setupxtable [...,*...^1] [...,*...^2...]`

1 NAME

<sup>OPT</sup>

2 textwidth = DIMENSION local  
bodyfont = inherits: \setupbodyfont  
spaceinbetween = inherits: \blank  
option = tight max stretch width height fixed  
textheight = DIMENSION  
maxwidth = DIMENSION  
columnndistance = DIMENSION  
leftmargindistance = DIMENSION  
rightmargindistance = DIMENSION  
header = repeat  
footer = repeat  
rulethickness = DIMENSION  
split = yes no repeat auto  
splitoffset = DIMENSION  
samepage = before after both  
distance = DIMENSION  
aligncharacter = yes no  
alignmentleftsample = TEXT  
alignmentrightsample = TEXT  
alignmentleftwidth = DIMENSION  
alignmentrightwidth = DIMENSION  
alignmentcharacter = TEXT  
inherits: \setupframed

`\setup {...}^*`

\* NAME

`\setuvalue {...} {...}^2`

1 NAME

2 CONTENT

`\setuxvalue {...} {...}^2`

1 NAME

2 CONTENT

`\setvalue {...} {...}^2`

1 NAME

2 CONTENT

`\setvariable {...} {...}^2 {...}^3`

1 NAME

2 KEY

3 VALUE

**\setvariables** [<sup>1</sup>...] [<sup>2</sup>...<sub>=</sub>...]

1 NAME  
2 set = COMMAND  
reset = COMMAND  
KEY = VALUE

**\setvboxregister** <sup>1</sup>... {<sup>2</sup>...}

1 CSNAME NUMBER  
2 CONTENT

**\setvisualizerfont** [<sup>\*</sup>...]

\* FONT OPT

**\setvtopregister** <sup>1</sup>... {<sup>2</sup>...}

1 CSNAME NUMBER  
2 CONTENT

**\setwidthof** <sup>1</sup>... \to \<sup>2</sup>...

1 TEXT  
2 CSNAME

**\setxmeasure** {<sup>1</sup>...} {<sup>2</sup>...}

1 NAME  
2 DIMENSION

**\setxvalue** {<sup>1</sup>...} {<sup>2</sup>...}

1 NAME  
2 CONTENT

**\setxvariable** {<sup>1</sup>...} {<sup>2</sup>...} {<sup>3</sup>...}

1 NAME  
2 KEY  
3 VALUE

**\setxvariables** [<sup>1</sup>...] [<sup>2</sup>...<sub>=</sub>...]

1 NAME  
2 set = COMMAND  
reset = COMMAND  
KEY = VALUE

**\shapedhbox** {<sup>\*</sup>...}

\* CONTENT

**\shiftbox** {<sup>1</sup>...}

1 CONTENT

**\SHIFT** {<sup>\*</sup>...}

\* CONTENT  
instances: shiftup shiftdown

**\shiftdown** {<sup>\*</sup>...}

\* CONTENT

**\shiftup** {<sup>\*</sup>...}

\* CONTENT

**\showallmakeup**

**\showattributes**

<pre> \showbodyfont [...] * inherits: \setupbodyfont </pre>
<pre> \showbodyfontenvironment [...] * inherits: \setupbodyfont </pre>
<pre> \showboxes </pre>
<pre> \showbtxdatasetauthors [...,*...,...] * specification = NAME          OPT   dataset       = NAME   field         = address assignee author booktitle chapter day dayfiled edition editor howpublished institution                   journal language month monthfiled nationality note number one two organization pages publisher                   school series title type volume year yearfiled NAME </pre>
<pre> \showbtxdatasetauthors [...] * NAME          OPT </pre>
<pre> \showbtxdatasetcompleteness [...,*...,...] * specification = NAME          OPT   dataset       = NAME   field         = address assignee author booktitle chapter day dayfiled edition editor howpublished institution                   journal language month monthfiled nationality note number one two organization pages publisher                   school series title type volume year yearfiled NAME </pre>
<pre> \showbtxdatasetcompleteness [...] * NAME          OPT </pre>
<pre> \showbtxdatasetfields [...,*...,...] * specification = NAME          OPT   dataset       = NAME   field         = address assignee author booktitle chapter day dayfiled edition editor howpublished institution                   journal language month monthfiled nationality note number one two organization pages publisher                   school series title type volume year yearfiled NAME </pre>
<pre> \showbtxdatasetfields [...] * NAME          OPT </pre>
<pre> \showbtxfields [...,*...,...] * rotation      = NUMBER<sup>PT</sup>   specification = NAME </pre>
<pre> \showbtxfields [...] * NAME          OPT </pre>
<pre> \showbtxhashedauthors [...] * TEXT          OPT </pre>
<pre> \showbtxtables [...] * TEXT          OPT </pre>
<pre> \showchardata {...} * TEXT </pre>
<pre> \showcharratio {...} * TEXT </pre>
<pre> \showcolor [...] * COLOR </pre>

```
\showcolorbar [..]
```

\* COLOR

```
\showcolorcomponents [...]
```

\* COLOR

```
\showcolorgroup [...] [...^2,...]
```

1 NAME

OPT

2    horizontal   vertical   number   value   name

```
\showcolorset [..]
```

\* COLOR

\showcolorstruts

```
\showcounter [..]
```

\* NAME

\showdirectives

\showdirsmargin

```
\showedebuginfo
```

```
\showexperiments
```

`\showfont` [<sup>1</sup>...] [<sup>2</sup>...,...]

## 1 FONT

OPT

2 NUMBER

\showfontdata

\showfontexpansion

```
\showfontitalics
```

\showfontkerns

```
\showfontparameters
```

```
\showfontstrip [...,*,...]
```

```
* inherits: \setupbodyfont
```

`\showfontstyle` [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...] [...<sup>4</sup>,...]

```
1 inherits: \setupbodyfont
```

OPT

OPT

OPT

2 rm ss tt mm hw cg

```
3  tf bf it sl bi bs
```

4 all NUMBER

```
\showframe [...1,...] [...2,...]
```

```
1  top header textOPT footer bottomOPT
```

```

1 top header text footer bottom
2 leftedge leftmargin text rightmargin rightedge

```

\showglyphdata

\showglyphs

\showgrid [...,\*...]  
 \* reset bottom <sup>OPT</sup>top none all lines frame nonumber right left outer inner columns

\showgridsnapping

\showhelp {...} [...]  
 1 TEXT  
 2 REFERENCE

\showhyphenationtrace [...<sup>1</sup>] [...<sup>2</sup>]  
 1 LANGUAGE <sup>OPT</sup>  
 2 TEXT

\showhyphens {...}  
 \* TEXT

\showinjector [...,\*...]  
 \* NAME <sup>OPT</sup>

\showjustification

\showkerning {...}  
 \* TEXT

\showlayout [...,\*...]  
 \* pt bp cm mm dd c<sup>OPT</sup>pc nd nc sp in

\showlayoutcomponents

\showligature {...}  
 \* TEXT

\showligatures [...]  
 \* FONT

\showlogcategories

\showmakeup [...\*]  
 \* makeup reset <sup>OPT</sup>b<sub>ox</sub>es all h**box** v**box** v**top** kern glue penalty fontkern strut whatsit glyph simple simple**hbox** simple**vbox** simple**vtop** user math italic origin discretionary expansion line space depth

\showmargins

\showmessage {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>,...}  
 1 NAME  
 2 NAME NUMBER  
 3 TEXT

\showminimalbaseline

\shownextbox \... {...<sup>2</sup>}  
 1 CSNAME  
 2 CONTENT

\showotfcomposition {...<sup>1</sup>} {...<sup>2</sup>} {...<sup>3</sup>}  
 1 FONT  
 2 -1 1 +1 l2r r2l  
 3 TEXT

<pre> \showpalet [...] [...] 1  NAME                OPT 2  <u>horizontal</u> vertical number value name </pre>
<pre> \showparentchain \... {...} 1  CSNAME 2  NAME </pre>
<pre> \showprint [...] [...] [...] 1  inherits: \setup<sup>OPT</sup>papersize  OPT  OPT 2  inherits: \setuppapersize 3  inherits: \setuplayout </pre>
<pre> \showsetups [...] *  pt bp <u>cm</u> mm dd c<sup>OPT</sup>pc nd nc sp in </pre>
<pre> \showsetupsdefinition [...] *  NAME </pre>
<pre> \showstruts </pre>
<pre> \showsymbolset [...] *  NAME </pre>
<pre> \showtimer {...} *  TEXT </pre>
<pre> \showtokens [...] *  NAME </pre>
<pre> \showtrackers </pre>
<pre> \showvalue {...} *  NAME </pre>
<pre> \showvariable {...} {...} 1  NAME 2  KEY </pre>
<pre> \showwarning {...} {...} {...} 1  NAME 2  NAME NUMBER 3  TEXT </pre>
<pre> \signalrightpage </pre>
<pre> \simplealignedbox {...} {...} {...} 1  DIMENSION 2  left right middle flushleft flushright inner outer 3  CONTENT </pre>
<pre> \simplealignedboxplus {...} {...} {...} {...} 1  DIMENSION 2  left right middle flushleft flushright inner outer 3  TEXT 4  CONTENT </pre>
<pre> \simplealignedspreadbox {...} {...} {...} 1  DIMENSION 2  left right middle flushleft flushright inner outer 3  CONTENT </pre>



$\backslash\text{simplegroupedcommand}$ $\{.^1.\}$ $\{.^2.\}$ 1    COMMAND 2    COMMAND
$\backslash\text{simplereversealignedbox}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ 1    DIMENSION 2    left right middle flushleft flushright inner outer 3    CONTENT
$\backslash\text{simplereversealignedboxplus}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ $\{.^4.\}$ 1    DIMENSION 2    left right middle flushleft flushright inner outer 3    TEXT 4    CONTENT
$\backslash\text{singalcharacteralign}$ $\{.^1.\}$ $\{.^2.\}$ 1    NUMBER 2    NUMBER
$\backslash\text{singlebond}$
$\backslash\text{sixthofsixarguments}$ $\{.^1.\}$ $\{.^2.\}$ $\{.^3.\}$ $\{.^4.\}$ $\{.^5.\}$ $\{.^6.\}$ 1    TEXT 2    TEXT 3    TEXT 4    TEXT 5    TEXT 6    TEXT
$\backslash\text{slanted}$
$\backslash\text{slantedbold}$
$\backslash\text{slantedface}$
$\backslash\text{slicepages}$ $[.^1.]$ $[.^2.\dots.\dots]$ $[.^3.\dots.\dots]$ 1    FILE 2    offset    = DIMENSION hoffset   = DIMENSION voffset   = DIMENSION width      = DIMENSION height     = DIMENSION n          = NUMBER 3    offset   = DIMENSION hoffset   = DIMENSION voffset   = DIMENSION width      = DIMENSION height     = DIMENSION n          = NUMBER
$\backslash\text{slovenianNumerals}$ $\{.^*.\}$ *    NUMBER
$\backslash\text{sloveniannumerals}$ $\{.^*.\}$ *    NUMBER
$\backslash\text{small}$
$\backslash\text{smallbodyfont}$
$\backslash\text{smallbold}$
$\backslash\text{smallbolditalic}$

<code>\smallboldslanted</code>
<code>\smallcapped {...}</code> * TEXT
<code>\smallcappedcharacters {...}</code> * NUMBER
<code>\smallcappedromannumerals {...}</code> * NUMBER
<code>\smallcaps {...}</code> * TEXT
<code>\smaller</code>
<code>\smallitalicbold</code>
<code>\smallnormal</code>
<code>\smallskip</code>
<code>\smallslanted</code>
<code>\smallslantedbold</code>
<code>\smalltype</code>
<code>\smash [...]<sup>1</sup> {...}</code> 1 <code>width</code> <small>OPT</small> 2 CONTENT
<code>\smashbox ...</code> * CSNAME NUMBER
<code>\smashboxed ...</code> * CSNAME NUMBER
<code>\smashedhbox ...<sup>1</sup> {...}</code> 1 TEXT <small>OPT</small> 2 CONTENT
<code>\smashedvbox ...<sup>1</sup> {...}</code> 1 TEXT <small>OPT</small> 2 CONTENT
<code>\snaptogrid [...]<sup>1</sup> \^2... {...}</code> 1 normal standardTypes strict tolerant top bottom both broad fit first last high one low none line strut box min max middle math math:line math:halfline math:-line math:-halfline NAME 2 CSNAME 3 CONTENT
<code>\snaptogrid [...]<sup>1</sup>,... \^2... {...}</code> 1 inherits: <code>\defineGridsnapping</code> 2 CSNAME 3 CONTENT

<code>\someheadnumber [...]<sup>1</sup> [...]<sup>2</sup></code> 1 SECTION 2 previous current next first last
<code>\somekindoftab [...]<sup>*</sup> [...]</code> * alternative = horizontal <sup>OPT</sup> <u>vertical</u> width = DIMENSION height = DIMENSION n = NUMBER m = NUMBER
<code>\someline [...]<sup>*</sup></code> * REFERENCE
<code>\somalocalfloat</code>
<code>\somenamedheadnumber {...}<sup>1</sup> {...}<sup>2</sup></code> 1 SECTION 2 previous current next first last
<code>\someplace {...}<sup>1</sup> {...}<sup>2</sup> {...}<sup>3</sup> {...}<sup>4</sup> {...}<sup>5</sup> [...]<sup>6</sup></code> 1 TEXT 2 TEXT 3 TEXT 4 TEXT 5 TEXT 6 REFERENCE
<code>\somewhere {...}<sup>1</sup> {...}<sup>2</sup> [...]<sup>3</sup></code> 1 TEXT 2 TEXT 3 REFERENCE
<code>\SORTING [...]<sup>1</sup> {...}<sup>2</sup></code> 1 NAME <sup>OPT</sup> 2 CONTENT <b>instances: logo</b>
<code>\logo [...]<sup>1</sup> {...}<sup>2</sup></code> 1 NAME <sup>OPT</sup> 2 CONTENT
<code>\space</code>
<code>\spaceddigits {...}</code> * NUMBER
<code>\spaceddigitismethod</code>
<code>\spaceddigitseparator</code>
<code>\spaceddigitssymbol</code>
<code>\spanishNumerals {...}<sup>*</sup></code> * NUMBER
<code>\spanishnumerals {...}<sup>*</sup></code> * NUMBER

$\backslash\text{splitatasterisk}$ $\dots \overset{1}{\backslash\dots} \overset{2}{\backslash\dots} \overset{3}{\backslash\dots}$ 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitatcolon}$ $\dots \overset{1}{\backslash\dots} \overset{2}{\backslash\dots} \overset{3}{\backslash\dots}$ 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitatcolons}$ $\dots \overset{1}{\backslash\dots} \overset{2}{\backslash\dots} \overset{3}{\backslash\dots}$ 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitatcomma}$ $\dots \overset{1}{\backslash\dots} \overset{2}{\backslash\dots} \overset{3}{\backslash\dots}$ 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitatperiod}$ $\dots \overset{1}{\backslash\dots} \overset{2}{\backslash\dots} \overset{3}{\backslash\dots}$ 1 TEXT 2 CSNAME 3 CSNAME
$\backslash\text{splitdfrac}$ $\{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ 1 CONTENT 2 CONTENT
$\backslash\text{splitfilename}$ $\{.\dots\}$ * FILE
$\backslash\text{splitfloat}$ $[\dots\overset{1}{=} \dots] \{\overset{2}{\dots}\} \{\overset{3}{\dots}\}$ 1 inherits: $\backslash\text{setupfloat}$ <sub>OPT</sub> $\text{splitting}$ 2 COMMAND 3 CONTENT
$\backslash\text{splitfrac}$ $\{\overset{1}{\dots}\} \{\overset{2}{\dots}\}$ 1 CONTENT 2 CONTENT
$\backslash\text{splitoffbase}$
$\backslash\text{splitofffull}$
$\backslash\text{splitoffkind}$
$\backslash\text{splitoffname}$
$\backslash\text{splitoffpath}$
$\backslash\text{splitoffroot}$
$\backslash\text{splitofftokens}$ $\dots \overset{1}{\backslash\text{from}} \dots \overset{2}{\backslash\text{to}} \overset{3}{\backslash\dots}$ 1 TEXT 2 TEXT 3 CSNAME
$\backslash\text{splitofftype}$

```
\splitstring 1... \at 2... \to 3... \and 4...
1 TEXT
2 TEXT
3 CSNAME
4 CSNAME
```

```
\spreadhbox *...
* CSNAME NUMBER
```

```
\sqrt [1...] {2...}
1 TEXT OPT
2 CONTENT
```

```
\stackrel{1...}{2...}
1 CONTENT
2 CONTENT
```

```
\stackscripts
```

```
\start [...*] ... \stop
* NAME OPT
```

```
\startalignment [...*,...] ... \stopalignment
* inherits: \setupalign
```

```
\startallmodes [...*,...] ... \stopallmodes
* NAME
```

```
\startATTACHMENT [1...] [...2,...2,...] ... \stopATTACHMENT
1 NAME OPT OPT
2 inherits: \setupattachment
instances: attachment
```

```
\startattachment [1...] [...2,...2,...] ... \stopattachment
1 NAME OPT OPT
2 inherits: \setupattachment
```

```
\startbackground [...*,...*,...] ... \stopbackground
* inherits: \setupbackgroundPT
```

```
\startBACKGROUND [...*,...*,...] ... \stopBACKGROUND
* inherits: \setupbackgroundPT
instances: background
```

```
\startbar [...*] ... \stopbar
* NAME
```

```
\startbbordermatrix ... \stopbbordermatrix
```

```
\startbitmapimage [...*,...*,...] ... \stopbitmapimage
* color = rgb cmyk gray
width = DIMENSION
height = DIMENSION
x = NUMBER
y = NUMBER
```

```
\startbordermatrix ... \stopbordermatrix
```

```
\startbtxrenderingdefinitions [...*] ... \stopbtxrenderingdefinitions
* NAME
```

<p><code>\startbuffer [...] ... \stopbuffer</code></p> <p>* NAME OPT</p>
<p><code>\startBUFFER ... \stopBUFFER</code></p> <p>instances: hiding</p>
<p><code>\starthiding ... \stophiding</code></p>
<p><code>\startcatcodetable \* ... \stopcatcodetable</code></p> <p>* CSNAME</p>
<p><code>\startcenteraligned ... \stopcenteraligned</code></p>
<p><code>\startcharacteralign [...,*=...,...] ... \stopcharacteralign</code></p> <p>* inherits: \setupcharacteralign</p>
<p><code>\startcharacteralign [...] ... \stopcharacteralign</code></p> <p>* TEXT number-&gt;TEXT text-&gt;TEXT</p>
<p><code>\startcheckedfences ... \stopcheckedfences</code></p>
<p><code>\startchemical [<sup>1</sup>] [...,<sup>2</sup>...,...] ... \stopchemical</code></p> <p>1 NAME OPT OPT</p> <p>2 inherits: \setupchemical</p>
<p><code>\startcollect ... \stopcollect</code></p>
<p><code>\startcollecting ... \stopcollecting</code></p>
<p><code>\startcolor [...] ... \stopcolor</code></p> <p>* COLOR</p>
<p><code>\startcolorintent [...] ... \stopcolorintent</code></p> <p>* knockout overprint none</p>
<p><code>\startcoloronly [...] ... \stopcoloronly</code></p> <p>* COLOR</p>
<p><code>\startcolorset [...] ... \stopcolorset</code></p> <p>* NAME</p>
<p><code>\startcolumnset [<sup>1</sup>] [...,<sup>2</sup>...,...] ... \stopcolumnset</code></p> <p>1 NAME OPT OPT</p> <p>2 inherits: \setupcolumnset</p>
<p><code>\startcolumnsetspan [<sup>1</sup>] [...,<sup>2</sup>...,...] ... \stopcolumnsetspan</code></p> <p>1 NAME OPT</p> <p>2 c = NUMBER</p> <p>r = NUMBER</p> <p>method = tblr lrtb tbrl rltb fxtb btlr lrbt btrl rlbt fxtb fixd</p> <p>option = <u>none</u> wide</p>
<p><code>\startCOLUMNSET [...,*=...,...] ... \stopCOLUMNSET</code></p> <p>* inherits: \setupcolumnset<sup>OPT</sup></p>
<p><code>\startcombination [<sup>1</sup>] [...,<sup>2</sup>...,...] ... \stopcombination</code></p> <p>1 NAME OPT OPT</p> <p>2 inherits: \setupcombination</p>

<code>\startcombination [...]<sup>1</sup> [...]<sup>2</sup> ... \stopcombination</code> 1    NAME                    OPT            OPT 2    N*M
<code>\startCOMMENT [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>2</sup> ... \stopCOMMENT</code> 1    TEXT                    OPT            OPT 2    inherits: \setupcomment instances: comment
<code>\startcomment [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>2</sup> ... \stopcomment</code> 1    TEXT                    OPT            OPT 2    inherits: \setupcomment
<code>\startcomponent [...]<sup>1</sup> ... \stopcomponent</code> *    FILE *
<code>\startcomponent ...<sup>1</sup> ... \stopcomponent</code> *    FILE *
<code>\startcontextcode ... \stopcontextcode</code>
<code>\startcontextdefinitioncode ... \stopcontextdefinitioncode</code>
<code>\startctxfunction ...<sup>1</sup> ... \stopctxfunction</code> *    NAME
<code>\startctxfunctiondefinition ...<sup>1</sup> ... \stopctxfunctiondefinition</code> *    NAME
<code>\startcurrentcolor ... \stopcurrentcolor</code>
<code>\startcurrentlistentrywrapper ... \stopcurrentlistentrywrapper</code>
<code>\startdelimited [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]<sup>3</sup> ... \stopdelimited</code> 1    NAME                    OPT            OPT 2    LANGUAGE 3    inherits: \startnarrower
<code>\startdelimitedtext [...]<sup>1</sup> [...]<sup>2</sup> [...,...<sup>3</sup>...,...]<sup>3</sup> ... \stopdelimitedtext</code> 1    NAME                    OPT            OPT 2    LANGUAGE 3    inherits: \startnarrower
<code>\startDELIMITEDTEXT [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>2</sup> ... \stopDELIMITEDTEXT</code> 1    LANGUAGE                    OPT            OPT 2    inherits: \startnarrower instances: quotation quote blockquote speech aside
<code>\startaside [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>2</sup> ... \stopaside</code> 1    LANGUAGE                    OPT            OPT 2    inherits: \startnarrower
<code>\startblockquote [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>2</sup> ... \stopblockquote</code> 1    LANGUAGE                    OPT            OPT 2    inherits: \startnarrower
<code>\startquotation [...]<sup>1</sup> [...,...<sup>2</sup>...,...]<sup>2</sup> ... \stopquotation</code> 1    LANGUAGE                    OPT            OPT 2    inherits: \startnarrower

`\startquote [...]1 [...]2,... ] ... \stopquote`

1 LANGUAGE OPT OPT  
2 inherits: \startnarrower

`\startspeech [...]1 [...]2,... ] ... \stopspeech`

1 LANGUAGE OPT OPT  
2 inherits: \startnarrower

`\startDESCRIPTION [...]*,... ] ... \stopDESCRIPTION`

\* title = TEXT OPT  
bookmark = TEXT  
list = TEXT  
reference = REFERENCE

`\startDESCRIPTION [...]1,... ] {...}2 ... \stopDESCRIPTION`

1 REFERENCE OPT OPT  
2 TEXT

`\startdisplaymath ... \stopdisplaymath`

`\startdmath ... \stopdmath`

`\startdocument [...]*,... ] ... \stopdocument`

\* inherits: \setupdocument<sup>PT</sup>

`\starteffect [... ] ... \stopeffect`

\* NAME

`\startEFFECT ... \stopEFFECT`

`\startelement {...}1 [...]2,... ] ... \stopelement`

1 NAME OPT  
2 KEY = VALUE

`\startembeddedxtable [...]*,... ] ... \stopembeddedxtable`

\* inherits: \setupxtable OPT

`\startembeddedxtable [... ] ... \stopembeddedxtable`

\* NAME OPT

`\startENUMERATION [...]*,... ] ... \stopENUMERATION`

\* title = TEXT OPT  
bookmark = TEXT  
list = TEXT  
reference = REFERENCE

`\startENUMERATION [...]1,... ] {...}2 ... \stopENUMERATION`

1 REFERENCE OPT OPT  
2 TEXT

`\startenvironment [... ] ... \stopenvironment`

\* FILE \*

`\startenvironment ... .. \stopenvironment`

\* FILE \*

`\startexceptions [... ] ... \stopexceptions`

\* LANGUAGE



<code>\startexpanded ... \stopexpanded</code>
<code>\startexpandedcollect ... \stopexpandedcollect</code>
<code>\startextendedcatcodetable \.* ... \stopextendedcatcodetable</code> <code>* CSNAME</code>
<code>\startexternalfigurecollection [...] ... \stopexternalfigurecollection</code> <code>* NAME</code>
<code>\startfacingfloat [...] ... \stopfacingfloat</code> <code>* NAME</code>
<code>\startfigure [...<sup>1</sup>] [...<sup>2</sup>] [...,<sup>3</sup>...<sup>3</sup>...] ... \stopfigure</code> <code>1 NAME</code> <code>2 FILE</code> <code>3 inherits: \externalfigure</code>
<code>\startfittingpage [...<sup>1</sup>] [...,<sup>2</sup>...<sup>2</sup>...] ... \stopfittingpage</code> <code>1 NAME</code> <code>2 inherits: \setupfittingpage</code>
<code>\startFITTINGPAGE [...,<sup>*</sup>...<sup>*</sup>...] ... \stopFITTINGPAGE</code> <code>* inherits: \setupfittingpage<sup>OPT</sup></code> <code>instances: TEXpage MPpage</code>
<code>\startMPpage [...,<sup>*</sup>...<sup>*</sup>...] ... \stopMPpage</code> <code>* inherits: \setupfittingpage<sup>OPT</sup></code>
<code>\startTEXpage [...,<sup>*</sup>...<sup>*</sup>...] ... \stopTEXpage</code> <code>* inherits: \setupfittingpage<sup>OPT</sup></code>
<code>\startfixed [...] ... \stopfixed</code> <code>* low middle high<sup>OPT</sup>lohi default</code>
<code>\startfloatcombination [...,<sup>*</sup>...<sup>*</sup>...] ... \stopfloatcombination</code> <code>* inherits: \setupcombination</code>
<code>\startfloatcombination [...] ... \stopfloatcombination</code> <code>* N*M NAME</code>
<code>\startFLOATtext [...,<sup>1</sup>...] [...,<sup>2</sup>...] {...<sup>3</sup>} ... \stopFLOATtext</code> <code>1 split always left right<sup>OPT</sup> inner outer<sup>OPT</sup> backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header footer tblr lrtb tblr lrtb fxtb btlr lrbt btlr lrbt fxbt fixd</code> <code>2 REFERENCE</code> <code>3 TEXT</code> <code>instances: chemical figure table intermezzo graphic</code>
<code>\startchemicaltext [...,<sup>1</sup>...] [...,<sup>2</sup>...] {...<sup>3</sup>} ... \stopchemicaltext</code> <code>1 split always left right inner<sup>OPT</sup> outer<sup>OPT</sup> backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header footer tblr lrtb tblr lrtb fxtb btlr lrbt btlr lrbt fxbt fixd</code> <code>2 REFERENCE</code> <code>3 TEXT</code>

`\startfiguretext [...1,...] [...2,...] {...3} ... \stopfiguretext`

1 split always left right <sup>OPT</sup>inner outer <sup>OPT</sup>backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header footer tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd

2 REFERENCE

3 TEXT

`\startgraphictext [...1,...] [...2,...] {...3} ... \stopgraphictext`

1 split always left right <sup>OPT</sup>inner outer <sup>OPT</sup>backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header footer tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd

2 REFERENCE

3 TEXT

`\startintermezzotext [...1,...] [...2,...] {...3} ... \stopintermezzotext`

1 split always left right inner<sup>OPT</sup>outer <sup>OPT</sup>backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header footer tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd

2 REFERENCE

3 TEXT

`\starttabletext [...1,...] [...2,...] {...3} ... \stoptabletext`

1 split always left right <sup>OPT</sup>inner outer <sup>OPT</sup>backspace cutspace inleft inright inmargin leftmargin rightmargin leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth [-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header footer tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd

2 REFERENCE

3 TEXT

`\startfont [...] ... \stopfont`

\* FONT <sup>OPT</sup>

`\startfontclass [...] ... \stopfontclass`

\* each NAME

`\startfontsolution [...] ... \stopfontsolution`

\* NAME

`\startformula [...,*...] ... \stopformula`

\* packed tight middle<sup>OPT</sup>frame depth line halfline -line -halfline inherits: \setupbodyfont

`\startformulas [...,*...] ... \stopformulas`

\* + - REFERENCE <sup>OPT</sup>

`\startformula [...,*=,...] ... \stopformula`

\* option = packed tight<sup>OPT</sup>middle frame depth line halfline -line -halfline inherits: \setupbodyfont  
margin = yes no standard DIMENSION  
grid = inherits: \snaptogrid

`\startFORMULAformula [...,*...] ... \stopFORMULAformula`

\* packed tight middle frame depth<sup>OPT</sup> line halfline -line -halfline inherits: \setupbodyfont

instances: sp sd mp md

`\startmdformula [...,*...] ... \stopmdformula`

\* packed tight middle frame depth line halfline -line -halfline inherits: \setupbodyfont

`\startmpformula [...,*...] ... \stopmpformula`

\* packed tight middle frame<sup>OPT</sup> depth line halfline -line -halfline inherits: \setupbodyfont

`\startsdformula [...,*...] ... \stopsdformula`

\* packed tight middle frame<sup>OPT</sup> depth line halfline -line -halfline inherits: \setupbodyfont

$\backslash\startspformula$ [...] $\dots$ $\backstopspformula$ * packed tight middle frame <sup>OPT</sup> depth line halfline -line -halfline inherits: \setupbodyfont
$\backstartframed$ [ <sup>1</sup> ...] [ $\dots$ , $\dots$ , $\dots$ , $\dots$ ] $\dots$ $\backstopframed$ 1 NAME OPT OPT 2 inherits: \setupframed
$\backstartframedcell$ [ $\dots$ , $\dots$ , $\dots$ , $\dots$ ] $\dots$ $\backstopframedcell$ * inherits: \setupframed OPT
$\backstartframedcontent$ [ $\dots$ ] $\dots$ $\backstopframedcontent$ * NAME off OPT
$\backstartframedrow$ [ $\dots$ , $\dots$ , $\dots$ , $\dots$ ] $\dots$ $\backstopframedrow$ * inherits: \setupframed OPT
$\backstartframedtable$ [ <sup>1</sup> ...] [ $\dots$ , $\dots$ , $\dots$ , $\dots$ ] $\dots$ $\backstopframedtable$ 1 NAME OPT OPT 2 inherits: \setupframed
$\backstartFRAMEDTEXT$ [ <sup>1</sup> ...] [ $\dots$ , $\dots$ , $\dots$ , $\dots$ ] $\dots$ $\backstopFRAMEDTEXT$ 1 left right middle none <sup>OPT</sup> OPT 2 inherits: \setupframedtext instances: framedtext
$\backstartframedtext$ [ <sup>1</sup> ...] [ $\dots$ , $\dots$ , $\dots$ , $\dots$ ] $\dots$ $\backstopframedtext$ 1 left right middle none <sup>OPT</sup> OPT 2 inherits: \setupframedtext
$\backstartgoto$ [ $\dots$ ] $\dots$ $\backstopgoto$ * REFERENCE
$\backstartgridsnapping$ [ $\dots$ ] $\dots$ $\backstopgridsnapping$ * normal standard yes strict tolerant top bottom both broad fit first last high one low none line strut box min max middle math math:line math:halfline math:-line math:-halfline NAME
$\backstartgridsnapping$ [ $\dots$ , $\dots$ ] $\dots$ $\backstopgridsnapping$ * inherits: \definegridsnapping <sup>OPT</sup>
$\backstarthanging$ [ $\dots$ , $\dots$ , $\dots$ , $\dots$ ] { $\dots$ } $\dots$ $\backstophanging$ 1 distance = DIMENSION <sup>OPT</sup> n = NUMBER location = left right 2 CONTENT
$\backstarthanging$ [ <sup>1</sup> ...] { $\dots$ } $\dots$ $\backstophanging$ 1 left right OPT 2 CONTENT
$\backstarthboxestohbox$ $\dots$ $\backstopboxestohbox$
$\backstarthboxregister$ $\dots$ $\dots$ $\backstopboxregister$ * CSNAME NUMBER
$\backstarthead$ [ $\dots$ , $\dots$ ] { $\dots$ } $\dots$ $\backstophead$ 1 REFERENCE OPT 2 TEXT
$\backstarthelptext$ [ $\dots$ ] $\dots$ $\backstophelptext$ * REFERENCE OPT

```
instances: helptext
```

	REF	OPT
* REFERENCE		

\* NAME

```
* original tex default hyphenate expanded traditional none
```

$$\dots$$

\* NAME

`\startINDENTEDTEXT ... \stopINDENTEDTEXT`

```
* hidden NAME
```

\* NAME

\* all LANGUAGE

`\startintertext ... \stopintertext`

*	<b>REFERENCE</b>	OPT
---	------------------	-----

```
2 inherits: \setupitemgroup
3 inherits: \setupitemgroup
```

```
instances: itemize
```

3 NAME

3 now later

`\startknockout ... \stopknockout`

`\startLABELtext [...]1 [...]2 ... \stopLABELtext`  
 1 LANGUAGE OPT  
 2 KEY  
 instances: head label mathlabel taglabel unit operator prefix suffix btxlabel

`\startbtxlabeltext [...]1 [...]2 ... \stopbtxlabeltext`  
 1 LANGUAGE OPT  
 2 KEY

`\startheadtext [...]1 [...]2 ... \stopheadtext`  
 1 LANGUAGE OPT  
 2 KEY

`\startlabeltext [...]1 [...]2 ... \stoplabeltext`  
 1 LANGUAGE OPT  
 2 KEY

`\startmathlabeltext [...]1 [...]2 ... \stopmathlabeltext`  
 1 LANGUAGE OPT  
 2 KEY

`\startoperatortext [...]1 [...]2 ... \stopoperatortext`  
 1 LANGUAGE OPT  
 2 KEY

`\startprefixtext [...]1 [...]2 ... \stopprefixtext`  
 1 LANGUAGE OPT  
 2 KEY

`\startsuffixtext [...]1 [...]2 ... \stopsuffixtext`  
 1 LANGUAGE OPT  
 2 KEY

`\starttaglabeltext [...]1 [...]2 ... \stoptaglabeltext`  
 1 LANGUAGE OPT  
 2 KEY

`\startunittext [...]1 [...]2 ... \stopunittext`  
 1 LANGUAGE OPT  
 2 KEY

`\startlanguage [...]* ... \stoplanguage`  
 \* LANGUAGE

`\startlayout [...]* ... \stoplayout`  
 \* NAME

`\startleftaligned ... \stopleftaligned`

`\startline [...]*`  
 \* REFERENCE

`\startlinealignment [...]* ... \stoplinealignment`  
 \* left middle right max

`\startlinecorrection [...]*, [...]* ... \stoplinecorrection`  
 \* blank inherits: \blank OPT

```
\startlinefiller [...] [...] ... \stoplinefiller
1 filler NAME
2 inherits: \setuplinefiller
```

```
\startLINENOTE [...] {...}
1 REFERENCE
2 TEXT
instances: linenote
```

```
\startlinenote [...] {...}
1 REFERENCE
2 TEXT
```

```
\startlinenumbers [...] [...] ... \stoplinenumbers
1 NAME
2 continue = yes no
start = NUMBER
step = NUMBER
method = page first next
```

```
\startlinenumbers [...] [...] ... \stoplinenumbers
1 NAME
2 continue NUMBER
```

```
\startLINES [...] [...] ... \stopLINES
* inherits: \setuplines
instances: lines
```

```
\startlines [...] [...] ... \stoplines
* inherits: \setuplines
```

```
\startlinetable ... \stoplinetable
```

```
\startlinetablebody ... \stoplinetablebody
```

```
\startlinetablecell [...] [...] ... \stoplinetablecell
* inherits: \setuplinetable
```

```
\startlinetablehead ... \stoplinetablehead
```

```
\startlocalfootnotes ... \stoplocalfootnotes
```

```
\startlocalheadsetup ... \stoplocalheadsetup
```

```
\startlocallinecorrection [...] [...] ... \stoplocallinecorrection
* blank inherits: \blank
```

```
\startlocalnotes [...] [...] ... \stoplocalnotes
* NAME
```

```
\startlocalsetups [...] [...] ... \stoplocalsetups
1 grid
2 NAME
```

```
\startlocalsetups ... \stoplocalsetups
* NAME
```

```
\startlua ... \stoplua
```

<code>\startluacode ... \stopluacode</code>
<code>\startluaparameterset [...] ... \stopluaparameterset</code> <code>* NAME</code>
<code>\startluasetups [<sup>1</sup>...] [<sup>2</sup>] ... \stopluasetups</code> <code>1 grid</code> <code>2 NAME</code>
<code>\startluasetups ... ... \stopluasetups</code> <code>* NAME</code>
<code>\startMPclip {...} ... \stopMPclip</code> <code>* NAME</code>
<code>\startMPcode {...} ... \stopMPcode</code> <code>* NAME</code>
<code>\startMPdefinitions {...} ... \stopMPdefinitions</code> <code>* NAME</code>
<code>\startMPdrawing [...] ... \stopMPdrawing</code> <code>* -</code>
<code>\startMPenvironment [...] ... \stopMPenvironment</code> <code>* reset global +</code>
<code>\startMPextensions {...,*...} ... \stopMPextensions</code> <code>* NAME</code>
<code>\startMPinclusions [<sup>1</sup>] {...<sup>2</sup>} ... \stopMPinclusions</code> <code>1 +</code> <code>2 NAME</code>
<code>\startMPinitializations ... \stopMPinitializations</code>
<code>\startMPpositiongraphic {...<sup>1</sup>} {...<sup>2</sup>,...} ... \stopMPpositiongraphic</code> <code>1 NAME</code> <code>2 KEY</code>
<code>\startMPpositionmethod {...} ... \stopMPpositionmethod</code> <code>* NAME</code>
<code>\startMPrun {...} ... \stopMPrun</code> <code>* NAME</code>
<code>\startmakeup [<sup>1</sup>] [...,<sup>2</sup>...,...] ... \stopmakeup</code> <code>1 NAME</code> <code>2 inherits: \setupmakeup</code>
<code>\startMAKEUPmakeup [...,*...,...] ... \stopMAKEUPmakeup</code> <code>* inherits: \setupmakeup</code> <code>instances: standard page text middle</code>
<code>\startmiddlemakeup [...,*...,...] ... \stopmiddlemakeup</code> <code>* inherits: \setupmakeup</code>

$\backslash\text{startpagemakeup}$ [... <sup>*</sup> ...] ... $\backslash\text{stoppagemakeup}$ * inherits: $\backslash\text{setupmakeup}$ <sup>OPT</sup>
$\backslash\text{startstandardmakeup}$ [... <sup>*</sup> ...] ... $\backslash\text{stopstandardmakeup}$ * inherits: $\backslash\text{setupmakeup}$ <sup>OPT</sup>
$\backslash\text{starttextmakeup}$ [... <sup>*</sup> ...] ... $\backslash\text{stoptextmakeup}$ * inherits: $\backslash\text{setupmakeup}$ <sup>OPT</sup>
$\backslash\text{startmarginblock}$ [... <sup>*</sup> ] ... $\backslash\text{stopmarginblock}$ * NAME <sup>OPT</sup>
$\backslash\text{startmarginrule}$ [... <sup>*</sup> ] ... $\backslash\text{stopmarginrule}$ * NUMBER <sup>OPT</sup>
$\backslash\text{startmarginrule}$ [... <sup>*</sup> ...] ... $\backslash\text{stopmarginrule}$ * inherits: $\backslash\text{setupmarginrule}$ <sup>OPT</sup>
$\backslash\text{startmarkedcontent}$ [... <sup>*</sup> ] ... $\backslash\text{stopmarkedcontent}$ * reset <u>all</u> NAME <sup>OPT</sup>
$\backslash\text{startmarkpages}$ [... <sup>*</sup> ] ... $\backslash\text{stopmarkpages}$ * NAME
$\backslash\text{startMATHALIGNMENT}$ [... <sup>*</sup> ...] ... $\backslash\text{stopMATHALIGNMENT}$ * inherits: $\backslash\text{setupmathalignment}$ <sup>OPT</sup> instances: align mathalignment
$\backslash\text{startalign}$ [... <sup>*</sup> ...] ... $\backslash\text{stopalign}$ * inherits: $\backslash\text{setupmathalignment}$ <sup>OPT</sup>
$\backslash\text{startmathalignment}$ [... <sup>*</sup> ...] ... $\backslash\text{stopmathalignment}$ * inherits: $\backslash\text{setupmathalignment}$ <sup>OPT</sup>
$\backslash\text{startMATHCASES}$ [... <sup>*</sup> ...] ... $\backslash\text{stopMATHCASES}$ * inherits: $\backslash\text{setupmathcases}$ <sup>OPT</sup> instances: cases mathcases
$\backslash\text{startcases}$ [... <sup>*</sup> ...] ... $\backslash\text{stopcases}$ * inherits: $\backslash\text{setupmathcases}$ <sup>OPT</sup>
$\backslash\text{startmathcases}$ [... <sup>*</sup> ...] ... $\backslash\text{stopmathcases}$ * inherits: $\backslash\text{setupmathcases}$ <sup>OPT</sup>
$\backslash\text{startMATHMATRIX}$ [... <sup>*</sup> ...] ... $\backslash\text{stopMATHMATRIX}$ * inherits: $\backslash\text{setupmathmatrix}$ <sup>OPT</sup> instances: matrix mathmatrix
$\backslash\text{startmathmatrix}$ [... <sup>*</sup> ...] ... $\backslash\text{stopmathmatrix}$ * inherits: $\backslash\text{setupmathmatrix}$ <sup>OPT</sup>
$\backslash\text{startmatrix}$ [... <sup>*</sup> ...] ... $\backslash\text{stopmatrix}$ * inherits: $\backslash\text{setupmathmatrix}$ <sup>OPT</sup>
$\backslash\text{startmathmode}$ ... $\backslash\text{stopmathmode}$



$\backslash\mathrm{startmathstyle}$ [...] $\backslash\mathrm{stopmathstyle}$ * display text script scriptscript cramped uncramped normal packed small big NAME
$\backslash\mathrm{startmatrices}$ [...] $\backslash\mathrm{stopmatrices}$ * inherits: $\backslash\mathrm{setupmathmatfix}$
$\backslash\mathrm{startmaxaligned}$ ... $\backslash\mathrm{stopmaxaligned}$
$\backslash\mathrm{startmidaligned}$ ... $\backslash\mathrm{stopmidaligned}$
$\backslash\mathrm{startmiddlealigned}$ ... $\backslash\mathrm{stopmiddlealigned}$
$\backslash\mathrm{startmixedcolumns}$ [...] $\backslash\mathrm{stopmixedcolumns}$ 1 NAME <small>OPT</small> 2 inherits: $\backslash\mathrm{setupmixedcolumns}$
$\backslash\mathrm{startMIXEDCOLUMNS}$ [...] $\backslash\mathrm{stopMIXEDCOLUMNS}$ * inherits: $\backslash\mathrm{setupmixedcolumns}$ <small>OPT</small> instances: itemgroupcolumns boxedcolumns columns
$\backslash\mathrm{startboxedcolumns}$ [...] $\backslash\mathrm{stopboxedcolumns}$ * inherits: $\backslash\mathrm{setupmixedcolumns}$ <small>OPT</small>
$\backslash\mathrm{startcolumns}$ [...] $\backslash\mathrm{stopcolumns}$ * inherits: $\backslash\mathrm{setupmixedcolumns}$ <small>OPT</small>
$\backslash\mathrm{startitemgroupcolumns}$ [...] $\backslash\mathrm{stopitemgroupcolumns}$ * inherits: $\backslash\mathrm{setupmixedcolumns}$ <small>OPT</small>
$\backslash\mathrm{startmode}$ [...] $\backslash\mathrm{stopmode}$ * NAME
$\backslash\mathrm{startmodeset}$ [...] $\backslash\mathrm{stopmodeset}$ 1 NAME default 2 CONTENT
$\backslash\mathrm{startmodule}$ [...] $\backslash\mathrm{stopmodule}$ * FILE
$\backslash\mathrm{startmoduletestsection}$ ... $\backslash\mathrm{stopmoduletestsection}$
$\backslash\mathrm{startmodule}$ ... $\backslash\mathrm{stopmodule}$ * FILE
$\backslash\mathrm{startnamedsection}$ [...] $\backslash\mathrm{stopnamedsection}$ 1 SECTION 2 title = TEXT bookmark = TEXT marking = TEXT list = TEXT reference = REFERENCE ownnumber = TEXT 3 KEY = VALUE
$\backslash\mathrm{startnamedsubformulas}$ [...] $\backslash\mathrm{stopnamedsubformulas}$ 1 + - REFERENCE <small>OPT</small> 2 TEXT

$\backslash\mathrm{startnarrow} [\dots] [\dots, \dots, \dots] \dots \backslash\mathrm{stopnarrow}$ 1    NAME                    OPT                    OPT 2    inherits: $\backslash\mathrm{setupnarrower}$
$\backslash\mathrm{startnarrower} [\dots, \dots] \dots \backslash\mathrm{stopnarrower}$ *    [-+]left [-+]middle $\{\textcircled{+}\}$ right NUMBER*left NUMBER*middle NUMBER*right reset reverse
$\backslash\mathrm{startNARROWER} [\dots, \dots] \dots \backslash\mathrm{stopNARROWER}$ *    [-+]left [-+]middle $\{\textcircled{+}\}$ right NUMBER*left NUMBER*middle NUMBER*right reset reverse
$\backslash\mathrm{startnarrow} [\dots, \dots, \dots] [\dots, \dots] \dots \backslash\mathrm{stopnarrow}$ 1    inherits: $\backslash\mathrm{setupnarrower}$ OPT 2    [-+]left [-+]middle [-+]right NUMBER*left NUMBER*middle NUMBER*right reset reverse
$\backslash\mathrm{startnarrow} [\dots] [\dots, \dots] \dots \backslash\mathrm{stopnarrow}$ 1    NAME                    OPT                    OPT 2    [-+]left [-+]middle [-+]right NUMBER*left NUMBER*middle NUMBER*right reset reverse
$\backslash\mathrm{startnegative} \dots \backslash\mathrm{stopnegative}$
$\backslash\mathrm{startnicelyfilledbox} [\dots, \dots, \dots] \dots \backslash\mathrm{stopnicelyfilledbox}$ *    width    = DIMENSION                    OPT height   = DIMENSION offset   = DIMENSION strut    = <u>yes</u> no
$\backslash\mathrm{startnointerference} \dots \backslash\mathrm{stopnointerference}$
$\backslash\mathrm{startnotallmodes} [\dots, \dots] \dots \backslash\mathrm{stopnotallmodes}$ *    NAME
$\backslash\mathrm{startnotext} \dots \backslash\mathrm{stopnotext}$
$\backslash\mathrm{startNOTE} [\dots, \dots] \dots \backslash\mathrm{stopNOTE}$ *    REFERENCE                    OPT instances: footnote endnote
$\backslash\mathrm{startNOTE} [\dots, \dots, \dots] \dots \backslash\mathrm{stopNOTE}$ *    title        = TEXT <sup>OPT</sup> bookmark    = TEXT list         = TEXT reference    = REFERENCE instances: footnote endnote
$\backslash\mathrm{startendnote} [\dots, \dots, \dots] \dots \backslash\mathrm{stopendnote}$ *    title        = TEXT                    OPT bookmark    = TEXT list         = TEXT reference    = REFERENCE
$\backslash\mathrm{startfootnote} [\dots, \dots, \dots] \dots \backslash\mathrm{stopfootnote}$ *    title        = TEXT                    OPT bookmark    = TEXT list         = TEXT reference    = REFERENCE
$\backslash\mathrm{startendnote} [\dots, \dots] \dots \backslash\mathrm{stopendnote}$ *    REFERENCE                    OPT
$\backslash\mathrm{startfootnote} [\dots, \dots] \dots \backslash\mathrm{stopfootnote}$ *    REFERENCE                    OPT

<code>\startnotmode [...,*...] ... \stopnotmode</code> <code>* NAME</code>
<code>\startopposite ... \stopopposite</code>
<code>\startoutputstream [...] ... \stopoutputstream</code> <code>* NAME</code>
<code>\startoverlay ... \stopoverlay</code>
<code>\startoverprint ... \stopoverprint</code>
<code>\startpacked [...] ... \stoppacked</code> <code>* blank</code> <small>OPT</small>
<code>\startpagecolumns [...,*...] ... \stoppagecolumns</code> <code>* inherits: \setuppagecolumns</code> <small>OPT</small>
<code>\startPAGECOLUMNS ... \stopPAGECOLUMNS</code>
<code>\startpagecolumns [...] ... \stoppagecolumns</code> <code>* NAME</code> <small>OPT</small>
<code>\startpagecomment ... \stoppagecomment</code>
<code>\startpagefigure [<sup>1</sup>...] [...,<sup>2</sup>...,...] ... \stoppagefigure</code> <code>1 FILE</code> <small>OPT</small> <code>2 offset = default overlay none DIMENSION</code>
<code>\startpagelayout [...] ... \stoppagelayout</code> <code>* page leftpage rightpage</code>
<code>\startpar [<sup>1</sup>...] [...,<sup>2</sup>...,...] ... \stoppar</code> <code>1 NAME</code> <small>OPT</small> <small>OPT</small> <code>2 inherits: \setupparagraph</code>
<code>\startparagraph [<sup>1</sup>...] [...,<sup>2</sup>...,...] ... \stopparagraph</code> <code>1 NAME</code> <small>OPT</small> <small>OPT</small> <code>2 inherits: \setupparagraph</code>
<code>\startparagraphs [...] ... \stopparagraphs</code> <code>* NAME</code>
<code>\startparagraphscell ... \stopparagraphscell</code>
<code>\startPARAGRAPHS ... \stopPARAGRAPHS</code>
<code>\startPARALLEL ... \stopPARALLEL</code>
<code>\startparbuilder [...] ... \stopparbuilder</code> <code>* default oneline basic NAME</code>

```

\startplacefloat [...1...] [...2...2...] [...3...3...] ... \stopplacefloat
1 SINGULAR
2 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
location = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
[-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang
hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header
footer tblr lrtb tblr rltb fxtb btlr lrbt btrl rltb fxbt fixd
reference = REFERENCE
3 KEY = VALUE

```

```

\startplaceFLOAT [...1...1...] [...2...2...] ... \stopplaceFLOAT
1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
location = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
[-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang
hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header
footer tblr lrtb tblr rltb fxtb btlr lrbt btrl rltb fxbt fixd
reference = REFERENCE
2 KEY = VALUE
instances: chemical figure table intermezzo graphic

```

```

\startplacechemical [...1...1...] [...2...2...] ... \stopplacechemical
1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
location = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
[-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang
hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header
footer tblr lrtb tblr rltb fxtb btlr lrbt btrl rltb fxbt fixd
reference = REFERENCE
2 KEY = VALUE

```

```

\startplacefigure [...1...1...] [...2...2...] ... \stopplacefigure
1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
location = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
[-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang
hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header
footer tblr lrtb tblr rltb fxtb btlr lrbt btrl rltb fxbt fixd
reference = REFERENCE
2 KEY = VALUE

```

```

\startplacegraphic [...1...1...] [...2...2...] ... \stopplacegraphic
1 title = TEXT
bookmark = TEXT
marking = TEXT
list = TEXT
location = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
[-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang
hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header
footer tblr lrtb tblr rltb fxtb btlr lrbt btrl rltb fxbt fixd
reference = REFERENCE
2 KEY = VALUE

```

```

\startplaceintermezzo [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stopplaceintermezzo
1 title = TEXT OPT OPT
bookmark = TEXT
marking = TEXT
list = TEXT
location = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
[-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang
hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header
footer tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd
reference = REFERENCE
2 KEY = VALUE

```

```

\startplacetable [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stopplacetable
1 title = TEXT OPT OPT
bookmark = TEXT
marking = TEXT
list = TEXT
location = split always left right inner outer backspace cutspace inleft inright inmargin leftmargin rightmargin
leftedge rightedge innermargin outermargin inneredge outeredge text opposite reset height depth
[-+]line halfline grid high low fit 90 180 270 nonumber none local here force margin [-+]hang
hanging tall both middle offset top bottom auto page leftpage rightpage somewhere effective header
footer tblr lrtb tblr rltb fxtb btlr lrbt btrl rlbt fxbt fixd
reference = REFERENCE
2 KEY = VALUE

```

```

\startplaceformula [...,\stackrel{*}{=},...] ... \stopplaceformula
* title = TEXT OPT
suffix = TEXT
reference = + - REFERENCE

```

```

\startplaceformula [...,\stackrel{*}{=},...] ... \stopplaceformula
* + - REFERENCE OPT

```

```

\startplacepairedbox [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stopplacepairedbox
1 NAME OPT
2 inherits: \setuppairedbox

```

```

\startplacePAIREDBOX [...,\stackrel{*}{=},...] ... \stopplacePAIREDBOX
* inherits: \setuppairedbox OPT
instances: legend

```

```

\startplacelegend [...,\stackrel{*}{=},...] ... \stopplacelegend
* inherits: \setuppairedbox OPT

```

```

\startpositioning [...,\stackrel{1}{=},...] [...,\stackrel{2}{=},...] ... \stoppositioning
1 NAME OPT OPT
2 inherits: \setuppositioning

```

```

\startpositionoverlay {...} ... \stoppositionoverlay
* NAME

```

```

\startpositive ... \stoppositive

```

```

\startpostponing [...] ... \stoppostponing
* [-+]NUMBER OPT

```

```

\startpostponingnotes ... \stoppostponingnotes

```

```

\startprocessassignmentcommand [...,\stackrel{*}{=},...] ... \stopprocessassignmentcommand
* KEY = VALUE

```

```

\startprocessassignmentlist [...,\stackrel{*}{=},...] ... \stopprocessassignmentlist
* KEY = VALUE

```

<pre> \startprocesscommand [,...,*,...] ... \stopprocesscommand *   COMMAND </pre>
<pre> \startprocesscommalist [,...,*,...] ... \stopprocesscommalist *   COMMAND </pre>
<pre> \startproduct [...] ... \stopproduct *   FILE * </pre>
<pre> \startproduct ... .. \stopproduct *   FILE * </pre>
<pre> \startproject [...] ... \stopproject *   FILE * </pre>
<pre> \startproject ... .. \stopproject *   FILE * </pre>
<pre> \startprotectedcolors ... \stopprotectedcolors </pre>
<pre> \startpublication [<sup>1</sup>...] [<sup>2</sup>...,...<sup>2</sup>,...] ... \stoppublication 1  NAME                OPT      OPT 2  tag      = REFERENCE    category = TEXT    k        = REFERENCE    t        = TEXT </pre>
<pre> \startrandomized ... \stoprandomized </pre>
<pre> \startrawsetups [<sup>1</sup>] [<sup>2</sup>] ... \stoprawsetups 1  grid      OPT 2  NAME </pre>
<pre> \startrawsetups ... .. \stoprawsetups *   NAME </pre>
<pre> \startreadingfile ... \stopreadingfile </pre>
<pre> \startregime [...] ... \stopregime *   inherits: \enableregime </pre>
<pre> \startregister [<sup>1</sup>] [<sup>2</sup>] [<sup>3</sup>] [<sup>4</sup>] {...<sup>5</sup>+...<sup>5</sup>} ... \stopregister [<sup>7</sup>] [<sup>8</sup>] 1  NAME                OPT      OPT 2  NAME 3  TEXT 4  TEXT PROCESSOR-&gt;TEXT 5  INDEX 6  CONTENT 7  NAME 8  NAME </pre>
<pre> \startreusableMPgraphic {...<sup>2</sup>,...<sup>2</sup>} ... \stopreusableMPgraphic 1  NAME                OPT 2  KEY </pre>
<pre> \startrightaligned ... \stoprightaligned </pre>
<pre> \startruby [...] ... \stopruby *   NAME </pre>

<pre> \startscript [...] ... \stopscript *   hangul hanzi nihongo ethiopic thai test NAME </pre>
<pre> \startsectionblock [<sup>1</sup>...] [<sup>2</sup>...,...<sup>2</sup>...,...] ... \stopsectionblock 1  NAME                                     OPT 2  bookmark = TEXT     inherits: \setupsectionblock </pre>
<pre> \startsectionblockenvironment [...] ... \stopsectionblockenvironment *   NAME </pre>
<pre> \startSECTIONBLOCK [...,<sup>*</sup>...,...] ... \stopSECTIONBLOCK *   bookmark = TEXT             OPT     inherits: \setupsectionblock instances: frontmatter bodymatter appendices backmatter </pre>
<pre> \startappendices [...,<sup>*</sup>...,...] ... \stopappendices *   bookmark = TEXT             OPT     inherits: \setupsectionblock </pre>
<pre> \startbackmatter [...,<sup>*</sup>...,...] ... \stopbackmatter *   bookmark = TEXT             OPT     inherits: \setupsectionblock </pre>
<pre> \startbodymatter [...,<sup>*</sup>...,...] ... \stopbodymatter *   bookmark = TEXT             OPT     inherits: \setupsectionblock </pre>
<pre> \startfrontmatter [...,<sup>*</sup>...,...] ... \stopfrontmatter *   bookmark = TEXT             OPT     inherits: \setupsectionblock </pre>
<pre> \startsectionlevel [<sup>1</sup>...] [<sup>2</sup>...,...<sup>2</sup>...,...] [<sup>3</sup>...,...<sup>3</sup>...,...] ... \stopsectionlevel 1  NAME                                     OPT      OPT      OPT 2  title      = TEXT     bookmark  = TEXT     marking   = TEXT     list      = TEXT     reference = REFERENCE     ownnumber = TEXT 3  KEY = VALUE </pre>
<pre> \startSECTION [...,<sup>1</sup>...,...] [...,<sup>2</sup>...,...<sup>2</sup>...,...] ... \stopSECTION 1  title      = TEXT             OPT      OPT     bookmark  = TEXT     marking   = TEXT     list      = TEXT     reference = REFERENCE     ownnumber = TEXT 2  KEY = VALUE instances: part chapter section subsection subsubsection subsubsubsection subsubsubsubsection title subject subsubject subsubsubject subsubsubsubject subsubsubsubsubject </pre>
<pre> \startchapter [...,<sup>1</sup>...,...] [...,<sup>2</sup>...,...<sup>2</sup>...,...] ... \stopchapter 1  title      = TEXT             OPT      OPT     bookmark  = TEXT     marking   = TEXT     list      = TEXT     reference = REFERENCE     ownnumber = TEXT 2  KEY = VALUE </pre>

`\startpart [...1...2...] ... \stoppart`

```
1 title      = TEXTOPT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference   = REFERENCE
  ownnumber  = TEXT
2 KEY = VALUE
```

`\startsection [...1...2...] ... \stopsection`

```
1 title      = TEXTOPT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference   = REFERENCE
  ownnumber  = TEXT
2 KEY = VALUE
```

`\startsubject [...1...2...] ... \stopsubject`

```
1 title      = TEXTOPT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference   = REFERENCE
  ownnumber  = TEXT
2 KEY = VALUE
```

`\startsubsection [...1...2...] ... \stopsubsection`

```
1 title      = TEXTOPT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference   = REFERENCE
  ownnumber  = TEXT
2 KEY = VALUE
```

`\startsubsubject [...1...2...] ... \stopsubsubject`

```
1 title      = TEXTOPT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference   = REFERENCE
  ownnumber  = TEXT
2 KEY = VALUE
```

`\startsubsubsection [...1...2...] ... \stopsubsubsection`

```
1 title      = TEXTOPT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference   = REFERENCE
  ownnumber  = TEXT
2 KEY = VALUE
```

`\startsubsubsubject [...1...2...] ... \stopsubsubsubject`

```
1 title      = TEXTOPT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference   = REFERENCE
  ownnumber  = TEXT
2 KEY = VALUE
```

`\startsubsubsubsection [...1...2...] ... \stopsubsubsubsection`

```
1 title      = TEXTOPT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference   = REFERENCE
  ownnumber  = TEXT
2 KEY = VALUE
```



`\startsubsubsubsubject [...,\subscript1...,...] [...,\subscript2...,...] ... \stopsubsubsubsubject`

```
1 title      = TEXT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference   = REFERENCE
  ownnumber  = TEXT
2 KEY = VALUE
```

`\startsubsubsubsubsection [...,\subscript1...,...] [...,\subscript2...,...] ... \stopsubsubsubsubsection`

```
1 title      = TEXT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference   = REFERENCE
  ownnumber  = TEXT
2 KEY = VALUE
```

`\startsubsubsubsubsubject [...,\subscript1...,...] [...,\subscript2...,...] ... \stopsubsubsubsubsubject`

```
1 title      = TEXT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference   = REFERENCE
  ownnumber  = TEXT
2 KEY = VALUE
```

`\starttitle [...,\subscript1...,...] [...,\subscript2...,...] ... \stoptitle`

```
1 title      = TEXT
  bookmark   = TEXT
  marking    = TEXT
  list       = TEXT
  reference   = REFERENCE
  ownnumber  = TEXT
2 KEY = VALUE
```

`\startsetups [...,\subscript1...] [...,\subscript2...] ... \stopsetups`

```
1 grid
2 NAME
```

`\startsetups ... .. \stopsetups`

```
* NAME
```

`\startshift [...,\subscript1...] ... \stopshift`

```
* NAME
```

`\startsidebar [...,\subscript1...] [...,\subscript2...,...] ... \stopsidebar`

```
1 NAME
2 inherits: \setupsidebar
```

`\startsimplecolumns [...,\subscript1...,...] ... \stopsimplecolumns`

```
* inherits: \setsimplecolumnshsize
```

`\startspecialitem [...,\subscript1...] [...,\subscript2...,...] ... \stopspecialitem`

```
1 item
2 REFERENCE
```

`\startspecialitem [...,\subscript1...] ... \stopspecialitem`

```
* sub its
```

`\startspecialitem [...,\subscript1...] {...,\subscript2...} ... \stopspecialitem`

```
1 sym ran mar
2 TEXT
```

`\startsplitformula ... \stopsplitformula`

<code>\startsplitttext ... \stopsplitttext</code>
<code>\startspread ... \stopspread</code>
<code>\startSTARTSTOP ... \stopSTARTSTOP</code>
<code>\startstaticMPfigure {...} ... \stopstaticMPfigure</code> <code>* NAME</code>
<code>\startstaticMPgraphic {...} {...,<sup>2</sup>...} ... \stopstaticMPgraphic</code> <code>1 NAME</code> <code>2 KEY</code>
<code>\STARTSTOP {...}</code> <code>* CONTENT</code>
<code>\startstrictinspectnextcharacter ... \stopstrictinspectnextcharacter</code>
<code>\startstructurepageregister [...]<sup>1</sup> [...]<sup>2</sup> [...,<sup>3</sup>...]<sup>3</sup> [...,<sup>4</sup>...]<sup>4</sup> ...<sup>5</sup> \stopstructurepageregister</code> <code>[...]<sup>6</sup> [...]<sup>7</sup></code> <code>1 NAME</code> <code>2 NAME</code> <code>3 label = NAME</code> <code>keys = TEXT PROCESSOR-&gt;TEXT</code> <code>entries = TEXT PROCESSOR-&gt;TEXT</code> <code>keys:1 = TEXT</code> <code>keys:2 = TEXT</code> <code>keys:3 = TEXT</code> <code>entries:1 = TEXT</code> <code>entries:2 = TEXT</code> <code>entries:3 = TEXT</code> <code>alternative = TEXT</code> <code>4 KEY = VALUE</code> <code>5 CONTENT</code> <code>6 NAME</code> <code>7 NAME</code>
<code>\startstyle [...,<sup>*</sup>...]<sup>*</sup> ... \stopstyle</code> <code>* inherits: \setupstyle</code>
<code>\startstyle [...]<sup>*</sup> ... \stopstyle</code> <code>* NAME FONT</code>
<code>\startSTYLE ... \stopSTYLE</code>
<code>\startsubformulas [...,<sup>*</sup>...]<sup>*</sup> ... \stopsubformulas</code> <code>* + - REFERENCE</code>
<code>\startsubjectlevel [...]<sup>1</sup> [...,<sup>2</sup>...]<sup>2</sup> [...,<sup>3</sup>...]<sup>3</sup> ... \stopsubjectlevel</code> <code>1 NAME</code> <code>2 title = TEXT</code> <code>bookmark = TEXT</code> <code>marking = TEXT</code> <code>list = TEXT</code> <code>reference = REFERENCE</code> <code>ownnumber = TEXT</code> <code>3 KEY = VALUE</code>
<code>\startsubsentence ... \stopsubsentence</code>
<code>\startsubstack ... \stopsubstack</code>

$\backslash\startsymbolset$ [ <sup>1</sup> ...] [ <sup>2</sup> ... <sub>OPT</sub> ...] ... $\stopsymbolset$ 1 NAME 2 font = FONT
$\startTABLE$ [... <sub>OPT</sub> ...] ... $\stopTABLE$ * inherits: $\setupTABLE$
$\startTABLEbody$ [... <sub>OPT</sub> ...] ... $\stopTABLEbody$ * inherits: $\setupTABLE$
$\startTABLEfoot$ [... <sub>OPT</sub> ...] ... $\stopTABLEfoot$ * inherits: $\setupTABLE$
$\startTABLEhead$ [... <sub>OPT</sub> ...] ... $\stopTABLEhead$ * inherits: $\setupTABLE$
$\startTABLEnext$ [... <sub>OPT</sub> ...] ... $\stopTABLEnext$ * inherits: $\setupTABLE$
$\starttable$ [  <sup>1</sup> ... ] [... <sub>OPT</sub> ...] ... $\stoptable$ 1 TEMPLATE 2 inherits: $\setuptables$
$\starttablehead$ [...] ... $\stoptablehead$ * NAME
$\starttables$ [  <sup>1</sup> ... ] ... $\stoptables$ * TEMPLATE
$\starttables$ [...] ... $\stoptables$ * NAME
$\starttabletail$ [...] ... $\stoptabletail$ * NAME
$\starttable$ [ <sup>1</sup> ...] [... <sub>OPT</sub> ...] ... $\stoptable$ 1 NAME 2 inherits: $\setuptables$
$\starttabulate$ [  <sup>1</sup> ... ] [... <sub>OPT</sub> ...] ... $\stoptabulate$ 1 TEMPLATE 2 inherits: $\setuptabulate$
$\starttabulatehead$ [... <sub>OPT</sub> ...] ... $\stoptabulatehead$ * NAME
$\starttabulatetail$ [... <sub>OPT</sub> ...] ... $\stoptabulatetail$ * NAME
$\startTABULATE$ [ <sup>1</sup> ...] [... <sub>OPT</sub> ...] ... $\stopTABULATE$ 1 NAME 2 inherits: $\setuptabulate$ instances: legend fact
$\startfact$ [ <sup>1</sup> ...] [... <sub>OPT</sub> ...] ... $\stopfact$ 1 NAME 2 inherits: $\setuptabulate$

`\startlegend [...]1 [...]2... ] ... \stoplegend`

1 NAME OPT OPT  
2 inherits: \setuptabulate

`\startTABULATION [...]1 [...]2... ] ... \stopTABULATION`

1 NAME OPT OPT  
2 inherits: \setuptabulation

`\starttexcode ... \stoptexcode`

`\starttexdefinition ...1 ...2 ...3 ...4 ...5 ...6 ...7 ... \stoptexdefinition`

1 spaces nospaces OPT OPT OPT OPT OPT OPT  
2 global  
3 unexpanded  
4 expanded  
5 singleempty doubleempty tripleempty quadrupleempty quintupleempty sextupleempty singleargument doubleargument  
tripleargument quadrupleargument quintupleargument sextupleargument  
6 NAME  
7 TEMPLATE

`\starttext ... \stoptext`

`\starttextbackground [...]1 [...]2... ] ... \stoptextbackground`

1 NAME OPT  
2 inherits: \setuptextbackground

`\starttextbackgroundmanual ... \stoptextbackgroundmanual`

`\startTEXTBACKGROUND [...]*... ] ... \stopTEXTBACKGROUND`

\* inherits: \setuptextbackground OPT

`\starttextcolor [...] ... \stoptextcolor`

\* COLOR

`\starttextcolorintent ... \stoptextcolorintent`

`\starttextflow [...] ... \stoptextflow`

\* NAME

`\starttextrule {...} ... \stoptextrule`

\* TEXT

`\starttokenlist [...] ... \stoptokenlist`

\* NAME

`\starttokens [...] ... \stoptokens`

\* NAME

`\starttransparent [...] ... \stoptransparent`

\* COLOR

`\starttypescript [...]1... ] [...]2... ] [...]3... ] ... \stoptypescript`

1 serif sans mono math handwriting calligraphy OPT  
2 NAME  
3 size name

`\starttypescriptcollection [...] ... \stoptypescriptcollection`

\* NAME

<pre> \startTYPING [...,*,...] ... \stopTYPING * inherits: \setuptyping<sup>OPT</sup> instances: typing LUA MP PARSEDXML TEX XML </pre>
<pre> \startTYPING [...,*,...] ... \stopTYPING * continue <sup>OPT</sup> instances: typing LUA MP PARSEDXML TEX XML </pre>
<pre> \startLUA [...,*,...] ... \stopLUA * continue <sup>OPT</sup> </pre>
<pre> \startMP [...,*,...] ... \stopMP * continue <sup>OPT</sup> </pre>
<pre> \startPARSEDXML [...,*,...] ... \stopPARSEDXML * continue <sup>OPT</sup> </pre>
<pre> \startTEX [...,*,...] ... \stopTEX * continue <sup>OPT</sup> </pre>
<pre> \starttyping [...,*,...] ... \stoptyping * continue <sup>OPT</sup> </pre>
<pre> \startXML [...,*,...] ... \stopXML * continue <sup>OPT</sup> </pre>
<pre> \startLUA [...,*,...] ... \stopLUA * inherits: \setuptyping<sup>OPT</sup> </pre>
<pre> \startMP [...,*,...] ... \stopMP * inherits: \setuptyping<sup>OPT</sup> </pre>
<pre> \startPARSEDXML [...,*,...] ... \stopPARSEDXML * inherits: \setuptyping<sup>OPT</sup> </pre>
<pre> \startTEX [...,*,...] ... \stopTEX * inherits: \setuptyping<sup>OPT</sup> </pre>
<pre> \starttyping [...,*,...] ... \stoptyping * inherits: \setuptyping<sup>OPT</sup> </pre>
<pre> \startXML [...,*,...] ... \stopXML * inherits: \setuptyping<sup>OPT</sup> </pre>
<pre> \startuniqueMPgraphic {...}<sup>1</sup> {...,<sup>2</sup>...} ... \stopuniqueMPgraphic 1 NAME <sup>OPT</sup> 2 KEY </pre>
<pre> \startuniqueMPpagegraphic {...}<sup>1</sup> {...,<sup>2</sup>...} ... \stopuniqueMPpagegraphic 1 NAME <sup>OPT</sup> 2 KEY </pre>
<pre> \startunpacked ... \stopunpacked </pre>
<pre> \startusableMPgraphic {...}<sup>1</sup> {...,<sup>2</sup>...} ... \stopusableMPgraphic 1 NAME <sup>OPT</sup> 2 KEY </pre>

$\backslash\text{startuseMPgraphic}$ $\{...\}^1 \{...\}^2 \dots \backslash\text{stopuseMPgraphic}$ 1 NAME OPT 2 KEY
$\backslash\text{startusemathstyleparameter}$ $\backslash.* \dots \backslash\text{stopusemathstyleparameter}$ * CSNAME
$\backslash\text{startuserdata}$ $[...]^1 [...\]^{2\dots} \dots \backslash\text{stopuserdata}$ 1 NAME OPT OPT 2 KEY = VALUE
$\backslash\text{startusingbtxs specification}$ $[...]^* \dots \backslash\text{stopusingbtxs specification}$ * NAME
$\backslash\text{startvboxregister}$ $.* \dots \backslash\text{stopvboxregister}$ * CSNAME NUMBER
$\backslash\text{startvboxto hbox}$ $\dots \backslash\text{stopvboxto hbox}$
$\backslash\text{startvboxto hbox separator}$ $\dots \backslash\text{stopvboxto hbox separator}$
$\backslash\text{startviewerlayer}$ $[...]^* \dots \backslash\text{stopviewerlayer}$ * NAME
$\backslash\text{startVIEWERLAYER} \dots \backslash\text{stopVIEWERLAYER}$
$\backslash\text{startvtopregister}$ $.* \dots \backslash\text{stopvtopregister}$ * CSNAME NUMBER
$\backslash\text{startxcell}$ $[...]^1 [...\]^{2\dots} \dots \backslash\text{stopxcell}$ 1 NAME OPT OPT 2 nx = NUMBER ny = NUMBER nc = NUMBER nr = NUMBER inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxcellgroup}$ $[...]^1 [...\]^{2\dots} \dots \backslash\text{stopxcellgroup}$ 1 NAME OPT OPT 2 inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxcolumn}$ $[...\]^{*} \dots \backslash\text{stopxcolumn}$ * inherits: $\backslash\text{setupxtable}^{\text{PT}}$
$\backslash\text{startxcolumn}$ $[...]^* \dots \backslash\text{stopxcolumn}$ * NAME OPT
$\backslash\text{startxgroup}$ $[...]^1 [...\]^{2\dots} \dots \backslash\text{stopxgroup}$ 1 NAME OPT OPT 2 inherits: $\backslash\text{setupxtable}$
$\backslash\text{startxmldisplayverbatim}$ $[...]^* \dots \backslash\text{stopxmldisplayverbatim}$ * NAME
$\backslash\text{startxmllineverbatim}$ $[...]^* \dots \backslash\text{stopxmllineverbatim}$ * NAME
$\backslash\text{startxmlraw} \dots \backslash\text{stopxmlraw}$

<code>\startxmlsetups [...]<sup>1</sup> [...]<sup>2</sup> ... \stopxmlsetups</code> 1    grid                    OPT 2    NAME
<code>\startxmlsetups ... \stopxmlsetups</code> *    NAME
<code>\startxrow [...]<sup>1</sup> [...]<sup>2</sup> ... \stopxrow</code> 1    NAME                    OPT                    OPT 2    inherits: \setupxtable
<code>\startxrowgroup [...]<sup>1</sup> [...]<sup>2</sup> ... \stopxrowgroup</code> 1    NAME                    OPT                    OPT 2    inherits: \setupxtable
<code>\startxtable [...]<sup>*</sup> ... \stopxtable</code> *    inherits: \setupxtable
<code>\startxtablebody [...]<sup>*</sup> ... \stopxtablebody</code> *    inherits: \setupxtable                    OPT
<code>\startxtablebody [...]<sup>*</sup> ... \stopxtablebody</code> *    NAME                    OPT
<code>\startxtablefoot [...]<sup>*</sup> ... \stopxtablefoot</code> *    inherits: \setupxtable                    OPT
<code>\startxtablefoot [...]<sup>*</sup> ... \stopxtablefoot</code> *    NAME                    OPT
<code>\startxtablehead [...]<sup>*</sup> ... \stopxtablehead</code> *    inherits: \setupxtable                    OPT
<code>\startxtablehead [...]<sup>*</sup> ... \stopxtablehead</code> *    NAME                    OPT
<code>\startxtablenext [...]<sup>*</sup> ... \stopxtablenext</code> *    inherits: \setupxtable                    OPT
<code>\startxtablenext [...]<sup>*</sup> ... \stopxtablenext</code> *    NAME                    OPT
<code>\startXTABLE [...]<sup>*</sup> ... \stopXTABLE</code> *    inherits: \setupxtable                    OPT
<code>\startxtable [...]<sup>*</sup> ... \stopxtable</code> *    NAME                    OPT
<code>\stopline [...]</code> *    REFERENCE
<code>\stopLINENOTE [...]</code> *    REFERENCE instances: linenote
<code>\stoplinenote [...]</code> *    REFERENCE

<code>\stretched [...<sup>1</sup>...] {...}</code> 1 inherits: \setupstretched 2 TEXT
<code>\strictdoifelsenextoptional {...} {...}</code> 1 TRUE 2 FALSE
<code>\strictdoifnextoptionalelse {...} {...}</code> 1 TRUE 2 FALSE
<code>\stripcharacter .<sup>1</sup>. \from ... \to \<sup>3</sup>..</code> 1 CHARACTER 2 TEXT 3 CSNAME
<code>\strippedcsname \*..</code> * CSNAME
<code>\strippedcsname ...</code> * TEXT
<code>\stripspaces \from .<sup>1</sup>. \to \<sup>2</sup>..</code> 1 TEXT 2 CSNAME
<code>\structurelistuservariable {...}</code> * KEY
<code>\structurenumber</code>
<code>\structuretitle</code>
<code>\structureuservariable {...}</code> * KEY
<code>\structurevariable {...}</code> * KEY
<code>\strut</code>
<code>\strutdp</code>
<code>\strutgap</code>
<code>\strutht</code>
<code>\struthtdp</code>
<code>\struttedbox {...}</code> * CONTENT
<code>\strutwd</code>
<code>\style [...<sup>1</sup>...] {...}</code> 1 inherits: \setupstyle 2 TEXT



<code>\styleinstance [...]</code> <code>* NAME</code>
<code>\style [<sup>1</sup>...] {<sup>2</sup>...}</code> <code>1 NAME FONT</code> <code>2 TEXT</code>
<code>\STYLE {...}</code> <code>* TEXT</code>
<code>\subpagenumber</code>
<code>\subsentence {...}</code> <code>* CONTENT</code>
<code>\substituteincommalist {...} {...} \<sup>3</sup>...</code> <code>1 TEXT</code> <code>2 TEXT</code> <code>3 CSNAME</code>
<code>\subtractfeature [...]</code> <code>* NAME</code>
<code>\subtractfeature {...}</code> <code>* NAME</code>
<code>\swapcounts \<sup>1</sup>... \<sup>2</sup>...</code> <code>1 CSNAME</code> <code>2 CSNAME</code>
<code>\swapdimens \<sup>1</sup>... \<sup>2</sup>...</code> <code>1 CSNAME</code> <code>2 CSNAME</code>
<code>\swapface</code>
<code>\swapmacros \<sup>1</sup>... \<sup>2</sup>...</code> <code>1 CSNAME</code> <code>2 CSNAME</code>
<code>\swaptypeface</code>
<code>\switchstyleonly [...]</code> <code>* rm ss tt hw cg roman serif regular sans sansserif support type teletype mono handwritten calligraphic</code>
<code>\switchstyleonly \<sup>*</sup>...</code> <code>* CSNAME</code>
<code>\switchtobodyfont [...,<sup>*</sup>...]</code> <code>* inherits: \setupbodyfont</code>
<code>\switchtocolour [...]</code> <code>* COLOR</code>
<code>\switchtointerlinespace [...,<sup>1</sup>...] [...,<sup>2</sup>...<sub>OPT</sub>,...]</code> <code>1 NAME</code> <code>2 inherits: \setupinterlinespace</code>

<code>\switchtointerlinespace [...,*...]</code> <code>* on off reset auto small medium <sup>OPT</sup>big NUMBER DIMENSION</code>
<code>\switchtointerlinespace [...]</code> <code>* NAME</code>
<code>\symbol [<sup>1</sup>...] [<sup>2</sup>...]</code> <code>1 NAME <sup>OPT</sup></code> <code>2 NAME</code>
<code>\symbolreference [...]</code> <code>* REFERENCE</code>
<code>\symbol {...}</code> <code>* NAME</code>
<code>\synchronizeblank</code>
<code>\synchronizeindenting</code>
<code>\synchronizemarking [<sup>1</sup>...] [<sup>2</sup>...] [<sup>3</sup>...]</code> <code>1 MARK <sup>OPT</sup></code> <code>2 NUMBER</code> <code>3 keep</code>
<code>\synchronizeoutputstreams [...,*...]</code> <code>* NAME</code>
<code>\synchronizestrut {...}</code> <code>* yes no auto cap fit line default CHARACTER</code>
<code>\synchronizewhitespace</code>
<code>\synctexblockfilename {...}</code> <code>* FILE</code>
<code>\synctexresetfilename</code>
<code>\synctexsetfilename {...}</code> <code>* FILE</code>
<code>\SYNONYM [<sup>1</sup>] {...} {...}</code> <code>1 NAME <sup>OPT</sup></code> <code>2 TEXT</code> <code>3 CONTENT</code> <code>instances: abbreviation</code>
<code>\abbreviation [<sup>1</sup>] {...} {...}</code> <code>1 NAME <sup>OPT</sup></code> <code>2 TEXT</code> <code>3 CONTENT</code>
<code>\systemlog {...} {...} {...}</code> <code>1 FILE</code> <code>2 TEXT</code> <code>3 TEXT</code>

<code>\systemlogfirst {...} {...} {...}</code> 1 FILE 2 TEXT 3 TEXT
<code>\systemloglast {...} {...} {...}</code> 1 FILE 2 TEXT 3 TEXT
<code>\systemsetups {...}</code> * NAME
<code>\TABLE</code>
<code>\TaBlE</code>
<code>\TEX</code>
<code>\TeX</code>
<code>\TheNormalizedFontSize</code>
<code>\TransparencyHack</code>
<code>\tabulateautoline</code>
<code>\tabulateautorule</code>
<code>\tabulateline</code>
<code>\tabulaterule</code>
<code>\taggedctxcommand {...}</code> * COMMAND
<code>\taggedlabeltexts {...} {...} {...}</code> 1 NAME 2 NAME 3 CONTENT
<code>\tbox {...}</code> * CONTENT
<code>\testandsplitstring ... \at ... \to ... \and ...</code> 1 TEXT 2 TEXT 3 CSNAME 4 CSNAME
<code>\testcolumn [...] [...]</code> 1 NUMBER OPT 2 DIMENSION
<code>\testfeature {...} {...}</code> 1 NUMBER 2 CONTENT

<pre> \testfeatureonce {...} {...} 1  NUMBER 2  CONTENT </pre>
<pre> \testpage [...] [...] 1  NUMBER          OPT 2  DIMENSION </pre>
<pre> \testpageonly [...] [...] 1  NUMBER          OPT 2  DIMENSION </pre>
<pre> \testpagesync [...] [...] 1  NUMBER          OPT 2  DIMENSION </pre>
<pre> \testtokens [...] *  NAME </pre>
<pre> \tex {...} *  CONTENT </pre>
<pre> \texdefinition {...} *  NAME </pre>
<pre> \texsetup {...} *  NAME </pre>
<pre> \TEXTBACKGROUND {...} *  CONTENT </pre>
<pre> \textcitation [...]\textcitation [...] 1  reference      = REFERENCE    alternative    = default category entry short page num textnum year index tag keywords author authoryears authornum                      authoryear    before        = COMMAND    after         = COMMAND    left          = COMMAND    right         = COMMAND    inherits: \setupbtx 2  REFERENCE </pre>
<pre> \textcitation [...] [...] 1  default category entry short page num textnum year index tag keywords author authoryears authornum authoryear 2  REFERENCE </pre>
<pre> \textcitation [...]\textcitation [...] 1  reference      = REFERENCE    alternative    = default category entry short page num textnum year index tag keywords author authoryears authornum                      authoryear    before        = COMMAND    after         = COMMAND    left          = COMMAND    right         = COMMAND    inherits: \setupbtx 2  KEY = VALUE </pre>

```

\textcite [...1...2] [...]
1  reference      = REFERENCE
   alternative    = default category entry short page num textnum year index tag keywords author authoryears authornum
                     authoryear
   before        = COMMAND
   after         = COMMAND
   left          = COMMAND
   right         = COMMAND
   inherits:     \setupbtx
2  REFERENCE

```

```

\textcite [...1] [...2]
1  default category entry short page num textnum year index tag keywords author authoryears authornum authoryear
2  REFERENCE

```

```

\textcite [...1...2] [...2...1]
1  reference      = REFERENCE
   alternative    = default category entry short page num textnum year index tag keywords author authoryears authornum
                     authoryear
   before        = COMMAND
   after         = COMMAND
   left          = COMMAND
   right         = COMMAND
   inherits:     \setupbtx
2  KEY = VALUE

```

```

\textcontrolspace

```

```

\textflowcollector {...}
*  NAME

```

```

\textmath {...}
*  CONTENT

```

```

\textminus

```

```

\textnote [...1...2] {...}
1  inherits:     \setuptextnote
2  TEXT

```

```

\textormathchar {...}
*  NUMBER

```

```

\textormathchars {...}
*  CHARACTER

```

```

\textplus

```

```

\textreference [...1...2] {...}
1  REFERENCE
2  TEXT

```

```

\textrule [...1] {...2}
1  top middle OPTbottom OPT
2  TEXT

```

```

\textvisiblespace

```

```

\thainumerals {...}
*  NUMBER

```

<code>\thefirstcharacter {...}</code> *    TEXT
<code>\thenormalizedbodyfontsize {...}</code> *    DIMENSION
<code>\theremainingcharacters {...}</code> *    TEXT
<code>\thickspace</code>
<code>\thinrule</code>
<code>\thinrules [...]*=...,...]</code> *    inherits: \setupthinrules
<code>\thinspace</code>
<code>\thirddoffivearguments {...} {...} {...} {...} {...}</code> 1    TEXT 2    TEXT 3    TEXT 4    TEXT 5    TEXT
<code>\thirddoffourarguments {...} {...} {...} {...}</code> 1    TEXT 2    TEXT 3    TEXT 4    TEXT
<code>\thirddofsixarguments {...} {...} {...} {...} {...} {...}</code> 1    TEXT 2    TEXT 3    TEXT 4    TEXT 5    TEXT 6    TEXT
<code>\thirddofthreearguments {...} {...} {...}</code> 1    TEXT 2    TEXT 3    TEXT
<code>\thirddofthreeunexpanded {...} {...} {...}</code> 1    TEXT 2    TEXT 3    TEXT
<code>\threedigitrounding {...}</code> *    NUMBER
<code>\tibetannumerals {...}</code> *    NUMBER
<code>\tightlayer [...]</code> *    NAME
<code>\tilde {...}</code> *    CHARACTER

<code>\tinyfont</code>
<code>\tlap {...}</code> *   CONTENT
<code>\tochar {...}</code> *   e:NAME x:NUMBER d:NUMBER s:NUMBER i:NUMBER n:NAME c:NAME u:NAME a:NAME
<code>\tolinenote [...]</code> *   REFERENCE
<code>\TOOLTIP [...<sup>1</sup>...<sup>2</sup>...<sup>3</sup>]{...}{...}</code> 1   inherits: \setup <sup>OPT</sup> tooltip 2   TEXT 3   TEXT instances: tooltip
<code>\TOOLTIP [...<sup>1</sup>]{...<sup>2</sup>}{...<sup>3</sup>}</code> 1   left middle <sup>OPT</sup> right 2   TEXT 3   TEXT instances: tooltip
<code>\tooltip [...<sup>1</sup>]{...<sup>2</sup>}{...<sup>3</sup>}</code> 1   left middle <sup>OPT</sup> right 2   TEXT 3   TEXT
<code>\tooltip [...<sup>1</sup>...<sup>2</sup>...<sup>3</sup>]{...}{...}</code> 1   inherits: \setup <sup>OPT</sup> tooltip 2   TEXT 3   TEXT
<code>\topbox {...}</code> *   CONTENT
<code>\topleftbox {...}</code> *   CONTENT
<code>\toplinebox {...}</code> *   CONTENT
<code>\toprightbox {...}</code> *   CONTENT
<code>\topskippedbox {...}</code> *   CONTENT
<code>\tracecatcodetables</code>
<code>\tracedfontname {...}</code> *   FONT
<code>\traceoutputroutines</code>
<code>\tracepositions</code>
<code>\translate [...<sup>*</sup>...<sup>*</sup>...<sup>*</sup>]{...}</code> *   LANGUAGE = TEXT <sup>OPT</sup>

<code>\transparencyparts {...}</code> * COLOR
<code>\transparent [<sup>1</sup>] {...} {<sup>2</sup>...}</code> 1 COLOR 2 CONTENT
<code>\triplebond</code>
<code>\truefilename {...}</code> * FILE
<code>\truefontname {...}</code> * FONT
<code>\ttraggedright</code>
<code>\twodigitrounding {...}</code> * NUMBER
<code>\tx</code>
<code>\txx</code>
<code>\typ [...,<sup>1</sup>...<sup>2</sup>...]</code> { <sup>2</sup> ...} 1 inherits: $\setuptype$ 2 CONTENT
<code>\type [...,<sup>1</sup>...<sup>2</sup>...]</code> { <sup>2</sup> ...} 1 inherits: $\setuptype$ 2 CONTENT
<code>\typebuffer [...,<sup>1</sup>...<sup>2</sup>...]</code> 1 BUFFER OPT OPT 2 inherits: $\setuptyping$
<code>\typeBUFFER [...,<sup>*</sup>...<sup>OPT</sup>...]</code> * inherits: $\setuptyping$
<code>\typedefinedbuffer [...<sup>1</sup>] [...,<sup>2</sup>...<sup>OPT</sup>...]</code> 1 BUFFER OPT 2 inherits: $\setuptyping$
<code>\typeface</code>
<code>\typefile [...<sup>1</sup>] [...,<sup>2</sup>...<sup>3</sup>...]</code> { <sup>3</sup> ...} 1 NAME OPT OPT 2 inherits: $\setuptyping$ 3 FILE
<code>\typeinlinebuffer [...,<sup>1</sup>...<sup>2</sup>...<sup>3</sup>...]</code> 1 BUFFER OPT OPT 2 inherits: $\setuptype$
<code>\typescriptone</code>
<code>\typescriptprefix {...}</code> * NAME



<code>\typescriptthree</code>
<code>\typescripttwo</code>
<code>\typesetbuffer</code> [ <sup>1</sup> ...] [ <sup>2</sup> ... <sup>2</sup> ...] 1 * BUFFER OPT OPT 2 inherits: \setupexternalfigure
<code>\typesetfile</code> [ <sup>1</sup> ] [ <sup>2</sup> ...] [ <sup>3</sup> ... <sup>3</sup> ...] 1 NAME FILE OPT OPT 2 FILE TEXT 3 inherits: \setupexternalfigure
<code>\type</code> [ <sup>1</sup> ... <sup>1</sup> ...] 1 inherits: \setuptype 2 ANGLES
<code>\TYPE</code> [ <sup>1</sup> ... <sup>1</sup> ...] 1 inherits: \setuptype 2 CONTENT
<code>\TYPE</code> [ <sup>1</sup> ... <sup>1</sup> ...] 1 inherits: \setuptype 2 ANGLES
<code>\typ</code> [ <sup>1</sup> ... <sup>1</sup> ...] 1 inherits: \setuptype 2 ANGLES
<code>\uconvertnumber</code> { <sup>1</sup> ...} { <sup>2</sup> ...} 1 inherits: \convertnumber 2 NUMBER
<code>\uedcatcodecommand</code> \ <sup>1</sup> ... <sup>2</sup> { <sup>3</sup> ...} 1 CSNAME 2 CHARACTER NUMBER 3 COMMAND
<code>\undefinevalue</code> {.*} * NAME
<code>\undepthed</code> {.*} * CONTENT
<code>\underset</code> { <sup>1</sup> ...} { <sup>2</sup> ...} 1 TEXT 2 TEXT
<code>\undoassign</code> [ <sup>1</sup> ...] [ <sup>2</sup> ...] 1 TEXT 2 KEY = VALUE
<code>\unexpandeddocumentvariable</code> {.*} * KEY
<code>\unhhbox</code> <sup>1</sup> ... \with { <sup>2</sup> ...} 1 CSNAME NUMBER 2 COMMAND

<code>\unihex {...}</code> *    NUMBER
<code>\uniqueMPgraphic {...} {...<sup>1</sup>...<sup>2</sup>...}</code> 1    NAME 2    KEY = VALUE
<code>\uniqueMPpagegraphic {...} {...<sup>1</sup>...<sup>2</sup>...}</code> 1    NAME 2    KEY = VALUE
<code>\UNIT {...}</code> *    CONTENT instances: unit
<code>\unit {...}</code> *    CONTENT
<code>\unknown</code>
<code>\unprotect ... \protect</code>
<code>\unprotected ... \par</code> *    CONTENT
<code>\unregisterhyphenationpattern [...<sup>1</sup>] [...<sup>2</sup>]</code> 1    LANGUAGE 2    TEXT
<code>\unspaceafter \... {...<sup>1</sup>...<sup>2</sup>...}</code> 1    CSNAME 2    TEXT
<code>\unspaceargument ... \to \...<sup>1</sup>...<sup>2</sup>...</code> 1    TEXT 2    CSNAME
<code>\unspaced {...}</code> *    TEXT
<code>\unspacestring ... \to \...<sup>1</sup>...<sup>2</sup>...</code> 1    TEXT 2    CSNAME
<code>\unstackscripts</code>
<code>\untexargument {...} \to \...<sup>1</sup>...<sup>2</sup>...</code> 1    TEXT 2    CSNAME
<code>\untexcommand {...} \to \...<sup>1</sup>...<sup>2</sup>...</code> 1    CSNAME 2    CSNAME
<code>\uppercased {...}</code> *    TEXT

<code>\uppercasestring <sup>1</sup>... \to <sup>2</sup>...</code> 1 TEXT 2 CSNAME
<code>\upperlefthdoubleninequote</code>
<code>\upperlefthdoublesixquote</code>
<code>\upperleftsingleninequote</code>
<code>\upperleftsinglesixquote</code>
<code>\upperrighthdoubleninequote</code>
<code>\upperrighthdoublesixquote</code>
<code>\upperrightsingleninequote</code>
<code>\upperrightsinglesixquote</code>
<code>\url [...]</code> * NAME
<code>\usealignparameter \...</code> * CSNAME
<code>\useblankparameter \...</code> * CSNAME
<code>\useblocks [...<sup>1</sup>,...] [...<sup>2</sup>,...] [...<sup>3</sup>,...<sup>3</sup>,...]</code> 1 NAME 2 NAME 3 criterium = <u>text</u> SECTION
<code>\usebodyfont [...*,...]</code> * inherits: \setupbodyfont
<code>\usebodyfontparameter \...</code> * CSNAME
<code>\usebtxdataset [...<sup>1</sup>] [...<sup>2</sup>] [...<sup>3</sup>,...<sup>3</sup>,...]</code> 1 NAME 2 FILE 3 specification = NAME
<code>\usebtxdefinitions [...]</code> * FILE
<code>\usecitation [...]</code> * REFERENCE
<code>\usecitation {...}</code> * REFERENCE
<code>\usecolors [...]</code> * FILE

\usecomponent [...] * FILE
\usedummycolorparameter {...} * KEY
\usedummystyleandcolor {...} {...} 1 KEY 2 KEY
\usedummystyleparameter {...} * KEY
\useenvironment [...] * FILE
\useexternaldocument [...] <sup>1</sup> [...] <sup>2</sup> [...] <sup>3</sup> 1 NAME OPT 2 FILE 3 TEXT
\useexternalfigure [...] <sup>1</sup> [...] <sup>2</sup> [...] <sup>3</sup> [...,...] <sup>4</sup> ... 1 NAME OPT OPT 2 FILE 3 NAME 4 inherits: \setupexternalfigure
\useexternalrendering [...] <sup>1</sup> [...] <sup>2</sup> [...] <sup>3</sup> [...] <sup>4</sup> 1 NAME 2 NAME 3 FILE 4 auto embed
\useexternalsoundtrack [...] <sup>1</sup> [...] <sup>2</sup> 1 NAME 2 FILE
\usefigurebase [...] * reset FILE
\usefile [...] <sup>1</sup> [...] <sup>2</sup> [...] <sup>3</sup> 1 NAME OPT 2 FILE 3 TEXT
\usegridparameter \*.. * CSNAME
\useindentingparameter \*.. * CSNAME
\useindentnextparameter \*.. * CSNAME
\useinterlinespaceparameter \*.. * CSNAME
\useJSscripts [...] <sup>1</sup> [...] <sup>2</sup> ,... 1 FILE OPT 2 NAME

$\backslash\text{uselanguageparameter } \backslash\ldots$ $\ast$ CSNAME
$\backslash\text{uselua module } [\ldots]$ $\ast$ FILE
$\backslash\text{useMPenvironmentbuffer } [\ldots]$ $\ast$ NAME
$\backslash\text{useMPgraphic } \{\ldots\}^1 \{\ldots,\ldots,\ldots\}^2$ $\text{1 NAME}$ $\text{2 KEY = VALUE}$
$\backslash\text{useMPlibrary } [\ldots]$ $\ast$ FILE
$\backslash\text{useMPrun } \{\ldots\}^1 \{\ldots\}^2$ $\text{1 NAME}$ $\text{2 NUMBER}$
$\backslash\text{useMPvariables } [\ldots]^1 [\ldots,\ldots]^2$ $\text{1 NAME}$ $\text{2 KEY}$
$\backslash\text{usemathstyleparameter } \backslash\ldots$ $\ast$ CSNAME
$\backslash\text{usemodule } [\ldots]^1 [\ldots,\ldots]^2 [\ldots,\ldots,\ldots]^3$ $\text{1 m p s x t}$ $\text{2 FILE}$ $\text{3 KEY = VALUE}$
$\backslash\text{usepath } [\ldots,\ldots]$ $\ast$ PATH
$\backslash\text{useproduct } [\ldots]$ $\ast$ FILE
$\backslash\text{useprofileparameter } \backslash\ldots$ $\ast$ CSNAME
$\backslash\text{useproject } [\ldots]$ $\ast$ FILE
$\backslash\text{userreferenceparameter } \backslash\ldots$ $\ast$ CSNAME
$\backslash\text{userpagenumber}$
$\backslash\text{usesetupparameter } \backslash\ldots$ $\ast$ CSNAME
$\backslash\text{usestaticMPfigure } [\ldots,\ldots,\ldots]^1 [\ldots]^2$ $\text{1 inherits: \setupscale}$ $\text{2 NAME}$
$\backslash\text{usesubpath } [\ldots,\ldots]$ $\ast$ PATH

<code>\usesymbols [...]</code> <code>* FILE</code>
<code>\usetexmodule [...]<sup>1</sup> [...,<sup>2</sup>...] [...,<sup>3</sup>...,...]</code> <code>1 m p s x t OPT OPT</code> <code>2 FILE</code> <code>3 KEY = VALUE</code>
<code>\usetypescript [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup></code> <code>1 serif sans mono math<sup>OPT</sup> handwriting<sup>OPT</sup> calligraphy casual all</code> <code>2 NAME fallback default dtp simple</code> <code>3 size name</code>
<code>\usetypescriptfile [...]</code> <code>* reset FILE</code>
<code>\useURL [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup> [...]<sup>4</sup></code> <code>1 NAME OPT OPT</code> <code>2 URL</code> <code>3 FILE</code> <code>4 TEXT</code>
<code>\useurl [...]<sup>1</sup> [...]<sup>2</sup> [...]<sup>3</sup> [...]<sup>4</sup></code> <code>1 NAME OPT OPT</code> <code>2 URL</code> <code>3 FILE</code> <code>4 TEXT</code>
<code>\usezipfile [...]<sup>1</sup> [...]<sup>2</sup></code> <code>1 FILE OPT</code> <code>2 FILE</code>
<code>\utfchar {...}</code> <code>* NUMBER</code>
<code>\utflower {...}</code> <code>* TEXT</code>
<code>\utfupper {...}</code> <code>* TEXT</code>
<code>\utilityregisterlength</code>
<code>\VerboseNumber {...}</code> <code>* NUMBER</code>
<code>\vboxreference [...]<sup>1</sup>,... {...}<sup>2</sup></code> <code>1 REFERENCE</code> <code>2 CONTENT</code>
<code>\vec {...}</code> <code>* CHARACTER</code>
<code>\verbatim {...}</code> <code>* CONTENT</code>
<code>\verbatimstring {...}</code> <code>* CONTENT</code>

<code>\verbosenumbers {...}</code> *    NUMBER
<code>\version [...]</code> *    concept file temporary final NAME
<code>\verticalgrowingbar [...,.*=...,...]</code> *    inherits: \setuppositionbar
<code>\verticalpositionbar [...,.*=...,...]</code> *    inherits: \setuppositionbar
<code>\veryraggedcenter</code>
<code>\veryraggedleft</code>
<code>\veryraggedright</code>
<code>\vglue ...</code> *    DIMENSION
<code>\viewerlayer [...<sup>1</sup>] {...<sup>2</sup>}</code> 1    NAME 2    CONTENT
<code>\vl [...]</code> *    NUMBER
<code>\vphantom {...}</code> *    CONTENT
<code>\vpos {...<sup>1</sup>} {...<sup>2</sup>}</code> 1    NAME 2    CONTENT
<code>\vsmash {...}</code> *    CONTENT
<code>\vsmashbox ...</code> *    CSNAME NUMBER
<code>\vsmashed {...}</code> *    CONTENT
<code>\vspace [...<sup>1</sup>] [...<sup>2</sup>]</code> 1    NAME        OPT        OPT 2    NAME
<code>\vspacing [...,*,...]</code> *    preference same <sup>OPT</sup> page max force enable disable nowhite packed back overlay always weak strong default before inbetween after fixed flexible none small medium big line halfline quarterline formula white height depth standard NUMBER*small NUMBER*medium NUMBER*big NUMBER*line NUMBER*halfline NUMBER*quarterline NUMBER*formula NUMBER*white NUMBER*height NUMBER*depth category:NUMBER order:NUMBER penalty:NUMBER DIMENSION NAME
<code>\WEEKDAY {...}</code> *    NUMBER

\WidthSpanningText {...} {...} {...} 1 TEXT 2 DIMENSION 3 FONT
\WORD {...} * TEXT
\WORDS {...} * TEXT
\Word {...} * TEXT
\Words {...} * TEXT
\wdofstring {...} * TEXT
\weekday {...} * NUMBER
\widthofstring {...} * TEXT
\widthspanningtext {...} {...} {...} 1 TEXT 2 DIMENSION 3 FONT
\withoutpt {...} * DIMENSION
\word {...} * TEXT
\wordright [... <sup>1</sup> ] {... <sup>2</sup> } 1 right DIMENSION 2 CONTENT
\words {...} * TEXT
\wordtonumber {...} {...} 1 one two three four five 2 TEXT
\writebetweenlist [... <sup>1</sup> ] [..., <sup>2</sup> ... <sup>2</sup> ,...] {... <sup>3</sup> } 1 LIST 2 inherits: \setuplist 3 COMMAND
\writadatatolist [... <sup>1</sup> ] [..., <sup>2</sup> ... <sup>2</sup> ,...] [..., <sup>3</sup> ... <sup>3</sup> ,...] 1 LIST 2 inherits: \setuplist 3 KEY = VALUE



`\writestatus {...} {...}`

1 TEXT  
2 TEXT

`\writetolist [...]1 [...,...2...,...]2 {...}3 {...}4`

1 LIST  
2 inherits: \setuplist  
3 NUMBER  
4 TEXT

`\XETEX`

`\XeTeX`

`\xdefconvertedargument \.1 {...}2`

1 CSNAME  
2 TEXT

`\xmladdindex {...}`

\* NODE

`\xmllafterdocumentsetup {...}1 {...}2 {...}3`

1 NAME  
2 SETUP  
3 SETUP

`\xmllaftersetup {...}1 {...}2`

1 SETUP  
2 SETUP

`\xmlall {...}1 {...}2`

1 NODE  
2 LPATH

`\xmlappenddocumentsetup {...}1 {...}2`

1 NAME  
2 SETUP

`\xmlappendsetup {...}`

\* SETUP

`\xmlapplyselectors {...}`

\* NODE

`\xmlatt {...}1 {...}2`

1 NODE  
2 NAME

`\xmlattdef {...}1 {...}2 {...}3`

1 NODE  
2 NAME  
3 TEXT

`\xmlattribute {...}1 {...}2 {...}3`

1 NODE  
2 LPATH  
3 NAME

\xmlattributedef {...} {...} {...} {...}

1 NODE  
2 LPATH  
3 NAME  
4 TEXT

\xmlbadinclusions {...}

\* NODE

\xmlbeforedocumentsetup {...} {...} {...}

1 NAME  
2 SETUP  
3 SETUP

\xmlbeforesetup {...} {...}

1 SETUP  
2 SETUP

\xmlchainatt {...} {...}

1 NODE  
2 NAME

\xmlchainattdef {...} {...} {...}

1 NODE  
2 NAME  
3 TEXT

\xmlchecknamespace {...} {...}

1 NODE  
2 NAME

\xmlcommand {...} {...} {...}

1 NODE  
2 LPATH  
3 XMLSETUP

\xmlconcat {...} {...} {...}

1 NODE  
2 LPATH  
3 TEXT

\xmlconcatrange {...} {...} {...} {...} {...}

1 NODE  
2 LPATH  
3 TEXT  
4 FIRST  
5 LAST

\xmlcontext {...} {...}

1 NODE  
2 LPATH

\xmlcount {...}

\* NODE

\xmldefaulttotext {...}

\* NODE

\xmldirectives {...}

\* NODE

\xmldirectivesafter {...}

\* NODE

```
\xmldirectivesbefore {...}  
*   NODE
```

```
\xmldisplayverbatim {...}  
*   NODE
```

```
\xmldoif {...} {...} {...}  
1   NODE  
2   LPATH  
3   TRUE
```

```
\xmldoifatt {...} {...}  
1   NODE  
2   TRUE
```

```
\xmldoifelse {...} {...} {...} {...}  
1   NODE  
2   LPATH  
3   TRUE  
4   FALSE
```

```
\xmldoifelseatt {...} {...} {...}  
1   NODE  
2   TRUE  
3   FALSE
```

```
\xmldoifelseempty {...} {...} {...} {...}  
1   NODE  
2   LPATH  
3   TRUE  
4   FALSE
```

```
\xmldoifelseselfempty {...} {...} {...}  
1   NODE  
2   TRUE  
3   FALSE
```

```
\xmldoifelsetext {...} {...} {...} {...}  
1   NODE  
2   LPATH  
3   TRUE  
4   FALSE
```

```
\xmldoifelsevalue {...} {...} {...} {...}  
1   CATEGORY  
2   NAME  
3   TRUE  
4   FALSE
```

```
\xmldoifnot {...} {...} {...}  
1   NODE  
2   LPATH  
3   TRUE
```

```
\xmldoifnotatt {...} {...}  
1   NODE  
2   TRUE
```

```
\xmldoifnotselfempty {...} {...}  
1   NODE  
2   TRUE
```

\xmldoifnottext {...} {...} {...} 1    NODE 2    LPATH 3    TRUE
\xmldoifselfempty {...} {...} 1    NODE 2    TRUE
\xmldoiftext {...} {...} {...} 1    NODE 2    LPATH 3    TRUE
\xmlelement {...} {...} 1    NODE 2    NUMBER
\xmlfilter {...} {...} 1    NODE 2    LPATH
\xmlfirst {...} {...} 1    NODE 2    LPATH
\xmlflush {...} *    NODE
\xmlflushcontext {...} *    NODE
\xmlflushdocumentsetups {...} {...} 1    NAME 2    SETUP
\xmlflushlinewise {...} *    NODE
\xmlflushpure {...} *    NODE
\xmlflushspacewise {...} *    NODE
\xmlflushtext {...} *    NODE
\xmlinclude {...} {...} {...} 1    NODE 2    LPATH 3    NAME
\xmlinclusion {...} *    NODE
\xmlinclusions {...} *    NODE

<code>\xmlinfo {...}</code> *    NODE
<code>\xmlinjector {...}</code> *    NAME
<code>\xmlinlineprettyprint {...} {...}</code> 1    NODE 2    mp lua xml parsed-xml nested tex context none NAME
<code>\xmlinlineprettyprinttext {...} {...}</code> 1    NODE 2    mp lua xml parsed-xml nested tex context none NAME
<code>\xmlinlineverbatim {...}</code> *    NODE
<code>\xmlinstalldirective {...} {...}</code> 1    NAME 2    CSNAME
<code>\xmllast {...} {...}</code> 1    NODE 2    LPATH
<code>\xmllastatt</code>
<code>\xmllastmatch</code>
<code>\xmllastpar</code>
<code>\xmlloadbuffer {...} {...} {...}</code> 1    BUFFER 2    NAME 3    XMLSETUP
<code>\xmlloaddata {...} {...} {...}</code> 1    NAME 2    TEXT 3    XMLSETUP
<code>\xmlloaddirectives {...}</code> *    FILE
<code>\xmlloadfile {...} {...} {...}</code> 1    NAME 2    FILE 3    XMLSETUP
<code>\xmlloadonly {...} {...} {...}</code> 1    NAME 2    FILE 3    XMLSETUP
<code>\xmlmain {...}</code> *    NAME
<code>\xmlmapvalue {...} {...} {...}</code> 1    CATEGORY 2    NAME 3    TEXT

<code>\xmlname {...}</code> *    NODE
<code>\xmlnamespace {...}</code> *    NODE
<code>\xmlnonspace {...} {...}</code> 1    NODE 2    LPATH
<code>\xmlpar {...} {...}</code> 1    NODE 2    NAME
<code>\xmlparam {...} {...} {...}</code> 1    NODE 2    LPATH 3    NAME
<code>\xmlpath {...}</code> *    NODE
<code>\xmlpos {...}</code> *    NODE
<code>\xmlposition {...} {...} {...}</code> 1    NODE 2    LPATH 3    NUMBER
<code>\xmlprependdocumentsetup {...} {...}</code> 1    NAME 2    SETUP
<code>\xmlprependsetup {...}</code> *    SETUP
<code>\xmlprettyprint {...} {...}</code> 1    NODE 2    mp lua xml parsed-xml nested tex context none NAME
<code>\xmlprettyprinttext {...} {...}</code> 1    NODE 2    mp lua xml parsed-xml nested tex context none NAME
<code>\xmlprocessbuffer {...} {...} {...}</code> 1    BUFFER 2    NAME 3    XMLSETUP
<code>\xmlprocessdata {...} {...} {...}</code> 1    NAME 2    TEXT 3    XMLSETUP
<code>\xmlprocessfile {...} {...} {...}</code> 1    NAME 2    FILE 3    XMLSETUP

\xmlpure {...} {...}

- 1 NODE
- 2 LPATH

\xmlraw {...}

- \* NODE

\xmlrefatt {...} {...}

- 1 NODE
- 2 NAME

\xmlregistereddokumentsetups {...} {...}

- 1 NAME
- 2 SETUP

\xmlregisteredsetups

\xmlregisterns {...} {...}

- 1 NAME
- 2 URL

\xmlremapname {...} {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 NAME
- 4 NAME

\xmlremapnamespace {...} {...} {...}

- 1 NODE
- 2 NAME
- 3 NAME

\xmlremoveddocumentsetup {...} {...}

- 1 NAME
- 2 SETUP

\xmlremovesetup {...}

- \* SETUP

\xmlresetdocumentsetups {...}

- \* NAME

\xmlresetinjectors

\xmlresetsetups {...}

- \* NAME

\xmlsave {...} {...}

- 1 NODE
- 2 FILE

\xmlsetatt {...} {...} {...}

- 1 NODE
- 2 NAME
- 3 TEXT

\xmlsetAttribute {...} {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 NAME
- 4 TEXT

\xmlsetentity {...} {...}

1 NAME  
2 TEXT

\xmlsetfunction {...} {...} {...}

1 NODE  
2 LPATH  
3 LUAFUNCTION

\xmlsetinjectors [...,\*...]

\* NAME

\xmlsetpar {...} {...} {...}

1 NODE  
2 NAME  
3 TEXT

\xmlsetparam {...} {...} {...} {...}

1 NODE  
2 LPATH  
3 NAME  
4 TEXT

\xmlsetsetup {...} {...} {...}

1 NAME  
2 LPATH  
3 SETUP

\xmlsetup {...} {...}

1 NODE  
2 SETUP

\xmlshow {...}

\* NODE

\xmlsnippet {...} {...}

1 NODE  
2 NUMBER

\xmlstrip {...} {...}

1 NODE  
2 LPATH

\xmlstripnolines {...} {...}

1 NODE  
2 LPATH

\xmlstripped {...} {...}

1 NODE  
2 LPATH

\xmlstrippednolines {...} {...}

1 NODE  
2 LPATH

\xmltag {...}

\* NODE

\xmltexentity {...} {...}

1 NAME  
2 TEXT



\xmltext {...} {...}

- 1 NODE
- 2 LPATH

\xmltobuffer {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 BUFFER

\xmltobufferverbose {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 BUFFER

\xmltofile {...} {...} {...}

- 1 NODE
- 2 LPATH
- 3 FILE

\xmlvalue {...} {...} {...}

- 1 CATEGORY
- 2 NAME
- 3 TEXT

\xmlverbatim {...}

- \* NODE

\xsplitstring \... {...}

- 1 CSNAME
- 2 TEXT

\xypos {...}

- \* NAME

\zeronumberconversion {...}

- \* NUMBER







**PRAGMA ADE**  
**Ridderstraat 27**  
**8061GH Hasselt NL**  
**[www.pragma-ade.com](http://www.pragma-ade.com)**